according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 1510

Chemical nature : Esters

Solvent

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

: mcm@oks-germany.com

responsible for the SDS

Material Compliance Management

National contact :

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)

+86 21 69225521

Recommended use of the chemical and restrictions on use

Recommended use : Release agent

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquidColour: yellowOdour: characteristic

Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. May cause drowsiness or dizziness. Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

Specific target organ toxicity - : Category 3 (Narcotic effects)



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

single exposure

Aspiration hazard : Category 1

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms









Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ ventilating/ lighting

equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off

immediately all contaminated clothing. Rinse skin with water/

shower.

P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/

doctor if you feel unwell.

P331 Do NOT induce vomiting.



according to GB/T 16483 and GB/T 17519 CN



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

P332 + P313 If skin irritation occurs: Get medical advice/

attention.

P362 + P364 Take off contaminated clothing and wash it before

reuse.

P370 + P378 In case of fire: Use alcohol-resistant foam, carbon

dioxide or water mist to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/containers according the local government requirements.

Physical and chemical hazards

Highly flammable liquid and vapour.

Health hazards

Causes skin irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Environmental hazards

Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 25 -< 30
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 10 -< 20
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 2.5 -< 10
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 2.5 -< 10

4. FIRST AID MEASURES

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water. Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention. If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause

damage.

Most important symptoms and effects, both acute and

delayed

Central nervous system depression

Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or



according to GB/T 16483 and GB/T 17519 CN



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

carbon dioxide.

Unsuitable extinguishing

media

: High volume water jet

Specific hazards during

firefighting

Do not let product enter drains.

Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Specific extinguishing

methods

Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.
Use personal protective equipment.

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13).

Non-sparking tools should be used.

7. HANDLING AND STORAGE

Handling

Advice on protection against : Keep away from heat and sources of ignition.



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

fire and explosion

Advice on safe handling : Use only in an area containing explosion proof equipment.

Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

Do not enter areas where used or stored until adequately

ventilated. Do not repack.

Do not re-use empty containers.

These safety instructions also apply to empty packaging which

may still contain product residues. Keep container closed when not in use.

Avoidance of contact : Oxidizing agents

Storage

Conditions for safe storage : Store in original container.

Keep container closed when not in use.

Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with the particular national regulations.

Keep in properly labelled containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : Use only in an area equipped with explosion proof exhaust

ventilation.

Handle only in a place equipped with local exhaust (or other

appropriate exhaust).



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:

Organic gas and low boiling vapour type

Eye/face protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : yellow

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

according to GB/T 16483 and GB/T 17519 CN



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

substance/mixture is non-polar/aprotic

Melting point/range : No data available

Boiling point/boiling range : > 60.1 °C

(1,013 hPa)

Flash point : < -18.00 °C

Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

7.3 %(V)

Lower explosion limit / Lower

flammability limit

1.0 %(V)

Vapour pressure : < 1,100 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0.795 (20 °C)

Reference substance: Water The value is calculated

Density : 0.80 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 7 mm2/s (40 °C)

according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central

nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation



according to GB/T 16483 and GB/T 17519 CN



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Components:

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Naphtha (petroleum), hydrotreated light:

Result : Skin irritation

Naphtha (petroleum), hydrotreated light:

Species : Rabbit

Result : Skin irritation

Naphtha (petroleum), hydrotreated light:

Result : Skin irritation

Naphtha (petroleum), hydrotreated light:

Species : Rabbit

Result : Skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

according to GB/T 16483 and GB/T 17519 CN



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development

: Remarks: No data available

STOT - single exposure

Components:

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

according to GB/T 16483 and GB/T 17519 CN



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.



according to GB/T 16483 and GB/T 17519 CN



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Toxicity to daphnia and other :

aquatic invertebrates Remarks: No data available

Toxicity to algae/aquatic

plants Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated light:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

aquatic invertebrates Exposure time: 48 h

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

: Remarks: No data available



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Components:

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: rapidly biodegradable

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: Not rapidly biodegradable

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-

octanol/water

Remarks: No data available

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-

octanol/water

log Pow: 4

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among : Rem

environmental compartments

Remarks: No data available

Other adverse effects

Product:

Additional ecological

information

: Toxic to aquatic life with long lasting effects.



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of waste product or used containers according to

local regulations.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 3295

Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.

(Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5%

n-hexane, Hydrocarbons, C6, isoalkanes, <5% n-hexane)

Class : 3
Packing group : II
Labels : 3

IATA-DGR

UN/ID No. : UN 3295

Proper shipping name : Hydrocarbons, liquid, n.o.s.

(Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane, Hydrocarbons, C6, isoalkanes, <5% n-hexane)

Class : 3 Packing group : II

Labels : Flammable Liquids

Packing instruction (cargo

aircraft)

: 364

Packing instruction : 353

(passenger aircraft)

IMDG-Code

UN number : UN 3295

Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.

(Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-

hexane, Hydrocarbons, C6, isoalkanes, <5% n-hexane)

Class : 3 Packing group : II



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

Labels : 3

EmS Code : F-E, S-D Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : UN 3295

Proper shipping name : HYDROCARBONS, LIQUID, N.O.S.

(,)

Class : 3
Packing group : II
Labels : 3

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals

Product name	Status	Reference number
OKS 1510	Listed	2828

Hazardous Chemicals for Priority Management under : Not applicable

SAWS

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not applicable

and Export



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

International Regulations

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration: NO(A)EL - No Observed (Adverse) Effect Level: NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods;



according to GB/T 16483 and GB/T 17519



OKS 1510

Version Revision Date: Date of last issue: 2020-08-12

2.5 2022-10-31 Date of first issue: 2014-05-21 Print Date: 2022-10-31

vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

