- RU



### **OKS 2351**

Print Date: Version Date of last issue: 08.09.2021 Revision Date: 20.01.2023 Date of first issue: 26.05.2014 20.01.2023 2.4

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : OKS 2351

Manufacturer or supplier's details

Company name of supplier OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person mcm@oks-germany.com

responsible for the SDS Material Compliance Management

Emergency telephone : +7 495 628 1687

number +49 8142 3051 517

Recommended use of the chemical and restrictions on use

Recommended use Lubricant spray

Restrictions on use Restricted to professional users.

#### 2. HAZARDS IDENTIFICATION

GHS Classification (According to GOST 32423, GOST 32424 and GOST 32425)

Aerosols : Category 1

Skin irritation Category 2

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

Aspiration hazard Category 1

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic Category 3

hazard

**GHS-Labelling (According to GOST 31340)** 

Hazard pictograms





- RU



**OKS 2351** 

 Version
 Revision Date:
 Date of last issue: 08.09.2021
 Print Date:

 2.4
 20.01.2023
 Date of first issue: 26.05.2014
 20.01.2023

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:** 

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical nature : Active agent with propellant and solvent.

# Components

Chemical name	Concentration (% w/w)	Occupational Exposure Limits		CAS-No.	EC-No.
		MAC value mg/m3 / TSEL value	Hazard Class		
butane	>= 30 - < 50	MPC-TWA: 300 mg/m3 Data Source: RU OEL	4	106-97-8	203-448-7
		MPC-STEL: 900 mg/m3 Data Source: RU OEL	4		

- RU



### **OKS 2351**

Version	Revision Date:	Date of last issue: 08.09.2021	Print Date:
2.4	20.01.2023	Date of first issue: 26.05.2014	20.01.2023

propane	>= 10 - < 20	No data available	74-98-6	200-827-9
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	>= 10 - < 20	No data available		921-024-6
Kaolin, calcined	>= 1 - < 10	No data available	92704-41-1	296-473-8
aluminium powder (stabilised)	>= 1 - < 10	No data available	7429-90-5	231-072-3
isobutane	>= 1 - < 10	No data available	75-28-5	200-857-2

#### 4. FIRST AID MEASURES

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse. Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

Most important symptoms and effects, both acute and

delayed

Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

Inhalation may provoke the following symptoms:

- RU



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Notes to physician : Treat symptomatically.

#### 5. FIREFIGHTING MEASURES

Flammable properties

Flash point : -97,00 °C

Method: Abel-Pensky

Ignition temperature : No data available

Upper explosion limit / Upper :

flammability limit

10,9 %(V)

Lower explosion limit / Lower :

flammability limit

0,8 %(V)

Flammability (solid, gas) : Extremely flammable aerosol.

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Nitrogen oxides (NOx)

Metal oxides

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

- RU



#### **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

Exposure to decomposition products may be a hazard to

health.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas. Ensure adequate ventilation.

Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

### 7. HANDLING AND STORAGE

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.



- RU



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in accordance with the particular national regulations.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Data Source		
butane	106-97-8	MPC-TWA (vapour and/or gas)	300 mg/m3	RU OEL (2021-02-03)		
	Further information: Class 4 - Low hazard					
		MPC-STEL (vapour and/or gas)	900 mg/m3	RU OEL (2021-02-03)		
	Further information: Class 4 - Low hazard					

**Engineering measures**: Use only in an area equipped with explosion proof exhaust

ventilation.

Handle only in a place equipped with local exhaust (or other

appropriate exhaust).

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type : Filter type A-P

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

- RU



**OKS 2351** 

Version **Revision Date:** Date of last issue: 08.09.2021 Print Date: 2.4 20.01.2023 Date of first issue: 26.05.2014 20.01.2023

Protective measures The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures Wash face, hands and any exposed skin thoroughly after

handling.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

**Appearance** aerosol

Colour grey

Odour characteristic

Odour Threshold No data available

рΗ Not applicable

substance/mixture is non-soluble (in water)

Melting point/range No data available

-44,5 °C Boiling point/boiling range

(1.013 hPa)

-97,00 °C Flash point

Method: Abel-Pensky

Evaporation rate No data available

Extremely flammable aerosol. Flammability (solid, gas)

Self-ignition not auto-flammable

Upper explosion limit / Upper

flammability limit

10,9 %(V)

Lower explosion limit / Lower : 0,8 %(V)

flammability limit

Vapour pressure 4.750 hPa (20 °C)

Relative vapour density : No data available

- RU



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

Relative density : 0,7 (20 °C)

Reference substance: Water The value is calculated

Density : 0,70 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic :  $< 20,5 \text{ mm2/s} (40 \,^{\circ}\text{C})$ 

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

#### 10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition : No decomposition if stored and applied as directed.

- RU



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

products

#### 11. TOXICOLOGICAL INFORMATION

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific

target organ toxicant, single exposure, category 3 with

narcotic effects.

Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

**Components:** 

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

- RU



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Kaolin, calcined:

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific

target organ toxicant, single exposure, category 3 with

respiratory tract irritation.

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5,09 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute

inhalation toxicity

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Skin corrosion/irritation

**Product:** 

Remarks : Irritating to skin.

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

Kaolin, calcined:

Result : Repeated exposure may cause skin dryness or cracking.

aluminium powder (stabilised):

Species : Rabbit

Assessment : No skin irritation
Result : No skin irritation

- RU



### **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

## Serious eye damage/eye irritation

**Product:** 

Remarks : Contact with eyes may cause irritation.

## **Components:**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Kaolin, calcined:

Result : Irritating to eyes.

## aluminium powder (stabilised):

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

# Respiratory or skin sensitisation

**Product:** 

Remarks : This information is not available.

#### **Components:**

# Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

## aluminium powder (stabilised):

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals. Result : Did not cause sensitisation on laboratory animals.

- RU



### **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

# Germ cell mutagenicity

**Product:** 

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### **Components:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Rodent cell line Method: OECD Test Guideline 473

Result: negative

# Carcinogenicity

**Product:** 

Remarks : No data available

## Reproductive toxicity

**Product:** 

Effects on fertility : Remarks: No data available

Effects on foetal development

Remarks: No data available

## STOT - single exposure

## **Components:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Kaolin, calcined:

Exposure routes : Inhalation

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with respiratory tract

irritation.

- RU



### **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

## STOT - repeated exposure

#### **Components:**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)

Assessment : No significant health effects observed in animals at

concentrations of 1 mg/l/6h/d or less.

## Repeated dose toxicity

**Product:** 

Remarks : This information is not available.

## **Aspiration toxicity**

#### **Product:**

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

#### **Components:**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

## **Further information**

**Product:** 

Remarks : Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

**Product:** 

Toxicity to fish

Remarks: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

- RU



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EbC50 (Pseudokirchneriella subcapitata (green algae)): 26

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

aluminium powder (stabilised):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,12 mg/l

Exposure time: 96 h Test Type: static test

Remarks: No toxicity at the limit of solubility

**Ecotoxicology Assessment** 

Acute aquatic toxicity : This product has no known ecotoxicological effects.

- RU



**OKS 2351** 

Version **Revision Date:** Date of last issue: 08.09.2021 Print Date: 2.4 20.01.2023 Date of first issue: 26.05.2014 20.01.2023

Chronic aquatic toxicity This product has no known ecotoxicological effects.

# Persistence and degradability

**Product:** 

Biodegradability Remarks: No data available

Physico-chemical

removability

Remarks: No data available

## Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

### Bioaccumulative potential

**Product:** 

Remarks: This mixture contains no substance considered to Bioaccumulation

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

#### **Components:**

butane:

Partition coefficient: nlog Pow: 2,89

Method: OECD Test Guideline 107 octanol/water

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

isobutane:

Partition coefficient: n-

log Pow: 2,88

Method: OECD Test Guideline 107 octanol/water

Mobility in soil

**Product:** 

Mobility Remarks: No data available

Distribution among Remarks: No data available

- RU



# **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

environmental compartments

## Other adverse effects

**Product:** 

Additional ecological

information

: Harmful to aquatic life with long lasting effects.

# Hygienic standards:

# (Allowable concentration in air, water, including fishery waters, soil)

Components	Air	Water	Soil	Data Source
butane	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 200 mg/m3 Limiting health hazard indicator: reflectory Hazard class: Class 4 - low hazard	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 1 List 5
propane	No data available	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 5
aluminium powder (stabilised)	No data available	Maximum Permissible Concentration: 0,04 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 4 Regional Maximum Permissible Concentration: 0,081 Milligrams per cubed decimeter	No data available	List 4 List 5

- RU



OKS 235	51				
Version Revision Date: 2.4 20.01.2023		Date of last issue: Date of first issue:	Print Date: 20.01.2023		
			Limiting health hazard indicator: sanitary and toxicological effects Hazard class: 3 Maximum Allowable Concentration: 0,2 mg/l (Aluminium) Limiting health hazard indicator: organoleptic; increases the turbidity of the water Hazard class: Class 3 - moderately dangerous		
isobu	tane	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 15 mg/m3 Limiting health hazard indicator: reflectory Hazard class: Class 4 - low hazard	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 1 List 5

For explanation of abbreviations see section 16.

# 13. DISPOSAL CONSIDERATIONS

# **Disposal methods**

Waste from residues : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:



- RU



### **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

Waste Code : unused product, packagings not completely emptied

16 05 04\*, gases in pressure containers (including halons)

containing hazardous substances

#### 14. TRANSPORT INFORMATION

ADR

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2

Packing group : Not assigned by regulation

Labels : 2.1 Tunnel restriction code : (D)

**IATA-DGR** 

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

203

Labels : Flammable Gas

Packing instruction (cargo :

aircraft)

Packing instruction : 203

(passenger aircraft)

**IMDG-Code** 

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : no

## Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 15. REGULATORY INFORMATION

#### National regulatory information

Federal Law of 21.07.1997 No. 116-FZ (amended on 11.06.2021) "On industrial safety of hazardous production facilities".

Federal Law of 24.06.1998 No. 89-FZ (amended on 02.07.2021) "On production and

- RU



#### **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

consumption waste".

Federal Law of 30.03.1999 No. 52-FZ (amended on 02.07.2021) "On the Sanitary and Epidemiological Well-Being of the Population" (amended and supplemented, entered into force on 31.10.2021).

Federal Law of 04.05.1999 No. 96-FZ "On the protection of atmospheric air" (as amended on December 8, 2020).

Federal Law of 27.12.2002 No. 184-FZ (amended on 02.07.2021) "On Technical Regulation" (amended and supplemented, entered into force on 01.09.2021).

Federal Law of 10.01.2002 No. 7-FZ (amended on 02.07.2021) "On environmental protection". Federal Law of 22.07.2008 No. 123-FZ "Technical Regulations on Fire Safety Requirements" TECHNICAL REGULATIONS OF THE CUSTOMS UNION TR CU 030/2012 On requirements for lubricants, oils and special fluids (amended on 03.03.2017).

#### **International Regulations**

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

#### 16. OTHER INFORMATION

#### List of data sources used in the preparation of the Safety Data Sheet

GOST 30333-2007. Interstate standard. Safety data sheet for chemical products. Primary requirements.

GOST 12.1.004-91 System of labor safety standards (SSBT). Fire safety. General requirements.

GOST 12.1.007-76 Occupational safety standards system. Noxious substances. Classification and general safety requirements

GOST 12.1.044-89 SSBT. Fire and explosion hazard of substances and materials. Nomenclature of indicators and methods for their determination.

GOST 12.4.021 System of labor safety standards (SSBT). Ventilation systems. General requirements.

GOST 12.4.137-2001 Special footwear with leather uppers for protection against oil, oil products, acids, alkalis, non-toxic and explosive dust. Technical conditions.

GOST 12.4.252-2013 System of labor safety standards (SSBT). Means of individual protection of hands. Gloves. General technical requirements. Test methods.

GOST 14192-96. Interstate standard. Cargo marking. Minsk, 1998.

GOST 19433-88 Dangerous goods. Classification and labeling.

GOST 31340-2013. Interstate standard. Precautionary labeling of chemical products. General requirements.

GOST 32419-2013 Classification of the hazard of chemical products. General requirements.

GOST 32421-2013 Classification of chemical products, the hazard of which is due to physical and chemical properties. Test methods for explosive chemical products.

GOST 32423-2013 Hazard classification of mixed chemical products by their effects on the body. GOST 32424-2013 Classification of the hazard of chemical products by their impact on the environment. Basic provisions.



- RU



#### **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

GOST 32425-2013 Hazard classification of mixed chemical products in terms of environmental impact.

GOST R 53264-2019 Fire fighting equipment. Special protective clothing for firefighters. General technical requirements. Test methods.

GOST R 53265-2019 Fire fighting equipment. Personal protective equipment for the feet of the firefighter. General technical requirements. Test methods.

GOST R 53268-2009 Fire fighting equipment. Fire rescue belts. General technical requirements. Test methods.

GOST R 53269-2019 Fire fighting equipment. Firefighters helmets. General technical requirements. Test methods.

SanPiN 1.2.2353-08 "Carcinogenic factors and basic requirements for the prevention of carcinogenic hazard".

SanPiN 1.2.3685-21 "Hygienic standards and requirements for ensuring the safety and (or) harmlessness to humans of environmental factors" dated 28.01.2021.

SanPiN 2.1.3684-21 "Sanitary and epidemiological requirements for the maintenance of the territories of urban and rural settlements, for water bodies, drinking water and drinking water supply, atmospheric air, soils, living quarters, the operation of industrial, public premises, the organization and implementation of sanitary and anti-epidemic (preventive) measures".

SanPiN 2.2.0.555-96. 2.2. Labor hygiene. Hygienic requirements for working conditions for women. Sanitary rules and regulations.

Carriage of dangerous goods, International maritime dangerous goods (IMDG) code.

Water quality standards for fishery water bodies, including standards for maximum permissible concentrations of harmful substances in the waters of fishery water bodies (approved by order of the Ministry of Agriculture of Russia dated December 13, 2016 No. 552).

Regulations for the carriage of dangerous goods (Appendix 1 and 2) to the Agreement on International Goods Transport by Rail (SMGS), 2009.

Agreement on International Goods Transport by Rail (SMGS).

UN Recommendations on the Transport of Dangerous Goods. Typical rules. Twenty-second revised edition. United Nations, New York and Geneva, 2021.

Montreal Protocol (Ozone Depleting Substances)

Stockholm Convention (Persistent Organic Pollutants)

#### Full text of other abbreviations

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Eye Irrit. : Eye irritation
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Flam. Sol. : Flammable solids
Press. Gas : Gases under pressure

Skin Irrit. : Skin irritation

STOT SE : Specific target organ toxicity - single exposure

RU OEL : SanPiN 1.2.3685-21 Table 2.1, Table 2.8, Table 2.16 & Table

2.17 Maximum permissible concentrations (MPC) in the air of

the working area

RU OEL / MPC-STEL : Maximum Permissible Concentration - Short Term Exposure RU OEL / MPC-TWA : Maximum Permissible Concentration - Time Weighted

Average

List 1 : SanPiN 1.2.3685-21 Table 1.1, Table 1.10, & Table 1.11

Maximum permissible concentration (MPC) in the air of urban

and rural settlements

List 4 : SanPiN 1.2.3685-21 Table 3.13, Table 3.15, Table 3.16 &

- RU



**OKS 2351** 

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

Table 3.17 Maximum permissible concentrations (MPC) of chemicals in the water of drinking systems of centralized, including hot, and non-centralized water supply, water of underground and surface water bodies of domestic drinking and cultural and domestic water use, water of swimming

pools, water parks

List 5 : Order of the Russian Federal Fisheries Agency "Standards of

maximum permissible concentrations of harmful substances in

fishery water bodies"

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road: AIIC - Australian Inventory of Industrial Chemicals: ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the

- RU



# **OKS 2351**

VersionRevision Date:Date of last issue: 08.09.2021Print Date:2.420.01.2023Date of first issue: 26.05.201420.01.2023

product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.