according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 471

Chemical nature : Active agent with propellant and solvent.

Mineral oil.

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

rson : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact :

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)

+86 21 69225521

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant spray

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance : aerosol Colour : white

Odour : hydrocarbon-like

Extremely flammable aerosol. Pressurised container: May burst if heated. May be fatal if

swallowed and enters airways.

GHS Classification

Aerosols : Category 1

Aspiration hazard : Category 1

GHS label elements



according to GB/T 16483 and GB/T 17519 CN



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters airways.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/containers according the local

government requirements.

Physical and chemical hazards

Extremely flammable aerosol. Pressurised container: May burst if heated.

Health hazards

May be fatal if swallowed and enters airways.

Environmental hazards

Not classified based on available information.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components



2/23

according to GB/T 16483 and GB/T 17519 ${
m CN}$



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 30 -< 50
Butane	106-97-8	>= 20 -< 30
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 10 -< 20
propane	74-98-6	>= 1 -< 10
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 1 -< 10
lithium 12-hydroxystearate	7620-77-1	>= 1 -< 10
Isobutane	75-28-5	>= 1 -< 10

4. FIRST AID MEASURES

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

Most important symptoms and effects, both acute and

delayed

Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Metal oxides

Specific extinguishing

methods

Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for : Contain spillage, and then collect with non-combustible

according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

containment and cleaning up absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

Prevention of secondary

hazards

Only qualified personnel equipped with suitable protective

equipment may intervene.

7. HANDLING AND STORAGE

Handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Avoidance of contact : Oxidizing agents

Storage

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in accordance with the particular national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components CAS-No. Value type Control Basis	
---	--

according to GB/T 16483 and GB/T 17519 CN



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

		(Form of exposure)	parameters / Permissible concentration	
Butane	106-97-8	STEL	1,000 ppm	ACGIH (2018-03-20)
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH (2013-03-01)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH (2013-03-01)
lithium 12-hydroxystearate	7620-77-1	TWA (Inhalable particulate matter)	10 mg/m3	ACGIH (2018-03-20)
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH (2018-03-20)
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH (2018-03-20)

Engineering measures : Use only in an area equipped with explosion proof exhaust

ventilation.

Handle only in a place equipped with local exhaust (or other

appropriate exhaust).

Personal protective equipment

Respiratory protection : Respirator with combination filter for vapour/particulate (EN

141)

Short term only

Filter type : ABEK-P3-filter

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Eye/face protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : white

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : -44 °C

(1,013 hPa)

Flash point : -97.00 °C

Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : not auto-flammable

Upper explosion limit / Upper

flammability limit

8.5 %(V)

Lower explosion limit / Lower : 1.5 %(V)

according to GB/T 16483 and GB/T 17519 CN



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

flammability limit

Vapour pressure : 3,500 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0.718 (20 °C)

Reference substance: Water The value is calculated

Density : 0.72 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

cause defatting resulting in drying, redness and possible

blistering.

Symptoms: Skin disorders

Components:

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

lithium 12-hydroxystearate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

lithium 12-hydroxystearate:

Assessment : No skin irritation

Method : OECD Test Guideline 439

Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic:



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

lithium 12-hydroxystearate:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

lithium 12-hydroxystearate:

Exposure routes : Dermal Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Genotoxicity in vivo : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

Distillates (petroleum), hydrotreated heavy naphthenic:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Effects on foetal : Remarks: No data available

development

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Reproductive toxicity - : - Fertility -

Assessment No toxicity to reproduction

Distillates (petroleum), hydrotreated heavy naphthenic:

Effects on foetal : Species: Rat

development Application Route: Dermal

General Toxicity Maternal: LOAEL: 125 mg/kg body weight

Teratogenicity: NOAEL: >= 2,000 mg/kg body weight

Developmental Toxicity: NOAEL: >= 2,000 mg/kg body weight Embryo-foetal toxicity: NOAEL: >= 2,000 mg/kg body weight

Method: OECD Test Guideline 414

Result: No effects on fertility and early embryonic

development were detected.

Reproductive toxicity - : - Fertility -

Assessment No toxicity to reproduction

- Teratogenicity -

No toxicity to reproduction

STOT - single exposure

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

according to GB/T 16483 and GB/T 17519 CN



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated heavy paraffinic:

No aspiration toxicity classification

Distillates (petroleum), hydrotreated heavy naphthenic:

No aspiration toxicity classification

Further information

Product:

Remarks : Information given is based on data on the components and

the toxicology of similar products.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: May cause long-term adverse effects in the aquatic

environment.



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Toxicity to daphnia and other :

aquatic invertebrates Remarks: No data available

Toxicity to algae/aquatic

plants Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

LC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

NOELR (Oncorhynchus mykiss (rainbow trout)): >= 1,000 mg/l

Exposure time: 28 d

Remarks: The value is calculated

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOELR (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Test Type: Reproduction Test Method: OECD Test Guideline 211

lithium 12-hydroxystearate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 160

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 160

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

according to GB/T 16483 and GB/T 17519



OKS 471

Version Date of last issue: 2021-05-12 Revision Date:

2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13 2.2

Components:

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: Not readily biodegradable.

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability aerobic

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability aerobic

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

lithium 12-hydroxystearate:

Biodegradability Primary biodegradation

> Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: 74.7 %

Exposure time: 28 d

Method: OECD Test Guideline 301C

Bioaccumulative potential

Product:

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Remarks: No data available

according to GB/T 16483 and GB/T 17519 CN



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Partition coefficient: n-

octanol/water

: Remarks: No data available

Butane:

Partition coefficient: n- : log Pow: 2.89

octanol/water Method: OECD Test Guideline 107

Distillates (petroleum), hydrotreated heavy paraffinic:

Partition coefficient: n-

octanol/water

: $\log Pow: > 2$

propane:

Partition coefficient: n-

octanol/water

log Pow: 2.36

lithium 12-hydroxystearate:

Partition coefficient: n-

octanol/water

log Pow: 2.6

Isobutane:

Partition coefficient: n- : log Pow: 2.88

octanol/water Method: OECD Test Guideline 107

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among

environmental compartments

Remarks: No data available

Other adverse effects

Product:

Additional ecological

information

May cause long lasting harmful effects to aquatic life.

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Results of PBT and vPvB

: Non-classified vPvB substance Non-classified PBT substance

assessment



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Distillates (petroleum), hydrotreated heavy naphthenic:

Results of PBT and vPvB

assessment

: Non-classified PBT substance Non-classified vPvB substance

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : Flammable Gas

Packing instruction (cargo : 203

aircraft)

Packing instruction : 203

(passenger aircraft)

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals

Product name	Status	Reference number
OKS 471	Listed	2828

List of ingredients	CAS-No.	Status	Reference number
Butane	106-97-8	Listed	2778
propane	74-98-6	Listed	139
Isobutane	75-28-5	Listed	2707

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

Category Threshold quantity

Aerosols 150 t

Hazardous Chemicals for Priority Management under : Not applicable

SAWS



according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not applicable

and Export

International Regulations

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average ACGIH / STEL : Short-term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test

according to GB/T 16483 and GB/T 17519



OKS 471

Version Revision Date: Date of last issue: 2021-05-12

2.2 2022-12-13 Date of first issue: 2014-03-20 Print Date: 2022-12-13

population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention: PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

