according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 601

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Lubricant spray

Substance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

responsible for the SDS

mcm@oks-germany.com

National contact :

1.4 Emergency telephone number

Emergency telephone : CIAV - Information Centre of Antipoison number (+351) 800 250 250 (free 24/7 service)

## **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H304 May be fatal if swallowed and enters

airways.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

#### Hazardous components which must be listed on the label:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics

# **Additional Labelling**

EUH208 Contains Sulfonic acids, petroleum, calcium salts. May produce an allergic

reaction.

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Active substance with propellant

Mineral oil.

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C10- C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics	918-481-9 01-2119457273-39- XXXX	Asp. Tox.1; H304; EUH066 ; EUH066	Note PNote P	>= 50 - < 70
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 1 - < 10
Sulfonic acids, petroleum, calcium salts	61789-86-4 263-093-9 01-2119488992-18- 0000	Skin Sens.1B; H317	>= 10 % Skin Sens.1B,	>= 1 - < 10



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 10 - < 20
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- XXXX	Not classified	Note L	>= 1 - < 10
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- XXXX	Not classified	Note L	>= 1 - < 10

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 2.4 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during : Fire Hazard

firefighting Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Nitrogen oxides (NOx)



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 2.4 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

Sulphur oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water

courses.

Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages

cannot be contained.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

#### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 2.4 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular

national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

#### **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form	Control parameters	Basis
		of exposure)		
butane	106-97-8	VLE_CDShort	1.000 ppm	PT OEL
		Term Exposure		(2014-11-14)
		Limit		
Distillates	64742-54-7	VLE-MPTime	5 mg/m3	PT OEL
(petroleum),		Weighted		(2014-11-14)
hydrotreated heavy		Average		



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



#### **OKS 601**

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

paraffinic; Baseoil — unspecified		(Inhalable fraction)		
	Further inform humans.	nation: Substances	that are not classified as card	inogenic for
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0	VLE-MPTime Weighted Average (Inhalable fraction)	5 mg/m3	PT OEL (2014-11-14)
	Further inform humans.	nation: Substances	that are not classified as card	inogenic for

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Distillates (petroleum), solvent- dewaxed heavy paraffinic; Baseoil — unspecified	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
Distillates (petroleum),	Oral	9,33 mg/kg
hydrotreated heavy paraffinic;		
Baseoil — unspecified		
Distillates (petroleum), solvent-	Oral	9,33 mg/kg
dewaxed heavy paraffinic;		
Baseoil — unspecified		

## 8.2 Exposure controls

# **Engineering measures**

Use only in an area equipped with explosion proof exhaust ventilation.

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

#### Personal protective equipment

Eye/face protection : Safety glasses with side-shields



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 2.4 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

#### **SECTION 9: Physical and chemical properties**

# 9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : brown

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : < -20 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

Upper explosion limit / Upper

flammability limit

: 9,4 %(V)

Lower explosion limit / Lower

flammability limit

0,7 %(V)

Flash point : -20 °C

Method: Abel-Pensky, closed cup

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 2.800 hPa (20 °C)

Relative density : 0,741 (20 °C)

Reference substance: Water The value is calculated

Density : 0,74 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No hazards to be specially mentioned.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

cause defatting resulting in drying, redness and possible

blistering.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 2.4 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

Symptoms: Skin disorders

**Components:** 

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

**Product:** 

Remarks : This information is not available.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 2.4 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : Mild skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Serious eye damage/eye irritation

**Product:** 

Remarks : Contact with eyes may cause irritation.

**Components:** 

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

a brand of
FREUDENBERG

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

## Respiratory or skin sensitisation

**Product:** 

Remarks : This information is not available.

**Components:** 

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Sulfonic acids, petroleum, calcium salts:

Assessment : The product is a skin sensitiser, sub-category 1B.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Germ cell mutagenicity

**Product:** 

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Components:** 

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Germ cell mutagenicity: Tests on bacterial or mammalian cell cultures did not show

Assessment mutagenic effects.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Genotoxicity in vitro : Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Carcinogenicity

**Product:** 

Remarks : No data available

**Components:** 

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Carcinogenicity -

Assessment

: Not classifiable as a human carcinogen.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Carcinogenicity -

: Not classifiable as a human carcinogen.

Assessment

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Mouse Application Route : Dermal

Method : OECD Test Guideline 451

Result : negative

Reproductive toxicity

**Product:** 

Effects on fertility : Remarks: No data available

Effects on foetal development

: Remarks: No data available

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Reproductive toxicity - : - Fertility -

Assessment No toxicity to reproduction

- Teratogenicity -

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

No toxicity to reproduction

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Reproductive toxicity - : - Fertility -

Assessment

No toxicity to reproduction

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Effects on foetal : Species: Rat

development Application Route: Dermal

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 30 mg/kg body weight

Method: OECD Test Guideline 414

STOT - single exposure

Product:

Remarks : No data available

**Components:** 

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

**Product:** 

Remarks : No data available

**Components:** 

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Repeated dose toxicity

**Product:** 

Remarks : This information is not available.

**Aspiration toxicity** 

**Product:** 

May be fatal if swallowed and enters airways.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 2.4 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

May be fatal if swallowed and enters airways.

#### Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

#### 11.2 Information on other hazards

#### **Endocrine disrupting properties**

**Product:** 

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

**Further information** 

**Product:** 

Remarks : Information given is based on data on the components and

the toxicology of similar products.

# **SECTION 12: Ecological information**

# 12.1 Toxicity

**Product:** 

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

a brand of

FREUDENBERG

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

**Components:** 

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

: NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

a brand of
FREUDENBERG

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Revision Date: Date of last issue: 20.12.2022 Print Date: 2.4 21.03.2024 Date of first issue: 06.06.2016 21.03.2024

Test Type: static test

Method: OECD Test Guideline 201

Toxicity to daphnia and other : aquatic invertebrates

NOEC: 10 mg/l Exposure time: 21 d

(Chronic toxicity)

Species: Daphnia magna (Water flea)

## 12.2 Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

#### **Components:**

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

#### 12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: Product does not contain substances which are

persistent, bioaccumulative, and toxic (PBT) at levels of 0.1%

or higher.

Product does not contain substances which are very

persistent and very bioaccumulative (vPvB) at levels of 0.1%

or higher.

**Components:** 

propane:



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

Partition coefficient: n-

octanol/water

: log Pow: 2,36

butane:

Partition coefficient: n- : log Pow: 2,89

octanol/water Method: OECD Test Guideline 107

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Partition coefficient: n-

octanol/water

: log Pow: > 2

#### 12.4 Mobility in soil

**Product:** 

Mobility : Remarks: No data available

Distribution among : Remarks: No data available

environmental compartments

## 12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

#### **Components:**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 2% aromatics:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

# 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

#### 12.7 Other adverse effects

**Product:** 

Additional ecological

information

: No information on ecology is available.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04\*\*, gases in pressure containers (including halons)

containing hazardous substances

# **SECTION 14: Transport information**

#### 14.1 UN number or ID number

 ADR
 : UN 1950

 RID
 : UN 1950

 IMDG
 : UN 1950

 IATA
 : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

#### 14.3 Transport hazard class(es)

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

**RID** 

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

**IMDG** 

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

rid

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

Version Date of last issue: 20.12.2022 **Revision Date:** Print Date: 21.03.2024 Date of first issue: 06.06.2016 21.03.2024 2.4

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

: Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern

(Regulation (EC) No

1907/2006 (REACH), Article 57).

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

(EC 1005/2009)

Not applicable

Regulation (EU) 2019/1021 on persistent organic

pollutants (recast)

(EU POP)

: Not applicable

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and

import of dangerous chemicals

(EU PIC)

Not applicable

Regulation (EU) 2019/1148 on the marketing and use of : Not applicable

explosives precursors

P2

34

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Petroleum products: (a) gasolines

a brand of **TREUDENBERG** 

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

18 Liquefied flammable gases (including LPG) and natural gas

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 83,88 %

# Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

# 15.2 Chemical safety assessment

This information is not available.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

EUH066 : Repeated exposure may cause skin dryness or cracking.

H220 : Extremely flammable gas.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H317 : May cause an allergic skin reaction.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Note C : Some organic substances may be marketed either in a

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



<b>OKS 601</b>	OKS 601				
Version 2.4	Revision Date: 21.03.2024	Date of last issue: 20.12.2022 Date of first issue: 06.06.2016	Print Date: 21.03.2024		
specific isomeric form or as a mixture of several this case the supplier must state on the label wh substance is a specific isomer or a mixture of isomerical substance is a specific and as a carcinogen a it can be shown that the substance contains less dimethyl sulphoxide extract as measured by IP 3 ("Determination of polycyclic aromatics in unused base oils and asphaltene free petroleum fraction sulphoxide extraction refractive index method"Instead Petroleum, London), in which case a classification		te on the label whether the or a mixture of isomers. as a carcinogen applies unless ance contains less than 3 % of measured by IP 346 romatics in unused lubricating petroleum fractions - Dimethyle index method "Institute of case a classification in			
Note F		case a classification in accordance Regulation shall be performed Where the substance is not cla	as a carcinogen or mutagen that the substance contains Einecs No 200-753-7), in which ance with Title II of this also for those hazard classes. assified as a carcinogen or onary statements (P102-)P260-		
Note (	J (table 3.1)	: When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved g The group depends on the physical state in which the gas packaged and therefore has to be assigned case by case. following codes are assigned: Press. Gas (Comp.) Press. (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shot be classified as gases under pressure (See Annex I, Pag., Section 2.3.2.1, Note 2).			
PT OF	ΞL		at the Workplace - Occupational ents		
	EL / VLE-MP EL / VLE_CD	<ul><li>: Time Weighted Average</li><li>: Short Term Exposure Limit</li></ul>			

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice: IARC - International Agency for Research on Cancer: IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



**OKS 601** 

VersionRevision Date:Date of last issue: 20.12.2022Print Date:2.421.03.2024Date of first issue: 06.06.201621.03.2024

International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

#### Classification of the mixture:

#### Classification procedure:

Aerosol 1 H222, H229 Asp. Tox. 1 H304 Based on product data or assessment Based on product data or assessment

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.