according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 670 含白色固体润滑剂的高性能润滑油

Chemical nature : Mineral oil.

solid lubricant

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

responsible for the SDS

mcm@oks-germany.com

National contact

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)

+86 21 69225521

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance : liquid Colour : beige

Odour : hydrocarbon-like

Combustible liquid. May be fatal if swallowed and enters airways. Causes mild skin irritation.

GHS Classification

Flammable liquids : Category 4

Skin irritation : Category 3

Aspiration hazard : Category 1

GHS label elements

1/26

according to GB/T 16483 and GB/T 17519 CN



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Hazard pictograms :

Signal word : Danger

Hazard statements : H227 Combustible liquid.

H304 May be fatal if swallowed and enters airways.

H316 Causes mild skin irritation.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P280 Wear protective gloves/ protective clothing/ eye

protection/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/

attention

P370 + P378 In case of fire: Use alcohol-resistant foam, carbon

dioxide or water mist to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

Disposal:

P501 Dispose of contents/containers according the local

government requirements.

Physical and chemical hazards

Combustible liquid.

Health hazards

Causes mild skin irritation. May be fatal if swallowed and enters airways.

Environmental hazards

Not classified based on available information.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 50 -< 70
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 10 -< 20
Distillates (petroleum), solvent-dewaxed heavy paraffinic	64742-65-0	>= 1 -< 10
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 1 -< 10
lithium 12-hydroxystearate	7620-77-1	>= 1 -< 10
Sulfonic acids, petroleum, calcium salts	61789-86-4	>= 1 -< 10

4. FIRST AID MEASURES

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.

Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause

damage.

Most important symptoms : Can be absorbed through skin.



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

and effects, both acute and

delayed

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Notes to physician Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

Hazardous combustion

products

Carbon oxides

Nitrogen oxides (NOx)

Sulphur oxides Metal oxides

Specific extinguishing

methods

Standard procedure for chemical fires.

Cool containers/tanks with water spray.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas.

Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition. Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions

Try to prevent the material from entering drains or water

courses.

Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

local / national regulations (see section 13).

Non-sparking tools should be used.

7. HANDLING AND STORAGE

Handling

Advice on protection against :

fire and explosion

Keep away from heat and sources of ignition.

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Take precautionary measures against static discharges. Wash hands and face before breaks and immediately after

handling the product.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not enter areas where used or stored until adequately

ventilated. Do not repack.

Do not re-use empty containers.

These safety instructions also apply to empty packaging which

may still contain product residues.

Keep container closed when not in use.

Avoidance of contact : Oxidizing agents

Storage

Conditions for safe storage : Store in original container.

Keep container closed when not in use. Keep in a dry, cool and well-ventilated place.

Do not store together with oxidizing and self-igniting products. Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with the particular national regulations.

Keep in properly labelled containers.



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH (2013-03-01)
Distillates (petroleum), solvent- dewaxed heavy paraffinic	64742-65-0	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH (2013-03-01)
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Inhalable particulate matter)	5 mg/m3	ACGIH (2013-03-01)
lithium 12-hydroxystearate	7620-77-1	TWA (Inhalable particulate matter)	10 mg/m3	ACGIH (2018-03-20)
		TWA (Respirable particulate matter)	3 mg/m3	ACGIH (2018-03-20)

Engineering measures : Effective exhaust ventilation system

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Filter type A-P

Eye/face protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends



according to GB/T 16483 and GB/T 17519 CN



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : beige

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : Not applicable

substance/mixture is non-polar/aprotic

Melting point/range : No data available

Boiling point/boiling range : 200 °C

(1,013 hPa)

Flash point : 64 °C

Method: DIN 51758, Pensky-Martens closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

7.0 %(V)

Lower explosion limit / Lower : 0.6 %(V)

according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

flammability limit

Vapour pressure : < 1,100 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0.8223 (20 °C)

Reference substance: Water The value is calculated

Density : 0.82 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 18 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

: No dangerous reaction known under conditions of normal use.



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

cause defatting resulting in drying, redness and possible

blistering.

Symptoms: Skin disorders

Components:

Naphtha (petroleum), hydrotreated heavy:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

lithium 12-hydroxystearate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 3,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : Mild skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

lithium 12-hydroxystearate:

Assessment : No skin irritation

Method : OECD Test Guideline 439

Result : No skin irritation

according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Serious eye damage/eye irritation

Product:

Remarks : This information is not available.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

lithium 12-hydroxystearate:

Species : Rabbit

Result : No eye irritation Assessment : No eye irritation

Method : OECD Test Guideline 405

according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Naphtha (petroleum), hydrotreated heavy:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

Distillates (petroleum), hydrotreated heavy paraffinic:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

lithium 12-hydroxystearate:

Exposure routes : Dermal Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Sulfonic acids, petroleum, calcium salts:



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Assessment : The product is a skin sensitiser, sub-category 1B.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated heavy:

Germ cell mutagenicity - : Tests

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow Application Route: Intraperitoneal injection

Method: OECD Test Guideline 474

Result: negative

according to GB/T 16483 and GB/T 17519 CN



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Germ cell mutagenicity -

Tests on bacterial or mammalian cell cultures did not show

Assessment

mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

Naphtha (petroleum), hydrotreated heavy:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

Distillates (petroleum), hydrotreated heavy paraffinic:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Mouse Application Route : Dermal

Method : OECD Test Guideline 451

Result : negative

Distillates (petroleum), hydrotreated heavy naphthenic:

Carcinogenicity - : Not classifiable as a human carcinogen.

Assessment

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal : Remarks: No data available

development

Components:

Naphtha (petroleum), hydrotreated heavy:

Reproductive toxicity - : - Fertility -

Assessment No toxicity to reproduction

according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

- Teratogenicity -

No toxicity to reproduction

Distillates (petroleum), hydrotreated heavy paraffinic:

Reproductive toxicity - : - Fertility -

Assessment No toxicity to reproduction

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on foetal : Species: Rat

development Application Route: Dermal

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 30 mg/kg body weight

Method: OECD Test Guideline 414

Distillates (petroleum), hydrotreated heavy naphthenic:

Effects on foetal : Species: Rat

development Application Route: Dermal

General Toxicity Maternal: LOAEL: 125 mg/kg body weight Teratogenicity: NOAEL: >= 2,000 mg/kg body weight

Developmental Toxicity: NOAEL: >= 2,000 mg/kg body weight Embryo-foetal toxicity: NOAEL: >= 2,000 mg/kg body weight

Method: OECD Test Guideline 414

Result: No effects on fertility and early embryonic

development were detected.

Reproductive toxicity -

Fertility -

Assessment

No toxicity to reproduction

- Teratogenicity -

No toxicity to reproduction

STOT - single exposure

Product:

Remarks : No data available

Components:

Naphtha (petroleum), hydrotreated heavy:

Assessment : The substance or mixture is not classified as specific target

according to GB/T 16483 and GB/T 17519 CN



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

organ toxicant, single exposure.

Distillates (petroleum), hydrotreated heavy naphthenic:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Product:

Remarks : No data available

Components:

Naphtha (petroleum), hydrotreated heavy:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

Distillates (petroleum), hydrotreated heavy naphthenic:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated heavy:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated heavy paraffinic:

No aspiration toxicity classification



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

No aspiration toxicity classification

Distillates (petroleum), hydrotreated heavy naphthenic:

No aspiration toxicity classification

Further information

Product:

Remarks Information given is based on data on the components and

the toxicology of similar products.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Remarks: No data available Toxicity to microorganisms

Components:

Naphtha (petroleum), hydrotreated heavy:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h

aquatic invertebrates

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

according to GB/T 16483 and GB/T 17519

CN



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Toxicity to daphnia and other : NOEC (Daphnia magna (Water flea)): 10 mg/l

aquatic invertebrates

Exposure time: 21 d

(Chronic toxicity)

Distillates (petroleum), hydrotreated heavy naphthenic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

LC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

NOELR (Oncorhynchus mykiss (rainbow trout)): >= 1,000 mg/l

Exposure time: 28 d

Remarks: The value is calculated

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

NOELR (Daphnia magna (Water flea)): 10 mg/l

Exposure time: 21 d

Test Type: Reproduction Test Method: OECD Test Guideline 211

lithium 12-hydroxystearate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): > 160

according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

plants mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 160

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability : aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

Distillates (petroleum), hydrotreated heavy naphthenic:

Biodegradability : aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Method: OECD Test Guideline 301B

GLP: yes

lithium 12-hydroxystearate:

Biodegradability : Primary biodegradation

Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: 74.7 % Exposure time: 28 d

Method: OECD Test Guideline 301C

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

Distillates (petroleum), hydrotreated heavy paraffinic:

Partition coefficient: n-

octanol/water

: log Pow: > 2

lithium 12-hydroxystearate:

Partition coefficient: n-

octanol/water

log Pow: 2.6

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among : Remarks:

environmental compartments

: Remarks: No data available

Other adverse effects

Product:

Additional ecological

information

: No information on ecology is available.



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Components:

Naphtha (petroleum), hydrotreated heavy:

Results of PBT and vPvB : Non-classified PBT substance Non-classified vPvB substance

assessment

Distillates (petroleum), hydrotreated heavy paraffinic:

Results of PBT and vPvB : Non-classified vPvB substance Non-classified PBT substance

assessment

Distillates (petroleum), hydrotreated heavy naphthenic:

Results of PBT and vPvB : Non-classified PBT substance Non-classified vPvB substance

assessment

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of waste product or used containers according to

local regulations.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Packing group : Not applicable Labels : Not applicable Packing instruction (cargo : Not applicable

aircraft)

Packing instruction : Not applicable

(passenger aircraft)

IMDG-Code

UN number Not applicable Proper shipping name Not applicable Not applicable Class Not applicable Subsidiary risk Packing group Not applicable Labels Not applicable **EmS Code** Not applicable Not applicable Marine pollutant

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Not applicable

Hazardous Chemicals for Priority Management under : Not applicable

SAWS

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not applicable



according to GB/T 16483 and GB/T 17519



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

and Export

International Regulations

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / TWA : 8-hour, time-weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the

according to GB/T 16483 and GB/T 17519 CN



OKS 670 含白色固体润滑剂的高性能润滑油

Version Revision Date: Date of last issue: 2023-01-24

3.4 2024-02-22 Date of first issue: 2014-04-15 Print Date: 2024-02-22

Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.