

OKS 5500

Lever Grease Gun

Description

Lever grease gun with press barrel made of steel for 400 ml grease cartridge or 500 ml loose grease.

Applications

- Grease lubrication of all important parts
- Maintenance of mechanical and industrial machines

Branches

- Catering equipment and food processing technology
- Plant and machine (tool) engineering
- Paper and packaging industry
- Chemical industry
- Rail vehicle technology
- Municipal services
- Glass and foundry industry
- Maintenance and servicing
- Iron and steel industry
- Logistics
- Rubber and plastic processing
- Shipbuilding and marine technology

Advantages and benefits

- Long and strong hand lever with plastic grip
- Grease press barrel smooth and without internal profiling
- Stable grip at the plunger rod that prevents bruising
- Grease press barrel and rear cover form a unit (in order to prevent accidents)
- Limit stop for the plunger rod
- Mounting of firm nozzle tubes easily possible
- Suitable for grease up to NLGI 3

Application tips

1. To replace the grease cartridge screw off the press barrel 2. Pull the rod back into the end position 3. Insert the open cartridge into the press barrel. Pull off the bottom beforehand 4. Screw in the press barrel and relieve the rod 5. Press the clamping lever and slide the rod back into the press barrel 6. Vent by pressing the vent valve

Technical data

	Standard	Conditions	Unit	Value
Product specific technical data				
Operating pressure			bar	400
Empty weight			g	1,250
Output			cm³/stroke	approx. 1.9
Press barrel of steel Ø	DIN 1283		mm	56

OKS Spezialschmierstoffe GmbH

Ganghoferstraße 47
 82216 Maisach
 ☎ +49 8142 3051 - 500
 ✉ info@oks-germany.com
 🏠 www.oks-germany.com

a brand of

FREUDENBERG

The information in this publication reflects state-of-the-art technology, as well as extensive testing and experience. Due to the diversity of possible applications and technical realities, they can only serve as recommendations and are not arbitrarily transferable. Therefore, no obligations, liability or warranty claims can be derived from them. We only accept liability for the suitability of our products for particular purposes, and for certain properties of our products, in the event that we have accepted such liability in writing in the individual case. Any case of justified warranty claims shall be limited to the delivery of replacement goods free of defects, in the event that this subsequent improvement fails, to reimbursement of the purchase price. Any and all further claims, in particular the liability for consequential injuries or damage, shall always be excluded. Prior to use, the customer must conduct its own testing to prove suitability. The data are subject to change for the sake of progress. ® = Registered trademark
Product restricted to professional users. Safety data sheet available for download at www.oks-germany.com
 Our Customer and Technical service will be pleased to help should you have any further questions.