



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

1. Identification of the substance/mixture and of the company/undertaking

Product information

Product name : OKS 111

Use of the Substance/Mixture : Lubricant spray

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599

E-mail address : mcm@oks-germany.com
National contact :
Emergency telephone number : +7 495 628 1687
+49 8142 3051 517

2. Hazards identification

GHS Classification

: Aerosols, Category 1
Skin irritation, Category 2
Specific target organ toxicity - single exposure, Category 3, Central nervous system
Aspiration hazard, Category 1
Chronic aquatic toxicity, Category 2

GHS-Labeling

Symbol(s) :    

Signal word : Danger

Hazard statements : H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H411: Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

3. Composition/information on ingredients

Chemical nature : Active agent with propellant and solvent.
Wax

Hazardous components

Chemical name	CAS-No.	Concentration[%]
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics		30 - 50
Butane	106-97-8	20 - 30
molybdenum disulphide	1317-33-5	10 - 20
propane	74-98-6	1 - 10
Isobutane	75-28-5	1 - 10

4. First aid measures

If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash skin thoroughly with soap and water or use recognized skin cleanser.



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If easy to do, remove contact lens, if worn.
Seek medical advice.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

Notes to physician

- Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

- Risks : Central nervous system depression
Can be absorbed through skin.
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.

- Treatment : Treat symptomatically.

5. Firefighting measures

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire may cause evolution of:
Carbon oxides
Metal oxides
Sulphur oxides



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

- Special protective equipment for firefighters
- Further information
- : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
 - : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
In the case of respirable dust and/or fumes, use self-contained breathing apparatus.
Exposure to decomposition products may be a hazard to health.
 - : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

6. Accidental release measures

- Personal precautions
- Environmental precautions
- Methods for cleaning up
- Additional advice
- : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
 - : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
 - : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.
 - : Only qualified personnel equipped with suitable protective equipment may intervene.

7. Handling and storage

Handling

- Advice on safe handling
- : Do not use in areas without adequate ventilation.



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

Do not breathe vapours or spray mist.
 In case of insufficient ventilation, wear suitable respiratory equipment.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Keep away from fire, sparks and heated surfaces.
 Smoking, eating and drinking should be prohibited in the application area.
 Wash hands and face before breaks and immediately after handling the product.
 Do not get in eyes or mouth or on skin.
 Do not get on skin or clothing.
 Do not ingest.
 Do not use sparking tools.
 These safety instructions also apply to empty packaging which may still contain product residues.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Storage

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
 Store in accordance with the particular national regulations.

8. Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Butane	106-97-8	MPC-TWA	300 mg/m ³	2011-07-12	RU OEL
Butane	106-97-8	MPC-STEL	900 mg/m ³	2011-07-12	RU OEL
molybdenum disulphide	1317-33-5	MPC-TWA	1 mg/m ³	2011-07-12	RU OEL
molybdenum disulphide	1317-33-5	MPC-STEL	6 mg/m ³	2011-07-12	RU OEL
molybdenum disulphide	1317-33-5	MPC-TWA	1 mg/m ³	2013-09-16	RU OEL



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

molybdenum disulphide	1317-33-5	MPC- STEL	6 mg/m3	2013-09-16	RU OEL
propane	74-98-6	MPC- TWA	300 mg/m3	2013-09-16	RU OEL
propane	74-98-6	MPC- STEL	900 mg/m3	2013-09-16	RU OEL
Isobutane	75-28-5	MPC- TWA	300 mg/m3	2013-09-16	RU OEL
Isobutane	75-28-5	MPC- STEL	900 mg/m3	2013-09-16	RU OEL

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Short term only
Filter type A-P

- Hand protection : Nitrile rubber
Manufacturer, importer, supplier: Class 1
Wear protective gloves.
The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.
The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

- Eye protection : Safety glasses with side-shields conforming to EN166

- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

concentration and amount of dangerous substances, and to the specific work-place.

9. Physical and chemical properties

Appearance

Physical state : aerosol
Colour : black
Odour : characteristic

Safety data

Flash point : -60 °C
Method: Abel-Pensky
Ignition temperature : Remarks: No data available
Lower explosion limit : 0,9 %(V)
Upper explosion limit : 10,9 %(V)
Flammability (solid, gas) : Extremely flammable aerosol.
Oxidizing properties : Note: No data available
Auto-ignition temperature : Note: No data available
pH : Note: Not applicable
Melting point/range : Note: No data available
Boiling point/boiling range : -161 °C
at 1.013,00 hPa
Sublimation point : Note: No data available
Vapour pressure : 3.800,00 hPa
at 20 °C
Density : 0,77 g/cm³
at 20 °C
Bulk density : Note: No data available
Water solubility : Note: insoluble



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

- Partition coefficient: n-octanol/water : Note: No data available
- Solubility in other solvents : Note: No data available
- Viscosity, dynamic : Note: No data available
- Viscosity, kinematic : < 20,5 mm²/s at 40 °C
- Relative vapour density : Note: No data available
- Evaporation rate : Note: No data available

10. Stability and reactivity

- Conditions to avoid : Heat, flames and sparks.
- Materials to avoid : Oxidizing agents
- Hazardous decomposition products : No decomposition if stored and applied as directed.
- Thermal decomposition : Note: No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

- Acute oral toxicity :
Remarks: Effects due to ingestion may include:
:
Symptoms: Central nervous system depression
- Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.
:
Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression
- Acute dermal toxicity :
Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.
:
Symptoms: Redness, Local irritation, Skin disorders



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

Skin corrosion/irritation

Skin irritation : Remarks: Irritating to skin.

Serious eye damage/eye irritation

Eye irritation : Remarks: Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Sensitisation : Remarks: This information is not available.

Germ cell mutagenicity

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Germ cell mutagenicity

Remarks
molybdenum disulphide : Animal testing did not show any mutagenic effects.

Carcinogenicity

Remarks
molybdenum disulphide : No evidence of carcinogenicity in animal studies.

Target Organ Systemic Toxicant - Single exposure

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics : Remarks: May cause drowsiness or dizziness.
molybdenum disulphide : Remarks: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Target Organ Systemic Toxicant - Repeated exposure

: This information is not available.

Target Organ Systemic Toxicant - Repeated exposure

molybdenum disulphide : Remarks: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Aspiration toxicity : May be fatal if swallowed and enters airways.
: May be fatal if swallowed and enters airways.

Further information : Ingestion causes irritation of upper respiratory system and



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

gastrointestinal disturbance.

12. Ecological information

Ecotoxicity effects

- Toxicity to fish :
Remarks:
Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

- Toxicity to daphnia and other aquatic invertebrates : Remarks:
No data available

- Toxicity to algae : Remarks:
No data available

- Toxicity to bacteria : Remarks:
No data available

Elimination information (persistence and degradability)

- Bioaccumulation : Remarks:
This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

- Mobility : Remarks:
No data available

- Distribution among environmental compartments : Remarks:
No data available

- Biodegradability : Remarks:
No data available

- Physico-chemical removability : Remarks:
No data available

Further information on ecology



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics :

Chronic aquatic toxicity
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics : Toxic to aquatic life with long lasting effects.
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics :
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics :
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics :
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics :
Additional ecological information : Toxic to aquatic life with long lasting effects.

13. Disposal considerations

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

14. Transport information

ADR

UN number : 1950

Description of the goods : AEROSOLS

Class : 2

Classification Code : 5F

Labels : 2.1

Environmentally hazardous : yes



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

IATA

UN number : 1950
Description of the goods : Aerosols, flammable
Class : 2.1
Labels : 2.1
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203
Packing instruction (passenger aircraft) : Y203
Environmentally hazardous : no

IMDG

UN number : 1950
Description of the goods : AEROSOLS
(Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics)
Class : 2.1
Labels : 2.1
EmS Number : F-D, S-U
Marine pollutant : no
Other information : No special precautions required.



OKS 111

Version 1.4

Revision Date 31.07.2018

Print Date 31.07.2018

15. Regulatory information

16. Other information

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety datasheet applies only to products originally packaged and labelled by OKS Spezialschmierstoffe. The information contained therein is protected by copyright and must not be reproduced or amended without the express written approval of OKS Spezialschmierstoffe. This document may be passed on only to the extent required by law. Any dissemination of our safety datasheets (e.g. as a document for download from the Internet) beyond this legally required extent is not permitted without express written consent. OKS Spezialschmierstoffe provides its customers with amended safety datasheets as prescribed by law. The customer is responsible for passing on safety datasheets and any amendments contained therein to its own customers, employees and other users of the product. OKS Spezialschmierstoffe provides no guarantee that safety datasheets received by users from third parties are up-to-date. All information and instructions in this safety datasheets were compiled to the best of our knowledge and are based on the information available to us. The data provided are intended to describe the product in relation to the required safety measures; they are neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and do not justify any contractual legal relationships.