

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

### 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 1301

Chemical nature : Active substance with propellant  
silicone oil

#### Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599  
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com  
Material Compliance Management

National contact :

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)  
+86 21 69225521

#### Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Restricted to professional users.

### 2. HAZARDS IDENTIFICATION

#### Emergency Overview

<b>Appearance</b>	: aerosol
<b>Colour</b>	: colourless
<b>Odour</b>	: characteristic

Extremely flammable aerosol. Pressurised container: May burst if heated. Causes skin irritation.  
May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.

#### GHS Classification

Aerosols : Category 1

Skin irritation : Category 2

Specific target organ toxicity - : Category 3 (Narcotic effects)

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5    Revision Date: 2023-07-10    Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06    Print Date: 2023-07-10

single exposure

Short-term (acute) aquatic hazard : Category 2

Long-term (chronic) aquatic hazard : Category 2

### GHS label elements

Hazard pictograms :   

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/ sparks/ open flames/ hot surfaces.  
No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P261 Avoid breathing mist.  
P264 Wash skin thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves.

#### Response:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P304 + P340 + P312 IF INHALED: Remove person to fresh air  
and keep comfortable for breathing. Call a POISON CENTER/  
doctor if you feel unwell.  
P332 + P313 If skin irritation occurs: Get medical advice/  
attention.  
P362 + P364 Take off contaminated clothing and wash it before  
reuse.

#### Storage:

P403 + P233 Store in a well-ventilated place. Keep container  
tightly closed.  
P405 Store locked up.  
P410 + P412 Protect from sunlight. Do not expose to  
temperatures exceeding 50 °C/ 122 °F.

#### Disposal:

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

P501 Dispose of contents/containers according to the local government requirements.

### Physical and chemical hazards

Extremely flammable aerosol. Pressurised container: May burst if heated.

### Health hazards

Causes skin irritation. May cause drowsiness or dizziness.

### Environmental hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

### Other hazards which do not result in classification

None known.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 50 -< 70
Butane	106-97-8	>= 20 -< 30
propane	74-98-6	>= 1 -< 10
Isobutane	75-28-5	>= 1 -< 10
n-Butyl acetate	123-86-4	>= 2.5 -< 10
n-hexane	110-54-3	>= 2.5 -< 3

## 4. FIRST AID MEASURES

- If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.  
Wash off immediately with plenty of water.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.
- Most important symptoms and effects, both acute and delayed : Central nervous system depression  
Causes skin irritation.  
Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema
- Notes to physician : Treat symptomatically.

---

## 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Carbon oxides  
Metal oxides
- Specific extinguishing methods : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.  
Exposure to decomposition products may be a hazard to

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

health.

### 6. ACCIDENTAL RELEASE MEASURES

- |   |   |  |
|---|---|--|
| Personal precautions, protective equipment and emergency procedures | : | Evacuate personnel to safe areas.<br>Ensure adequate ventilation.<br>Remove all sources of ignition.<br>Do not breathe vapours or spray mist.<br>Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.<br>Refer to protective measures listed in sections 7 and 8.   |
| Environmental precautions   | : | Do not allow contact with soil, surface or ground water.<br>Prevent further leakage or spillage if safe to do so.<br>If the product contaminates rivers and lakes or drains inform respective authorities.   |
| Methods and materials for containment and cleaning up               | : | Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).<br>Keep in suitable, closed containers for disposal.<br>Non-sparking tools should be used. |
| Prevention of secondary hazards                                     | : | Only qualified personnel equipped with suitable protective equipment may intervene.  |

### 7. HANDLING AND STORAGE

#### Handling

- |                         |   |  |
|-------------------------|---|--|
| Advice on safe handling | : | Do not use in areas without adequate ventilation.<br>Do not breathe vapours or spray mist.<br>In case of insufficient ventilation, wear suitable respiratory equipment.<br>Avoid contact with skin and eyes.<br>For personal protection see section 8.<br>Keep away from fire, sparks and heated surfaces.<br>Smoking, eating and drinking should be prohibited in the application area.<br>Wash hands and face before breaks and immediately after handling the product.<br>Do not get in eyes or mouth or on skin.<br>Do not get on skin or clothing.<br>Do not ingest.<br>Do not use sparking tools.<br>These safety instructions also apply to empty packaging which may still contain product residues. |
|-------------------------|---|--|

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5    Revision Date: 2023-07-10    Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06    Print Date: 2023-07-10

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Avoidance of contact : Oxidizing agents

### Storage

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Store in accordance with the particular national regulations.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	STEL	1,000 ppm	ACGIH (2018-03-20)
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH (2018-03-20)
n-Butyl acetate	123-86-4	PC-TWA	200 mg/m <sup>3</sup>	CN OEL (2019-08-27)
		PC-STEL	300 mg/m <sup>3</sup>	CN OEL (2019-08-27)
		TWA	50 ppm	ACGIH (2017-03-01)
		STEL	150 ppm	ACGIH (2017-03-01)
n-hexane	110-54-3	PC-TWA	100 mg/m <sup>3</sup>	CN OEL (2019-08-27)
	Further information: Skin			
		PC-STEL	180 mg/m <sup>3</sup>	CN OEL (2019-08-27)
	Further information: Skin			
		TWA	50 ppm	ACGIH (2007-01-01)

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
n-hexane	110-54-3	2,5-hexanedion	Urine	After shift	4 mg/l	CN BEI (2019-08-

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5    Revision Date: 2023-07-10    Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06    Print Date: 2023-07-10

		e				27)
		2,5-hexanedione	Urine	After shift	35 micromol per litre	CN BEI (2019-08-27)
		2,5-Hexanedione	Urine	End of shift	0.5 mg/l	ACGIH BEI (2020-02-01)

**Engineering measures** : Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

**Respiratory protection** : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
Short term only

Filter type : Filter type A-P

**Eye/face protection** : Safety glasses with side-shields

**Skin and body protection** : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

### Hand protection

Material : butyl-rubber  
Break through time : > 10 min  
Protective index : Class 1

**Remarks** : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

**Protective measures** : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Hygiene measures** : Wash face, hands and any exposed skin thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

Colour	:	colourless
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/range	:	No data available
Boiling point/boiling range	:	No data available
Flash point	:	-60.00 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Self-ignition	:	not auto-flammable
Upper explosion limit / Upper flammability limit	:	8.5 %(V)
Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapour pressure	:	<= 2,500 hPa (20 °C)
Relative vapour density	:	No data available
Relative density	:	0.66 (20 °C) Reference substance: Water The value is calculated
Density	:	0.66 g/cm <sup>3</sup> (20 °C)
Bulk density	:	No data available
Solubility(ies)		
Water solubility	:	partly miscible
Solubility in other solvents	:	No data available



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : < 7 mm<sup>2</sup>/s ( 40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

## 10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.  
Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No decomposition if stored and applied as directed.

## 11. TOXICOLOGICAL INFORMATION

### Acute toxicity

#### Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.  
Harmful by inhalation.

Symptoms: Inhalation may provoke the following symptoms:  
Respiratory disorder, Dizziness, Drowsiness, Vomiting,  
Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

### Components:

#### **Naphtha (petroleum), hydrotreated light:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 25.2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute  
inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes  
Assessment: The substance or mixture has no acute dermal  
toxicity

#### **Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

#### **Isobutane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

#### **n-Butyl acetate:**

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

- Acute oral toxicity : LD50 (Rat): 10,768 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 21 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 17,600 mg/kg
- n-hexane:**
- Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401
- Acute inhalation toxicity : LC50 (Rat): 259.35 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403
- Acute dermal toxicity : LD50 (Rabbit): 3,350 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Skin corrosion/irritation

#### Product:

Remarks : Irritating to skin.

#### Components:

##### **Naphtha (petroleum), hydrotreated light:**

Species : Rabbit  
Assessment : Irritating to skin.  
Method : OECD Test Guideline 404  
Result : Irritating to skin.  
GLP : yes

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

### **n-Butyl acetate:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : Repeated exposure may cause skin dryness or cracking.

### **n-hexane:**

Species : Rabbit  
Assessment : Irritating to skin.  
Method : OECD Test Guideline 404  
Result : Irritating to skin.

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks : Contact with eyes may cause irritation.

#### **Components:**

##### **Naphtha (petroleum), hydrotreated light:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

##### **n-Butyl acetate:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
GLP : yes

##### **n-hexane:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation  
Method : OECD Test Guideline 405

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

### Respiratory or skin sensitisation

#### Product:

Remarks : This information is not available.

#### Components:

##### **Naphtha (petroleum), hydrotreated light:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

##### **n-Butyl acetate:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

##### **n-hexane:**

Species : Mouse  
Assessment : Does not cause skin sensitisation.  
Result : Does not cause skin sensitisation.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

##### **n-Butyl acetate:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Method: OECD Test Guideline 471  
Result: negative

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

Test Type: Chromosome aberration test in vitro  
Test system: Chinese hamster cells  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Species: Mouse  
Application Route: Oral  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity - Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

### Carcinogenicity

#### Product:

Remarks : No data available

#### Components:

##### **n-Butyl acetate:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### Components:

##### **n-Butyl acetate:**

Effects on fertility : Test Type: Two-generation study  
Species: Rat  
Application Route: inhalation (vapour)  
General Toxicity - Parent: NOAEC: 750 mg/l  
General Toxicity F1: NOAEC: 750 mg/l  
General Toxicity F2: NOAEC: 750 mg/l

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

Method: OECD Test Guideline 416  
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Reproductive toxicity - Assessment : - Fertility -  
No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.  
- Teratogenicity -  
No toxicity to reproduction

**n-hexane:**  
Reproductive toxicity - Assessment : - Fertility -  
Suspected human reproductive toxicant

### STOT - single exposure

**Product:**  
Remarks : No data available

### Components:

#### **Naphtha (petroleum), hydrotreated light:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : May cause drowsiness or dizziness.

#### **n-Butyl acetate:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

#### **n-hexane:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

### STOT - repeated exposure

#### Product:

Remarks : No data available

#### Components:

##### **n-Butyl acetate:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### **n-hexane:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

### Repeated dose toxicity

#### Product:

Remarks : This information is not available.

#### Components:

##### **n-Butyl acetate:**

Species : Rat  
NOAEL : 125 mg/kg  
Application Route : Oral

### Aspiration toxicity

#### Product:

This information is not available.

#### Components:

##### **Naphtha (petroleum), hydrotreated light:**

May be fatal if swallowed and enters airways.



# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

### **n-Butyl acetate:**

No aspiration toxicity classification

### **n-hexane:**

May be fatal if swallowed and enters airways.

### **Further information**

#### **Product:**

Remarks : Risks of irreversible effects after a single exposure.  
Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

---

## 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

#### **Product:**

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

#### **Components:**

##### **Naphtha (petroleum), hydrotreated light:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Test Type: static test

### Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### n-Butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Test Type: flow-through test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 44 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l  
Exposure time: 72 h  
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 23 mg/l  
Exposure time: 21 d  
Test Type: Reproduction Test  
GLP: yes

Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h  
Test Type: Growth inhibition

### n-hexane:

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 12.51 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 21.85 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): 9.285 mg/l  
Exposure time: 72 h

### Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

#### Components:

##### **Naphtha (petroleum), hydrotreated light:**

Biodegradability : aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 90.35 %  
Exposure time: 28 d

##### **n-Butyl acetate:**

Biodegradability : Primary biodegradation  
Result: rapidly biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **n-hexane:**

Biodegradability : aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 21 %  
Exposure time: 28 d  
GLP: yes

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

### Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

#### Components:

##### **Naphtha (petroleum), hydrotreated light:**

Partition coefficient: n-octanol/water : log Pow: 3.4 - 5.2

##### **Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.89  
Method: OECD Test Guideline 107

##### **propane:**

Partition coefficient: n-octanol/water : log Pow: 2.36

##### **Isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.88  
Method: OECD Test Guideline 107

##### **n-Butyl acetate:**

Partition coefficient: n-octanol/water : log Pow: 2.3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

##### **n-hexane:**

Bioaccumulation : Bioconcentration factor (BCF): 501.19

Partition coefficient: n-octanol/water : log Pow: 4 (20 °C)  
pH: 7

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

### Mobility in soil

#### Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

### Other adverse effects

#### Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

#### Components:

##### **n-Butyl acetate:**

Results of PBT and vPvB assessment : Non-classified PBT substance Non-classified vPvB substance

---

## 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

---

## 14. TRANSPORT INFORMATION

### International Regulations

#### **UNRTDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

#### **IATA-DGR**

UN/ID No. : UN 1950

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

### IMDG-Code

UN number : UN 1950  
Proper shipping name : AEROSOLS  
(naphtha (petroleum), hydrotreated light)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : yes

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

### National Regulations

#### GB 6944/12268

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 15. REGULATORY INFORMATION

### National regulatory information

#### Law on the Prevention and Control of Occupational Diseases

#### Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Not applicable

#### Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code	Chemical name / Category	Threshold quantity
W3	Aerosols	150 t

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

Hazardous Chemicals for Priority Management under SAWS : Not applicable

### Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import and Export : Not applicable

### International Regulations

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

### The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

## 16. OTHER INFORMATION

Date format : yyyy/mm/dd

### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)  
CN BEI : China. Biological Occupational Exposure Indices  
CN OEL : Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
CN OEL / PC-TWA : Permissible concentration - time weighted average  
CN OEL / PC-STEEL : Permissible concentration - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory

# SAFETY DATA SHEET

according to GB/T 16483 and GB/T 17519  
CN



## OKS 1301

Version 1.5      Revision Date: 2023-07-10      Date of last issue: 2023-02-02  
Date of first issue: 2014-05-06      Print Date: 2023-07-10

---

concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

### Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.