

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 1301

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricant

Recommended restrictions : Restricted to professional users.
on use

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599
info@oks-germany.com

E-mail address of person : mcm@oks-germany.com
responsible for the SDS Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone num- : CIAV - Information Centre of Antipoison
ber (+351) 800 250 250 (free 24/7 service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.
posure, Category 3, Central nervous
system

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)






OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

Long-term (chronic) aquatic hazard, Category 2 H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :   

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P261 Avoid breathing mist.
P273 Avoid release to the environment.

Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

n-butyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version 1.3 Revision Date: 02.02.2023 Date of last issue: 28.09.2021 Print Date: 02.02.2023
Date of first issue: 21.06.2016

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active substance with propellant
silicone oil

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6 01-2119475514-35-XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 50 - < 70
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 1 - < 10
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	Flam. Liq.3; H226 STOT SE3; H336; EUH066		>= 1 - < 10
Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 20 - < 30
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash off immediately with plenty of water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema
- Risks : Central nervous system depression
Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Metal oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version 1.3 Revision Date: 02.02.2023 Date of last issue: 28.09.2021 Print Date: 02.02.2023
Date of first issue: 21.06.2016

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	VLE_CD	1.000 ppm	PT OEL (2014-11-14)
isobutane	75-28-5	VLE_CD	1.000 ppm	PT OEL (2014-11-14)
n-butyl acetate	123-86-4	VLE-MP	150 ppm	PT OEL (2007-03-26)
		VLE_CD	200 ppm	PT OEL (2007-03-26)
		STEL	150 ppm 723 mg/m ³	2019/1831/EU (2019-10-31)
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	2019/1831/EU (2019-10-31)
Further information: Indicative				
		TWA	50 ppm 241 mg/m ³	PT DL 305/2007 (2021-01-06)
		STEL	150 ppm 723 mg/m ³	PT DL 305/2007 (2021-01-06)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m ³
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Dermal	Long-term local effects	11 mg/cm ²

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
----------------	---------------------------	-------

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Microbiological Activity in Sewage Treatment Systems	35,6 mg/l
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,09 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

Colour : yellow

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 8,5 %(V)

Lower explosion limit / Lower flammability limit : 0,6 %(V)

Flash point : -60,00 °C

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : < 7 mm²/s (40 °C)

Solubility(ies)

 Water solubility : partly miscible

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : <= 2.500 hPa (20 °C)

Relative density : 0,66 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,66 g/cm³
(20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness. Harmful by inhalation.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg
Assessment: The substance or mixture has no acute dermal toxicity

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17.600 mg/kg

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

n-butyl acetate:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

n-butyl acetate:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

Exposure routes : Dermal
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.

n-butyl acetate:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Test system: Rodent cell line
Method: OECD Test Guideline 473
Result: negative

n-butyl acetate:

Genotoxicity in vitro : Test Type: Ames test
Test system: Salmonella typhimurium
Method: OECD Test Guideline 471
Result: negative

Test Type: Chromosome aberration test in vitro
Test system: Chinese hamster cells
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

Carcinogenicity

Product:

Remarks : No data available

Components:

n-butyl acetate:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

n-butyl acetate:

Effects on fertility : Test Type: Two-generation study
Species: Rat
Application Route: inhalation (vapour)
General Toxicity - Parent: NOAEC: 750 mg/l
General Toxicity F1: NOAEC: 750 mg/l
General Toxicity F2: NOAEC: 750 mg/l
Method: OECD Test Guideline 416
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Reproductive toxicity - Assessment : - Fertility -
No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.
- Teratogenicity -
No toxicity to reproduction

STOT - single exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Exposure routes : Inhalation
Target Organs : Central nervous system
Assessment : The substance or mixture is classified as specific target organ

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

n-butyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

n-butyl acetate:

Species : Rat
NOAEL : 125 mg/kg
Application Route : Oral

Aspiration toxicity

Product:

This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

n-butyl acetate:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

levels of 0.1% or higher.

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure.
Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae/aquatic plants : EbC50 (Pseudokirchneriella subcapitata (green algae)): 26 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

n-butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 44 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l
Exposure time: 72 h
Test Type: static test

Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h
Test Type: Growth inhibition

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: Reproduction Test
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

n-butyl acetate:

Biodegradability : Test Type: Primary biodegradation
Result: rapidly biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version 1.3	Revision Date: 02.02.2023	Date of last issue: 28.09.2021 Date of first issue: 21.06.2016	Print Date: 02.02.2023
----------------	------------------------------	---	---------------------------

persistent and very bioaccumulating (vPvB).

Components:

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Components:

n-butyl acetate:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
(naphtha (petroleum), hydrotreated light)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2

RID : 2

IMDG : 2.1

IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F

Labels : 2.1

Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F

Hazard Identification Number : 23

Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009) : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable

: P2

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

18 Liquefied extremely flammable gases (including LPG) and natu-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

ral gas

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 94,72 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.
H220 : Extremely flammable gas.
H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.
H315 : Causes skin irritation.
H336 : May cause drowsiness or dizziness.
H411 : Toxic to aquatic life with long lasting effects.
EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values

PT DL 305/2007 : Portugal. Indicative Occupational Exposure Limits

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

PT OEL	:	Portugal. Security and Health at the Workplace - Occupational exposure limits of chemical agents
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
PT DL 305/2007 / TWA	:	8 Hour limit value
PT DL 305/2007 / STEL	:	Short term limit value
PT OEL / VLE-MP	:	Time Weighted Average
PT OEL / VLE_CD	:	Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
STOT SE 3	H336
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT
(Commission Regulation (EU) 2020/878)



OKS 1301

Version	Revision Date:	Date of last issue: 28.09.2021	Print Date:
1.3	02.02.2023	Date of first issue: 21.06.2016	02.02.2023

forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.