according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

#### **1. PRODUCT AND COMPANY IDENTIFICATION**

Product name	:	OKS 2100
Chemical nature	:	Solvent Wax

#### Manufacturer or supplier's details

Company name of supplier	:	OKS Spezialschmierstoffe GmbH Ganghoferstr. 47 D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com
E-mail address of person responsible for the SDS	:	mcm@oks-germany.com Material Compliance Management
National contact	:	
Emergency telephone number	:	+86 532 8388 9090 (NRCC, only for hazardous chemicals) +86 21 69225521
Recommended use of the che	em	ical and restrictions on use
Recommended use	:	Lubricant
Restrictions on use	:	Restricted to professional users.

#### 2. HAZARDS IDENTIFICATION

Emergency Overview		
Appearance Colour	:	liquid yellow
Odour	:	solvent-like
		/ be fatal if swallowed and enters airways. May cause aquatic life with long lasting effects.
GHS Classification		
Flammable liquids	:	Category 3
Specific target organ toxicity - single exposure	:	Category 3 (Narcotic effects)
Aspiration hazard	:	Category 1



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



	e of last issue: 2018-10-09 e of first issue: 2014-03-20 Print Date: 2022-08-26
Short-term (acute) aquatic hazard	: Category 2
Long-term (chronic) aquatic hazard	: Category 2
GHS label elements	
Hazard pictograms	
Signal word	: Danger
Hazard statements	<ul> <li>H226 Flammable liquid and vapour.</li> <li>H304 May be fatal if swallowed and enters airways.</li> <li>H336 May cause drowsiness or dizziness.</li> <li>H411 Toxic to aquatic life with long lasting effects.</li> </ul>
Precautionary statements	<ul> <li>Prevention:</li> <li>P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.</li> <li>P233 Keep container tightly closed.</li> <li>P240 Ground/bond container and receiving equipment.</li> <li>P241 Use explosion-proof electrical/ ventilating/ lighting equipment.</li> <li>P242 Use only non-sparking tools.</li> <li>P243 Take precautionary measures against static discharge.</li> <li>P261 Avoid breathing vapours.</li> <li>P271 Use only outdoors or in a well-ventilated area.</li> <li>P273 Avoid release to the environment.</li> <li>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</li> </ul>
	Response:
	<ul> <li>P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.</li> <li>P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.</li> <li>P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.</li> <li>P331 Do NOT induce vomiting.</li> <li>P370 + P378 In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.</li> <li>P391 Collect spillage.</li> </ul>
	<b>Storage:</b> P403 + P233 Store in a well-ventilated place. Keep container



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

tightly closed. P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

#### Disposal:

P501 Dispose of contents/containers according the local government requirements.

#### Physical and chemical hazards

Flammable liquid and vapour.

#### **Health hazards**

May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

#### Environmental hazards

Toxic to aquatic life. Toxic to aquatic life with long lasting effects.

#### Other hazards which do not result in classification

None known.

#### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

#### Components

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated heavy	64742-48-9	>= 70 -< 90
Paraffin waxes and Hydrocarbon waxes	8002-74-2	>= 1 -< 10
calcium bis(dinonyInaphthalenesulphonate)	57855-77-3	>= 0.1 -< 1
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0	>= 0.1 -< 1

#### 4. FIRST AID MEASURES

If inhaled	<ul> <li>Call a physician or poison control centre immediately. Remove person to fresh air. If signs/symptoms continue, get medical attention.</li> <li>Keep patient warm and at rest.</li> <li>If unconscious, place in recovery position and seek medical advice.</li> <li>Keep respiratory tract clear.</li> <li>If breathing is irregular or stopped, administer artificial respiration.</li> </ul>
In case of skin contact	<ul> <li>Take off all contaminated clothing immediately. Get medical attention immediately if irritation develops and persists.</li> </ul>



according to GB/T 16483 and GB/T 17519 CN



Version 1.3	Revision Date: 2022-08-25		ast issue: 2018-10-09 irst issue: 2014-03-20 Print Date: 2022-08-26
In ca	ase of eye contact	:	Wash clothing before reuse. Thoroughly clean shoes before reuse. Wash skin thoroughly with soap and water or use recognized skin cleanser. Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes. Seek medical advice.
lf sw	vallowed	:	Move the victim to fresh air. If accidentally swallowed obtain immediate medical attention. If unconscious, place in recovery position and seek medical advice. Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage.
Most important symptoms and effects, both acute and delayed			Central nervous system depression Can be absorbed through skin. Risk of product entering the lungs on vomiting after ingestion. Health injuries may be delayed. May cause an allergic skin reaction. Inhalation may provoke the following symptoms: Unconsciousness Dizziness Dizziness Drowsiness Headache Nausea Tiredness Skin contact may provoke the following symptoms: Erythema Allergic appearance Aspiration may cause pulmonary oedema and pneumonitis.
Note	es to physician	:	The first aid procedure should be established in consultation with the doctor responsible for industrial medicine. Treat symptomatically.
5. FIREF	IGHTING MEASU	RES	
Suita	able extinguishing	media :	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Unsi med	uitable extinguishir ia	ig :	High volume water jet
	cific hazards during ghting	<b>)</b> :	Do not let product enter drains. Container may explode if heated.



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

Versio 1.3	on Revision Date: 2022-08-25		ast issue: 2018-10-09 irst issue: 2014-03-20 Print Date: 2022-08-26
			Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
-	lazardous combustion products	ı :	Carbon oxides
	Specific extinguishing nethods	:	Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.
	Special protective equi or firefighters	pment :	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

#### 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, : protective equipment and emergency procedures	Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.
Environmental precautions :	Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
Methods and materials for : containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Non-sparking tools should be used.

#### 7. HANDLING AND STORAGE

Handling Advice on protection against fire and explosion	:	Keep away from heat and sources of ignition.
Advice on safe handling	:	Use only in an area containing explosion proof equipment. Do not use in areas without adequate ventilation. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

Version 1.3	Revision Date: 2022-08-25	Date of last issue: 2018-10-09 Date of first issue: 2014-03-20 Print Date: 2022-08-26
equipment. Avoid contact with skin and eyes. For personal protection see section 8. Keep away from fire, sparks and heat Persons with a history of skin sensitis asthma, allergies, chronic or recurren should not be employed in any proces being used. Smoking, eating and drinking should I application area. Wash hands and face before breaks a handling the product. Ensure all equipment is electrically greater transfer operations. Do not get in eyes or mouth or on skir Do not get on skin or clothing. Do not ingest. Do not use sparking tools. Do not enter areas where used or sto ventilated. Do not repack. Do not re-use empty containers. These safety instructions also apply to		<ul> <li>Avoid contact with skin and eyes.</li> <li>For personal protection see section 8.</li> <li>Keep away from fire, sparks and heated surfaces.</li> <li>Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.</li> <li>Smoking, eating and drinking should be prohibited in the application area.</li> <li>Wash hands and face before breaks and immediately after handling the product.</li> <li>Ensure all equipment is electrically grounded before beginning transfer operations.</li> <li>Do not get in eyes or mouth or on skin.</li> <li>Do not get on skin or clothing.</li> <li>Do not use sparking tools.</li> <li>Do not enter areas where used or stored until adequately ventilated.</li> <li>Do not repack.</li> </ul>
Avoi	dance of contact	: Oxidizing agents
<b>Stor</b> Conc	<b>age</b> ditions for safe sto	rage : Store in original container. Keep container closed when not in use. Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place. Do not store together with oxidizing and self-igniting products. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

#### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Paraffin waxes and Hydrocarbon waxes	8002-74-2	PC-TWA (Fumes)	2 mg/m3	CN OEL (2019-08-27)



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

VersionRevision Date:Date of last issue: 2018-10-091.32022-08-25Date of first issue: 2014-03-20Print Date: 2022-08-26

			PC-STEL (Fumes)	4 mg/m3	CN OEL (2019-08-27)
			TWA (Fumes)	2 mg/m3	ACGIH (2010-03-01)
Engineering measures :		ventilation. Handle only ir	Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).		
Personal protective equip	ment				
Respiratory protection	ventilation is p	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.			
Filter type	:	Filter type A-F	Filter type A-P		
Eye/face protection	:	Safety glasses with side-shields			
Skin and body protection	:	Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.			
Hand protection Material Break through time Protective index	al : Nitrile rubber through time : > 10 min				
Remarks	:	Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.			
Protective measures	:	The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.			
Hygiene measures	:	Wash face, ha handling.	ands and any ex	posed skin thorough	ly after

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	liquid
Colour	:	yellow
Odour	:	solvent-like



according to GB/T 16483 and GB/T 17519 CN



		st issue: 2018-10-09 st issue: 2014-03-20 Print Date: 2022-08-26
Odour Threshold	:	No data available
рН	:	Not applicable substance/mixture is non-polar/aprotic
Melting point/range	:	No data available
Boiling point/boiling range	:	145 °C
Flash point	:	39 °C
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Not applicable
Self-ignition	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Vapour pressure	:	<= 1,100 hPa (20 °C)
Relative vapour density	:	No data available
Relative density	:	0.78 (20 °C) Reference substance: Water The value is calculated
Density	:	0.78 g/cm3 (20 °C)
Bulk density	:	No data available
Solubility(ies) Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

#### Viscosity

Viscosity, dynamic	: No data available
Viscosity, kinematic	: 4.3 mm2/s ( 40 °C)
Explosive properties	: Not explosive
Oxidizing properties	: No data available
Sublimation point	: No data available

#### **10. STABILITY AND REACTIVITY**

Reactivity	:	No hazards to be specially mentioned.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	No dangerous reaction known under conditions of normal use.
Conditions to avoid	:	Heat, flames and sparks. Strong sunlight for prolonged periods.
Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

#### **11. TOXICOLOGICAL INFORMATION**

Acute toxicity		
Product: Acute oral toxicity	Remarks: Effects due	to ingestion may include:
	Symptoms: Central ne	ervous system depression
Acute inhalation toxicity	Remarks: Respiration Irritating to respiratory	of solvent vapour may cause dizziness. system.
	Local irritation, Respir	may provoke the following symptoms:, atory disorders, Dizziness, Drowsiness, rtigo, Central nervous system



according to GB/T 16483 and GB/T 17519 CN



sion	Revision Date: 2022-08-25		ast issue: 2018-10-09 irst issue: 2014-03-20 Print Date: 2022-08-26
Acut	e dermal toxicity	:	Remarks: Prolonged or repeated skin contact with liquid ma cause defatting resulting in drying, redness and possible blistering.
			Symptoms: Redness, Local irritation, Skin disorders
<u>Com</u>	ponents:		
Nap	htha (petroleum),	hydrotre	ated heavy:
Acut	e inhalation toxicity	y :	Assessment: The substance or mixture is classified as spectraget organ toxicant, single exposure, category 3 with narcotic effects.
calc	ium bis(dinonylna	aphthalen	esulphonate):
Acut	e oral toxicity	:	LD50 (Rat): > 5,000 mg/kg
Acut	e dermal toxicity	:	LD50 (Rabbit): > 20,000 mg/kg
Benz	zenesulfonic acid	. mono-C	16-24-alkyl derivs., calcium salts:
	e oral toxicity		LD50 (Rat): > 5,000 mg/kg Method: OECD Test Guideline 401
Acut	e inhalation toxicit	y :	LC50 (Rat): > 1.9 mg/l Exposure time: 4 h Test atmosphere: dust/mist Assessment: The substance or mixture has no acute inhalation toxicity
Acut	e dermal toxicity	:	(Rabbit): > 5,000 mg/kg Method: OECD Test Guideline 402
			GLP: yes
Skin	n corrosion/irritati	on	
	n corrosion/irritati <u>duct:</u>	on	



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

#### **Components:**

# Naphtha (petroleum), hydrotreated heavy:Result: Repeated exposure may cause skin dryness or cracking.

#### calcium bis(dinonyInaphthalenesulphonate):

Species	:	Rabbit
Assessment	:	Irritating to skin.
Result	:	Irritating to skin.

#### Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Species	:	Rabbit
Assessment	:	No skin irritation
Method	:	OECD Test Guideline 404
Result	:	No skin irritation

#### Serious eye damage/eye irritation

#### Product:

Remarks

: Contact with eyes may cause irritation.

#### **Components:**

#### calcium bis(dinonyInaphthalenesulphonate):

Species	:	Rabbit
Result	:	Irritating to eyes.
Assessment	:	Irritating to eyes.

#### Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Species	:	Rabbit
Result	:	No eye irritation
Assessment	:	No eye irritation
Method	:	OECD Test Guideline 405

#### Respiratory or skin sensitisation

#### Product:

Remarks :	This information is not available.
-----------	------------------------------------



according to GB/T 16483 and GB/T 17519 CN



## **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

#### **Components:**

#### calcium bis(dinonyInaphthalenesulphonate):

Species	:	Guinea pig
Assessment	:	May cause sensitisation by skin contact.
Result	:	May cause sensitisation by skin contact.

#### Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:

Test Type :	Buehler Test
Species :	Guinea pig
Assessment	The product is a skin sensitiser, sub-category 1B.
Result :	The product is a skin sensitiser, sub-category 1B.

#### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro	: Remarks: No data available	

: Remarks: No data available Genotoxicity in vivo

#### **Components:**

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:			
Genotoxicity in vitro :	Test Type: In vitro mammalian cell gene mutation test Method: OECD Test Guideline 476 Result: negative		
Genotoxicity in vivo :	Test Type: Micronucleus test Species: Mouse Application Route: Oral Method: OECD Test Guideline 474 Result: negative		
Germ cell mutagenicity - : Assessment	Tests on bacterial or mammalian cell cultures did not show mutagenic effects.		
Carcinogenicity			

#### Carcinogenicity

## Product:

Remarks	:	No data available
---------	---	-------------------



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

#### **Components:**

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:		
Carcinogenicity -	Not classifiable as a human carcinogen.	
Reproductive toxicity		
Product:		
Effects on fertility	Remarks: No data available	
Effects on foetal : development	Remarks: No data available	
Components:		
calcium bis(dinonylnaphthale	nesulphonate):	
Reproductive toxicity -	- Fertility -	
Assessment	No toxicity to reproduction	
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts:		
Effects on fertility	Test Type: reproductive and developmental toxicity study Species: Rat	

#### STOT - single exposure

Reproductive toxicity -

**Components:** 

Assessment

#### Naphtha (petroleum), hydrotreated heavy:

Exposure routes	:	Inhalation
Assessment	:	The substance or mixture is classified as specific target organ
		toxicant, single exposure, category 3 with narcotic effects.

Application Route: Oral

No toxicity to reproduction

No toxicity to reproduction

- Teratogenicity -

: - Fertility -

Method: OECD Test Guideline 415

General Toxicity - Parent: NOAEL: > 500 mg/kg body weight General Toxicity F1: NOAEL: > 500 mg/kg body weight

calcium bis(dinonyInaphthalenesulphonate):



according to GB/T 16483 and GB/T 17519 CN



	00	
ersion .3	Revision Date: 2022-08-25	Date of last issue: 2018-10-09 Date of first issue: 2014-03-20 Print Date: 2022-08-26
Asse	ssment	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
Benz	enesulfonic acid	I, mono-C16-24-alkyl derivs., calcium salts:
Asse	ssment	: The substance or mixture is not classified as specific target organ toxicant, single exposure.
STO	T - repeated exp	osure
<u>Com</u>	ponents:	
calci	um bis(dinonyIn	aphthalenesulphonate):
Asse	ssment	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Benz	enesulfonic acio	I, mono-C16-24-alkyl derivs., calcium salts:
Asse	ssment	: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.
Repe	eated dose toxic	ty
Prod	uct:	
Rema		: This information is not available.
<u>Com</u>	ponents:	
Benz	enesulfonic acid	I, mono-C16-24-alkyl derivs., calcium salts:
Spec		: Rat
NOAI NOAI		: 500 mg/kg : 500 mg/kg
	cation Route	: Oral
Expo	sure time	: 28 0500 Test 0 : 10 <sup>11</sup> 0 - 107
Meth	od	: OECD Test Guideline 407
Spec	ies	: Rat
NOAI NOAI		: 0.05 mg/l
	EL cation Route	: 0.05 mg/l : Inhalation
Test	atmosphere	: dust/mist
Expo Meth	sure time od	: 28 : OECD Test Guideline 412



according to GB/T 16483 and GB/T 17519 CN



#### **OKS 2100**

VersionRevision Date:Date of last issue: 2018-10-091.32022-08-25Date of first issue: 2014-03-20Print Date: 2022-08-26

Species NOAEL NOAEL	:	Rat > 1000 mg/kg > 1,000 mg/kg Dermal
Application Route	-	Dermai
Exposure time	:	28
Method	:	OECD Test Guideline 410

#### Aspiration toxicity

#### Product:

May be fatal if swallowed and enters airways.

#### **Components:**

#### Naphtha (petroleum), hydrotreated heavy:

May be fatal if swallowed and enters airways.

#### calcium bis(dinonyInaphthalenesulphonate):

No aspiration toxicity classification

#### **Further information**

#### **Product:**

Remarks

: Information given is based on data on the components and the toxicology of similar products.

#### **Components:**

# Paraffin waxes and Hydrocarbon waxes: Remarks : Information given is based on data on the components and the toxicology of similar products.

#### **12. ECOLOGICAL INFORMATION**

#### Ecotoxicity

#### Product:

Toxicity to fish

Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



1

according to GB/T 16483 and GB/T 17519 CN



Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Components:		
Naphtha (petroleum), hydrotr	rea	ited heavy:
Ecotoxicology Assessment		
Acute aquatic toxicity	:	Toxic to aquatic life.
Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.
calcium bis(dinonylnaphthale	en	esulphonate):
Toxicity to fish	:	LC50 (Cyprinus carpio (Carp)): > 0.28 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): > 0.27 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 Remarks: No toxicity at the limit of solubility
Ecotoxicology Assessment Chronic aquatic toxicity	:	This product has no known ecotoxicological effects.
Benzenesulfonic acid, mono- Toxicity to fish	-C <sup>,</sup>	<b>16-24-alkyl derivs., calcium salts:</b> LC50 (Pimephales promelas (fathead minnow)): > 10,000 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203 Remarks: No toxicity at the limit of solubility



according to GB/T 16483 and GB/T 17519 CN



Versio 1.3	on	Revision Date: 2022-08-25			st issue: 2018-10-09 rst issue: 2014-03-20 Print Date: 2022-08-26
		ty to daphnia and ic invertebrates	other	:	EC50 (Daphnia magna (Water flea)): > 1,000 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 Remarks: No toxicity at the limit of solubility
	Toxici blants	ty to algae/aquati	С	:	EC50 (Pseudokirchneriella subcapitata (green algae)): > 1,500 mg/l Exposure time: 72 h Test Type: Growth inhibition Remarks: No toxicity at the limit of solubility
Т	<sup>-</sup> oxici	ty to microorganis	sms	:	LC50 (activated sludge): > 10,000 mg/l Exposure time: 3 h Test Type: Respiration inhibition Method: OECD Test Guideline 209
		oxicology Assess ic aquatic toxicity		:	This product has no known ecotoxicological effects., No toxicity at the limit of solubility
F	Persis	stence and degra	adabili	ty	
	<b>Produ</b> Biode	<b>ıct:</b> gradability		:	Remarks: No data available
		co-chemical /ability		:	Remarks: No data available
<u>c</u>	Comp	oonents:			
		<b>ım bis(dinonylna</b> gradability	phtha	leno :	esulphonate): Result: Not readily biodegradable.
		enesulfonic acid gradability	, monc	<b>b-C</b> 1 :	<b>I6-24-alkyl derivs., calcium salts:</b> aerobic Inoculum: activated sludge Result: Not rapidly biodegradable Biodegradation: 8 % Exposure time: 28 d Method: OECD Test Guideline 301D



according to GB/T 16483 and GB/T 17519 CN



Version 1.3			st issue: 2018-10-09 rst issue: 2014-03-20 Print Date: 2022-08-26
			GLP: yes
Bioa	accumulative poter	ntial	
Pro	duct:		
Bioa	accumulation	:	Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).
Con	nponents:		
calc	ium bis(dinonylna	phthalen	esulphonate):
	ition coefficient: n- nol/water	:	log Pow: 10.96
Ben	zenesulfonic acid,	mono-C1	l6-24-alkyl derivs., calcium salts:
Bioa	accumulation	:	Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is possible.
	ition coefficient: n- nol/water	:	log Pow: 16.09 (25 °C)
Mot	oility in soil		
Pro	duct:		
Mob	ility	:	Remarks: No data available
	ribution among ronmental compartn		Remarks: No data available
Oth	er adverse effects		
Pro	duct:		
	itional ecological mation	:	Toxic to aquatic life with long lasting effects.
Con	nponents:		
Res	i <b>um bis(dinonyIna</b> ults of PBT and vPv essment	-	



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



## **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

#### **13. DISPOSAL CONSIDERATIONS**

Disposal methods	
Waste from residues :	The product should not be allowed to enter drains, water courses or the soil. Do not dispose of with domestic refuse. Dispose of as hazardous waste in compliance with local and national regulations.
Contaminated packaging :	Packaging that is not properly emptied must be disposed of as the unused product. Dispose of waste product or used containers according to local regulations.

#### **14. TRANSPORT INFORMATION**

#### International Regulations

<b>UNRTDG</b> UN number Proper shipping name Class Packing group Labels	:	UN 1993 FLAMMABLE LIQUID, N.O.S. (Naphtha, petroleum, hydrotreated heavy) 3 III 3
IATA-DGR UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft)	:	UN 1993 Flammable liquid, n.o.s. (Naphtha, petroleum, hydrotreated heavy) 3 III Flammable Liquids 366
Packing instruction (passenger aircraft)	:	355
<b>IMDG-Code</b> UN number Proper shipping name	:	UN 1993 FLAMMABLE LIQUID, N.O.S. (Naphtha, petroleum, hydrotreated heavy)
Class Packing group Labels EmS Code Marine pollutant	:	3 III 3 F-E, <u>S-E</u> yes

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.



according to GB/T 16483 and GB/T 17519 CN



#### **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

#### **National Regulations**

#### GB 6944/12268 UN 1993 UN number : Proper shipping name FLAMMABLE LIQUID, N.O.S. : (Naphtha, petroleum, hydrotreated heavy) Class ÷ 3 Packing group Ш 1 Labels : 3

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **15. REGULATORY INFORMATION**

#### National regulatory information Law on the Prevention and Control of Occupational Diseases

#### **Regulations on Safety Management of Hazardous Chemicals**

Catalogue of Hazardous Chemicals

Product name	Status	Reference number
OKS 2100	Listed	2828

Hazardous Chemicals for Priority Management under : Not applicable SAWS

#### Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals

: Not applicable

## Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not applicable and Export

#### International Regulations

Montreal Protocol : Not applicable



according to GB/T 16483 and GB/T 17519  $\ensuremath{\text{CN}}$ 



#### **OKS 2100**

Version 1.3	Revision Date: 2022-08-25	Date of last issue: 2018-10-09 Date of first issue: 2014-03-20 Print Date: 2022-08-26				
Rotterdam Convention (Prior Informed Consent) : Not applicable						
Stockholm Convention (Persistent Organic Pollutants) : Not applicable						
The components of this product are reported in the following inventories:						
IECS	SC	: On the inventory, or in compliance with the inventory				
16. OTHE	ER INFORMATIO	J				
Date	format	: yyyy/mm/dd				
Full	text of other abb	reviations				

ACGIH CN OEL		USA. ACGIH Threshold Limit Values (TLV) Occupational exposure limits for hazardous agents in the workplace - Chemical hazardous agents.
ACGIH / TWA		8-hour, time-weighted average
CN OEL / PC-TWA	:	Permissible concentration - time weighted average
CN OEL / PC-STEL	:	Permissible concentration - short term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand



CN



#### **OKS 2100**

Version	Revision Date:	Date of last issue: 2018-10-09	
1.3	2022-08-25	Date of first issue: 2014-03-20	Print Date: 2022-08-26

Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

#### Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

