according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2101

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Anticorrosion additive

Substance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

responsible for the SDS

mcm@oks-germany.com

National contact :

1.4 Emergency telephone number

Emergency telephone

: +34 91 562 04 20

number

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

Long-term (chronic) aquatic hazard,

Category 2

H411: Toxic to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters

airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

pentane

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

Hydrocarbons, C6, isoalkanes, <5% n-hexane



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

Additional Labelling

EUH208 Contains calcium bis(dinonylnaphthalenesulphonate). May produce an allergic

reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active substance with propellant

Solvent

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
pentane	109-66-0 203-692-4 601-006-00-1 01-2119459286-30- XXXX	Flam. Liq.2; H225 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 10 - < 20
Hydrocarbons, C9- C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	265-150-3 01-2119463258-33	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411;	Note P	>= 2,5 - < 10



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

		EUH066		
Hydrocarbons, C11- C12, isoalkanes, < 2% aromatics	918-167-1	Flam. Liq.3; H226 Asp. Tox.1; H304; EUH066	Note P	>= 1 - < 10
	01-2119472146-39- XXXX			
Hydrocarbons, C6, isoalkanes, <5% n-hexane	931-254-9 01-2119484651-34- XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 2,5 - < 10
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	926-605-8 01-2119486291-36- XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 2,5 - < 10
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36- XXXX	Acute Tox.4; H302 Acute Tox.3; H331 Skin Irrit.2; H315 Eye Irrit.2; H319	ATE (Oral): 1.200 mg/kg;	>= 1 - < 10
			ATE (Inhalation): 3 mg/l;	
calcium bis(dinonylnaphthalen esulphonate)	57855-77-3 260-991-2	Skin Irrit.2; H315 Eye Irrit.2; H319 Skin Sens.1; H317		>= 0,1 - < 1
Substances with a work	place exposure limit :	1		
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 30 - < 50
propane	74-98-6 200-827-9	Flam. Gas1A; H220 Press. GasCompr.	Note U (table	>= 10 - < 20

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Date of last issue: 07.03.2024 Print Date: Revision Date: 07.03.2024 Date of first issue: 22.06.2016 07.03.2024 2.6

	601-003-00-5 01-2119486944-21- XXXX	Gas; H280	3.1)	
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10
Paraffin waxes and Hydrocarbon waxes	8002-74-2 232-315-6	Not classified		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water. Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Rinse immediately with plenty of water, also under the eyelids, In case of eye contact

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Risks : Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes.



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular

national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	VLA- EDEnvironmental Daily Limit Value (gas)	1.000 ppm	ES VLA (2013-02-22)
pentane	109-66-0	TWALimit Value - eight hours	1.000 ppm 3.000 mg/m3	2006/15/EC (2006-02-09)
	Further inform	nation: Indicative		,
		VLA- EDEnvironmental Daily Limit Value	1.000 ppm 3.000 mg/m3	ES VLA (2012-01-01)



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

propane	74-98-6	VLA- EDEnvironmental Daily Limit Value	1.000 ppm	ES VLA (2011-03-03)
isobutane	75-28-5	VLA- EDEnvironmental Daily Limit Value (gas)	1.000 ppm	ES VLA (2013-02-22)
Paraffin waxes and Hydrocarbon waxes	8002-74-2	VLA- EDEnvironmental Daily Limit Value (Fumes)	2 mg/m3	ES VLA (2013-02-22)
2-butoxyethanol	111-76-2	TWALimit Value - eight hours	20 ppm 98 mg/m3	2000/39/EC (2000-06-16)
	Further inform skin, Indicative		possibility of significant uptak	ke through the
		STELShort term exposure limit	50 ppm 246 mg/m3	2000/39/EC (2000-06-16)
	Further inform skin, Indicative		possibility of significant uptak	ke through the
	,	VLA- EDEnvironmental Daily Limit Value	20 ppm 98 mg/m3	ES VLA (2022-04-01)
	Further inform			
	Further inform	VLA- ECEnvironmental Short Term Value	50 ppm 245 mg/m3	ES VLA (2022-04-01)
	Further inform	ation: Skin		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
2-butoxyethanol	111-76-2	butoxy acetic acid:	End of workday	ES VLB
		200 mg/g		(2011-03-
		Creatinine		03)
		(Urine)		

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
pentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m3
	Workers	Skin contact	Long-term systemic effects	432 mg/kg
Hydrocarbons, C11- C12, isoalkanes, < 2% aromatics	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
	Workers	Inhalation	Long-term local effects	837,5 mg/m3
Hydrocarbons, C6, isoalkanes, <5% n-hexane	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

	Workers	Inhalation	Long-term local effects	837,5 mg/m3
Hydrocarbons, C6- C7, isoalkanes, cyclics, <5% n- hexane	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
	Workers	Inhalation	Long-term local effects	837,5 mg/m3
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m3
	Workers	Inhalation	Acute systemic effects	1091 mg/m3
	Workers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	89 mg/kg bw/day
	Workers	Inhalation	Acute local effects	246 mg/m3
calcium bis(dinonylnaphthalen esulphonate)	Workers	Inhalation	Long-term systemic effects	2,23 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,32 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-butoxyethanol	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Soil	2,33 mg/kg
	Intermittent use/release	26,4 mg/l
calcium	Fresh water	0,27 mg/l
bis(dinonylnaphthalenesulphonat		
e)		
	Marine water	0,027 mg/l
	Intermittent use/release	2,7 mg/l
	Microbiological Activity in Sewage	10 mg/l
	Treatment Systems	
	Fresh water sediment	4,69 mg/kg
_	Marine sediment	0,469 mg/kg
	Soil	0,936 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : yellow

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -161 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

Upper explosion limit / Upper :

flammability limit

9,4 %(V)

Lower explosion limit / Lower

flammability limit

0,6 %(V)

Flash point : 0 °C

Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 8.327 hPa (20 °C)

Relative density : 0,638 (20 °C)

Reference substance: Water The value is calculated

Density : 0,64 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

Particle characteristics

Particle size : No data available

9.2 Other information

Explosives : Not explosive

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

Oxidizing properties : No data available

Self-ignition : No data available

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific

target organ toxicant, single exposure, category 3 with

narcotic effects.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

2-butoxyethanol:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 (Guinea pig): 1.414 mg/kg Method: OECD Test Guideline 401

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l

Test atmosphere: vapour

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LC50: 3 mg/l Exposure time: 4 h



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Test atmosphere: vapour

Assessment: The component/mixture is toxic after short term

inhalation.

Acute dermal toxicity : LD50 (Guinea pig): > 2.000 mg/kg

Method: OECD Test Guideline 402

Assessment: The substance or mixture has no acute dermal

toxicity

calcium bis(dinonylnaphthalenesulphonate):

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:
Result : Skin irritation

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit Result : Skin irritation

2-butoxyethanol:

a brand of
FREUDENBERG

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

Species : Rabbit

Assessment : Irritating to skin. Result : Irritating to skin.

calcium bis(dinonylnaphthalenesulphonate):

Species : Rabbit

Assessment : Irritating to skin. Result : Irritating to skin.

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

2-butoxyethanol:

Species : Rabbit

Assessment : Irritating to eyes. Result : Irritating to eyes.

calcium bis(dinonylnaphthalenesulphonate):

Species : Rabbit

Assessment : Irritating to eyes. Result : Irritating to eyes.

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

2-butoxyethanol:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals. Result : Did not cause sensitisation on laboratory animals.

calcium bis(dinonylnaphthalenesulphonate):

Species : Guinea pig

Assessment : May cause sensitisation by skin contact.
Result : May cause sensitisation by skin contact.



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

2-butoxyethanol:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Method: OECD Test Guideline 476

Result: negative

Remarks: In vitro tests did not show mutagenic effects

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Rat

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity-

Assessment

In vitro tests did not show mutagenic effects

Carcinogenicity

Product:

Remarks : No data available

Components:

2-butoxyethanol:

Carcinogenicity -

Assessment

Animal testing did not show any carcinogenic effects.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal

development

Remarks: No data available

Components:

2-butoxyethanol:

Reproductive toxicity -

: - Fertility -

Assessment

No toxicity to reproduction

a brand of

FREUDENBERG

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

- Teratogenicity -

Animal testing did not show any effects on foetal

development.

calcium bis(dinonylnaphthalenesulphonate):

Reproductive toxicity - : - Fertility -

Assessment No toxicity to reproduction

STOT - single exposure

Product:

Remarks : No data available

Components:

pentane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Exposure routes : Inhalation

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

2-butoxyethanol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

calcium bis(dinonylnaphthalenesulphonate):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Product:

Remarks : No data available

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Components:

2-butoxyethanol:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

calcium bis(dinonylnaphthalenesulphonate):

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

pentane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

2-butoxyethanol:

No aspiration toxicity classification

calcium bis(dinonylnaphthalenesulphonate):

No aspiration toxicity classification



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

Components:

Paraffin waxes and Hydrocarbon waxes:

Remarks : Information given is based on data on the components and

the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

pentane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

a brand of
FREUDENBERG

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

aquatic invertebrates Exposure time: 48 h

Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

2-butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.474 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1.550 mg/l

Exposure time: 48 h
Test Type: Immobilization

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 1.840

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 286

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

NOEC: > 100 mg/l Exposure time: 21 d

Species: Danio rerio (zebra fish)

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC: 100 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: Reproduction Test Method: OECD Test Guideline 211

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

calcium bis(dinonylnaphthalenesulphonate):

Toxicity to fish : LC50 (Cyprinus carpio (Carp)): > 0,28 mg/l

Exposure time: 96 h
Test Type: static test

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 0,27 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

: Remarks: No data available

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Biodegradability : Result: Not readily biodegradable.

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Biodegradability : Result: Not rapidly biodegradable

2-butoxyethanol:

Biodegradability : Test Type: aerobic

Result: rapidly biodegradable Biodegradation: 90 % Exposure time: 28 d

Method: OECD Test Guideline 301B

calcium bis(dinonylnaphthalenesulphonate):

Biodegradability : Result: Not readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-

octanol/water

Remarks: No data available

Hydrocarbons, C6, isoalkanes, <5% n-hexane:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-

octanol/water

log Pow: 4

2-butoxyethanol:

Bioaccumulation : Bioconcentration factor (BCF): 3,16

Partition coefficient: n- : log Pow: 0,81 (25 °C)

octanol/water Method: OECD Test Guideline 107

calcium bis(dinonylnaphthalenesulphonate):

Partition coefficient: n-

octanol/water

: log Pow: 10,96

butane:

Partition coefficient: n-

: log Pow: 2,89

octanol/water

Method: OECD Test Guideline 107

propane:

Partition coefficient: n-

•

log Pow: 2,36

isobutane:

octanol/water

Partition coefficient: n-

log Pow: 2,88

octanol/water

Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

VersionRevision Date:Date of last issue: 07.03.2024Print Date:2.607.03.2024Date of first issue: 22.06.201607.03.2024

Distribution among : Remarks: No data available

environmental compartments

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Components:

calcium bis(dinonylnaphthalenesulphonate):

Assessment : Non-classified PBT substance. Non-classified vPvB substance

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological

information

: Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04**, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950

RID : UN 1950

IMDG : UN 1950

IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS

()

RID : AEROSOLS IMDG : AEROSOLS

(naphtha (petroleum), hydrotreated light, cyclohexane)

IATA : Aerosols, flammable

(naphtha (petroleum), hydrotreated light)

14.3 Transport hazard class(es)

 ADR
 : 2

 RID
 : 2

 IMDG
 : 2.1

 IATA
 : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo :

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

203

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be considered:

Number on list 75

2-butoxyethanol (Number on list 3)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No

1907/2006 (REACH), Article 57).

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Date of last issue: 07.03.2024 **Revision Date:** Print Date: 07.03.2024 Date of first issue: 22.06.2016 07.03.2024 2.6

Regulation (EC) No 1005/2009 on substances that

deplete the ozone layer

(EC 1005/2009)

Not applicable

Regulation (EU) 2019/1021 on persistent organic

pollutants (recast)

(EU POP)

: Not applicable

Regulation (EC) No 649/2012 of the European

Parliament and the Council concerning the export and

import of dangerous chemicals

(EU PIC)

Not applicable

Regulation (EU) 2019/1148 on the marketing and use of : Not applicable

explosives precursors

P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of

major-accident hazards involving dangerous substances.

P3a

FLAMMABLE AEROSOLS

E2 **ENVIRONMENTAL HAZARDS**

18 Liquefied flammable gases (including LPG) and natural gas

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils

(including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and

environmental hazards as the products referred to in points (a) to

(d)

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 93,32 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H317 : May cause an allergic skin reaction.
H319 : Causes serious eye irritation.

H331 : Toxic if inhaled.

H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Note C : Some organic substances may be marketed either in a

specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the



according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

substance is a specific isomer or a mixture of isomers.

Note P

: The harmonised classification as a carcinogen or muta

The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which

case a classification in accordance with Title II of this

Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-

P262-P301 + P310-P331 shall apply.

Note U (table 3.1) : When put on the market gases have to be classified as

"Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2006/15/EC : Europe. Indicative occupational exposure limit values

ES VLA : Spain. Environmental Limits for exposure to Chemical agents

- Table 1: Occupational Exposure Values

ES VLB : Occupational Exposure Limits for Chemical Agents in Spain -

Biological Exposure Values Limit Value - eight hours

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit 2006/15/EC / TWA : Limit Value - eight hours

ES VLA / VLA-ED : Environmental Daily Limit Value ES VLA / VLA-EC : Environmental Short Term Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation: Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration: ICAO - International Civil Aviation Organization: IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of

according to Regulation (EC) No. 1907/2006 - ES (Commission Regulation (EU) 2020/878)



OKS 2101

Version Revision Date: Date of last issue: 07.03.2024 Print Date: 2.6 07.03.2024 Date of first issue: 22.06.2016 07.03.2024

Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure: Aerosol 1 H222, H229 Based on product data or assessment Skin Irrit. 2 H315 Calculation method STOT SE 3 H336 Calculation method H304 Asp. Tox. 1 Based on product data or assessment Aquatic Chronic 2 H411 Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.