

Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1	Product identifier		
	Product name	:	OKS 2101
1.2	Relevant identified uses of the	ne s	ubstance or mixture and uses advised against
	Use of the Substance/Mixture	:	Anticorrosion additive
	Recommended restrictions on use	:	Restricted to professional users.
1.3	Details of the supplier of the	saf	ety data sheet
	Company	:	OKS Spezialschmierstoffe GmbH Ganghoferstr. 47 D-82216 Maisach-Gernlinden
			Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599
			info@oks-germany.com
			5 ,
	E-mail address of person responsible for the SDS	:	mcm@oks-germany.com
	National contact	:	

1.4 Emergency telephone number

Emergency telephone	:	+33 1 45 42 59 59
number		

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)				
Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.			
Skin irritation, Category 2	H315: Causes skin irritation.			
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.			





Version 2.6	Revision Date: 07.03.2024			ue: 07.03.2024 sue: 22.06.2016	Print Date: 07.03.2024
Aspiration hazard, Category 1		y 1		H304: May be fatal if swallowed and enters airways.	
Long-term (chronic) aquatic haz Category 2		ard,	H411: Toxic to aquatic	life with long lasting effects	
2.2 Label	elements				
Labe	lling (REGULATION ((EC)	No 1272/20	08)	
	rd pictograms	:			¥2
Signa	al word	:	Danger		
Haza	rd statements	:	H222 H229 H304 H315 H336 H411	May be fatal if s airways. Causes skin irr May cause dro	ntainer: May burst if heated. swallowed and enters
Proc	autionary statements		Preventio	n•	
FIECO	autionary statements	•	P210	Keep away fror	n heat, hot surfaces, sparks nd other ignition sources. No
			P211	5	n an open flame or other
			P251 P273		r burn, even after use. o the environment.
			Response	:	
			P301 + P3	POISON CENT	
			P331	Do NOT induce	e vomiting.
			Storage:		
			P410 + P4		nlight. Do not expose to exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

pentane

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

Hydrocarbons, C6, isoalkanes, <5% n-hexane





Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Additional Labelling

EUH208 Contains calcium bis(dinonylnaphthalenesulphonate). May produce an allergic reaction.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature

: Active substance with propellant Solvent

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
pentane	109-66-0 203-692-4 601-006-00-1 01-2119459286-30- XXXX	Flam. Liq.2; H225 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 10 - < 20
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 10 - < 20



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 - FR (Commission Regulation (EU) 2020/878)



VersionRevision Date:Date of last issue: 07.032.607.03.2024Date of first issue: 22.06				Print Date: 07.03.2024	
	xxxx				
Hydrocarbons, C9- C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	265-150-3 01-2119463258-33	Flam. Liq.3; H226 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411; EUH066	Note P	>= 2,5 - < 10	
Hydrocarbons, C11- C12, isoalkanes, < 2% aromatics	01-2119472146-39-	Flam. Liq.3; H226 Asp. Tox.1; H304; EUH066	Note P	>= 1 - < 10	
	XXXX				
Hydrocarbons, C6, isoalkanes, <5% n- hexane	931-254-9	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304		>= 2,5 - < 10	
	01-2119484651-34- XXXX	Aquatic Chronic2; H411			
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27-	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10	
	XXXX				
Hydrocarbons, C6-C7, isoalkanes, cyclics, <5% n-hexane	926-605-8 01-2119486291-36-	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2;		>= 2,5 - < 10	
	XXXX	H411			
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36-	Acute Tox.4; H302 Acute Tox.3; H331 Skin Irrit.2; H315 Eye Irrit.2; H319		>= 1 - < 10	
	XXXX		ATE (Oral): 1.200 mg/kg; ATE (Inhalation): 3 mg/l;		
calcium bis(dinonyInaphthalen	57855-77-3 260-991-2	Skin Irrit.2; H315 Eye Irrit.2; H319		>= 0,1 - < 1	





Version 2.6	Revision Da 07.03.2024		issue: 07.03.2024 issue: 22.06.2016		Date: 3.2024
esulphonate)			Skin Sens.1; H317		
Substance	es with a work	kplace exposure limit :			
butane		106-97-8 203-448-7 601-004-00-0 01-2119474691-32- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 30 - < 50
	oon waxes	8002-74-2 232-315-6	Not classified		>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled :	Call a physician or poison control centre immediately. Remove person to fresh air. If signs/symptoms continue, get medical attention. Keep patient warm and at rest. If unconscious, place in recovery position and seek medical advice. Keep respiratory tract clear. If breathing is irregular or stopped, administer artificial respiration.
In case of skin contact :	Take off all contaminated clothing immediately. Wash off immediately with soap and plenty of water. Get medical attention immediately if irritation develops and persists. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact :	Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes. If eye irritation persists, consult a specialist.
If swallowed :	Move the victim to fresh air. If accidentally swallowed obtain immediate medical attention. Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water. Aspiration hazard if swallowed - can enter lungs and cause





UN3 210	J1		
Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
		damage.	
4.2 Most in	mportant symptoms	s and effects, both acute and delayed	
Symp	toms	: Aspiration may cause pulmonary	oedema and pneumonitis.
		Inhalation may provoke the follow Unconsciousness Dizziness Drowsiness Headache Nausea Tiredness Skin contact may provoke the follo Erythema	
Risks		 Central nervous system depression Risk of product entering the lungs Health injuries may be delayed. Causes skin irritation. May cause an allergic skin reaction 	on vomiting after ingestion.

4.3 Indication of any immediate medical attention and special treatment needed

Treatme	nt
i reatme	ent

OKS 2101

: Treat symptomatically.

SECTION 5: Firefighting measures

5.1	Extinguishing media		
	Suitable extinguishing media	:	ABC powder
	Unsuitable extinguishing media	:	High volume water jet
5.2	Special hazards arising from	the	substance or mixture
	Specific hazards during firefighting	:	Fire Hazard Do not let product enter drains. Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
	Hazardous combustion products	:	Carbon oxides
5.3	Advice for firefighters		
	Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to





OKS 2101					
Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024		
Furth	er information	 decomposition products may be a Standard procedure for chemical Collect contaminated fire extingui must not be discharged into drain Cool containers/tanks with water 	fires. shing water separately. This s.		

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective
	Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions	:	Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
---------------------------	---	---

6.3 Methods and material for containment and cleaning up

Methods for cleaning up	:	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. Non-sparking tools should be used.
-------------------------	---	---

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling:Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory
equipment.
Avoid contact with skin and eyes.





OKS 21	OKS 2101					
Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024			
Нудіє	ene measures	 For personal protection see section Keep away from fire, sparks and he Smoking, eating and drinking shoul application area. Wash hands and face before break handling the product. Do not get in eyes or mouth or on s Do not get on skin or clothing. Do not use sparking tools. These safety instructions also apply may still contain product residues. Pressurized container: protect from expose to temperatures exceeding burn, even after use. Wash face, hands and any expose handling. 	eated surfaces. Id be prohibited in the as and immediately after skin. y to empty packaging which a sunlight and do not 50 °C. Do not pierce or			
7 2 Cond	itions for sofe stores	including any incompatibilities				
Requ	irements for storage s and containers	 including any incompatibilities BEWARE: Aerosol is pressurized. I exposure and temperatures over 50 or throw into fire even after use. Do red-hot objects. Store in accordance national regulations. 	0 °C. Do not open by force o not spray on flames or			
-	f ic end use(s) ific use(s)	: Specific instructions for handling, n	ot required.			

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	VMETime Weighted Average	800 ppm 1.900 mg/m3	FR VLE (2005-02-01)
	Further inform	rmation: Indicative exposure limits		
pentane	109-66-0	TWALimit Value - eight hours	1.000 ppm 3.000 mg/m3	2006/15/EC (2006-02-09)
	Further inform	nation: Indicative		
		VMETime Weighted Average	1.000 ppm 3.000 mg/m3	FR VLE (2012-07-01)





Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

	Further inform	ation: Regulatory bi	nding exposure limits			
Hydrocarbons, C9-	Not	VMETime	1.000 mg/m3	FR VLE		
C11, n-alkanes,	Assigned	Weighted		(2016-10-01)		
isoalkanes, cyclics,	-	Average				
<2% aromatics		(Vapour)				
	Further inform	ation: Indicative exp	osure limits			
		VLCT (VLE)Short	1.500 mg/m3	FR VLE		
		Term Exposure	_	(2016-10-01)		
		Limit (Vapour)				
	Further inform	ation: Indicative exp	osure limits			
Paraffin waxes and	8002-74-2	VMETime	2 mg/m3	FR VLE		
Hydrocarbon		Weighted		(2012-05-10)		
waxes		Average (Fumes)				
	Further inform	ation: Indicative exp	osure limits			
2-butoxyethanol	111-76-2	TWALimit Value -	20 ppm	2000/39/EC		
		eight hours	98 mg/m3	(2000-06-16)		
	Further inform	Further information: Identifies the possibility of significant uptake through the				
	skin, Indicativ	skin, Indicative				
		STELShort term	50 ppm	2000/39/EC		
		exposure limit	246 mg/m3	(2000-06-16)		
	Further inform	ation: Identifies the	possibility of significant uptal	through the		
	skin, Indicativ					
		VMETime	10 ppm	FR VLE		
		Weighted	49 mg/m3	(2012-07-01)		
		Average				
	Further inform	ation: Risk of peneti	ration through skin, Regulato	ry binding		
	exposure limit	S	_			
		VLCT (VLE)Short	50 ppm	FR VLE		
		Term Exposure	246 mg/m3	(2012-07-01)		
		Limit				
	Further inform	ation: Risk of peneti	ration through skin, Regulato	ry binding		
	exposure limit	S	exposure limits			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

	. ,			
Substance name	End Use	Exposure routes	Potential health effects	Value
pentane	Workers	Inhalation	Long-term systemic effects	3000 mg/m3
	Workers	Skin contact	Long-term systemic effects	432 mg/kg
Hydrocarbons, C11- C12, isoalkanes, < 2% aromatics	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
	Workers	Inhalation	Long-term local effects	837,5 mg/m3
Hydrocarbons, C6, isoalkanes, <5% n- hexane	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
	Workers	Inhalation	Long-term local effects	837,5 mg/m3



SAFETY DATA SHEET according to Regulation (EC) No. 1907/2006 - FR (Commission Regulation (EU) 2020/878)



OKS 2101

Version 2.6	Revision Date: 07.03.2024		last issue: 07.03.2024 first issue: 22.06.2016	Print D 07.03.	
C7, is	ocarbons, C6- soalkanes, cs, <5% n- ne	Workers	Inhalation	Acute systemic effects	1286,4 mg/m3
		Workers	Inhalation	Long-term local effects	837,5 mg/m3
2-but	toxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m3
		Workers	Inhalation	Acute systemic effects	1091 mg/m3
		Workers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
		Workers	Skin contact	Acute systemic effects	89 mg/kg bw/day
		Workers	Inhalation	Acute local effects	246 mg/m3
	um linonylnaphthalen phonate)	Workers	Inhalation	Long-term systemic effects	2,23 mg/m3
		Workers	Skin contact	Long-term systemic effects	0,32 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-butoxyethanol	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Soil	2,33 mg/kg
	Intermittent use/release	26,4 mg/l
calcium	Fresh water	0,27 mg/l
bis(dinonylnaphthalenesulphonat e)		
	Marine water	0,027 mg/l
	Intermittent use/release	2,7 mg/l
	Microbiological Activity in Sewage Treatment Systems	10 mg/l
	Fresh water sediment	4,69 mg/kg
	Marine sediment	0,469 mg/kg
	Soil	0,936 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection





	• •			
Version 2.6	Revision Date: 07.03.2024		e of last issue: 07.03.2024 e of first issue: 22.06.2016	Print Date: 07.03.2024
Material Break through time Protective index		:	Nitrile rubber > 10 min Class 1	
Remarks		:	Wear protective gloves. The break t amongst other things on the materia type of glove and therefore has to be case. The selected protective gloves have specifications of Regulation (EU) 20 EN 374 derived from it.	al, the thickness and the e measured for each e to satisfy the
Skin	and body protection	:	Choose body protection in relation to concentration and amount of dangent the specific work-place.	
Resp	iratory protection	:	Use respiratory protection unless ac ventilation is provided or exposure a that exposures are within recommer Short term only	ssessment demonstrates
Fi	lter type	:	Filter type A-P	
Prote	ctive measures	:	The type of protective equipment me to the concentration and amount of at the specific workplace.	

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state	:	aerosol
Colour	:	yellow
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	-161 °C (1.013 hPa)
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper	:	9,4 %(V)





Versi 2.6	ion	Revision Date: 07.03.2024		of last issue: 07.03.2024 of first issue: 22.06.2016	Print Date: 07.03.2024
f	flamma	ability limit			
		explosion limit / Lower ability limit	:	0,6 %(V)	
	Flash p	point	:	0 °C Method: Abel-Pensky	
	Auto-ig	nition temperature	:	No data available	
	Decom	position temperature	:	No data available	
	pН		:	Not applicable substance/mixture is non-soluble	e (in water)
,	Viscosi Visc	ity cosity, dynamic	:	No data available	
	Viso	cosity, kinematic	:	< 20,5 mm2/s (40 °C)	
:	Solubil Wat	ity(ies) ter solubility	:	insoluble	
	Solu	ubility in other solvents	5 :	No data available	
	Partitio octano	n coefficient: n- I/water	:	No data available	
,	Vapou	r pressure	:	8.327 hPa (20 °C)	
	Relativ	e density	:	0,638 (20 °C) Reference substance: Water The value is calculated	
	Density	4	:	0,64 g/cm3 (20 °C)	
	Bulk de	ensity	:	No data available	
	Relativ	e vapour density	:	No data available	
		e characteristics ticle size	:	No data available	
)ther ir Explos	nformation ives	:	Not explosive	
	Oxidizi	ng properties	:	No data available	





Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
Self-i	gnition	: No data available	
Metal corrosion rate		: Not corrosive to metals	
Evaporation rate		: No data available	
Sublimation point		: No data available	

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions	:	No dangerous reaction known under conditions of normal use.
---------------------	---	---

10.4 Conditions to avoid

Conditions to avoid	:	Heat, flames and sparks.
		Strong sunlight for prolonged periods.
		Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	
Product:	
Acute oral toxicity	: Remarks: Effects due to ingestion may include:
	Symptoms: Central nervous system depression
	Acute toxicity estimate: > 2.000 mg/kg Method: Calculation method





ersion 6	Revision Date: 07.03.2024		e of last issue: 07.03.2024 e of first issue: 22.06.2016	Print Date: 07.03.2024
Acute	e inhalation toxicity	:	Remarks: Respiration of solvent va	pour may cause dizziness.
			Symptoms: Inhalation may provoke Respiratory disorder, Dizziness, Dr Fatigue, Vertigo, Central nervous s	owsiness, Vomiting,
			Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method	
Acute	e dermal toxicity	:	Symptoms: Redness, Local irritatio	n
<u>Com</u>	ponents:			
Hydr	ocarbons, C9-C11, r	n-alkar	es, isoalkanes, cyclics, <2% arom	atics:
Acute	e inhalation toxicity	:	Assessment: The substance or mix target organ toxicant, single exposit narcotic effects.	
Hydr	ocarbons, C11-C12,	isoalk	anes, < 2% aromatics:	
Acute	e oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg Method: OECD Test Guideline 401	
Acute	e dermal toxicity	:	LD50 (Rabbit): > 5.000 mg/kg Method: OECD Test Guideline 402	
Hydr	ocarbons, C6, isoall	kanes,	<5% n-hexane:	
Acute	e oral toxicity	:	LD50 Oral (Rat): > 5.000 mg/kg	
isobu	utane:			
Acute	e inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: gas	
2-but	toxyethanol:			
Acute	e oral toxicity	:	Acute toxicity estimate: 1.200 mg/k Method: Acute toxicity estimate acc No. 1272/2008	
			LD50 (Guinea pig): 1.414 mg/kg Method: OECD Test Guideline 401	
Acute			Acute toxicity estimate: 3 mg/l	
	e inhalation toxicity		Test atmosphere: vapour Method: Acute toxicity estimate acc	cording to Regulation (EC)





OKS 21	OKS 2101						
Version 2.6	Revision Date: 07.03.2024		e of last issue: 07.03.2024 e of first issue: 22.06.2016	Print Date: 07.03.2024			
			No. 1272/2008				
			LC50: 3 mg/l Exposure time: 4 h Test atmosphere: vapour Assessment: The component/mixt inhalation.	ture is toxic after short term			
Acut	e dermal toxicity	:	LD50 (Guinea pig): > 2.000 mg/kg Method: OECD Test Guideline 40 Assessment: The substance or m toxicity	2			
calci	um bis(dinonyInaph	thalen	esulphonate):				
Acut	e oral toxicity	:	LD50 (Rat): > 5.000 mg/kg				
Acute	e dermal toxicity	:	LD50 (Rabbit): > 20.000 mg/kg				
buta Acute	ne: e inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: gas				
Skin	corrosion/irritation						
Prod	luct:						
Rem	arks	:	Irritating to skin.				
Com	ponents:						
Hydr	ocarbons, C9-C11, n	-alkan	es, isoalkanes, cyclics, <2% aror	natics:			
Resu	ılt	:	Repeated exposure may cause sk	in dryness or cracking.			
Hydı	ocarbons, C11-C12,	isoalk	anes, < 2% aromatics:				
Resu	ılt	:	Repeated exposure may cause sk	kin dryness or cracking.			
Hydı	ocarbons, C6, isoalk	anes,	<5% n-hexane:				
Resu	ılt	:	Skin irritation				
Hydr	ocarbons, C6-C7, iso	oalkan	es, cyclics, <5% n-hexane:				
Spec Resu		:	Rabbit Skin irritation				
2-bu	toxyethanol:						
Spec	cies	:	Rabbit				







sion	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
Asses Resu	ssment It	Irritating to skin.Irritating to skin.	
calci	um bis(dinonyInapl	nthalenesulphonate):	
Speci		: Rabbit	
•	ssment	: Irritating to skin.	
Resu	lt	: Irritating to skin.	
Serio	ous eye damage/eye	irritation	
Prod			
Rema	arks	: Irritating to eyes.	
<u>Com</u>	ponents:		
	oxyethanol:		
Speci		: Rabbit	
	ssment	: Irritating to eyes.	
Resu	It	: Irritating to eyes.	
calci	um bis(dinonyInapł	nthalenesulphonate):	
Speci		: Rabbit	
	ssment	: Irritating to eyes.	
Resu	It	: Irritating to eyes.	
Resp	iratory or skin sens	sitisation	
Prod			
Rema	arks	: This information is not available.	
<u>Com</u>	ponents:		
	oxyethanol:		
Test		: Maximisation Test	
Speci		: Guinea pig	
	ssment	: Did not cause sensitisation on labor	
Resu	It	: Did not cause sensitisation on labor	ratory animals.
		nthalenesulphonate):	
calci	um bis(dinonyInapł		
Speci	ies	: Guinea pig	
Speci	ies ssment	 Guinea pig May cause sensitisation by skin cor May cause sensitisation by skin cor 	





Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024
Germ	n cell mutagenicity		
Produ	uct:		
Geno	toxicity in vitro	: Remarks: No data availab	le
Geno	toxicity in vivo	: Remarks: No data availab	le
<u>Com</u>	ponents:		
2-but	oxyethanol:		
Geno	toxicity in vitro	: Test Type: In vitro mamma Method: OECD Test Guide Result: negative	alian cell gene mutation test eline 476
		Remarks: In vitro tests did	not show mutagenic effects
Geno	toxicity in vivo	: Test Type: In vivo micronu Species: Rat Method: OECD Test Guide Result: negative	
	cell mutagenicity- ssment	: In vitro tests did not show	mutagenic effects
Carci	inogenicity		
Produ	uct:		
Rema	arks	: No data available	
<u>Com</u>	ponents:		
2-but	oxyethanol:		
	nogenicity - ssment	: Animal testing did not show	w any carcinogenic effects.
Repro	oductive toxicity		
Produ	uct:		
Effect	ts on fertility	: Remarks: No data availab	le
	ts on foetal opment	: Remarks: No data availab	le
Com	ponents:		
2-but	oxyethanol:		
•	oductive toxicity - ssment	: - Fertility - No toxicity to reproduction	





KS 21	01			
ersion .6	Revision Date: 07.03.2024		e of last issue: 07.03.2024 e of first issue: 22.06.2016	Print Date: 07.03.2024
			- Teratogenicity -	
			Animal testing did not show any e development.	ffects on foetal
calci	um bis(dinonylnaph	thalen	esulphonate):	
Repro	oductive toxicity -	:	- Fertility -	
Asse	ssment		No toxicity to reproduction	
STO	T - single exposure			
Prod	uct:			
Rema	arks	:	No data available	
<u>Com</u>	ponents:			
penta	ane:			
Asse	ssment	:	May cause drowsiness or dizzine	SS.
Hydr	ocarbons, C9-C11, ı	n-alkar	nes, isoalkanes, cyclics, <2% aro	matics:
	sure routes ssment	:	Inhalation The substance or mixture is class toxicant, single exposure, categor	
Hydr	ocarbons, C6, isoal	kanes,	<5% n-hexane:	
Asse	ssment	:	May cause drowsiness or dizzine	SS.
Hydr	ocarbons, C6-C7, is	oalkar	nes, cyclics, <5% n-hexane:	
Asse	ssment	:	May cause drowsiness or dizzine	SS.
2-but	toxyethanol:			
Asse	ssment	:	The substance or mixture is not c organ toxicant, single exposure.	lassified as specific target
calci	um bis(dinonylnaph	thalen	esulphonate):	
Asse	ssment	:	The substance or mixture is not c organ toxicant, single exposure.	lassified as specific target
STO	T - repeated exposu	re		
Prod				
Rema	arks	:	No data available	





Version 2.6	Revision Date: 07.03.2024		e of last issue: 07.03.2024 e of first issue: 22.06.2016	Print Date: 07.03.2024
Co	mponents:			
2-b	utoxyethanol:			
	essment	:	The substance or mixture is not cla organ toxicant, repeated exposure	
cal	cium bis(dinonylnaph	thalen	esulphonate):	
Ass	sessment	:	The substance or mixture is not cla organ toxicant, repeated exposure	
Rej	peated dose toxicity			
Pro	duct:			
Rer	marks	:	This information is not available.	
Asj	piration toxicity			
Pro	duct:			
Ma	y be fatal if swallowed a	and ent	ers airways.	
Ma	y be fatal if swallowed a	and ent	ers airways.	
<u>Co</u>	mponents:			
per	ntane:			
Ma	y be fatal if swallowed a	and ent	ers airways.	
•	drocarbons, C9-C11, ı y be fatal if swallowed a		es, isoalkanes, cyclics, <2% aron ers airways.	natics:
Hve	drocarbons, C11-C12,	isoalk	anes, < 2% aromatics:	
-	y be fatal if swallowed a			
Нус	drocarbons, C6, isoal	kanes,	<5% n-hexane:	
Ma	y be fatal if swallowed a	and ente	ers airways.	
•			es, cyclics, <5% n-hexane:	
Ma	y be fatal if swallowed a	and ent	ers airways.	
2-b	utoxyethanol:			
No	aspiration toxicity class	sification	1	
	cium bis(dinonylnaph		• •	
No	aspiration toxicity class	sificatior	1	
			10 / 31	a brand of





Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

11.2 Information on other hazards

Endocrine disrupting properties					
Product:					
Assessment	: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.				
Further information					
Product:					
Remarks	: Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.				
Components:					
Paraffin waxes and Hydrocarbon waxes:					
Remarks	 Information given is based on data on the components and the toxicology of similar products. 				

SECTION 12: Ecological information

12.1 Toxicity

Product:		
Toxicity to fish	:	Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available
Components:		
pentane:		
Ecotoxicology Assessment		
Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.





Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

··· , ·································		,
Ecotoxicology Assessment Acute aquatic toxicity		Toxic to aquatic life.
Addie aqualle texicity	•	
Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.
Hydrocarbons, C6, isoalkan	es,	<5% n-hexane:
Toxicity to daphnia and other aquatic invertebrates		EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l Exposure time: 48 h
Hydrocarbons, C6-C7, isoall	kan	es, cyclics, <5% n-hexane:
Ecotoxicology Assessment		
Chronic aquatic toxicity	:	Toxic to aquatic life with long lasting effects.
2-butoxyethanol:		
Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 1.474 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 203
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 1.550 mg/l Exposure time: 48 h Test Type: Immobilization Method: OECD Test Guideline 202
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 1.840 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
		NOEC (Pseudokirchneriella subcapitata (green algae)): 286 mg/l Exposure time: 72 h Method: OECD Test Guideline 201
Toxicity to fish (Chronic toxicity)	:	NOEC: > 100 mg/l Exposure time: 21 d Species: Danio rerio (zebra fish)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	:	NOEC: 100 mg/l Exposure time: 21 d Species: Daphnia magna (Water flea) Test Type: Reproduction Test Method: OECD Test Guideline 211





UK5 210	U1			
Version 2.6	Revision Date: 07.03.2024		f last issue: 07.03.2024 f first issue: 22.06.2016	Print Date: 07.03.2024
calci	um bis(dinonyInaphth	alenesi	Ilphonate):	
Toxic	ity to fish	E: To M	C50 (Cyprinus carpio (Carp)): > kposure time: 96 h est Type: static test ethod: OECD Test Guideline 20 emarks: No toxicity at the limit o	03
	ity to daphnia and other tic invertebrates	E: To M	C50 (Daphnia magna (Water fle kposure time: 48 h est Type: static test ethod: OECD Test Guideline 20 emarks: No toxicity at the limit o)2
	oxicology Assessmen			
Chroi	nic aquatic toxicity	: TI	nis product has no known ecoto	xicological effects.
2.2 Pers	istence and degradab	ility		
Prod	uct:			
Biode	egradability	: R	emarks: No data available	
	ico-chemical vability	: R	emarks: No data available	
Com	ponents:			
Hydr	ocarbons, C11-C12, is	oalkan	es, < 2% aromatics:	
Biode	egradability	: R	esult: Not readily biodegradable).
Hydr	ocarbons, C6, isoalka	nes, <5	% n-hexane:	
Biode	egradability	: R	esult: Not rapidly biodegradable	•
2-but	oxyethanol:			
	egradability	R Bi Ei	est Type: aerobic esult: rapidly biodegradable odegradation: 90 % kposure time: 28 d ethod: OECD Test Guideline 30)1B
calci	um bis(dinonyInaphth	alenesi	Ilphonate):	
Biode	egradability	: R	esult: Not readily biodegradable).
2.3 Bioa	ccumulative potential			
Prod	uct:			
Bioac	cumulation	: R	emarks: This mixture contains r	to substance considered to
			22/24	a brand of





OK	OKS 2101					
Vers 2.6	sion	Revision Date: 07.03.2024		e of last issue: 07.03.2024 e of first issue: 22.06.2016	Print Date: 07.03.2024	
				be persistent, bioaccumulating and to This mixture contains no substance contains and very bioaccumulating (onsidered to be very	
	<u>Comp</u>	onents:				
		ne: on coefficient: n- I/water	:	log Pow: 2,36		
	Hydro	carbons, C11-C12, i	isoalk	anes, < 2% aromatics:		
	Bioaco	cumulation	:	Remarks: No data available		
		on coefficient: n- I/water	:	Remarks: No data available		
	Hvdro	carbons, C6, isoalk	anes.	<5% n-hexane:		
	•	umulation	:	Remarks: No data available		
		on coefficient: n- I/water	:	log Pow: 4		
	isobut	ane:				
		on coefficient: n- I/water	:	log Pow: 2,88 Method: OECD Test Guideline 107		
	2-butc	oxyethanol:				
	Bioaco	cumulation	:	Bioconcentration factor (BCF): 3,16		
		on coefficient: n- I/water	:	log Pow: 0,81 (25 °C) Method: OECD Test Guideline 107		
	calciu	m bis(dinonylnapht	halen	esulphonate):		
	Partitic	on coefficient: n- I/water	:	log Pow: 10,96		
	butan	e:				
	Partitic	on coefficient: n- I/water	:	log Pow: 2,89 Method: OECD Test Guideline 107		
12.4	Mobili	ity in soil				
	Produ	-				
	Mobilit		:	Remarks: No data available		





Version 2.6	Revision Date: 07.03.2024	Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	
	ibution among onmental compartme	: Remarks: No data availa ts	ble
12.5 Resi	ults of PBT and vPvE	assessment	
Prod	luct:		
Assessment		to be either persistent, bi	contains no components considered oaccumulative and toxic (PBT), or bioaccumulative (vPvB) at levels of
Com	ponents:		
calci	um bis(dinonylnaph	halenesulphonate):	
Asse	essment	: Non-classified PBT subs	tance. Non-classified vPvB substance
12.6 End	ocrine disrupting pro	perties	
Prod	luct:		
Asse	ssment	considered to have endo to REACH Article 57(f) o	oes not contain components crine disrupting properties according r Commission Delegated regulation nission Regulation (EU) 2018/605 at
12.7 Othe	er adverse effects		
Prod	luct:		
	tional ecological mation	: Toxic to aquatic life with	long lasting effects.
SECTIO	N 13: Disposal con	siderations	
13.1 Was	te treatment method		
Product		: Do not dispose of with do	omestic refuse. waste in compliance with local and
		Waste codes should be a application for which the	assigned by the user based on the product was used.
Cant	aminated packaging	De alva sin a that is not and	party amptiad must be disposed of a





OKS 2101						
		Date of last issue: 07.03.2024 Date of first issue: 22.06.2016	Print Date: 07.03.2024			
Wast	e Code	 The following Waste Codes are o unused product, packagings not o 16 05 04**, gases in pressure cor containing hazardous substances 	completely emptied ntainers (including halons)			

SECTION 14: Transport information

14.1	14.1 UN number or ID number				
	ADN	:	UN 1950		
	ADR	:	UN 1950		
	RID	:	UN 1950		
	IMDG	:	UN 1950		
	ΙΑΤΑ	:	UN 1950		
14.2	UN proper shipping name				
	ADN	:	AEROSOLS		
	ADR	:	AEROSOLS ()		
	RID	:	AEROSOLS		
	IMDG	:	AEROSOLS (naphtha (petroleum), hydrotreated light, cyclohexane)		
	ΙΑΤΑ	:	Aerosols, flammable (naphtha (petroleum), hydrotreated light)		
14.3	Transport hazard class(es)				
	ADN	:	2		
	ADR	:	2		
	RID	:	2		
	IMDG	:	2.1		
	ΙΑΤΑ	:	2.1		
14.4	Packing group				
	ADN Packing group Classification Code Labels ADR Packing group Classification Code	::	Not assigned by regulation 5F 2.1 Not assigned by regulation 5F		



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR (Commission Regulation (EU) 2020/878)



OKS 2101

Ver 2.6	sion			e of last issue: 07.03.2024 e of first issue: 22.06.2016	Print Date: 07.03.2024	
		l restriction code	:	2.1 (D)		
	Classif	g group ication Code d Identification Number	: : :	Not assigned by regulation 5F 23 2.1		
	IMDG Packin Labels EmS C		::	Not assigned by regulation 2.1 F-D, S-U		
	Packin aircraft Packin	g instruction (LQ) g group	:	203 Y203 Not assigned by regulation Flammable Gas		
	Packin (passe Packin	Passenger) g instruction nger aircraft) g instruction (LQ) g group	:	203 Y203 Not assigned by regulation Flammable Gas		
14.5	5 Enviro	onmental hazards				
	ADN Enviro	nmentally hazardous	:	yes		
	ADR Enviro	nmentally hazardous	:	yes		
	RID Enviro	nmentally hazardous	:	yes		
	IMDG Marine	pollutant	:	yes		

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks

: Not applicable for product as supplied.





Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/le mixture	gislatio	n specific for the substance or
REACH - Restrictions on the manufacture, placing the market and use of certain dangerous substance mixtures and articles (Annex XVII)		Conditions of restriction for the following entries should be considered: Number on list 75 2-butoxyethanol (Number on list 3)
REACH - Candidate List of Substances of Very Hig Concern for Authorisation (Article 59). (EU SVHC)	jh :	This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009)	:	Not applicable
Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP)	:	Not applicable
Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export a import of dangerous chemicals (EU PIC)	: and	Not applicable
Regulation (EU) 2019/1148 on the marketing and u explosives precursors	ise of :	Not applicable
	P2	
Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.	P3a	FLAMMABLE AEROSOLS
	E2	ENVIRONMENTAL HAZARDS
	18	Liquefied flammable gases (including LPG) and natural gas
		a brand of





Version 2.6	Revision Date: 07.03.2024		e of last issue: 07.03.2024 e of first issue: 22.06.2016	Print Date: 07.03.2024
			34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)
	ational Illnesses (R- France)	:	84, 36, 36 bis	
	vrced medical vision (R4624-18)	:	The product has no CMR	properties
protec	ations classified for the tion of the environment onment Code R511-9)		4320, 4511, 4718, 4734, 1	436
Volatil	e organic compounds	:	emissions (integrated pollu	4 November 2010 on industrial ution prevention and control) ds (VOC) content: 93,32 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066	:	Repeated exposure may cause skin dryness or cracking.
H220	:	Extremely flammable gas.
H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H280	:	Contains gas under pressure; may explode if heated.





Version	Revision Date:	Date of last issue: 07.03.2024	Print Date: 07.03.2024
2.6	07.03.2024	Date of first issue: 22.06.2016	
H302 H304 H315 H317 H319 H331 H336 H411 EUH0	66	 Harmful if swallowed. May be fatal if swallowed and en Causes skin irritation. May cause an allergic skin reacti Causes serious eye irritation. Toxic if inhaled. May cause drowsiness or dizzine Toxic to aquatic life with long last Repeated exposure may cause series 	on. ess. ting effects.

Full text of other abbreviations

Note C	:	Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Note P	:	The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply.
Note U (table 3.1)	:	When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC FR VLE 2000/39/EC / TWA 2000/39/EC / STEL 2006/15/EC / TWA FR VLE / VME		Europe. Indicative occupational exposure limit values France. Occupational Exposure Limits Limit Value - eight hours Short term exposure limit Limit Value - eight hours Time Weighted Average





Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

FR VLE / VLCT (VLE)

: Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development: OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance: PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification	of	the	mixture:	

Classification of the mixte	ıre:	Classification procedure:
Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Based on product data or assessment
Aquatic Chronic 2	H411	Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with





Version	Revision Date:	Date of last issue: 07.03.2024	Print Date:
2.6	07.03.2024	Date of first issue: 22.06.2016	07.03.2024

amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

