

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2351

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricant spray

Recommended restrictions
on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599
info@oks-germany.com

E-mail address of person
responsible for the SDS : mcm@oks-germany.com
Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone num-
ber : +34 91 562 04 20

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single ex-
posure, Category 3, Central nervous
system H336: May cause drowsiness or dizziness.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-
ways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)






OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :   

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H336 May cause drowsiness or dizziness.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331 Do NOT induce vomiting.
Storage:
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | specific concentration limit M-Factor Notes Acute toxicity estimate | Concentration (% w/w) |
|---|---|--|--|-----------------------|
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | 921-024-6 01-2119475514-35-XXXX | Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411 | | >= 10 - < 20 |
| Kaolin, calcined | 92704-41-1 296-473-8 | Eye Irrit.2; H319 STOT SE3; H335 | | >= 1 - < 10 |
| Substances with a workplace exposure limit : | | | | |
| butane | 106-97-8 203-448-7 601-004-00-0 | Flam. Gas1A; H220 Press. GasCompr. Gas; H280 | Note U (table 3.1), Note C | >= 30 - < 50 |
| propane | 74-98-6 200-827-9 601-003-00-5 01-2119486944-21-XXXX | Flam. Gas1A; H220 Press. GasCompr. Gas; H280 | Note U (table 3.1) | >= 10 - < 20 |
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | 64742-54-7 265-157-1 649-467-00-8 | Not classified | Note L | >= 10 - < 20 |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.1 Revision Date: 08.09.2021 Date of last issue: 19.04.2021 Print Date: 09.09.2021
Date of first issue: 26.10.2016

| | | | | |
|---|--|---|----------------------------|------------------|
| | 01-2119484627-25-XXXX | | | |
| distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 265-169-7 649-474-00-6 01-2119471299-27-XXXX | Not classified | Note L | $\geq 10 - < 20$ |
| aluminium powder (stabilised) | 7429-90-5 231-072-3 013-002-00-1 01-2119529243-45-XXXX | Flam. Sol.1; H228 | | $\geq 1 - < 10$ |
| isobutane | 75-28-5 200-857-2 601-004-00-0 01-2119485395-27-XXXX | Flam. Gas1A; H220 Press. GasCompr. Gas; H280 | Note U (table 3.1), Note C | $\geq 1 - < 10$ |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash off immediately with plenty of water.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness

Drowsiness

Headache

Nausea

Tiredness

Skin contact may provoke the following symptoms:

Erythema

Risks : Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Metal oxides

5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.
- Further information : Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

- Environmental precautions : Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not use in areas without adequate ventilation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|---|------------|-------------------------------|---------------------|---------------------|
| butane | 106-97-8 | VLA-ED (gas) | 1.000 ppm | ES VLA (2013-02-22) |
| propane | 74-98-6 | VLA-ED | 1.000 ppm | ES VLA (2011-03-03) |
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | 64742-54-7 | VLA-ED (Mist) | 5 mg/m ³ | ES VLA (2013-02-22) |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

Version 3.1 Revision Date: 08.09.2021 Date of last issue: 19.04.2021 Print Date: 09.09.2021
Date of first issue: 26.10.2016

| | | | | |
|---|------------|---------------|----------------------|---------------------|
| | | VLA-EC (Mist) | 10 mg/m ³ | ES VLA (2013-02-22) |
| distillates (petroleum), solvent-dewaxed heavy paraffinic | 64742-65-0 | VLA-ED (Mist) | 5 mg/m ³ | ES VLA (2013-02-22) |
| | | VLA-EC (Mist) | 10 mg/m ³ | ES VLA (2013-02-22) |
| aluminium powder (stabilised) | 7429-90-5 | VLA-ED (Dust) | 10 mg/m ³ | ES VLA (2013-02-22) |
| isobutane | 75-28-5 | VLA-ED (gas) | 1.000 ppm | ES VLA (2013-02-22) |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health effects | Value |
|---|---------|-----------------|----------------------------|------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | Workers | Inhalation | Long-term local effects | 5,6 mg/m ³ |
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | Workers | Skin contact | Long-term systemic effects | 773 mg/kg bw/day |
| | Workers | Inhalation | Long-term systemic effects | 2035 mg/m ³ |
| aluminium powder (stabilised) | Workers | Inhalation | Long-term systemic effects | 3,72 mg/m ³ |
| | Workers | Inhalation | Long-term local effects | 3,72 mg/m ³ |

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

| Substance name | Environmental Compartment | Value |
|---|---------------------------|-------------|
| Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified | Oral | 9,33 mg/kg |
| distillates (petroleum), solvent-dewaxed heavy paraffinic | Oral | 9,33 mg/kg |
| aluminium powder (stabilised) | Fresh water | 0,0749 mg/l |
| | Sewage treatment plant | 20 mg/l |

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

- Protective index : Class 1
- Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Short term only
- Filter type : Filter type A-P
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- Physical state : aerosol
- Colour : grey
- Odour : characteristic
- Odour Threshold : No data available
- Melting point/range : No data available
- Boiling point/boiling range : -44,5 °C (1.013 hPa)
- Flammability : Extremely flammable aerosol.
- Upper explosion limit / Upper flammability limit : 10,9 %(V)
- Lower explosion limit / Lower flammability limit : 0,8 %(V)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Flash point : -97,00 °C
Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature
Decomposition temperature : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 4.750 hPa (20 °C)

Relative density : 0,7 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,70 g/cm³
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg
Assessment: The substance or mixture has no acute dermal toxicity

Kaolin, calcined:

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5,09 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Test atmosphere: dust/mist
Assessment: The substance or mixture has no acute inhalation toxicity

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : Irritating to skin.
Method : OECD Test Guideline 404
Result : Irritating to skin.

Kaolin, calcined:

Result : Repeated exposure may cause skin dryness or cracking.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit
Assessment : No skin irritation
Method : OECD Test Guideline 404
Result : No skin irritation
GLP : yes

aluminium powder (stabilised):

Species : Rabbit
Assessment : No skin irritation
Result : No skin irritation

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

Kaolin, calcined:

Result : Irritating to eyes.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Rabbit
Assessment : No eye irritation
Method : OECD Test Guideline 405
Result : No eye irritation
GLP : yes

aluminium powder (stabilised):

Species : Rabbit
Assessment : No eye irritation
Result : No eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test
Exposure routes : Dermal
Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Did not cause sensitisation on laboratory animals.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Guinea pig
Assessment : Does not cause skin sensitisation.
Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.
GLP : yes

aluminium powder (stabilised):

Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available
Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro
Test system: Rodent cell line
Method: OECD Test Guideline 473
Result: negative

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Genotoxicity in vitro : Test system: Salmonella typhimurium
Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Carcinogenicity

Product:

Remarks : No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Species : Mouse
Application Route : Dermal
Method : OECD Test Guideline 451
Result : negative

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Reproductive toxicity - Assessment : - Fertility -
No toxicity to reproduction

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Effects on foetal development : Species: Rat
Application Route: Dermal
General Toxicity Maternal: NOAEL: 30 mg/kg body weight
Developmental Toxicity: NOAEL: 30 mg/kg body weight
Method: OECD Test Guideline 414

STOT - single exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Kaolin, calcined:

Exposure routes : Inhalation
Assessment : The substance or mixture is classified as specific target organ

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

toxicant, single exposure, category 3 with respiratory tract irritation.

STOT - repeated exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

distillates (petroleum), solvent-dewaxed heavy paraffinic:

No aspiration toxicity classification

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

SECTION 12: Ecological information

12.1 Toxicity

Product:

- Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available
- Toxicity to algae/aquatic plants : Remarks: No data available
- Toxicity to microorganisms : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202
GLP: yes
- Toxicity to algae/aquatic plants : EbC50 (Pseudokirchneriella subcapitata (green algae)): 26 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Ecotoxicology Assessment

- Acute aquatic toxicity : Toxic to aquatic life.
- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 48 h
Test Type: Immobilization

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10.000 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 10 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

aluminium powder (stabilised):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,12 mg/l
Exposure time: 96 h
Test Type: static test
Remarks: No toxicity at the limit of solubility

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 3 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
GLP: yes

distillates (petroleum), solvent-dewaxed heavy paraffinic:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: Not rapidly biodegradable
Biodegradation: 31 %
Exposure time: 28 d
Method: OECD Test Guideline 301B
GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Partition coefficient: n-octanol/water : log Pow: > 2

isobutane:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

Distillates (petroleum), hydrotreated heavy paraffinic; Baseoil — unspecified:

Assessment : Non-classified vPvB substance. Non-classified PBT substance.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS
IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR
Packing group : Not assigned by regulation
Classification Code : 5F
Labels : 2.1
Tunnel restriction code : (D)

RID
Packing group : Not assigned by regulation
Classification Code : 5F
Hazard Identification Number : 23

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Labels : 2.1

IMDG

Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passenger aircraft) : 203
Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

(EU. REACH - Annex XIV)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009) : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors :

Acquisition, introduction, possession or use of the explosive precursor by the general public is subject to reporting obligations. aluminium powder (stabilised) (ANNEX II)

: P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P3a FLAMMABLE AEROSOLS

18 Liquefied extremely flammable gases (including LPG) and natural gas

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 62,5 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

| | |
|--------|---|
| H220 | : Extremely flammable gas. |
| H225 | : Highly flammable liquid and vapour. |
| H228 | : Flammable solid. |
| H280 | : Contains gas under pressure; may explode if heated. |
| H304 | : May be fatal if swallowed and enters airways. |
| H315 | : Causes skin irritation. |
| H319 | : Causes serious eye irritation. |
| H335 | : May cause respiratory irritation. |
| H336 | : May cause drowsiness or dizziness. |
| H411 | : Toxic to aquatic life with long lasting effects. |
| EUH066 | : Repeated exposure may cause skin dryness or cracking. |

Full text of other abbreviations

| | |
|--------------------|---|
| Note C | : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers. |
| Note L | : The classification as a carcinogen need not apply if it can be shown that the substance contains less than 3 % DMSO extract as measured by IP 346 "Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method", Institute of Petroleum, London. This note applies only to certain complex oil-derived substances in Part 3. |
| Note U (table 3.1) | : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part |

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

ES VLA : 2, Section 2.3.2.1, Note 2).
Spain. Environmental Limits for exposure to Chemical agents
- Table 1: Occupational Exposure Values
ES VLA / VLA-ED : Environmental Daily Limit Value
ES VLA / VLA-EC : Environmental Short Term Value

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

| | |
|-------------------|------------|
| Aerosol 1 | H222, H229 |
| Skin Irrit. 2 | H315 |
| STOT SE 3 | H336 |
| Asp. Tox. 1 | H304 |
| Aquatic Chronic 3 | H412 |

Classification procedure:

| |
|-------------------------------------|
| Based on product data or assessment |
| Calculation method |
| Based on product data or assessment |
| Based on product data or assessment |
| Calculation method |

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particu-

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES
(Commission Regulation (EU) 2020/878)



OKS 2351

| | | | |
|---------|----------------|---------------------------------|-------------|
| Version | Revision Date: | Date of last issue: 19.04.2021 | Print Date: |
| 3.1 | 08.09.2021 | Date of first issue: 26.10.2016 | 09.09.2021 |

lar public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.