according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2351

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant spray

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone num: +49 8142 3051 517

ber Warszawa: +48 22 619 66 54

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Long-term (chronic) aquatic hazard, Cat-

egory 3

H412: Harmful to aquatic life with long lasting ef-

fects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters air-

ways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness. H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6 01-2119475514-35- XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 10 - < 20	
Kaolin, calcined	92704-41-1 296-473-8	Eye Irrit.2; H319 STOT SE3; H335; EUH066		>= 1 - < 10	
aluminium powder (stabilised)	7429-90-5 231-072-3 013-002-00-1 01-2119529243-45- XXXX	Flam. Sol.1; H228	Note T	>= 1 - < 10	
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10	
	Substances with a workplace exposure limit :				
butane	106-97-8	Flam. Gas1A;		>= 30 - < 50	

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

	203-448-7 601-004-00-0 01-2119474691-32- XXXX	H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 10 - < 20
distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- XXXX	Not classified	Note L	>= 10 - < 20
Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	64742-65-0 265-169-7 649-474-00-6 01-2119471299-27- XXXX	Not classified	Note L	>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse. Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod- : Carbon oxides

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

ucts Nitrogen oxides (NOx)

Metal oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	NDS	1.900 mg/m3	PL OEL (2018-07-07)
		NDSch	3.000 mg/m3	PL OEL (2018-07-07)
propane	74-98-6	NDS	1.800 mg/m3	PL OEL (2018-07-07)
distillates (petrole- um), hydrotreated	64742-54-7	NDS (inhalable fraction)	5 mg/m3	PL OEL (2021-02-19)

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

heavy paraffinic				
Distillates (petrole-	64742-65-0	NDS (inhalable	5 mg/m3	PL OEL
um), solvent-		fraction)		(2021-02-19)
dewaxed heavy				
paraffinic; Baseoil				
 unspecified 				

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
distillates (petroleum), hydrotreated heavy paraffinic	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Distillates (petrole- um), solvent-dewaxed heavy paraffinic; Baseoil — unspecified	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
aluminium powder (stabilised)	Workers	Inhalation	Long-term systemic effects	3,72 mg/m3
	Workers	Inhalation	Long-term local ef- fects	3,72 mg/m3

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
distillates (petroleum), hy-	Oral	9,33 mg/kg
drotreated heavy paraffinic		
Distillates (petroleum), solvent-	Oral	9,33 mg/kg
dewaxed heavy paraffinic;		
Baseoil — unspecified		

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Break through time : > 10 min Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : grey

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -44,5 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

10,9 %(V)

Lower explosion limit / Lower : 0,8 %(V)

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

flammability limit

Flash point : -97,00 °C

Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 4.750 hPa (20 °C)

Relative density : 0,7 (20 °C)

Reference substance: Water The value is calculated

Density : 0,70 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific

target organ toxicant, single exposure, category 3 with narcot-

ic effects.

Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fa-

tigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Kaolin, calcined:

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific

target organ toxicant, single exposure, category 3 with respira-

tory tract irritation.

aluminium powder (stabilised):

Acute inhalation toxicity : LC50 (Rat): > 5,09 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

Kaolin, calcined:

Result : Repeated exposure may cause skin dryness or cracking.

aluminium powder (stabilised):

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation

distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

Kaolin, calcined:

Result : Irritating to eyes.

aluminium powder (stabilised):

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

aluminium powder (stabilised):

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals. Result : Did not cause sensitisation on laboratory animals.

distillates (petroleum), hydrotreated heavy paraffinic:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406
Result : Does not cause skin sensitisation.

GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Rodent cell line Method: OECD Test Guideline 473

Result: negative

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Genotoxicity in vitro : Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

Carcinogenicity

Product:

Remarks : No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Species : Mouse Application Route : Dermal

Method : OECD Test Guideline 451

Result : negative

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

: Remarks: No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Reproductive toxicity - As- : - Fertility -

sessment No toxicity to reproduction

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Effects on foetal develop- : Species: Rat

ment Application Route: Dermal

General Toxicity Maternal: NOAEL: 30 mg/kg body weight Developmental Toxicity: NOAEL: 30 mg/kg body weight

Method: OECD Test Guideline 414

STOT - single exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Kaolin, calcined:

Exposure routes : Inhalation

Assessment : The substance or mixture is classified as specific target organ

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

toxicant, single exposure, category 3 with respiratory tract

irritation.

STOT - repeated exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)

Assessment : No significant health effects observed in animals at concentra-

tions of 1 mg/l/6h/d or less.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

distillates (petroleum), hydrotreated heavy paraffinic:

No aspiration toxicity classification

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

Remarks : Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EbC50 (Pseudokirchneriella subcapitata (green algae)): 26

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

aluminium powder (stabilised):

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,12 mg/l

Exposure time: 96 h Test Type: static test

Remarks: No toxicity at the limit of solubility

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Ecotoxicology Assessment

Acute aquatic toxicity This product has no known ecotoxicological effects.

Chronic aquatic toxicity This product has no known ecotoxicological effects.

distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

> Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOEC: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Toxicity to fish

> Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

NOEC (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOEC: 10 mg/l Exposure time: 21 d

ic toxicity)

Species: Daphnia magna (Water flea)

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

12.2 Persistence and degradability

Product:

Biodegradability Remarks: No data available

Physico-chemical removabil- : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

: Result: Readily biodegradable. Biodegradability

distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability Test Type: aerobic

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

Distillates (petroleum), solvent-dewaxed heavy paraffinic; Baseoil — unspecified:

Biodegradability Test Type: aerobic

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 31 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

12.3 Bioaccumulative potential

Product:

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

isobutane:

Partition coefficient: nlog Pow: 2,88

octanol/water Method: OECD Test Guideline 107

butane:

Partition coefficient: nlog Pow: 2,89

Method: OECD Test Guideline 107 octanol/water

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Date of last issue: 08.09.2021 Version Revision Date: Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

distillates (petroleum), hydrotreated heavy paraffinic:

Partition coefficient: n-

octanol/water

: log Pow: > 2

12.4 Mobility in soil

Product:

Mobility Remarks: No data available

Distribution among environ-

mental compartments

: Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

mation

Additional ecological infor- : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



Not applicable

Article 57).

Not applicable

Not applicable

Not applicable

Not applicable

(ANNEX II)

This product does not contain sub-

stances of very high concern (Regu-

lation (EC) No 1907/2006 (REACH),

OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

(EU SVHC)

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH-Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer (EC 1005/2009)

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast) (EU POP)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

(EU PIC)

Regulation (EU) 2019/1148 on the marketing and use of : Listed

explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant na-

tional contact point. Please see

https://ec.europa.eu/home-affairs/sites/ homeaf-

fairs/files/what-we-do/policies/crisis-and-

terrorism/explosives/explosives-

precur-

sors/docs/list_of_competent_authorities_and_national_c

ontact_points_en.pdf

: P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous sub-

stances.

P3a FLAMMABLE AEROSOLS

18 Liquefied extremely flammable

aluminium powder (stabilised)

a brand of

FREUDENBERG

24 / 28

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

VersionRevision Date:Date of last issue: 08.09.2021Print Date:3.220.01.2023Date of first issue: 26.10.201620.01.2023

gases (including LPG) and natural gas

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 62,5 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Act of 25 February 2011 on chemical substances and their mixtures (i.e. Journal of Laws of 2019, No. 0, item 1225)

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2020/878

Ordinance of the Minister of Health of 10 August 2012 concerning the criteria and procedure of classification of chemical substances and their mixtures (consolidated text Dz. U. of 2015., pos. 208).

Ordinance of the Minister of Economy, Labour and Social Policy of 21st December 2005 concerning the basic requirements for personal protective equipment (Dz. U. Nr. 259, item 2173). Ordinance of the Minister of Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286, with later amendments).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166 wraz z późn. zm.). Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (Dz. U. from 2005, Nr. 11, item 86, as amended). Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

Act of 13 June 2013. On packaging and packaging waste Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Climate of 2nd January 2020 on Waste Catalog (Dz. U. 2020 item 10).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of 18 February 2019 on enforcing of changes Annexes A and B of Agreement concerning international transport of dangerous goods by road (ADR) (Dz. U. 2019, item 769).

Ordinance of the Minister of Health of 20th April 2012 concerning labeling of containers of dangerous substances and dangerous mixtures and some mixtures ((consolidated text) Dz. U. z 2015 nr. 0 poz. 450).

Ordinance of the Minister of Health of 11th June 2012 concerning categories of dangerous substances and dangerous mixtures for which containers must be fitted with child-resistant fastenings and a tactile warning of danger (Dz. U. from 2012, item 688 as amended).

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.

H228 : Flammable solid.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.
H335 : May cause respiratory irritation.
H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Note C

: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this

case the supplier must state on the label whether the sub-



according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

Version Revision Date: Date of last issue: 08.09.2021 Print Date: 3.2 20.01.2023 Date of first issue: 26.10.2016 20.01.2023

stance is a specific isomer or a mixture of isomers.

Note L : The harmonised classification as a carcinogen applies unless

it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method"Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard

class.

Note T : This substance may be marketed in a form which does not

have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be in-

cluded in the safety data sheet.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

PL OEL : Poland. Occupational exposure limits for airborne toxic sub-

stances

PL OEL / NDS : Maximal Admissible Concentration

PL OEL / NDSch : Maximal Admissible Temporary Concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified;

according to Regulation (EC) No. 1907/2006 - PL (Commission Regulation (EU) 2020/878)



OKS 2351

 Version
 Revision Date:
 Date of last issue: 08.09.2021
 Print Date:

 3.2
 20.01.2023
 Date of first issue: 26.10.2016
 20.01.2023

NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment Skin Irrit. 2 H315 Calculation method STOT SE 3 H336 Based on product data or assessment Asp. Tox. 1 H304 Based on product data or assessment Aquatic Chronic 3 H412 Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.