

OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

1. Identification of the substance/mixture and of the company/undertaking

Product information

Product name : OKS 235

Use of the Substance/Mixture : Lubricant

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599

E-mail address : mcm@oks-germany.com

National contact :

Emergency telephone number : +7 495 628 1687
+49 8142 3051 517

2. Hazards identification

GHS Classification

: Skin sensitisation, Category 1

GHS-Labeling

Symbol(s) :



Signal word : Warning

Hazard statements : H317: May cause an allergic skin reaction.

Precautionary statements : **Prevention:**
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves.
Response:
P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P362 + P364 Take off contaminated clothing and wash it before reuse.

3. Composition/information on ingredients

Chemical nature : Synthetic hydrocarbon oil



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

Metal powder

Hazardous components

Chemical name	CAS-No.	Concentration[%]
Aluminium powder (desensitized)	7429-90-5	1 - 10
Silicon dioxide	7631-86-9	1 - 10
Titanium dioxide	13463-67-7	1 - 10
White mineral oil (petroleum)	8042-47-5	1 - 10
calcium bis(dinonylnaphthalenesulphonate)	57855-77-3	0,1 - 1
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts	70024-69-0	0,1 - 1

4. First aid measures

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do not induce vomiting without medical advice.
Never give anything by mouth to an unconscious person.

Notes to physician



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

- Symptoms : Allergic appearance
- Risks : May cause an allergic skin reaction.
- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.

5. Firefighting measures

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire may cause evolution of:
Carbon oxides
Metal oxides
Oxides of phosphorus
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.
- Further information : Standard procedure for chemical fires.

6. Accidental release measures

- Personal precautions : Evacuate personnel to safe areas. Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release (dust). Do not breathe vapours, aerosols. Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Try to prevent the material from entering drains or water courses. Local authorities should be advised if significant spillages cannot be contained.
- Methods for cleaning up : Clean up promptly by sweeping or vacuum. Keep in suitable, closed containers for disposal.

7. Handling and storage

Handling



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

Advice on safe handling : Avoid contact with skin and eyes.
 For personal protection see section 8.
 Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
 Smoking, eating and drinking should be prohibited in the application area.
 Wash hands and face before breaks and immediately after handling the product.
 Do not get in eyes or mouth or on skin.
 Do not get on skin or clothing.
 Do not ingest.
 Do not repack.
 These safety instructions also apply to empty packaging which may still contain product residues.
 Keep container closed when not in use.

Storage

Requirements for storage areas and containers : Store in original container.
 Keep container closed when not in use.
 Keep in a dry, cool and well-ventilated place.
 Containers which are opened must be carefully resealed and kept upright to prevent leakage.
 Store in accordance with the particular national regulations.
 Keep in properly labelled containers.

8. Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Silicon dioxide	7631-86-9	MPC-TWA	1 mg/m3	2018-04-23	RU OEL
Silicon dioxide	7631-86-9	MPC-STEL	3 mg/m3	2018-04-23	RU OEL
Silicon dioxide	7631-86-9	MPC-TWA	2 mg/m3	2018-04-23	RU OEL
Silicon dioxide	7631-86-9	MPC-STEL	6 mg/m3	2018-04-23	RU OEL
Titanium dioxide	13463-67-7	MPC-TWA	10 mg/m3	2018-04-23	RU OEL
White	8042-47-5	MPC-	5 mg/m3	2018-04-23	RU OEL



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

mineral oil (petroleum)		STEL			
-------------------------	--	------	--	--	--

Engineering measures

none

Personal protective equipment

- Respiratory protection : Not required; except in case of aerosol formation. Filter type A-P

- Hand protection : butyl-rubber
Manufacturer, importer, supplier: Class 1
Wear protective gloves.
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

- Eye protection : Tightly fitting safety goggles

- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

9. Physical and chemical properties

Appearance

- Form : paste
- Colour : grey

- Odour : characteristic

Safety data

- Flash point : Note: Not applicable

- Ignition temperature : Remarks: No data available



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

Lower explosion limit	: Note: No data available
Upper explosion limit	: Note: No data available
Flammability (solid, gas)	: Combustible Solids
Oxidizing properties	: Note: No data available
Auto-ignition temperature	: Note: not auto-flammable
pH	: Note: Not applicable
Melting point/range	: Note: No data available
Boiling point/boiling range	: Note: No data available
Sublimation point	: Note: No data available
Vapour pressure	: < 0,001 hPa at 20 °C
Density	: 0,98 g/cm ³ at 20 °C
Bulk density	: Note: No data available
Water solubility	: Note: insoluble
Partition coefficient: n-octanol/water	: Note: No data available
Solubility in other solvents	: Note: No data available
Viscosity, dynamic	: Note: No data available
Viscosity, kinematic	: Note: No data available
Relative vapour density	: Note: No data available
Evaporation rate	: Note: No data available

10. Stability and reactivity

Conditions to avoid	: No conditions to be specially mentioned.
Materials to avoid	: No materials to be especially mentioned.
Hazardous decomposition products	: No decomposition if stored and applied as directed.
Thermal decomposition	: Note: No data available



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity

Silicon dioxide : LD50: > 5.000 mg/kg
Species: Rabbit

White mineral oil (petroleum) : LD50: > 2.000 mg/kg
Species: Rabbit
Method: OECD Test Guideline 402

calcium bis(dinonylnaphthalenesulphonate) : LD50: > 20.000 mg/kg
Species: Rabbit

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts : > 5.000 mg/kg
Species: Rabbit
Method: OECD Test Guideline 402

Skin corrosion/irritation

Skin irritation : Remarks: This information is not available.

Serious eye damage/eye irritation

Eye irritation : Remarks: This information is not available.

Respiratory or skin sensitisation

Sensitisation : Remarks: This information is not available.

Germ cell mutagenicity

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Germ cell mutagenicity

Remarks

Silicon dioxide : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

Titanium dioxide : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

White mineral oil (petroleum) : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

Carcinogenicity

Remarks

Silicon dioxide : No evidence of carcinogenicity in animal studies.

Titanium dioxide : No evidence of carcinogenicity in animal studies.

White mineral oil (petroleum) : No evidence of carcinogenicity in animal studies.

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts : Not classifiable as a human carcinogen.

Teratogenicity

Remarks

Teratogenicity

Teratogenicity

Teratogenicity

Teratogenicity

Silicon dioxide : No effects on or via lactation
No toxicity to reproduction

Titanium dioxide : No effects on or via lactation
No toxicity to reproduction

White mineral oil (petroleum) : No effects on or via lactation
No toxicity to reproduction

calcium bis(dinonylnaphthalenesulphonate) : No toxicity to reproduction

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts : No toxicity to reproduction
No toxicity to reproduction

Target Organ Systemic Toxicant - Single exposure

Silicon dioxide : Remarks: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Titanium dioxide : Remarks: The substance or mixture is not classified as specific target organ toxicant, single exposure.

White mineral oil (petroleum) : Remarks: The substance or mixture is not classified as



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

specific target organ toxicant, single exposure.

calcium bis(dinonylnaphthalenesulphonate) : Remarks: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts : Remarks: The substance or mixture is not classified as specific target organ toxicant, single exposure.

Target Organ Systemic Toxicant - Repeated exposure

: This information is not available.

Target Organ Systemic Toxicant - Repeated exposure

Silicon dioxide : Remarks: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Titanium dioxide : Remarks: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

White mineral oil (petroleum) : Remarks: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

calcium bis(dinonylnaphthalenesulphonate) : Remarks: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts : Remarks: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Aspiration hazard

Aspiration toxicity : This information is not available.

Further information : Information given is based on data on the components and the toxicology of similar products.

12. Ecological information

Ecotoxicity effects

Toxicity to fish :
Remarks:
No data available

Toxicity to daphnia and other aquatic invertebrates :
Remarks:
No data available

Toxicity to algae :
Remarks:



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

No data available

Toxicity to bacteria : Remarks:
No data available

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)
White mineral oil (petroleum) : NOEC: >= 1.000 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)

Elimination information (persistence and degradability)

Bioaccumulation : Remarks:
This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Mobility : Remarks:
No data available

Distribution among environmental compartments : Remarks:
No data available

Biodegradability : Remarks:
No data available

Physico-chemical removability : Remarks:
No data available

Further information on ecology

Short-term (acute) aquatic hazard
Aluminium powder : This product has no known ecotoxicological effects.
(desensitized)
calcium :
bis(dinonylnaphthalenesulph onate)
Benzenesulfonic acid, mono- :
C16-24-alkyl derivs., calcium salts

Long-term (chronic) aquatic hazard
Aluminium powder : This product has no known ecotoxicological effects.
(desensitized)
calcium : This product has no known ecotoxicological effects.



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

- bis(dinonylnaphthalenesulph onate)
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts : This product has no known ecotoxicological effects., No toxicity at the limit of solubility
- Aluminium powder (desensitized)
calcium :
- bis(dinonylnaphthalenesulph onate)
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts :
- Aluminium powder (desensitized)
calcium :
- bis(dinonylnaphthalenesulph onate)
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts :
- Aluminium powder (desensitized)
calcium :
- bis(dinonylnaphthalenesulph onate)
Benzenesulfonic acid, mono-C16-24-alkyl derivs., calcium salts :

- Results of PBT assessment
- Silicon dioxide : Non-classified vPvB substance, Non-classified PBT substance

- Titanium dioxide : Non-classified vPvB substance, Non-classified PBT substance

- White mineral oil (petroleum) : Non-classified PBT substance, Non-classified vPvB substance

- calcium : Non-classified PBT substance, Non-classified vPvB substance
- bis(dinonylnaphthalenesulph onate)
- Additional ecological information : No information on ecology is available.

13. Disposal considerations

- Product : The product should not be allowed to enter drains, water courses or the soil.
Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

- Contaminated packaging : Packaging that is not properly emptied must be disposed of as



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

the unused product.
Dispose of waste product or used containers according to local regulations.

14. Transport information

ADR

Not dangerous goods

IATA

Not dangerous goods

IMDG

Not dangerous goods

Other information : No special precautions required.

15. Regulatory information

16. Other information

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety data sheet applies only to products originally packed and labelled by OKS Spezialschmierstoffe. The information contained therein may not be reproduced or modified without the express written permission of OKS Spezialschmierstoffe. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of our safety data sheets (e.g. as a document for download from the Internet) is not permitted without the express written consent of OKS Spezialschmierstoffe. OKS Spezialschmierstoffe provides its customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. OKS Spezialschmierstoffe provides no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the



OKS 235

Version 1.4

Revision Date 07.11.2019

Print Date 14.01.2021

day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorised trading partner of OKS Spezialschmierstoffe.
