according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 241

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Lubricant spray

Substance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

responsible for the SDS

National contact

mcm@oks-germany.com

1.4 Emergency telephone number

Emergency telephone

number

06 68593726 Roma - CAV "Osp. Pediatrico Bambino

Gesù" Dip. Emergenza e Accettazione DEA 800183459 Foggia - Az. Osp. Univ. Foggia 081-5453333 Napoli - Az. Osp. "A. Cardarelli" 06-49978000 Roma - CAV Policlinico "Umberto I" 06-3054343 Roma - CAV Policlinico "A. Gemelli"

055-7947819 Firenze - Az. Osp. "Careggi" U.O.

Tossicologia Medica

0382-24444 Pavia - CAV Centro Nazionale di

Informazione Tossicologica

02-66101029 Milano - Osp. Niguarda Ca' Granda 800883300 Bergamo - Az. Osp. Papa Giovanni XXII Verona - Az. Osp. Integrata Verona

+49 8142 3051 517 (Service 24/7)

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

#### **SECTION 2: Hazards identification**

#### 2.1 Classification of the substance or mixture

## Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

Short-term (acute) aquatic hazard,

Category 1

H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard,

Category 1

H410: Very toxic to aquatic life with long lasting

effects.

#### 2.2 Label elements

## Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms









Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters

airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.
H410 Very toxic to aquatic life with long lasting

effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

## Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

n-butyl acetate

#### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Active substance with propellant

Solvent mixture

Components

Components				
Chemical name	CAS-No.	Classification	specific	Concentration
	EC-No.		concentration	(% w/w)
			limit	
	Index-No.		M-Factor	
	Registration number		Notes	
			Acute toxicity	
			estimate	
Hydrocarbons, C6-C7,		Flam. Liq.2; H225		>= 25 - < 30
n-alkanes, isoalkanes,	921-024-6	Skin Irrit.2; H315		



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

cyclics, <5% n-hexane	01-2119475514-35- XXXX	STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		
copper	7440-50-8 231-159-6 029-019-01-X 01-2119480154-42- XXXX	Acute Tox.4; H302 Eye Irrit.2; H319 Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 10/10  ATE (Oral): 500 mg/kg; ATE (Inhalation): 0,733 mg/l;	>= 2,5 - < 10
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29- XXXX	Flam. Liq.3; H226 STOT SE3; H336; EUH066		>= 1 - < 10
Substances with a work	xplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37- XXXX	Flam. Gas1A; H220 Press. GasLiquefied gas; H280	Note U (table 3.1)	>= 30 - < 50
tin	7440-31-5 231-141-8	Not classified		>= 1 - < 10
molybdenum disulphide	1317-33-5 215-263-9	Not classified		>= 1 - < 10

For explanation of abbreviations see section 16.

# **SECTION 4: First aid measures**

## 4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse. Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

## 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Aspiration may cause pulmonary oedema and pneumonitis.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Risks : Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Date of last issue: 14.12.2022 Revision Date: Print Date: 04.12.2023 Date of first issue: 21.06.2016 04.12.2023 3.0

# **SECTION 5: Firefighting measures**

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Nitrogen oxides (NOx)

Sulphur oxides

Oxides of phosphorus

Metal oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

## **SECTION 6: Accidental release measures**

# 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions Do not allow contact with soil, surface or ground water.

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

VersionRevision Date:Date of last issue: 14.12.2022Print Date:3.004.12.2023Date of first issue: 21.06.201604.12.2023

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

#### 6.4 Reference to other sections

For personal protection see section 8.

## **SECTION 7: Handling and storage**

#### 7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWALimit Value - eight hours	1.000 ppm 1.920 mg/m3	2000/39/EC (2000-06-16)
	Further inforn	Further information: Indicative		
		TWA8 hour exposure limit	1.000 ppm 1.920 mg/m3	IT OEL (2020-05-19)
n-butyl acetate	123-86-4	STELShort term exposure limit	150 ppm 723 mg/m3	2019/1831/E U (2019-10-31)
	Further information: Indicative			
		TWALimit Value - eight hours	50 ppm 241 mg/m3	2019/1831/E U (2019-10-31)
	Further information: Indicative			
		STELShort term exposure limit	150 ppm 723 mg/m3	IT OEL (2021-05-18)
		TWA8 hour exposure limit	50 ppm 241 mg/m3	IT OEL (2021-05-18)
tin	7440-31-5	TWALimit Value - eight hours	2 mg/m3 (Tin)	91/322/EEC (1991-07-05)
	Further information: Indicative			

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl ether	Workers	Inhalation	Long-term exposure	1894 mg/m3
Hydrocarbons, C6- C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m3
Benzene, mono-C10- 13-alkyl derivs., distn. residues	Workers	Inhalation	Long-term systemic effects	2,2 mg/m3
	Workers	Skin contact	Long-term systemic	3,15 mg/kg



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



## **OKS 241**

VersionRevision Date:Date of last issue: 14.12.2022Print Date:3.004.12.2023Date of first issue: 21.06.201604.12.2023

			effects	bw/day
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Dermal	Long-term local effects	11 mg/cm2

## Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment Value	
dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg
	Marine sediment	0,069 mg/kg
	Soil	0,045 mg/kg
Benzene, mono-C10-13-alkyl	Fresh water	0,001 mg/l
derivs., distn. residues	Intermittent use/release	0.001 mg/l
	Intermittent use/release	0,001 mg/l
	Marine water	0 mg/l
	Microbiological Activity in Sewage	2 mg/l
	Treatment Systems	
	Fresh water sediment	16,5 mg/kg
	Marine sediment	1,65 mg/kg
	Soil	3,7 mg/kg
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Microbiological Activity in Sewage	35,6 mg/l
	Treatment Systems	
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,09 mg/kg

## 8.2 Exposure controls

## **Engineering measures**

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

# Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : butyl-rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Date of last issue: 14.12.2022 Version **Revision Date:** Print Date: 04.12.2023 Date of first issue: 21.06.2016 04.12.2023 3.0

case.

The selected protective gloves have to satisfy the

specifications of Regulation (EU) 2016/425 and the standard

EN 374 derived from it.

Skin and body protection Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type A-P Filter type

Protective measures The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

Physical state aerosol

Colour red brown

Odour solvent-like

Odour Threshold No data available

Melting point/range No data available

: < -20 °C (1.013 hPa) Boiling point/boiling range

Flammability (solid, gas) Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

26,2 %(V)

Lower explosion limit / Lower : 0,6 %(V)

flammability limit

Flash point -20 °C

Method: Abel-Pensky

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

VersionRevision Date:Date of last issue: 14.12.2022Print Date:3.004.12.2023Date of first issue: 21.06.201604.12.2023

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 4.600 hPa (20 °C)

Relative density : 0,818 (20 °C)

Reference substance: Water The value is calculated

Density : 0,82 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

# **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No hazards to be specially mentioned.

## 10.2 Chemical stability

Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## **SECTION 11: Toxicological information**

## 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Remarks: Respiration of solvent vapour may cause dizziness.

Harmful by inhalation.

Acute dermal toxicity : Symptoms: Redness, Local irritation



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg

Assessment: The substance or mixture has no acute dermal

toxicity

copper:

Acute oral toxicity : Acute toxicity estimate: 500 mg/kg

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

LD50 Oral (Rat): > 300 - 2.000 mg/kg

Assessment: The component/mixture is moderately toxic after

single ingestion.

Acute inhalation toxicity : Acute toxicity estimate: 0,733 mg/l

Test atmosphere: dust/mist

Method: Acute toxicity estimate according to Regulation (EC)

No. 1272/2008

Acute dermal toxicity : LD50 (Rat, male and female): > 2.000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17.600 mg/kg

dimethyl ether:



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

Acute inhalation toxicity : LC50 (Rat): 309 mg/l

Exposure time: 4 h
Test atmosphere: gas

tin:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 423

GLP: yes

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Assessment: The substance or mixture has no acute dermal

toxicity

molybdenum disulphide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 16.000 mg/kg

Skin corrosion/irritation

**Product:** 

Remarks : Irritating to skin.

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

n-butyl acetate:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

Result : Repeated exposure may cause skin dryness or cracking.

dimethyl ether:

Assessment : No skin irritation Result : No skin irritation

tin:

Assessment : No skin irritation Result : No skin irritation

molybdenum disulphide:

Assessment : No skin irritation Result : No skin irritation

Serious eye damage/eye irritation

**Product:** 

Remarks : Irritating to eyes.

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

copper:

Result : Eye irritation

n-butyl acetate:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

dimethyl ether:

Assessment : No eye irritation Result : No eye irritation

tin:

Assessment : No eye irritation Result : No eye irritation



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

molybdenum disulphide:

Assessment : No eye irritation Result : No eye irritation

Respiratory or skin sensitisation

**Product:** 

Remarks : This information is not available.

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

n-butyl acetate:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

dimethyl ether:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

molybdenum disulphide:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

Test system: Rodent cell line Method: OECD Test Guideline 473

Result: negative

n-butyl acetate:

Genotoxicity in vitro : Test Type: Ames test

Test system: Salmonella typhimurium Method: OECD Test Guideline 471

Result: negative

Test Type: Chromosome aberration test in vitro

Test system: Chinese hamster cells Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo : Species: Mouse

Application Route: Oral

Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity-

Assessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects., Animal testing did not show any mutagenic

effects.

dimethyl ether:

Genotoxicity in vitro : Test Type: Ames test

Method: OECD Test Guideline 471

Result: negative

Genotoxicity in vivo : Species: Drosophila melanogaster (vinegar fly)

Application Route: inhalation (gas) Method: OECD Test Guideline 477

Result: negative

molybdenum disulphide:

Germ cell mutagenicity-

Assessment

Animal testing did not show any mutagenic effects.

Carcinogenicity

**Product:** 

Remarks : No data available

**Components:** 

n-butyl acetate:

Carcinogenicity - : Not classifiable as a human carcinogen.

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

VersionRevision Date:Date of last issue: 14.12.2022Print Date:3.004.12.2023Date of first issue: 21.06.201604.12.2023

Assessment

dimethyl ether:

Species : Rat

Application Route : inhalation (gas)

Exposure time : 2 Years

: 47 mg/l

Method : OECD Test Guideline 453

Result : negative

molybdenum disulphide:

Carcinogenicity - Assessment

: No evidence of carcinogenicity in animal studies.

Reproductive toxicity

**Product:** 

Effects on fertility : Remarks: No data available

Effects on foetal development

Remarks: No data available

**Components:** 

n-butyl acetate:

Effects on fertility : Test Type: Two-generation study

Species: Rat

Application Route: inhalation (vapour)
General Toxicity - Parent: NOAEC: 750 mg/l
General Toxicity F1: NOAEC: 750 mg/l
General Toxicity F2: NOAEC: 750 mg/l

Method: OECD Test Guideline 416

Result: Embryotoxic effects and adverse effects on the

offspring were detected.

Reproductive toxicity -

Assessment

: - Fertility -

No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

- Teratogenicity -

No toxicity to reproduction

dimethyl ether:

Reproductive toxicity -

: - Fertility -

Assessment

Animal testing did not show any effects on fertility.

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

STOT - single exposure

**Product:** 

Remarks : No data available

**Components:** 

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

n-butyl acetate:

Exposure routes : Inhalation

Target Organs : Central nervous system

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

molybdenum disulphide:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

**Product:** 

Remarks : No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)

Assessment : No significant health effects observed in animals at

concentrations of 1 mg/l/6h/d or less.

n-butyl acetate:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

molybdenum disulphide:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

**Product:** 

Remarks : This information is not available.



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

## **Components:**

#### n-butyl acetate:

Species : Rat
NOAEL : 125 mg/kg
Application Route : Oral

## **Aspiration toxicity**

#### **Product:**

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

# **Components:**

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

## n-butyl acetate:

No aspiration toxicity classification

#### dimethyl ether:

No aspiration toxicity classification

#### 11.2 Information on other hazards

## **Endocrine disrupting properties**

# **Product:**

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

## **Further information**

**Product:** 

Remarks : Risks of irreversible effects after a single exposure.

Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

#### Components:

molybdenum disulphide:

Remarks : Information given is based on data on the components and

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

the toxicology of similar products.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

**Product:** 

Toxicity to fish : Remarks: May cause long-term adverse effects in the aquatic

environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

#### Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EbC50 (Pseudokirchneriella subcapitata (green algae)): 26

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

copper:

M-Factor (Acute aquatic

toxicity)

: 10



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

M-Factor (Chronic aquatic

toxicity)

10

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

n-butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l

Exposure time: 96 h

Test Type: flow-through test

Method: OECD Test Guideline 203

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia (water flea)): 44 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l

Exposure time: 72 h Test Type: static test

Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l

Exposure time: 40 h

Test Type: Growth inhibition

Toxicity to daphnia and other :

aquatic invertebrates

(Chronic toxicity)

NOEC: 23 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: Reproduction Test

GLP: yes

dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l

Exposure time: 96 h Test Type: semi-static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 4.400 mg/l

Exposure time: 48 h Test Type: static test

Toxicity to algae/aquatic

plants

EC50 (green algae): 154,9 mg/l

Exposure time: 96 h

tin:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 0,0124 mg/l

Exposure time: 96 h Test Type: static test



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): >

0,0192 mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

Remarks: No toxicity at the limit of solubility

molybdenum disulphide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/

Exposure time: 72 h

## 12.2 Persistence and degradability

**Product:** 

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

## **Components:**

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

copper:

Biodegradability : Result: Not rapidly biodegradable

n-butyl acetate:

Biodegradability : Test Type: Primary biodegradation

Result: rapidly biodegradable Biodegradation: 83 % Exposure time: 28 d

Method: OECD Test Guideline 301D

dimethyl ether:

Biodegradability : Test Type: aerobic

Inoculum: activated sludge

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

Result: Not readily biodegradable.

Biodegradation: 5 % Exposure time: 28 d

Method: OECD Test Guideline 301D

#### 12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

**Components:** 

n-butyl acetate:

Partition coefficient: n- : log Pow: 2,3 (25 °C)

octanol/water pH: 7

Method: OECD Test Guideline 117

GLP: yes

dimethyl ether:

Partition coefficient: n-

octanol/water

log Pow: 0,07 (25 °C)

#### 12.4 Mobility in soil

**Product:** 

Mobility : Remarks: No data available

Distribution among : Remarks: No data available

environmental compartments

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

**Components:** 

n-butyl acetate:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

dimethyl ether:

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

Assessment : Non-classified vPvB substance. Non-classified PBT substance

tin:

Assessment : Remarks: Not applicable

## 12.6 Endocrine disrupting properties

**Product:** 

Assessment : The substance/mixture does not contain components

considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

**Product:** 

Additional ecological

information

: Very toxic to aquatic organisms, may cause long-term adverse

effects in the aquatic environment.

## **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04\*, gases in pressure containers (including halons)

containing hazardous substances

## **SECTION 14: Transport information**

#### 14.1 UN number or ID number



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

(naphtha (petroleum), hydrotreated light, copper)

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

**ADN** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

**ADR** 

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

IATA (Cargo)



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

**ADN** 

Environmentally hazardous : no

**ADR** 

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

**IMDG** 

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) Conditions of restriction for the following entries should be

considered: Number on list 75

copper (Number on list 75) tin (Number on list 75)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No

1907/2006 (REACH), Article 57).

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

Regulation (EC) No 1005/2009 on substances that : Not applicable

deplete the ozone layer

(EC 1005/2009)

Regulation (EU) 2019/1021 on persistent organic : Not applicable

pollutants (recast)

(EU POP)

Regulation (EC) No 649/2012 of the European : Not applicable

Parliament and the Council concerning the export and

import of dangerous chemicals

(EU PIC)

Regulation (EU) 2019/1148 on the marketing and use of : Not applicable

explosives precursors

P<sub>5</sub>c

Seveso III: Directive 2012/18/EU of the European P3a FLAMM

Parliament and of the Council on the control of major-accident hazards involving dangerous

substances.

P3a FLAMMABLE AEROSOLS

E1 ENVIRONMENTAL HAZARDS

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 70,39 %

## Other regulations:

Legislative Decree April 9,2008, 81 (Implementation of Article 1 of the Law of 3 August 2007, n. 123, concerning the protection of health and safety in the workplace.) and subsequent amendments

Legislative Decree April 3, 2006, n.152, (Environmental standards) and subsequent amendments

Legislative Decree February 6, 2009, 21 (Regulations for the execution of the provisions laid down in Regulation (EC) no. 648/2004 on detergents)

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

## 15.2 Chemical safety assessment

This information is not available.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

EUH066 : Repeated exposure may cause skin dryness or cracking.

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H302 : Harmful if swallowed.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation. H336 : May cause drowsiness or dizziness.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H411 : Toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Note U (table 3.1) : When put on the market gases have to be classified as

"Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

2019/1831/EU : Europe. Commission Directive 2019/1831/EU establishing a

fifth list of indicative occupational exposure limit values

91/322/EEC : Europe. Commission Directive 91/322/EEC on establishing

indicative limit values

IT OEL : Italy. List of indicative limit values for professional exposure to

chemical agents.

2000/39/EC / TWA : Limit Value - eight hours 2019/1831/EU / TWA : Limit Value - eight hours 2019/1831/EU / STEL : Short term exposure limit 91/322/EEC / TWA : Limit Value - eight hours



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

IT OEL / TWA : 8 hour exposure limit IT OEL / STEL : Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways: ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate: NZIoC - New Zealand Inventory of Chemicals: OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID -Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

#### **Further information**

# Classification of the mixture: Classification procedure:

Aerosol 1	H222, H229	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Based on product data or assessment
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



**OKS 241** 

Version Revision Date: Date of last issue: 14.12.2022 Print Date: 3.0 04.12.2023 Date of first issue: 21.06.2016 04.12.2023

particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.