

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : OKS 241

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-stance/Mixture : Lubricant spray

Recommended restrictions on use : Restricted to professional users.

#### 1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599

E-mail address of person responsible for the SDS : mcm@oks-germany.com  
National contact :

#### 1.4 Emergency telephone number

Emergency telephone number : (+351) 808 250 143

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.

##### Skin irritation, Category 2

H315: Causes skin irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

##### Aspiration hazard, Category 1

H304: May be fatal if swallowed and enters airways.

Acute aquatic toxicity, Category 1

H400: Very toxic to aquatic life.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

Chronic aquatic toxicity, Category 2

H411: Toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H304 May be fatal if swallowed and enters air-ways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statements :

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P273 Avoid release to the environment.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version 2.0      Revision Date: 09.08.2018      Date of last issue: 21.06.2016      Print Date: 09.08.2018  
Date of first issue: 21.06.2016

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Active substance with propellant  
Solvent mixture

#### Hazardous components

Chemical name	CAS-No. EC-No.  Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light; Low boiling point hy- drogen treated naph- tha	64742-49-0  265-151-9  649-328-00-1	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	Note P	$\geq 25 - < 30$
copper flakes (coated with aliphatic acid)	7440-50-8  231-159-6  029-019-01-X	Aquatic Acute1; H400	M-Factor: 10/1	$\geq 2,5 - < 10$
n-hexane	110-54-3  203-777-6  601-037-00-0	Flam. Liq.2; H225 Skin Irrit.2; H315 Repr.2; H361f STOT SE3; H336 STOT RE2; H373 Asp. Tox.1; H304 Aquatic Chronic2; H411	$\geq 5$ % STOT RE2, H373  ** *** ,	$\geq 1 - < 2,5$
Substances with a workplace exposure limit :				
dimethyl ether	115-10-6  204-065-8  603-019-00-8 01-2119472128-37- XXXX	Flam. Gas1; H220 Press. GasLique- fied gas; H280	Note U (table 3.1)	$\geq 30 - < 50$
n-butyl acetate	123-86-4  204-658-1  607-025-00-1 01-2119485493-29- XXXX	Flam. Liq.3; H226 STOT SE3; H336		$\geq 1 - < 10$
tin	7440-31-5			$\geq 1 - < 10$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version 2.0      Revision Date: 09.08.2018      Date of last issue: 21.06.2016      Print Date: 09.08.2018  
Date of first issue: 21.06.2016

	231-141-8			
molybdenum disulphide	1317-33-5 215-263-9			$\geq 1 - < 10$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
If easy to do, remove contact lens, if worn.  
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Aspiration hazard if swallowed - can enter lungs and cause damage.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema  
  
Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire may cause evolution of:  
Carbon oxides  
Metal oxides  
Oxides of phosphorus  
Sulphur oxides

Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. In the case of respirable dust and/or fumes, use self-contained breathing apparatus. Exposure to decomposition products may be a hazard to

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

health.

Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Refer to protective measures listed in sections 7 and 8.  
Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Non-sparking tools should be used.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

### 7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	1.000 ppm 1.920 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information	Indicative	TWA	1.000 ppm 1.920 mg/m <sup>3</sup>	PT DL 305/2007 (2007-08-24)
copper flakes (coated with aliphatic acid)	7440-50-8	VLE-MP (Dust and mist)	1 mg/m <sup>3</sup> (Copper)	PT OEL (2007-03-26)
Further information	Irritation, Gastrointestinal tract, metal fume fever	VLE-MP (Fumes)	0,2 mg/m <sup>3</sup> (Copper)	PT OEL (2007-03-26)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version 2.0      Revision Date: 09.08.2018      Date of last issue: 21.06.2016      Date of first issue: 21.06.2016      Print Date: 09.08.2018

Further information	Irritation, Gastrointestinal tract, metal fume fever			
n-butyl acetate	123-86-4	VLE-MP	150 ppm	PT OEL (2007-03-26)
Further information	irritation of the upper respiratory tract, Eye irritation			
		VLE_CD	200 ppm	PT OEL (2007-03-26)
Further information	irritation of the upper respiratory tract, Eye irritation			
tin	7440-31-5	VLE-MP	2 mg/m <sup>3</sup>	PT OEL (2014-11-14)
Further information	Pneumoconiosis (or Stannosis), Included by specific national legislation or by not transposed communitary legilation			
		TWA	2 mg/m <sup>3</sup> (Tin)	PT DL 305/2007 (2007-08-24)
		TWA	2 mg/m <sup>3</sup> (Tin)	91/322/EEC (1991-07-05)
Further information	Indicative, Existing scientific data on health effects appear to be particularly limited			
molybdenum disulphide	1317-33-5	VLE-MP (Inhalable fraction)	10 mg/m <sup>3</sup> (Molybdenum)	PT OEL (2014-11-14)
		VLE-MP (Respirable fraction)	3 mg/m <sup>3</sup> (Molybdenum)	PT OEL (2014-11-14)
n-hexane	110-54-3	TWA	20 ppm 72 mg/m <sup>3</sup>	2006/15/EC (2006-02-09)
Further information	Indicative			
		VLE-MP	50 ppm	PT OEL (2007-03-26)
Further information	Included by specific national legislation or by not transposed communitary legislation, Danger for absorption by the skin, Identification of substances for which biological exposure values are available. There are two types: IBE A refers to acetylcholinesterase inhibitors pesticides and IBE M to metahaemoglobin inductors., impairment of central nervous system, Eye irritation, peripheral neuropathy			
		TWA	20 ppm 72 mg/m <sup>3</sup>	PT DL 305/2007 (2007-08-24)

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
n-hexane	110-54-3	2,5-Hexanedione: 0,4 mg/l (Urine)	At the end of the shift and at the end of the working week	PT NP1796

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl ether	Workers	Inhalation	Long-term exposure	1894 mg/m <sup>3</sup>
Naphtha (petroleum), hydrotreated light; Low boiling point hy-	Workers	Inhalation	Long-term systemic effects	1300 mg/m <sup>3</sup>



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version 2.0      Revision Date: 09.08.2018      Date of last issue: 21.06.2016      Print Date: 09.08.2018  
Date of first issue: 21.06.2016

drogen treated naphtha				
	Workers	Inhalation	Long-term local effects	840 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	1100 mg/m <sup>3</sup>
Benzene, mono-C10-13-alkyl derivs., distn. residues	Workers	Inhalation	Long-term systemic effects	3,2 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	4,3 mg/kg bw/day
n-hexane	Workers	Inhalation	Long-term systemic effects	75 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	11 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg
	Marine sediment	0,069 mg/kg
	Soil	0,045 mg/kg
Benzene, mono-C10-13-alkyl derivs., distn. residues	Fresh water	0,001 mg/l
	Intermittent use/release	0,001 mg/l
	Marine water	0 mg/l
	Microbiological Activity in Sewage Treatment Systems	2 mg/l
	Fresh water sediment	1,65 mg/kg
	Marine sediment	0,165 mg/kg
	Soil	0,329 mg/kg

## 8.2 Exposure controls

### Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

### Hand protection

Material : butyl-rubber  
Protective index : Class 1

Remarks : Wear protective gloves. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. The break through time

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Short term only
- Filter type : Filter type A-P
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.  
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Appearance : aerosol
- Colour : red brown
- Odour : solvent-like
- Odour Threshold : No data available
- pH : Not applicable
- Melting point/range : No data available
- Boiling point/boiling range : < -20 °C  
(1.013 hPa)
- Flash point : < -20 °C  
Method: Abel-Pensky
- Evaporation rate : No data available
- Flammability (solid, gas) : Extremely flammable aerosol.
- Upper explosion limit : 26,2 %(V)
- Lower explosion limit : 0,6 %(V)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

Vapour pressure : 4.600 hPa (20 °C)

Relative vapour density : No data available

Density : 0,82 g/cm<sup>3</sup>  
(20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

### 9.2 Other information

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazards to be specially mentioned.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

- Acute oral toxicity : Remarks: Effects due to ingestion may include:  
Symptoms: Central nervous system depression
- Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.  
Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression
- Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.  
Symptoms: Redness, Local irritation, Skin disorders

##### Components:

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

- Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes
- Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes  
Assessment: The substance or mixture has no acute dermal toxicity

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### **copper flakes (coated with aliphatic acid):**

Acute oral toxicity : Acute toxicity estimate: 500,0 mg/kg  
Method: Converted acute toxicity point estimate

### **n-hexane:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 259,35 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 3.350 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### **dimethyl ether:**

Acute inhalation toxicity : LC50 (Rat): 309 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

### **n-butyl acetate:**

Acute oral toxicity : LD50 Oral (Rat): 10.760 mg/kg

### **tin:**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 423  
GLP: yes  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes  
Assessment: The substance or mixture has no acute dermal toxicity

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### **molybdenum disulphide:**

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 16.000 mg/kg

### **Skin corrosion/irritation**

#### **Product:**

Remarks: Irritating to skin.

#### **Components:**

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Species: Rabbit

Assessment: Irritating to skin.

Method: OECD Test Guideline 404

Result: Irritating to skin.

GLP: yes

#### **n-hexane:**

Species: Rabbit

Assessment: Irritating to skin.

Method: OECD Test Guideline 404

Result: Irritating to skin.

#### **dimethyl ether:**

Assessment: No skin irritation

Result: No skin irritation

#### **n-butyl acetate:**

Result: Repeated exposure may cause skin dryness or cracking.

#### **tin:**

Assessment: No skin irritation

Result: No skin irritation

#### **molybdenum disulphide:**

Assessment: No skin irritation

Result: No skin irritation

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks: Contact with eyes may cause irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### Components:

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Species: Rabbit  
Assessment: No eye irritation  
Method: OECD Test Guideline 405  
Result: No eye irritation  
GLP: yes

#### **n-hexane:**

Species: Rabbit  
Assessment: No eye irritation  
Method: OECD Test Guideline 405  
Result: No eye irritation

#### **dimethyl ether:**

Assessment: No eye irritation  
Result: No eye irritation

#### **tin:**

Assessment: No eye irritation  
Result: No eye irritation

#### **molybdenum disulphide:**

Assessment: No eye irritation  
Result: No eye irritation

### **Respiratory or skin sensitisation**

#### Product:

Remarks: This information is not available.

### Components:

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Test Type: Buehler Test  
Species: Guinea pig  
Assessment: Does not cause skin sensitisation.  
Method: OECD Test Guideline 406  
Result: Does not cause skin sensitisation.  
GLP: yes

#### **n-hexane:**

Species: Mouse  
Assessment: Does not cause skin sensitisation.  
Result: Does not cause skin sensitisation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### **dimethyl ether:**

Assessment: Does not cause skin sensitisation.

Result: Does not cause skin sensitisation.

### **molybdenum disulphide:**

Assessment: Does not cause skin sensitisation.

Result: Does not cause skin sensitisation.

### **Germ cell mutagenicity**

#### **Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### **Components:**

##### **dimethyl ether:**

Genotoxicity in vitro : Test Type: Ames test  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Species: Drosophila melanogaster (vinegar fly)  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 477  
Result: negative

##### **molybdenum disulphide:**

Germ cell mutagenicity- Assessment : Animal testing did not show any mutagenic effects.

### **Carcinogenicity**

#### **Product:**

Remarks: No data available

#### **Components:**

##### **dimethyl ether:**

Species: Rat  
Application Route: inhalation (gas)  
Exposure time: 2 Years  
47 mg/l  
Method: OECD Test Guideline 453  
Result: negative



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version 2.0	Revision Date: 09.08.2018	Date of last issue: 21.06.2016 Date of first issue: 21.06.2016	Print Date: 09.08.2018
----------------	------------------------------	---	---------------------------

### **molybdenum disulphide:**

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

### **Reproductive toxicity**

#### **Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### **Components:**

##### **n-hexane:**

Reproductive toxicity - Assessment : Suspected human reproductive toxicant

##### **dimethyl ether:**

Reproductive toxicity - Assessment : Animal testing did not show any effects on fertility.

### **STOT - single exposure**

#### **Components:**

##### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Exposure routes: Inhalation  
Target Organs: Central nervous system  
Assessment: May cause drowsiness or dizziness.

##### **n-hexane:**

Exposure routes: Inhalation  
Target Organs: Central nervous system  
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

##### **n-butyl acetate:**

Exposure routes: Inhalation  
Assessment: May cause drowsiness or dizziness.

##### **molybdenum disulphide:**

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version 2.0	Revision Date: 09.08.2018	Date of last issue: 21.06.2016 Date of first issue: 21.06.2016	Print Date: 09.08.2018
----------------	------------------------------	---	---------------------------

### STOT - repeated exposure

#### Components:

##### **n-hexane:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

##### **molybdenum disulphide:**

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### Repeated dose toxicity

#### Product:

Remarks: This information is not available.

### Aspiration toxicity

#### Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

#### Components:

##### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

May be fatal if swallowed and enters airways.

##### **n-hexane:**

May be fatal if swallowed and enters airways.

##### **dimethyl ether:**

No aspiration toxicity classification

### Further information

#### Product:

Remarks: Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

#### Components:

##### **molybdenum disulphide:**

Remarks: Information given is based on data on the components and the toxicology of similar products.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

- Toxicity to fish : Remarks: Very toxic to aquatic organisms.
- Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available
- Toxicity to algae : Remarks: No data available
- Toxicity to microorganisms :  
Remarks: No data available

#### Components:

##### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,5 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3,1 mg/l  
Exposure time: 72 h  
Test Type: static test

#### **Ecotoxicology Assessment**

- Acute aquatic toxicity : Toxic to aquatic life.
- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

##### **copper flakes (coated with aliphatic acid):**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 0,0094 mg/l  
Exposure time: 96 h
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,044 mg/l  
Exposure time: 48 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

M-Factor (Acute aquatic toxicity) : 10

M-Factor (Chronic aquatic toxicity) : 1

### Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

### n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 21,85 mg/l  
Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 9,285 mg/l  
Exposure time: 72 h

### dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l  
Exposure time: 96 h  
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae : EC50 (green algae): 154,9 mg/l  
Exposure time: 96 h

### tin:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 0,0124 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 0,0192 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
Remarks: No toxicity at the limit of solubility

### molybdenum disulphide:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
Exposure time: 72 h

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

#### Components:

##### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 90,35 %  
Exposure time: 28 d

##### **copper flakes (coated with aliphatic acid):**

Biodegradability : Remarks: The methods for determining biodegradability are not applicable to inorganic substances.

##### **n-hexane:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 21 %  
Exposure time: 28 d  
GLP: yes

##### **dimethyl ether:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **n-butyl acetate:**

Biodegradability : Result: Readily biodegradable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

#### Components:

##### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Partition coefficient: n-octanol/water : log Pow: 3,4 - 5,2

##### **n-hexane:**

Bioaccumulation : Bioconcentration factor (BCF): 501,19

Partition coefficient: n-octanol/water : log Pow: 4 (20 °C)  
pH: 7

##### **dimethyl ether:**

Partition coefficient: n-octanol/water : log Pow: 0,07 (25 °C)

##### **n-butyl acetate:**

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : log Pow: 2,3

### 12.4 Mobility in soil

#### Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### Components:

#### **dimethyl ether:**

Assessment : Non-classified vPvB substance. Non-classified PBT substance.

#### **tin:**

Assessment : Remarks: Not applicable

### 12.6 Other adverse effects

#### Product:

Additional ecological information : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1950

IMDG : UN 1950

IATA : UN 1950

### 14.2 UN proper shipping name

ADR : AEROSOLS

IMDG : AEROSOLS  
(naphtha (petroleum), hydrotreated light, copper)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

**IATA** : Aerosols, flammable

### 14.3 Transport hazard class(es)

**ADR** : 2

**IMDG** : 2.1

**IATA** : 2.1

### 14.4 Packing group

#### **ADR**

Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

#### **IMDG**

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

#### **IATA (Cargo)**

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

#### **IATA (Passenger)**

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

#### **ADR**

Environmentally hazardous : yes

#### **IMDG**

Marine pollutant : yes

#### **IATA (Passenger)**

Environmentally hazardous : no

#### **IATA (Cargo)**

Environmentally hazardous : no

### 14.6 Special precautions for user

No special precautions required.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

### SECTION 15: Regulatory information

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

- REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
- REACH - List of substances subject to authorisation (Annex XIV) : Not applicable
- Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable
- Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable
- Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable
- REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t
E1	ENVIRONMENTAL HAZARDS	100 t	200 t
P2			
E1			
P5c			
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams), (d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environ-	2.500 t	25.000 t

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

mental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 70,39 %  
Volatile CMR compounds: 28,03 %  
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: Other information

### Full text of H-Statements

H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H336 : May cause drowsiness or dizziness.  
H361f : Suspected of damaging fertility.  
H373 : May cause damage to organs through prolonged or repeated exposure.  
H400 : Very toxic to aquatic life.  
H411 : Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

\*\* : Route of exposure cannot be excluded: For certain hazard classes, e.g. STOT, the route of exposure should be indicated in the hazard statement only if it is conclusively proven that no other route of exposure can cause the hazard in accordance to the criteria in Annex I. Under Directive 67/548/EEC the route of exposure was indicated for classifications with R48 when there was data justifying the classification for this route

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

- of exposure. The classification under 67/548/EEC indicating the route of exposure has been translated into the corresponding class and category according to this Regulation, but with a general hazard statement not specifying the route of exposure as the necessary information is not available.
- \*\*\* : Hazard statements for reproductive toxicity: Hazard statements H360 and H361 indicate a general concern for effects on fertility and/or development: 'May damage/Suspected of damaging fertility or the unborn child'. According to the criteria, the general hazard statement can be replaced by the hazard statement indicating the specific effect of concern in accordance with Section 1.1.2.1.2. When the other differentiation is not mentioned, this is due to evidence proving no such effect, inconclusive data or no data and the obligations in Article 4(3) shall apply for that differentiation. In order not to lose information from the harmonised classifications for fertility and developmental effects under Directive 67/548/EEC, the classifications have been translated only for those effects classified under that Directive
- Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.
- Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 241

Version	Revision Date:	Date of last issue: 21.06.2016	Print Date:
2.0	09.08.2018	Date of first issue: 21.06.2016	09.08.2018

Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Aerosol 1 H222, H229

**Skin Irrit. 2** H315

STOT SE 3 H336

**Asp. Tox. 1** H304

Aquatic Acute 1 H400

Aquatic Chronic 2 H411

#### Classification procedure:

Based on product data or assessment

Calculation method

Calculation method

Based on product data or assessment

Calculation method

Calculation method

This safety datasheet applies only to products originally packaged and labelled by OKS Spezial-schmierstoffe. The information contained therein is protected by copyright and must not be reproduced or amended without the express written approval of OKS Spezialschmierstoffe. This document may be passed on only to the extent required by law. Any dissemination of our safety datasheets (e.g. as a document for download from the Internet) beyond this legally required extent is not permitted without express written consent. OKS Spezialschmierstoffe provides its customers with amended safety datasheets as prescribed by law. The customer is responsible for passing on safety datasheets and any amendments contained therein to its own customers, employees and other users of the product. OKS Spezialschmierstoffe provides no guarantee that safety datasheets received by users from third parties are up-to-date. All information and instructions in this safety datasheets were compiled to the best of our knowledge and are based on the information available to us. The data provided are intended to describe the product in relation to the required safety measures; they are neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and do not justify any contractual legal relationships.