

OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

1. Identification of the substance/mixture and of the company/undertaking

Product information

Product name : OKS 241

Use of the Substance/Mixture : Lubricant spray

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599

E-mail address : mcm@oks-germany.com

National contact :

Emergency telephone number : +7 495 628 1687
+49 8142 3051 517

2. Hazards identification

GHS Classification

: Aerosols, Category 1
Skin irritation, Category 2
Reproductive toxicity, Category 2
Specific target organ toxicity - single exposure, Category 3, Central nervous system
Specific target organ toxicity - repeated exposure, Category 2, Inhalation, Central nervous system
Aspiration hazard, Category 1
Short-term (acute) aquatic hazard, Category 1
Long-term (chronic) aquatic hazard, Category 2

GHS-Labeling

Symbol(s) :    

Signal word : Danger

Hazard statements : H222: Extremely flammable aerosol.
H229: Pressurised container: May burst if heated.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H336: May cause drowsiness or dizziness.
H361: Suspected of damaging fertility or the unborn child.
H373: May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.
H400: Very toxic to aquatic life.
H411: Toxic to aquatic life with long lasting effects.



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe mist.
P273 Avoid release to the environment.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P331 Do NOT induce vomiting.
P391 Collect spillage.
Storage:
P405 Store locked up.
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

3. Composition/information on ingredients

Chemical nature : Active substance with propellant
Solvent mixture

Hazardous components

Chemical name	CAS-No.	Concentration[%]
Dimethyl ether	115-10-6	30 - 50
Naphtha (petroleum), hydrotreated light	64742-49-0	25 - 30
copper	7440-50-8	2,5 - 10
n-Butyl acetate	123-86-4	1 - 10
Tin	7440-31-5	1 - 10
molybdenum disulphide	1317-33-5	1 - 10
n-hexane	110-54-3	1 - 2,5

4. First aid measures

If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

- respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash skin thoroughly with soap and water or use recognized skin cleanser.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

Notes to physician

- Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.
- Risks : Central nervous system depression
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.
- Treatment : Treat symptomatically.

5. Firefighting measures

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing media : High volume water jet



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

- Specific hazards during firefighting : Fire may cause evolution of:
Carbon oxides
Metal oxides
Oxides of phosphorus
Sulphur oxides
- : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.
- Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

6. Accidental release measures

- Personal precautions : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.
- Additional advice : Only qualified personnel equipped with suitable protective equipment may intervene.

7. Handling and storage

Handling



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

Advice on safe handling : Do not use in areas without adequate ventilation.
 Do not breathe vapours or spray mist.
 In case of insufficient ventilation, wear suitable respiratory equipment.
 Avoid exposure - obtain special instructions before use.
 Avoid contact with skin and eyes.
 For personal protection see section 8.
 Keep away from fire, sparks and heated surfaces.
 Smoking, eating and drinking should be prohibited in the application area.
 Wash hands and face before breaks and immediately after handling the product.
 Do not get in eyes or mouth or on skin.
 Do not get on skin or clothing.
 Do not ingest.
 Do not use sparking tools.
 These safety instructions also apply to empty packaging which may still contain product residues.
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Storage

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
 Store in accordance with the particular national regulations.

8. Exposure controls/personal protection

Components with workplace control parameters

Components	CAS-No.	Value	Control parameters	Update	Basis
Dimethyl ether	115-10-6	MPC-TWA	200 mg/m3	2018-04-23	RU OEL
Dimethyl ether	115-10-6	MPC-STEL	600 mg/m3	2018-04-23	RU OEL
n-Butyl acetate	123-86-4	MPC-TWA	50 mg/m3	2018-04-23	RU OEL
n-Butyl acetate	123-86-4	MPC-STEL	200 mg/m3	2018-04-23	RU OEL
molybdenum disulphide	1317-33-5	MPC-TWA	1 mg/m3	2011-07-12	RU OEL



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

molybdenum disulphide	1317-33-5	MPC-STEL	6 mg/m3	2011-07-12	RU OEL
molybdenum disulphide	1317-33-5	MPC-TWA	1 mg/m3	2018-04-23	RU OEL
molybdenum disulphide	1317-33-5	MPC-STEL	6 mg/m3	2018-04-23	RU OEL
n-hexane	110-54-3	MPC-TWA	300 mg/m3	2018-04-23	RU OEL
n-hexane	110-54-3	MPC-STEL	900 mg/m3	2018-04-23	RU OEL

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
 Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
 Short term only
 Filter type A-P

- Hand protection : butyl-rubber
 Manufacturer, importer, supplier: Class 1
 Wear protective gloves.
 The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
 The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

- Eye protection : Safety glasses with side-shields conforming to EN166

- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
 Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

9. Physical and chemical properties

Appearance

Physical state : aerosol
Colour : red brown
Odour : solvent-like

Safety data

Flash point : < -20 °C
Method: Abel-Pensky
Ignition temperature : Remarks: No data available
Lower explosion limit : 0,6 %(V)
Upper explosion limit : 26,2 %(V)
Flammability (solid, gas) : Extremely flammable aerosol.
Oxidizing properties : Note: No data available
Auto-ignition temperature : Note: No data available
pH : Note: Not applicable
Melting point/range : Note: No data available
Boiling point/boiling range : < -20 °C
at 1.013,00 hPa
Sublimation point : Note: No data available
Vapour pressure : 4.600,00 hPa
at 20 °C
Density : 0,82 g/cm³
at 20 °C
Bulk density : Note: No data available
Water solubility : Note: insoluble
Partition coefficient: n-octanol/water : Note: No data available
Solubility in other solvents : Note: No data available



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

Viscosity, dynamic	: Note: No data available
Viscosity, kinematic	: < 20,5 mm ² /s at 40 °C
Relative vapour density	: Note: No data available
Evaporation rate	: Note: No data available

10. Stability and reactivity

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.
Thermal decomposition	: Note: No data available

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Acute oral toxicity	: Remarks: Effects due to ingestion may include: : Symptoms: Central nervous system depression
Acute inhalation toxicity	: Remarks: Respiration of solvent vapour may cause dizziness. : Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression
Acute dermal toxicity	: Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering. : Symptoms: Redness, Local irritation, Skin disorders

Skin corrosion/irritation

Skin irritation	: Remarks: Irritating to skin.
-----------------	--------------------------------

Serious eye damage/eye irritation



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

Eye irritation : Remarks: Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Sensitisation : Remarks: This information is not available.

Germ cell mutagenicity

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Germ cell mutagenicity

Remarks
molybdenum disulphide : Animal testing did not show any mutagenic effects.

Carcinogenicity

Dimethyl ether : Species: Rat
Exposure time: 2
Print Date: OECD Test Guideline 453

Carcinogenicity

Remarks
molybdenum disulphide : No evidence of carcinogenicity in animal studies.

Teratogenicity

Remarks

Teratogenicity

Dimethyl ether : Animal testing did not show any effects on fertility.

n-hexane : Suspected human reproductive toxicant

Target Organ Systemic Toxicant - Single exposure

Naphtha (petroleum), hydrotreated light : Exposure routes: Inhalation
Target Organs: Central nervous system
Remarks: May cause drowsiness or dizziness.

n-Butyl acetate : Exposure routes: Inhalation
Remarks: May cause drowsiness or dizziness.

molybdenum disulphide : Remarks: The substance or mixture is not classified as specific target organ toxicant, single exposure.

n-hexane : Exposure routes: Inhalation
Target Organs: Central nervous system
Remarks: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

Target Organ Systemic Toxicant - Repeated exposure

: This information is not available.

Target Organ Systemic Toxicant - Repeated exposure

molybdenum disulphide : Remarks: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

n-hexane : Exposure routes: Inhalation
Target Organs: Central nervous system
Remarks: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Aspiration hazard

Aspiration toxicity : May be fatal if swallowed and enters airways.

: May be fatal if swallowed and enters airways.

Further information : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

12. Ecological information

Ecotoxicity effects

Toxicity to fish :
Remarks:
Very toxic to aquatic organisms.

Toxicity to daphnia and other aquatic invertebrates : Remarks:
No data available

Toxicity to algae : Remarks:
No data available

copper : 10

Toxicity to bacteria : Remarks:
No data available

Elimination information (persistence and degradability)

Bioaccumulation : Remarks:
This mixture contains no substance considered to be



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Mobility : Remarks:
No data available

Distribution among environmental compartments : Remarks:
No data available

Biodegradability : Remarks:
No data available

Physico-chemical removability : Remarks:
No data available

Further information on ecology

Short-term (acute) aquatic hazard

Naphtha (petroleum), hydrotreated light copper : Toxic to aquatic life.
: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard

Naphtha (petroleum), hydrotreated light copper : Toxic to aquatic life with long lasting effects.
: Very toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated light copper :
:

Naphtha (petroleum), hydrotreated light copper :
:

Naphtha (petroleum), hydrotreated light copper :
:

Results of PBT assessment

Dimethyl ether : Non-classified vPvB substance, Non-classified PBT substance

Tin :
:

Additional ecological : Very toxic to aquatic organisms, may cause long-term adverse



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

information

effects in the aquatic environment.

13. Disposal considerations

- Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.
- Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

14. Transport information

ADR

- UN number : 1950
- Description of the goods : AEROSOLS
- Class : 2
- Classification Code : 5F
- Labels : 2.1
- Environmentally hazardous : yes

IATA

- UN number : 1950
- Description of the goods : Aerosols, flammable
- Class : 2.1
- Labels : 2.1
- Packing instruction (cargo aircraft) : 203



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

Packing instruction : 203
(passenger aircraft)

Packing instruction : Y203
(passenger aircraft)

Environmentally hazardous : no

IMDG

UN number : 1950

Description of the goods : AEROSOLS
(naphtha (petroleum), hydrotreated light, copper)

Class : 2.1

Labels : 2.1

EmS Number : F-D, S-U

Marine pollutant : yes

Other information : No special precautions required.

15. Regulatory information

16. Other information

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety data sheet applies only to products originally packed and labelled by OKS Spezialschmierstoffe. The information contained therein may not be reproduced or modified without the express written permission of OKS Spezialschmierstoffe. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of our safety data sheets (e.g. as a document for download from the Internet) is not permitted without the express written consent of OKS Spezialschmierstoffe. OKS Spezialschmierstoffe provides its customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments



OKS 241

Version 2.1

Revision Date 27.06.2019

Print Date 29.06.2019

contained therein to its own customers, employees and other users of the product. OKS Spezi­alschmierstoffe provides no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorised trading partner of OKS Spezi­alschmierstoffe.
