



## OKS 241

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

### 1. Identification of the substance/mixture and of the company/undertaking

#### Product information

Product name : OKS 241

Use of the Substance/Mixture : Lubricant spray

Company : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599

E-mail address : mcm@oks-germany.com

National contact :





Emergency telephone number : +7 495 628 1687  
+49 8142 3051 517

### 2. Hazards identification

#### GHS Classification

: Aerosols, Category 1  
**Skin irritation, Category 2**  
Reproductive toxicity, Category 2  
Specific target organ toxicity - single exposure, Category 3, Central nervous system  
Specific target organ toxicity - repeated exposure, Category 2, Inhalation, Central nervous system  
**Aspiration hazard, Category 1**  
Acute aquatic toxicity, Category 1  
Chronic aquatic toxicity, Category 2

#### GHS-Labeling

Symbol(s) :    

Signal word : Danger

Hazard statements : H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H336: May cause drowsiness or dizziness.  
H361: Suspected of damaging fertility or the unborn child.  
H373: May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.



## OKS 241

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

H400: Very toxic to aquatic life.

H411: Toxic to aquatic life with long lasting effects.

Precautionary statements

: **Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.

P331 Do NOT induce vomiting.

P391 Collect spillage.

**Storage:**

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### 3. Composition/information on ingredients

Chemical nature : Active substance with propellant  
Solvent mixture

#### Hazardous components

Chemical name	CAS-No.	Concentration[%]
Dimethyl ether	115-10-6	30 - 50
Naphtha (petroleum), hydrotreated light	64742-49-0	25 - 30
copper	7440-50-8	2,5 - 10
n-Butyl acetate	123-86-4	1 - 10
Tin	7440-31-5	1 - 10
molybdenum disulphide	1317-33-5	1 - 10
n-hexane	110-54-3	1 - 2,5

### 4. First aid measures

If inhaled

: Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.



**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

- If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
If easy to do, remove contact lens, if worn.  
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Aspiration hazard if swallowed - can enter lungs and cause damage.

**Notes to physician**

- Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema  
  
Aspiration may cause pulmonary oedema and pneumonitis.
- Risks : Central nervous system depression  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.
- Treatment : Treat symptomatically.



**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

**5. Firefighting measures**

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during firefighting : Fire may cause evolution of:  
Carbon oxides  
Metal oxides  
Oxides of phosphorus  
Sulphur oxides
- : Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.  
In the case of respirable dust and/or fumes, use self-contained breathing apparatus.  
Exposure to decomposition products may be a hazard to health.
- Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

**6. Accidental release measures**

- Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to



**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

local / national regulations (see section 13).  
 Keep in suitable, closed containers for disposal.  
 Non-sparking tools should be used.

Additional advice : Only qualified personnel equipped with suitable protective equipment may intervene.

**7. Handling and storage**

**Handling**

Advice on safe handling : Do not use in areas without adequate ventilation.  
 Do not breathe vapours or spray mist.  
 In case of insufficient ventilation, wear suitable respiratory equipment.  
 Avoid exposure - obtain special instructions before use.  
 Avoid contact with skin and eyes.  
 For personal protection see section 8.  
 Keep away from fire, sparks and heated surfaces.  
 Smoking, eating and drinking should be prohibited in the application area.  
 Wash hands and face before breaks and immediately after handling the product.  
 Do not get in eyes or mouth or on skin.  
 Do not get on skin or clothing.  
 Do not ingest.  
 Do not use sparking tools.  
 These safety instructions also apply to empty packaging which may still contain product residues.  
 Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

**Storage**

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
 Store in accordance with the particular national regulations.

**8. Exposure controls/personal protection**

**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Update	Basis



**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

Dimethyl ether	115-10-6	MPC-TWA	200 mg/m3	2011-07-12	RU OEL
Dimethyl ether	115-10-6	MPC-STEL	600 mg/m3	2011-07-12	RU OEL
copper	7440-50-8	MPC-TWA	0,5 mg/m3	2011-07-12	RU OEL
copper	7440-50-8	MPC-STEL	1 mg/m3	2011-07-12	RU OEL
n-Butyl acetate	123-86-4	MPC-TWA	50 mg/m3	2011-07-12	RU OEL
n-Butyl acetate	123-86-4	MPC-STEL	200 mg/m3	2011-07-12	RU OEL
molybdenum disulphide	1317-33-5	MPC-TWA	1 mg/m3	2011-07-12	RU OEL
molybdenum disulphide	1317-33-5	MPC-STEL	6 mg/m3	2011-07-12	RU OEL
molybdenum disulphide	1317-33-5	MPC-TWA	1 mg/m3	2013-09-16	RU OEL
molybdenum disulphide	1317-33-5	MPC-STEL	6 mg/m3	2013-09-16	RU OEL
n-hexane	110-54-3	MPC-TWA	300 mg/m3	2011-07-12	RU OEL
n-hexane	110-54-3	MPC-STEL	900 mg/m3	2011-07-12	RU OEL

**Engineering measures**

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
Short term only  
Filter type A-P



**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

- Hand protection : butyl-rubber  
Manufacturer, importer, supplier: Class 1  
Wear protective gloves.  
The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.  
The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.
- Eye protection : Safety glasses with side-shields conforming to EN166
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.  
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

---

**9. Physical and chemical properties**

**Appearance**

- Physical state : aerosol  
Colour : red brown  
Odour : solvent-like

**Safety data**

- Flash point : < -20 °C  
Method: Abel-Pensky
- Ignition temperature : Remarks: No data available
- Lower explosion limit : 0,6 %(V)
- Upper explosion limit : 26,2 %(V)
- Flammability (solid, gas) : Extremely flammable aerosol.
- Oxidizing properties : Note: No data available



## OKS 241

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

Auto-ignition temperature	: Note: No data available
pH	: Note: Not applicable
Melting point/range	: Note: No data available
Boiling point/boiling range	: < -20 °C at 1.013,00 hPa
Sublimation point	: Note: No data available
Vapour pressure	: 4.600,00 hPa at 20 °C
Density	: 0,82 g/cm <sup>3</sup> at 20 °C
Bulk density	: Note: No data available
Water solubility	: Note: insoluble
Partition coefficient: n-octanol/water	: Note: No data available
Solubility in other solvents	: Note: No data available
Viscosity, dynamic	: Note: No data available
Viscosity, kinematic	: < 20,5 mm <sup>2</sup> /s at 40 °C
Relative vapour density	: Note: No data available
Evaporation rate	: Note: No data available

### 10. Stability and reactivity

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.
Thermal decomposition	: Note: No data available





**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

**11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

- Acute oral toxicity :  
Remarks: Effects due to ingestion may include:  
:  
Symptoms: Central nervous system depression
- Acute inhalation toxicity :  
Remarks: Respiration of solvent vapour may cause dizziness.  
:  
Symptoms: Inhalation may provoke the following symptoms:,  
Respiratory disorder, Dizziness, Drowsiness, Vomiting,  
Fatigue, Vertigo, Central nervous system depression
- Acute dermal toxicity :  
Remarks: Prolonged or repeated skin contact with liquid may  
cause defatting resulting in drying, redness and possible  
blistering.  
:  
Symptoms: Redness, Local irritation, Skin disorders

**Skin corrosion/irritation**

- Skin irritation : Remarks: Irritating to skin.

**Serious eye damage/eye irritation**

- Eye irritation : Remarks: Contact with eyes may cause irritation.

**Respiratory or skin sensitisation**

- Sensitisation : Remarks: This information is not available.

**Germ cell mutagenicity**

- Genotoxicity in vitro : Remarks: No data available
- Genotoxicity in vivo : Remarks: No data available

**Germ cell mutagenicity**

- Remarks  
molybdenum disulphide : Animal testing did not show any mutagenic effects.

**Carcinogenicity**

- Dimethyl ether : Species: Rat  
Exposure time: 2



**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

Print Date: OECD Test Guideline 453

**Carcinogenicity**

Remarks  
molybdenum disulphide : No evidence of carcinogenicity in animal studies.

**Teratogenicity**

Remarks  
**Teratogenicity**  
Dimethyl ether : Animal testing did not show any effects on fertility.  
n-hexane : Suspected human reproductive toxicant

**Target Organ Systemic Toxicant - Single exposure**

Naphtha (petroleum), hydrotreated light : Exposure routes: Inhalation  
Target Organs: Central nervous system  
Remarks: May cause drowsiness or dizziness.  
n-Butyl acetate : Exposure routes: Inhalation  
Remarks: May cause drowsiness or dizziness.  
molybdenum disulphide : Remarks: The substance or mixture is not classified as specific target organ toxicant, single exposure.  
n-hexane : Exposure routes: Inhalation  
Target Organs: Central nervous system  
Remarks: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

**Target Organ Systemic Toxicant - Repeated exposure**

: This information is not available.

**Target Organ Systemic Toxicant - Repeated exposure**

molybdenum disulphide : Remarks: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.  
n-hexane : Exposure routes: Inhalation  
Target Organs: Central nervous system  
Remarks: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

**Aspiration hazard**

Aspiration toxicity : May be fatal if swallowed and enters airways.



**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

: May be fatal if swallowed and enters airways.

Further information : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

---

**12. Ecological information**

**Ecotoxicity effects**

Toxicity to fish :  
Remarks:  
Very toxic to aquatic organisms.

Toxicity to daphnia and other aquatic invertebrates : Remarks:  
No data available

Toxicity to algae : Remarks:  
No data available

copper : 10

Toxicity to bacteria : Remarks:  
No data available

**Elimination information (persistence and degradability)**

Bioaccumulation : Remarks:  
This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Mobility : Remarks:  
No data available

Distribution among environmental compartments : Remarks:  
No data available

Biodegradability : Remarks:  
No data available



**OKS 241**

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

Physico-chemical removability : Remarks:  
No data available

**Further information on ecology**

Acute aquatic toxicity  
Naphtha (petroleum), hydrotreated light copper : Toxic to aquatic life.  
: Very toxic to aquatic life.

Chronic aquatic toxicity  
Naphtha (petroleum), hydrotreated light copper : Toxic to aquatic life with long lasting effects.  
: This product has no known ecotoxicological effects.

Naphtha (petroleum), hydrotreated light copper :  
:

Naphtha (petroleum), hydrotreated light copper :  
:

Naphtha (petroleum), hydrotreated light copper :  
:

Results of PBT assessment  
Dimethyl ether : Non-classified vPvB substance, Non-classified PBT substance

Tin :  
:

Additional ecological information : Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

---

**13. Disposal considerations**

Product : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.



## OKS 241

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

---

### 14. Transport information

#### ADR

UN number : 1950  
Description of the goods : AEROSOLS  
Class : 2  
Classification Code : 5F  
Labels : 2.1  
Environmentally hazardous : yes

#### IATA

UN number : 1950  
Description of the goods : Aerosols, flammable  
Class : 2.1  
Labels : 2.1  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203  
Packing instruction (passenger aircraft) : Y203  
Environmentally hazardous : no

#### IMDG



## OKS 241

Version 2.0

Revision Date 09.08.2018

Print Date 09.08.2018

UN number	: 1950
Description of the goods	: AEROSOLS (naphtha (petroleum), hydrotreated light, copper)
Class	: 2.1
Labels	: 2.1
EmS Number	: F-D, S-U
Marine pollutant	: no
Other information	: No special precautions required.

---

### 15. Regulatory information

---

### 16. Other information

#### Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

This safety datasheet applies only to products originally packaged and labelled by OKS Spezialschmierstoffe. The information contained therein is protected by copyright and must not be reproduced or amended without the express written approval of OKS Spezialschmierstoffe. This document may be passed on only to the extent required by law. Any dissemination of our safety datasheets (e.g. as a document for download from the Internet) beyond this legally required extent is not permitted without express written consent. OKS Spezialschmierstoffe provides its customers with amended safety datasheets as prescribed by law. The customer is responsible for passing on safety datasheets and any amendments contained therein to its own customers, employees and other users of the product. OKS Spezialschmierstoffe provides no guarantee that safety datasheets received by users from third parties are up-to-date. All information and instructions in this safety datasheets were compiled to the best of our knowledge and are based on the information available to us. The data provided are intended to describe the product in relation to the required safety measures; they are neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and do not justify any contractual legal relationships.