

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : OKS 2511

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Anticorrosion additive

Recommended restrictions  
on use : Restricted to professional users.

#### 1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599  
info@oks-germany.com

E-mail address of person  
responsible for the SDS : mcm@oks-germany.com  
Material Compliance Management

National contact :

#### 1.4 Emergency telephone number

Emergency telephone num-  
ber : CIAV - Information Centre of Antipoison  
(+351) 800 250 250 (free 24/7 service)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - repeated  
exposure, Category 2, Auditory system H373: May cause damage to organs through pro-  
longed or repeated exposure if inhaled.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

Short-term (acute) aquatic hazard, Category 1      H400: Very toxic to aquatic life.

Long-term (chronic) aquatic hazard, Category 1      H410: Very toxic to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements :

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H373	May cause damage to organs (Auditory system) through prolonged or repeated exposure if inhaled.
H410	Very toxic to aquatic life with long lasting effects.

Precautionary statements :

#### Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe mist.
P273	Avoid release to the environment.

#### Response:

P391	Collect spillage.
------	-------------------

#### Storage:

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
-------------	---

Hazardous components which must be listed on the label:  
reaction mass of ethylbenzene and xylene

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version 2.5      Revision Date: 19.04.2021      Date of last issue: 02.02.2021      Print Date: 19.04.2021  
Date of first issue: 28.06.2016

### SECTION 3: Composition/information on ingredients

#### 3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.  
Metal powder

#### Components

Chemical name	CAS-No. EC-No.  Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3  030-001-01-9 01-2119467174-37-XXXX	Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 1/1	$\geq 25 - < 30$
reaction mass of ethylbenzene and xylene	905-588-0  01-2119488216-32-XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 Asp. Tox.1; H304	Note C	$\geq 10 - < 20$
propane	74-98-6 200-827-9  601-003-00-5 01-2119486944-21-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	$\geq 10 - < 20$
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9  607-195-00-7 01-2119475791-29-XXXX	Flam. Liq.3; H226 STOT SE3; H336		$\geq 1 - < 10$
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	918-167-1  01-2119472146-39-XXXX	Flam. Liq.3; H226 Asp. Tox.1; H304	Note P	$\geq 1 - < 10$
n-butyl acetate	123-86-4 204-658-1	Flam. Liq.3; H226 STOT SE3; H336		$\geq 1 - < 10$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version 2.5      Revision Date: 19.04.2021      Date of last issue: 02.02.2021      Print Date: 19.04.2021  
Date of first issue: 28.06.2016

	607-025-00-1 01-2119485493-29-XXXX			
acetone	67-64-1 200-662-2  606-001-00-8 01-2119471330-49-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		>= 1 - < 10
Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7  601-004-00-0	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 30 - < 50
isobutane	75-28-5 200-857-2  601-004-00-0 01-2119485395-27-XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
Seek medical advice.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

If swallowed : Move the victim to fresh air.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema

Risks : Causes skin irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : ABC powder  
Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.  
Hazardous combustion products : Carbon oxides  
Metal oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.  
Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

Cool containers/tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Refer to protective measures listed in sections 7 and 8.  
Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Non-sparking tools should be used.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

Do not ingest.  
Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

### 7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	VLE_CD	1.000 ppm	PT OEL (2014-11-14)
reaction mass of ethylbenzene and xylene	Not Assigned	TWA	50 ppm 221 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		VLE-MP	100 ppm	PT OEL (2007-03-26)
Further information	Substances that are not classified as carcinogenic for humans.			
		VLE_CD	150 ppm	PT OEL (2007-03-26)
Further information	Substances that are not classified as carcinogenic for humans.			
		TWA	50 ppm 221 mg/m <sup>3</sup>	PT DL 305/2007 (2007-08-24)
Further information	A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version  
2.5

Revision Date:  
19.04.2021

Date of last issue: 02.02.2021  
Date of first issue: 28.06.2016

Print Date:  
19.04.2021

		STEL	100 ppm 442 mg/m <sup>3</sup>	PT DL 305/2007 (2007-08-24)
Further information	A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.			
2-methoxy-1-methylethyl acetate	108-65-6	TWA	50 ppm 275 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 550 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		TWA	50 ppm 275 mg/m <sup>3</sup>	PT DL 305/2007 (2012-02-06)
Further information	A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.			
		STEL	100 ppm 550 mg/m <sup>3</sup>	PT DL 305/2007 (2012-02-06)
Further information	A skin notation assigned to the occupational exposure limit value indicates the possibility of significant uptake through the skin.			
isobutane	75-28-5	VLE_CD	1.000 ppm	PT OEL (2014-11-14)
n-butyl acetate	123-86-4	VLE-MP	150 ppm	PT OEL (2007-03-26)
		VLE_CD	200 ppm	PT OEL (2007-03-26)
acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
Further information	Indicative			
		VLE-MP	500 ppm	PT OEL (2014-11-14)
Further information	Substances that are not classified as carcinogenic for humans.			
		VLE_CD	750 ppm	PT OEL (2014-11-14)
Further information	Substances that are not classified as carcinogenic for humans.			
		TWA	500 ppm 1.210 mg/m <sup>3</sup>	PT DL 305/2007 (2007-08-24)

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
reaction mass of ethylbenzene and xylene	Not Assigned	Methylhippuric acids (o, m, p): 1.5 g/g creatinine (Urine)	End of shift	PT NP1796 (2014-11-14)
acetone	67-64-1	Acetone: 50 mg/l (Urine)	End of shift	PT NP1796 (2014-11-14)

**Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version  
2.5

Revision Date:  
19.04.2021

Date of last issue: 02.02.2021  
Date of first issue: 28.06.2016

Print Date:  
19.04.2021

Substance name	End Use	Exposure routes	Potential health effects	Value
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	83 mg/kg
reaction mass of ethylbenzene and xylene	Workers	Inhalation	Long-term systemic effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	442 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	221 mg/m <sup>3</sup>
	Workers	Inhalation	Acute local effects	442 mg/m <sup>3</sup>
2-methoxy-1-methylethyl acetate	Workers	Skin contact	Long-term systemic effects	212 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term systemic effects	275 mg/m <sup>3</sup>
	Workers	Inhalation	Long-term local effects	550 mg/m <sup>3</sup>
n-butyl acetate	Workers	Skin contact	Long-term systemic effects	796 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	300 mg/m <sup>3</sup>
	Workers	Inhalation	Acute systemic effects	600 mg/m <sup>3</sup>
	Workers	Dermal	Long-term local effects	11 mg/cm <sup>2</sup>

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
zinc powder — zinc dust (stabilised)	Fresh water	0,0206 mg/l
	Fresh water sediment	235,6 mg/kg
	Marine water	0,0061 mg/l
	Marine sediment	121 mg/kg
	Microbiological Activity in Sewage Treatment Systems	0,052 mg/l
reaction mass of ethylbenzene and xylene	Soil	106,8 mg/kg
	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Sewage treatment plant	6,58 mg/l
	Fresh water sediment	12,46 mg/kg
2-methoxy-1-methylethyl acetate	Marine sediment	12,46 mg/kg
	Soil	2,31 mg/kg
	Fresh water	0,635 mg/l
	Marine water	0,0635 mg/l
	Intermittent use/release	6,35 mg/l
	Microbiological Activity in Sewage Treatment Systems	100 mg/l
	Fresh water sediment	3,29 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version 2.5      Revision Date: 19.04.2021      Date of last issue: 02.02.2021      Print Date: 19.04.2021  
Date of first issue: 28.06.2016

	Marine sediment	0,329 mg/kg
	Soil	0,29 mg/kg
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Microbiological Activity in Sewage Treatment Systems	35,6 mg/l
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,09 mg/kg

### 8.2 Exposure controls

#### Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

#### Personal protective equipment

Eye protection : Safety glasses with side-shields

#### Hand protection

Material : Nitrile rubber  
Break through time : > 10 min  
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.  
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:  
Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.  
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version 2.5	Revision Date: 19.04.2021	Date of last issue: 02.02.2021 Date of first issue: 28.06.2016	Print Date: 19.04.2021
----------------	------------------------------	---	---------------------------

Appearance : aerosol

Colour : grey

Odour : characteristic

Odour Threshold : No data available

  

pH : substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : -41 °C  
(1.013 hPa)

Flash point : -60,00 °C  
Method: Abel-Pensky, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper flammability limit : 10,9 %(V)

Lower explosion limit / Lower flammability limit : 1,1 %(V)

Vapour pressure : 4.000 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0,8 (20 °C)  
Reference substance: Water  
The value is calculated

Density : 0,80 g/cm<sup>3</sup>  
(20 °C)

Bulk density : No data available

Solubility(ies)  
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version 2.5	Revision Date: 19.04.2021	Date of last issue: 02.02.2021 Date of first issue: 28.06.2016	Print Date: 19.04.2021
----------------	------------------------------	---	---------------------------

Decomposition temperature : No data available

### Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : not determined

Explosive properties : Not explosive

Oxidizing properties : No data available

### 9.2 Other information

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : not auto-flammable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazards to be specially mentioned.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

#### Product:

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

Respiratory disorder

Acute toxicity estimate: > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method

Acute dermal toxicity : Symptoms: Redness, Local irritation

Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

### Components:

#### **zinc powder — zinc dust (stabilised):**

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 5,41 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity

#### **reaction mass of ethylbenzene and xylene:**

Acute oral toxicity : LD50 (Rat): 3.523 - 4.000 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

#### **2-methoxy-1-methylethyl acetate:**

Acute oral toxicity : LD50 (Rat): 6.190 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 35,7 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17.600 mg/kg

### acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

### butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

### isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

### Skin corrosion/irritation

#### Product:

Remarks : Irritating to skin.

#### Components:

##### zinc powder — zinc dust (stabilised):

Species : Rabbit  
Assessment : No skin irritation  
Result : No skin irritation

##### reaction mass of ethylbenzene and xylene:

Assessment : Irritating to skin.  
Result : Irritating to skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### 2-methoxy-1-methylethyl acetate:

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation  
GLP : yes

### Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

### n-butyl acetate:

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : Repeated exposure may cause skin dryness or cracking.

### acetone:

Result : Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

#### Product:

Remarks : Irritating to eyes.

#### Components:

##### zinc powder — zinc dust (stabilised):

Species : Rabbit  
Exposure time : 24 h  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

##### reaction mass of ethylbenzene and xylene:

Assessment : Irritating to eyes.  
Result : Irritating to eyes.

### 2-methoxy-1-methylethyl acetate:

Species : Rabbit  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### **n-butyl acetate:**

Species : Rabbit  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

### **acetone:**

Species : Rabbit  
Result : Eye irritation

### **Respiratory or skin sensitisation**

#### **Product:**

Remarks : This information is not available.

#### **Components:**

##### **zinc powder — zinc dust (stabilised):**

Species : Guinea pig  
Assessment : Did not cause sensitisation on laboratory animals.  
Method : OECD Test Guideline 406  
Result : Did not cause sensitisation on laboratory animals.  
GLP : yes

##### **reaction mass of ethylbenzene and xylene:**

Assessment : Did not cause sensitisation on laboratory animals.  
Result : Did not cause sensitisation on laboratory animals.

##### **2-methoxy-1-methylethyl acetate:**

Test Type : Maximisation Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

##### **n-butyl acetate:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

##### **zinc powder — zinc dust (stabilised):**

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

##### **2-methoxy-1-methylethyl acetate:**

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

##### **n-butyl acetate:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Test system: Chinese hamster cells  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Species: Mouse  
Application Route: Oral  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

### Carcinogenicity

#### Product:

Remarks : No data available

#### Components:

##### **zinc powder — zinc dust (stabilised):**

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### 2-methoxy-1-methylethyl acetate:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### n-butyl acetate:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### Components:

#### zinc powder — zinc dust (stabilised):

Reproductive toxicity - Assessment : No toxicity to reproduction  
No effects on or via lactation

#### reaction mass of ethylbenzene and xylene:

Reproductive toxicity - Assessment : Animal testing did not show any effects on fertility.

### 2-methoxy-1-methylethyl acetate:

Reproductive toxicity - Assessment : No toxicity to reproduction  
No toxicity to reproduction

### n-butyl acetate:

Effects on fertility : Test Type: Two-generation study  
Species: Rat  
Application Route: inhalation (vapour)  
General Toxicity - Parent: NOAEC: 750 mg/l  
General Toxicity F1: NOAEC: 750 mg/l  
General Toxicity F2: NOAEC: 750 mg/l  
Method: OECD Test Guideline 416  
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.  
No toxicity to reproduction

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### STOT - single exposure

#### Components:

##### reaction mass of ethylbenzene and xylene:

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

##### 2-methoxy-1-methylethyl acetate:

Exposure routes : Ingestion  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

##### n-butyl acetate:

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

##### acetone:

Exposure routes : Inhalation  
Assessment : May cause drowsiness or dizziness.

### STOT - repeated exposure

#### Components:

##### reaction mass of ethylbenzene and xylene:

Exposure routes : Inhalation  
Target Organs : Auditory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

##### 2-methoxy-1-methylethyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### n-butyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### Repeated dose toxicity

#### Product:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

Remarks : This information is not available.

### Components:

#### **n-butyl acetate:**

Species : Rat  
NOAEL : 125 mg/kg  
Application Route : Oral

#### **Aspiration toxicity**

### Product:

This information is not available.

### Components:

#### **zinc powder — zinc dust (stabilised):**

No aspiration toxicity classification

#### **reaction mass of ethylbenzene and xylene:**

May be fatal if swallowed and enters airways.

#### **2-methoxy-1-methylethyl acetate:**

No aspiration toxicity classification

#### **Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:**

May be fatal if swallowed and enters airways.

#### **n-butyl acetate:**

No aspiration toxicity classification

### **Further information**

### Product:

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

### Product:

Toxicity to fish : Remarks: May cause long-term adverse effects in the aquatic environment.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms :  
Remarks: No data available

### Components:

#### **zinc powder — zinc dust (stabilised):**

Toxicity to fish : LC50 (Oncorhynchus kisutch (coho salmon)): 0,727 mg/l  
Exposure time: 96 h  
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,937 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202

M-Factor (Acute aquatic toxicity) : 1

M-Factor (Chronic aquatic toxicity) : 1

### **Ecotoxicology Assessment**

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : Very toxic to aquatic life with long lasting effects.

### **reaction mass of ethylbenzene and xylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

### **2-methoxy-1-methylethyl acetate:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 - 180 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 373 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

Toxicity to algae/aquatic plants : NOEC (Pseudokirchneriella subcapitata (green algae)): >= 1.000 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to microorganisms : EC10 (activated sludge): > 1.000 mg/l  
Exposure time: 0,5 h  
Test Type: static test  
Method: OECD Test Guideline 209

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: > 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: Reproduction Test  
Method: OECD Test Guideline 211

### **n-butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Test Type: flow-through test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 44 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l  
Exposure time: 72 h  
Test Type: static test

Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h  
Test Type: Growth inhibition

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: Reproduction Test  
GLP: yes

## 12.2 Persistence and degradability

### **Product:**

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### Components:

#### **reaction mass of ethylbenzene and xylene:**

Biodegradability : Result: rapidly biodegradable  
Biodegradation: 90 %  
Exposure time: 28 d

#### **2-methoxy-1-methylethyl acetate:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
GLP: yes

#### **Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:**

Biodegradability : Result: Not readily biodegradable.

#### **n-butyl acetate:**

Biodegradability : Test Type: Primary biodegradation  
Result: rapidly biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

#### **acetone:**

Biodegradability : Result: rapidly biodegradable

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

### Components:

#### **reaction mass of ethylbenzene and xylene:**

Partition coefficient: n-octanol/water : log Pow: 3,12 - 3,2

#### **propane:**

Partition coefficient: n-octanol/water : log Pow: 2,36

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### 2-methoxy-1-methylethyl acetate:

Bioaccumulation : Bioconcentration factor (BCF): 3,16

Partition coefficient: n-octanol/water : log Pow: 0,36 (25 °C)  
Method: OECD Test Guideline 107  
GLP: yes

### Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

### n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

### acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

### butane:

Partition coefficient: n-octanol/water : log Pow: 2,89  
Method: OECD Test Guideline 107

### isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88  
Method: OECD Test Guideline 107

## 12.4 Mobility in soil

### Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### Components:

#### **2-methoxy-1-methylethyl acetate:**

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

#### **n-butyl acetate:**

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

### 12.6 Other adverse effects

#### Product:

Endocrine disrupting potential : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Additional ecological information : No information on ecology is available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied  
16 05 04\*, gases in pressure containers (including halons)  
containing hazardous substances

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

### SECTION 14: Transport information

#### 14.1 UN number

ADR : UN 1950  
RID : UN 1950  
IMDG : UN 1950  
IATA : UN 1950

#### 14.2 UN proper shipping name

ADR : AEROSOLS  
RID : AEROSOLS  
IMDG : AEROSOLS  
(zinc powder - zinc dust (stabilized))  
IATA : Aerosols, flammable

#### 14.3 Transport hazard class(es)

ADR : 2  
RID : 2  
IMDG : 2.1  
IATA : 2.1

#### 14.4 Packing group

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**RID**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Hazard Identification Number : 23  
Labels : 2.1

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### 14.5 Environmental hazards

#### ADR

Environmentally hazardous : yes

#### RID

Environmentally hazardous : yes

#### IMDG

Marine pollutant : yes

#### IATA (Passenger)

Environmentally hazardous : no

#### IATA (Cargo)

Environmentally hazardous : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

the market and use of certain dangerous substances, preparations and articles (Annex XVII)

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors

Acquisition, introduction, possession or use of the explosive precursor by the general public is subject to reporting obligations. acetone (ANNEX II)

P2

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

E1 ENVIRONMENTAL HAZARDS

18 Liquefied extremely flammable gases (including LPG) and natural gas

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 73,38 %

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: Other information

### Full text of H-Statements

H220 : Extremely flammable gas.  
H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H280 : Contains gas under pressure; may explode if heated.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

- H315 : Causes skin irritation.
- H319 : Causes serious eye irritation.
- H332 : Harmful if inhaled.
- H335 : May cause respiratory irritation.
- H336 : May cause drowsiness or dizziness.
- H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.
- H400 : Very toxic to aquatic life.
- H410 : Very toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

- Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.
- Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part 2, Section 2.3.2.1, Note 2).
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- PT DL 305/2007 : Portugal. Indicative Occupational Exposure Limits
- PT NP1796 : Portuguese Norm 1796 - Biological Exposure Indices
- PT OEL : Portugal. Security and Health at the Workplace - Occupational exposure limits of chemical agents
- 2000/39/EC / TWA : Limit Value - eight hours
- 2000/39/EC / STEL : Short term exposure limit
- PT DL 305/2007 / TWA : 8 Hour limit value
- PT DL 305/2007 / STEL : Short term limit value
- PT OEL / VLE-MP : Time Weighted Average
- PT OEL / VLE\_CD : Short Term Exposure Limit

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT RE 2	H373
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Calculation method
Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PT



## OKS 2511

Version	Revision Date:	Date of last issue: 02.02.2021	Print Date:
2.5	19.04.2021	Date of first issue: 28.06.2016	19.04.2021

---

from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.