According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2521

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Anticorrosion additive

Substance/Mixture

Recommended restrictions

on use

: Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone

number

: +49 8142 3051 517 (24/7 service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Skin irritation, Category 2 H315: Causes skin irritation.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters

airways.

Long-term (chronic) aquatic hazard,

Category 3

H412: Harmful to aquatic life with long lasting

effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters

airways.

H315 Causes skin irritation.

H412 Harmful to aquatic life with long lasting

effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

xylene

ethylbenzene

Additional Labelling

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

VersionRevision Date:Date of last issue: 11.05.2021Print Date:2.206.12.2022Date of first issue: 30.03.201306.12.2022

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Metal powder

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
xylene	1330-20-7 215-535-7 601-022-00-9	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Asp. Tox.1; H304		>= 30 - < 50
propane	74-98-6 200-827-9 601-003-00-5	Flam. Gas1; H220 Press. GasCompr. Gas; H280		>= 20 - < 30
isobutane	75-28-5 200-857-2 601-004-00-0	Flam. Gas1A; H220 Press. GasCompr. Gas; H280		>= 1 - < 10
ethylbenzene	100-41-4 202-849-4 601-023-00-4	Flam. Liq.2; H225 Acute Tox.4; H332 STOT RE2; H373 Asp. Tox.1; H304 Aquatic Chronic3; H412		>= 2.5 - < 10
acetone	67-64-1 200-662-2 606-001-00-8	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		>= 1 - < 10
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3 030-001-01-9	Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 1/1	>= 0.25 - < 1
Substances with a wo	rkplace exposure limit :	•	•	•

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

VersionRevision Date:Date of last issue: 11.05.2021Print Date:2.206.12.2022Date of first issue: 30.03.201306.12.2022

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Obtain medical attention.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB $\,$



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

: High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible

absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular

national regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis	
xylene	1330-20-7	TWA	50 ppm 220 mg/m3	GB EH40GB EH40 (2018-08-01)	
	substances a	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		STEL	100 ppm 441 mg/m3	GB EH40GB EH40 (2018-08-01)	
	substances a	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	50 ppm 221 mg/m3	2000/39/EC2 000/39/EC (2000-06-16)	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	100 ppm 442 mg/m3	2000/39/EC2 000/39/EC (2000-06-16)	
		Further information: Identifies the possibility of significant uptake through the skin, Indicative			
butane	106-97-8	STEL	750 ppm 1,810 mg/m3	GB EH40GB EH40 (2007-08-01)	

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

VersionRevision Date:Date of last issue: 11.05.2021Print Date:2.206.12.2022Date of first issue: 30.03.201306.12.2022

	Further info	rmation: Capable	e of causing cancer and/or he	eritable genetic	
	adago:	TWA	600 ppm 1,450 mg/m3	GB EH40GB EH40 (2007-08-01)	
	Further info	rmation: Capable	e of causing cancer and/or he	eritable genetic	
ethylbenzene	100-41-4	TWA	100 ppm 441 mg/m3	GB EH40GB EH40 (2005-04-06)	
	substances		absorbed through the skin. Tich there are concerns that c		
		STEL	125 ppm 552 mg/m3	GB EH40GB EH40 (2005-04-06)	
	substances	Further information: Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.			
		TWA	100 ppm 442 mg/m3	2000/39/EC2 000/39/EC (2000-06-16)	
	Further info	t uptake through the			
		STEL	200 ppm 884 mg/m3	2000/39/EC2 000/39/EC (2000-06-16)	
	Further information: Identifies the possibility of significant uptake through the skin, Indicative				
acetone	67-64-1	TWA	500 ppm 1,210 mg/m3	GB EH40GB EH40 (2005-04-06)	
		STEL	1,500 ppm 3,620 mg/m3	GB EH40GB EH40 (2005-04-06)	
		TWA	500 ppm 1,210 mg/m3	2000/39/EC2 000/39/EC (2000-06-16)	
	Further info	rmation: Indicativ	/e		

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methyl hippuric acid: 650 Millimoles per mole Creatinine (Urine)	After shift	GB EH40 BAT (2011-12- 18)

Derived No Effect Level (DNEL):



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

VersionRevision Date:Date of last issue: 11.05.2021Print Date:2.206.12.2022Date of first issue: 30.03.201306.12.2022

Substance name	End Use	Exposure routes	Potential health effects	Value
ethylbenzene	Workers	Skin contact	Long-term systemic effects	180 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	77 mg/m3
	Workers	Inhalation	Acute local effects	293 mg/m3
acetone	Workers	Inhalation	Long-term systemic effects	1210 mg/m3
	Workers	Skin contact	Long-term systemic effects	186 mg/kg
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Skin contact	Long-term systemic effects	83 mg/kg

Predicted No Effect Concentration (PNEC):

Substance name	Environmental Compartment	Value
ethylbenzene	Fresh water	0.1 mg/l
	Marine water	0.01 mg/l
	Intermittent use/release	0.1 mg/l
	Microbiological Activity in Sewage	9.6 mg/l
	Treatment Systems	
	Fresh water sediment	13.7 mg/kg
	Marine sediment	1.37 mg/kg
	Soil	2.68 mg/kg
	Oral	20 mg/kg
acetone	Fresh water	10.6 mg/l
	Marine water	1.06 mg/l
	Sewage treatment plant	100 mg/l
	Fresh water sediment	30.4 mg/kg
	Marine sediment	3.04 mg/kg
	Soil	29.5 mg/kg
zinc powder — zinc dust (stabilised)	Fresh water	0.0206 mg/l
	Fresh water sediment	235.6 mg/kg
	Marine water	0.0061 mg/l
	Marine sediment	121 mg/kg
	Microbiological Activity in Sewage Treatment Systems	0.052 mg/l
	Soil	106.8 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Material : Fluorinated rubber

Break through time : > 10 min Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Respiratory protection : Respirator with combination filter for vapour/particulate (EN

141)

Short term only

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : ABEK-P3-filter

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : silver

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : -161 °C (1,013 hPa)

Not applicable

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Flash point : -60 °C

Method: Abel-Pensky

Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

10.9 %(V)

Lower explosion limit / Lower :

flammability limit

1.1 %(V)

Vapour pressure : 5,500 hPa (20 °C)

not determined

Relative vapour density : No data available

Relative density : 0.66 (20 °C)

Reference substance: Water The value is calculated

Density : 0.66 g/cm3

(20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : > 200 °C

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : water

Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Harmful if swallowed.

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Remarks: Harmful by inhalation.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder

Acute dermal toxicity : Acute toxicity estimate: > 2,000 mg/kg

Method: Calculation method

Symptoms: Redness, Local irritation

Components:

xylene:

Acute inhalation toxicity : LC50 (Rat): 21 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rat): > 1,000 mg/kg

Assessment: The component/mixture is moderately toxic after

single contact with skin.

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3,500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17.2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 15,400 mg/kg

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

zinc powder - zinc dust (stabilised):

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Assessment: The substance or mixture has no acute oral

toxicity

Acute inhalation toxicity : LC50 (Rat): > 5.41 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute

inhalation toxicity

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

xylene:

Result : Severe skin irritation

ethylbenzene:

Species : Rabbit

Result : Mild skin irritation

zinc powder — zinc dust (stabilised):

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

ethylbenzene:

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

acetone:

Species : Rabbit Result : Eye irritation

zinc powder - zinc dust (stabilised):

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Species : Rabbit Exposure time : 24 h

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

ethylbenzene:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

zinc powder - zinc dust (stabilised):

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

ethylbenzene:

Germ cell mutagenicity: Tests on bacterial or mammalian cell cultures did not show

Assessment mutagenic effects.

zinc powder — zinc dust (stabilised):

Germ cell mutagenicity: Tests on bacterial or mammalian cell cultures did not show

Assessment mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

VersionRevision Date:Date of last issue: 11.05.2021Print Date:2.206.12.2022Date of first issue: 30.03.201306.12.2022

Components:

ethylbenzene:

Carcinogenicity - Assessment

: Not classifiable as a human carcinogen.

zinc powder - zinc dust (stabilised):

Carcinogenicity -

: No evidence of carcinogenicity in animal studies.

Assessment

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development

: Remarks: No data available

Components:

ethylbenzene:

Reproductive toxicity - : - Fertility -

Assessment

No toxicity to reproduction

- Teratogenicity -

No toxicity to reproduction

zinc powder - zinc dust (stabilised):

Reproductive toxicity - : - Fertility -

Assessment

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

STOT - single exposure

Components:

ethylbenzene:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

acetone:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

VersionRevision Date:Date of last issue: 11.05.2021Print Date:2.206.12.2022Date of first issue: 30.03.201306.12.2022

STOT - repeated exposure

Components:

ethylbenzene:

Exposure routes : Inhalation
Target Organs : hearing organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

xylene:

May be fatal if swallowed and enters airways.

ethylbenzene:

May be fatal if swallowed and enters airways.

zinc powder - zinc dust (stabilised):

No aspiration toxicity classification

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure.

Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

Possible risk of irreversible effects.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version **Revision Date:** Date of last issue: 11.05.2021 Print Date: 06.12.2022 Date of first issue: 30.03.2013 06.12.2022 2.2

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish Remarks: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

12.2 Persistence and degradability

Product:

Biodegradability Remarks: No data available

Physico-chemical removability

Remarks: No data available

12.3 Bioaccumulative potential

Product:

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

12.4 Mobility in soil

Product:

Remarks: No data available Mobility

Distribution among

environmental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

12.6 Other adverse effects

Product:

Endocrine disrupting

potential

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Additional ecological

information

: Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS RID : AEROSOLS



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

VersionRevision Date:Date of last issue: 11.05.2021Print Date:2.206.12.2022Date of first issue: 30.03.201306.12.2022

IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction : 203

(passenger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version **Revision Date:** Date of last issue: 11.05.2021 Print Date: 06.12.2022 Date of first issue: 30.03.2013 06.12.2022 2.2

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

: Not applicable for product as supplied. Remarks

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered: xylene (Number on list 3)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57). Not applicable

REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV)

Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone laver (EC 1005/2009)

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP)

Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC)

xylene

UK REACH List of substances subject to authorisation (Annex XIV)

Not applicable

(UK. REACH Annex XIV)

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation

Not applicable

(GB PIC)

Regulation (EU) 2019/1148 on the marketing and use of : Listed

explosives precursors

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see https://ec.europa.eu/home-affairs/sites/homeaffairs/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list_of_competent_authorities_and_national contact points en.pdf

acetone (ANNEX II)

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of R-Phrases

Note C : Some organic substances may be marketed either in a

specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Note U (table 3.1) : When put on the market gases have to be classified as

"Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

Full text of H-Statements

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin. H315 : Causes skin irritation.

H319 : Causes serious eve irritation.

H332 : Harmful if inhaled.

H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated

exposure if inhaled.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.H412 : Harmful to aquatic life with long lasting effects.

Full text of other abbreviations



According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

Note C : Some organic substances may be marketed either in a

specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Substance is a specific isomer or a mixture of isomers.

Note U (table 3.1) : When put on the market gases have to be classified as

"Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

list of indicative occupational exposure limit values

GB EH40 : UK. EH40 WEL - Workplace Exposure Limits
GB EH40 BAT : UK. Biological monitoring guidance values

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit

GB EH40 / TWA : Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL : Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN -Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx -Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship;

According to REACH Regulation (EC) No 1907/2006, as amended by UK REACH Regulations SI 2019/758 - GB



OKS 2521

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 2.2 06.12.2022 Date of first issue: 30.03.2013 06.12.2022

REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Classification of the mixture: Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment Skin Irrit. 2 H315 Calculation method
Asp. Tox. 1 H304 Based on product data or assessment Aquatic Chronic 3 H412 Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

