according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

VersionRevision Date:Date of last issue: 11.05.2021Print Date:4.020.05.2022Date of first issue: 28.06.201625.05.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2531

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub: : Anticorrosion additive

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

responsible for the SDS

mcm@oks-germany.com

Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone num-

ber

06 68593726 Roma - CAV "Osp. Pediatrico Bambino

Gesù" Dip. Emergenza e Accettazione DEA 800183459 Foggia - Az. Osp. Univ. Foggia 081-5453333 Napoli - Az. Osp. "A. Cardarelli" 06-49978000 Roma - CAV Policlinico "Umberto I" 06-3054343 Roma - CAV Policlinico "A. Gemelli"

055-7947819 Firenze - Az. Osp. "Careggi" U.O.

Tossicologia Medica

0382-24444 Pavia - CAV Centro Nazionale di

Informazione Tossicologica

02-66101029 Milano - Osp. Niguarda Ca' Granda 800883300 Bergamo - Az. Osp. Papa Giovanni XXII 800011858 Verona - Az. Osp. Integrata Verona

+49 8142 3051 517 (Service 24/7)

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 4.0 20.05.2022 Date of first issue: 28.06.2016 25.05.2022

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Acute toxicity, Category 4 H332: Harmful if inhaled.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated	H373: May cause damage to organs through pro-

exposure, Category 2, hearing organs longed or repeated exposure.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters airways.

H412: Harmful to aquatic life with long lasting ef-

y 3

Long-term (chronic) aquatic hazard, Cat-

egory 3

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :







Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters air-

ways.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H373 May cause damage to organs (hearing

organs) through prolonged or repeated ex-

posure.

H412 Harmful to aquatic life with long lasting ef-

fects.

Precautionary statements : Prevention:



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



\sim	1/0	2531
u	r	Z3.5 L

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 4.0 20.05.2022 Date of first issue: 28.06.2016 25.05.2022

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe mist.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

xylene

ethylbenzene

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active substance with propellant

Solvent Metal powder

Components

Chemical n	CAS-No.	Classification	specific concen-	Concentration
	EC-No.		tration limit M-Factor	(% w/w)
	Index-No.		Notes	



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

VersionRevision Date:Date of last issue: 11.05.2021Print Date:4.020.05.2022Date of first issue: 28.06.201625.05.2022

	Registration number		Acute toxicity estimate	
xylene	1330-20-7 215-535-7 601-022-00-9	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Asp. Tox.1; H304	Note C	>= 30 - < 50
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 20 - < 30
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49- XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 1 - < 10
ethylbenzene	100-41-4, 100-41-4 202-849-4 601-023-00-4	Flam. Liq.2; H225 Acute Tox.4; H332 STOT RE2; H373 Asp. Tox.1; H304		>= 1 - < 10
zinc powder — zinc dust (stabilised)	7440-66-6 231-175-3 030-001-01-9 01-2119467174-37- XXXX	Aquatic Acute1; H400 Aquatic Chronic1; H410	M-Factor: 1/1	>= 0,25 - < 1
Substances with a wor	kplace exposure limit :			
butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 10 - < 20
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10

For explanation of abbreviations see section 16.



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date: 25.05.2022

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Obtain medical attention.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

VersionRevision Date:Date of last issue: 11.05.2021Print Date:4.020.05.2022Date of first issue: 28.06.201625.05.2022

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod: :

ucts

Carbon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8.

Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 4.0 20.05.2022 Date of first issue: 28.06.2016 25.05.2022

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

EBEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

VersionRevision Date:Date of last issue: 11.05.2021Print Date:4.020.05.2022Date of first issue: 28.06.201625.05.2022

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis		
xylene	1330-20-7	TWA	50 ppm	IT OEL		
•			221 mg/m3	(2004-03-10)		
	Further inform	nation: The notation	Skin' attributes to the exposu			
	and indicates	the possibility of abs	sorption through the skin.			
		STEL	100 ppm	IT OEL		
			442 mg/m3	(2004-03-10)		
	Further inforn	nation: The notation	'Skin' attributes to the exposu	ıre limit values		
	and indicates	the possibility of abs	sorption through the skin.			
		TWA	50 ppm	2000/39/EC		
			221 mg/m3	(2000-06-16)		
	Further inforn skin, Indicativ		possibility of significant uptak	ce through the		
		STEL	100 ppm	2000/39/EC		
			442 mg/m3	(2000-06-16)		
	Further inform	nation: Identifies the	possibility of significant uptak			
	skin, Indicativ		. , , , , , , , , , , , , , , , , , , ,	Ü		
acetone	67-64-1	TWA	500 ppm	2000/39/EC		
			1.210 mg/m3	(2000-06-16)		
	Further inform	Further information: Indicative				
		TWA	500 ppm	IT OEL		
			1.210 mg/m3	(2008-02-26)		
ethylbenzene	100-41-4	TWA	100 ppm	2000/39/EC		
			442 mg/m3	(2000-06-16)		
		Further information: Identifies the possibility of significant uptake through the skin, Indicative				
		STEL	200 ppm	2000/39/EC		
			884 mg/m3	(2000-06-16)		
	Further information: Identifies the possibility of significant uptake through the skin, Indicative					
	, , , , , , , , , , , , , , , , , , , ,	TWA	100 ppm	IT OEL		
			442 mg/m3	(2004-03-10)		
	Further information: The notation 'Skin' attributes to the exposure limit values					
	and indicates the possibility of absorption through the skin.					
		STEL	200 ppm	IT OEL		
			884 mg/m3	(2004-03-10)		
	Further information: The notation 'Skin' attributes to the exposure limit values					
	and indicates	the possibility of abs	sorption through the skin.			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date:

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

Substance name	End Use	Exposure routes	Potential health effects	Value
zinc powder — zinc dust (stabilised)	Workers	Inhalation	Long-term systemic effects	5 mg/m3
	Workers	Skin contact	Long-term systemic effects	83 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
zinc powder — zinc dust (stabi-	Fresh water	0,0206 mg/l
lised)		
	Fresh water sediment	235,6 mg/kg
	Marine water	0,0061 mg/l
	Marine sediment	121 mg/kg
	Microbiological Activity in Sewage Treat-	0,052 mg/l
	ment Systems	
	Soil	106,8 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Fluorinated rubber

Break through time : > 10 min Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : Respirator with combination filter for vapour/particulate (EN

141)

Short term only

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date: 25.05.2022

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

Filter type : ABEK-P3-filter

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : silver

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -161 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

10,9 %(V)

Lower explosion limit / Lower :

flammability limit

1,1 %(V)

Flash point : -60 °C

Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date:

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 5.500 hPa (20 °C)

Relative density : 0,66 (20 °C)

Reference substance: Water The value is calculated

Density : 0,66 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

VersionRevision Date:Date of last issue: 11.05.2021Print Date:4.020.05.2022Date of first issue: 28.06.201625.05.2022

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : LC50 (Rat): > 1,0 - 5 mg/l

Test atmosphere: dust/mist

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Remarks: Harmful by inhalation. Irritating to respiratory system.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Local irritation, Respiratory disorders

Acute dermal toxicity : Symptoms: Redness, Local irritation

Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Components:

xylene:

Acute inhalation toxicity : LC50 (Rat): 21 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The component/mixture is moderately toxic after

short term inhalation.

Acute dermal toxicity : LD50 Dermal (Rat): > 1.000 mg/kg

Assessment: The component/mixture is moderately toxic after

single contact with skin.

acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

ethylbenzene:

Acute inhalation toxicity : (Rat): 17,5 mg/l

a brand of

FREUDENBERG

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 4.0 20.05.2022 Date of first issue: 28.06.2016 25.05.2022

Exposure time: 4 h

zinc powder - zinc dust (stabilised):

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 5,41 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute inhala-

tion toxicity

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

xylene:

Result : Severe skin irritation

acetone:

Result : Repeated exposure may cause skin dryness or cracking.

zinc powder — zinc dust (stabilised):

Species : Rabbit

Assessment : No skin irritation Result : No skin irritation



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 4.0 20.05.2022 Date of first issue: 28.06.2016 25.05.2022

Serious eye damage/eye irritation

Product:

Result : Eye irritation

Remarks : Irritating to eyes.

Components:

acetone:

Species : Rabbit Result : Eye irritation

zinc powder - zinc dust (stabilised):

Species : Rabbit Exposure time : 24 h

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

zinc powder - zinc dust (stabilised):

Species : Guinea pig

Assessment : Did not cause sensitisation on laboratory animals.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.

GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

zinc powder - zinc dust (stabilised):

Germ cell mutagenicity- As-

sessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

VersionRevision Date:Date of last issue: 11.05.2021Print Date:4.020.05.2022Date of first issue: 28.06.201625.05.2022

Carcinogenicity

Product:

Remarks : No data available

Components:

zinc powder - zinc dust (stabilised):

Carcinogenicity - Assess-

ment

: No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

: Remarks: No data available

Components:

zinc powder - zinc dust (stabilised):

Reproductive toxicity - As- :

: - Fertility -

sessment

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

STOT - single exposure

Product:

Exposure routes : Inhalation

Assessment : May cause respiratory irritation.

Components:

acetone:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

STOT - repeated exposure

Product:

Target Organs : hearing organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date:

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

Components:

ethylbenzene:

Target Organs : hearing organs

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Components:

ethylbenzene:

Assessment : The substance or mixture is classified as specific target organ

toxicant, repeated exposure, category 2.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

xylene:

May be fatal if swallowed and enters airways.

ethylbenzene:

May be fatal if swallowed and enters airways.

zinc powder — zinc dust (stabilised):

No aspiration toxicity classification

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 4.0 20.05.2022 Date of first issue: 28.06.2016 25.05.2022

Further information

Product:

Remarks Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish Remarks: Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

zinc powder - zinc dust (stabilised):

Toxicity to fish LC50 (Oncorhynchus kisutch (coho salmon)): 0,727 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 0,937 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

M-Factor (Acute aquatic tox-

icity)

M-Factor (Chronic aquatic

toxicity)

: 1

Ecotoxicology Assessment

Acute aquatic toxicity Very toxic to aquatic life.

Chronic aquatic toxicity Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product:



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

VersionRevision Date:Date of last issue: 11.05.2021Print Date:4.020.05.2022Date of first issue: 28.06.201625.05.2022

Biodegradability : Remarks: No data available

Physico-chemical removabil- :

itν

Remarks: No data available

Components:

acetone:

Biodegradability : Result: rapidly biodegradable

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-

octanol/water

log Pow: 0,2

butane:

Partition coefficient: n-

: log Pow: 2,89

octanol/water

Method: OECD Test Guideline 107

isobutane:

Partition coefficient: n-

log Pow: 2,88

octanol/water

Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

Remarks: No data available



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 20.05.2022 Date of first issue: 28.06.2016 25.05.2022 4.0

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered

> to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

mation

Additional ecological infor- : Harmful to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

Version Revision Date: Date of last issue: 11.05.2021 Print Date: 4.0 20.05.2022 Date of first issue: 28.06.2016 25.05.2022

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADN

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date: 25.05.2022

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen: 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADN

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: xylene (Number on list 3) ethylbenzene (Number on list 3)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV)

: Not applicable

(EU. REACH-Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer (EC 1005/2009)

: Not applicable



according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date: 25.05.2022

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast) (EU POP)

: Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

(EU PIC)

xylene ethylbenzene

Regulation (EU) 2019/1148 on the marketing and use of : Listed

explosives precursors

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see https://ec.europa.eu/home-affairs/sites/ homeaffairs/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list_of_competent_authorities_and_national_c ontact_points_en.pdf

acetone (ANNEX II)

: P5c

P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Liquefied extremely flammable gases (including LPG) and natural gas

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 99,5 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Legislative Decree April 9,2008, 81 (Implementation of Article 1 of the Law of 3 August 2007, n. 123, concerning the protection of health and safety in the workplace.) and subsequent amendments

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date:

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

Legislative Decree April 3, 2006, n.152, (Environmental standards) and subsequent amendments

Legislative Decree February 6, 2009, 21 (Regulations for the execution of the provisions laid down in Regulation (EC) no. 648/2004 on detergents)

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H312 : Harmful in contact with skin.

H315 : Causes skin irritation.

H319 : Causes serious eye irritation.

H332 : Harmful if inhaled.

H336 : May cause drowsiness or dizziness.

H373 : May cause damage to organs through prolonged or repeated

exposure.

H400 : Very toxic to aquatic life.

H410 : Very toxic to aquatic life with long lasting effects.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-

stance is a specific isomer or a mixture of isomers.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date: 25.05.2022

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

list of indicative occupational exposure limit values

IT OEL : Italy. List of indicative limit values for professional exposure to

chemical agents.

2000/39/EC / TWA : Limit Value - eight hours 2000/39/EC / STEL : Short term exposure limit IT OEL / TWA : 8 hour exposure limit IT OEL / STEL : Short term exposure limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada): ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		Classification procedure:
Aerosol 1	H222, H229	Based on product data or assessment
Acute Tox. 4	H332	Based on product data or assessment
Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Based on product data or assessment
STOT SE 3	H335	Based on product data or assessment
STOT RE 2	H373	Based on product data or assessment
Asp. Tox. 1	H304	Based on product data or assessment

according to Regulation (EC) No. 1907/2006 - IT (Commission Regulation (EU) 2020/878)



OKS 2531

 Version
 Revision Date:
 Date of last issue: 11.05.2021
 Print Date: 25.05.2022

 4.0
 20.05.2022
 Date of first issue: 28.06.2016
 25.05.2022

Aquatic Chronic 3 H412 Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.