according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 2660

Chemical nature : Solvent mixture

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

: mcm@oks-germany.com

responsible for the SDS

Material Compliance Management

National contact :

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)

+86 21 69225521

Recommended use of the chemical and restrictions on use

Recommended use : Cleaning agent / Cleaner

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquidColour: colourlessOdour: hydrocarbon-like

Highly flammable liquid and vapour. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

GHS Classification

Flammable liquids : Category 2

Skin irritation : Category 2

according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Eye irritation : Category 2A

Specific target organ toxicity - :

single exposure

Category 3 (Narcotic effects)

Aspiration hazard : Category 1

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 2

GHS label elements

Hazard pictograms









Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ ventilating/ lighting equip-

ment

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P261 Avoid breathing vapours.

P264 Wash skin thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/ protective clothing/ eye protec-

tion/ face protection.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediate-

according to GB/T 16483 and GB/T 17519 CN



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

ly all contaminated clothing. Rinse skin with water/ shower. P304 + P340 + P312 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P331 Do NOT induce vomiting.

P332 + P313 If skin irritation occurs: Get medical advice/ attention

P337 + P313 If eye irritation persists: Get medical advice/ attention.

P362 + P364 Take off contaminated clothing and wash it before reuse

P370 + P378 In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.

P391 Collect spillage.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P403 + P235 Store in a well-ventilated place. Keep cool. P405 Store locked up.

Disposal:

P501 Dispose of contents/containers according the local government requirements.

Physical and chemical hazards

Highly flammable liquid and vapour.

Health hazards

Causes skin irritation. Causes serious eye irritation. May cause drowsiness or dizziness. May be fatal if swallowed and enters airways.

Environmental hazards

Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components



according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Chemical name	CAS-No.	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 30 -< 50
Acetone	67-64-1	>= 20 -< 30
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 10 -< 20
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 2.5 -< 10
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 2.5 -< 10
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 2.5 -< 10

4. FIRST AID MEASURES

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention. If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause

damage.

Most important symptoms and effects, both acute and

delayed

Central nervous system depression

Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

Inhalation may provoke the following symptoms:

Unconsciousness



according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or car-

bon dioxide.

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire-

fighting

Do not let product enter drains.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod- :

ucts

Carbon oxides

Specific extinguishing meth-

ods

Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation.

Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.



according to GB/T 16483 and GB/T 17519



OKS 2660

Version Date of last issue: 2018-05-11 Revision Date:

Date of first issue: 2014-04-07 Print Date: 2022-05-19 2022-05-12 2.1

Environmental precautions Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13). Non-sparking tools should be used.

7. HANDLING AND STORAGE

Handling

fire and explosion

Advice on protection against : Keep away from heat and sources of ignition.

Advice on safe handling Use only in an area containing explosion proof equipment.

Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Ensure all equipment is electrically grounded before beginning

transfer operations.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

Do not enter areas where used or stored until adequately ven-

tilated.

Do not repack.

Do not re-use empty containers.

These safety instructions also apply to empty packaging which

may still contain product residues. Keep container closed when not in use.

Avoidance of contact : Oxidizing agents

Storage



according to GB/T 16483 and GB/T 17519 CN



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Conditions for safe storage : Store in original container.

Keep container closed when not in use.

Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with the particular national regulations.

Keep in properly labelled containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Acetone	67-64-1	PC-TWA	300 mg/m3	CN OEL (2019-08-27)
		PC-STEL	450 mg/m3	CN OEL (2019-08-27)
		TWA	250 ppm	ACGIH (2021-01-01)
		STEL	500 ppm	ACGIH (2021-01-01)

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam- pling time	Permissible concentration	Basis
Acetone	67-64-1	Acetone	Urine	End of shift	50 mg/l	CN BEI (2019-08- 27)
		Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI (2017-03- 01)

Engineering measures : Use only in an area equipped with explosion proof exhaust

ventilation.

Handle only in a place equipped with local exhaust (or other

appropriate exhaust).

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates



according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

that exposures are within recommended exposure guidelines.

Filter type : Filter type A-P

Eye/face protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the spe-

cific work-place.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : colourless

Odour : hydrocarbon-like

Odour Threshold : No data available

pH : Not applicable

substance/mixture is non-polar/aprotic

Melting point/range : No data available

Boiling point/boiling range : 61.4 °C

according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

(1,013 hPa)

Flash point : -18 °C

Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Self-ignition : not auto-flammable

Upper explosion limit / Upper

flammability limit

7.7 %(V)

Lower explosion limit / Lower :

flammability limit

0.7 %(V)

Vapour pressure : 8.4 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0.7285 (20 °C)

Reference substance: Water The value is calculated

Density : 0.73 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm2/s (40 °C)

Explosive properties : Not explosive

according to GB/T 16483 and GB/T 17519 CN



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central

nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19 2.1

Components:

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Acetone:

Acute oral toxicity : LD50 Oral (Rat): 5,800 mg/kg

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Naphtha (petroleum), hydrotreated light:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg

Skin corrosion/irritation

Product:

Remarks Irritating to skin.

Components:

Naphtha (petroleum), hydrotreated light:

Result : Skin irritation

Naphtha (petroleum), hydrotreated light:

Species Rabbit Result Skin irritation

Naphtha (petroleum), hydrotreated light:

Result : Skin irritation

Naphtha (petroleum), hydrotreated light:

Species Rabbit

Result Skin irritation



11 / 21

according to GB/T 16483 and GB/T 17519 CN



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

Acetone:

Species : Rabbit Result : Eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

: Remarks: No data available



according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

STOT - single exposure

Components:

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Acetone:

Exposure routes : Inhalation

Assessment : May cause drowsiness or dizziness.

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Naphtha (petroleum), hydrotreated light:

Assessment : May cause drowsiness or dizziness.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.



according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Components:

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Naphtha (petroleum), hydrotreated light:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic :

according to GB/T 16483 and GB/T 17519



OKS 2660

Version Date of last issue: 2018-05-11 Revision Date:

Date of first issue: 2014-04-07 Print Date: 2022-05-19 2.1 2022-05-12

Remarks: No data available plants

Toxicity to microorganisms Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity Toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Naphtha (petroleum), hydrotreated light:

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): > 1 - 10 mg/l

aquatic invertebrates Exposure time: 48 h

Naphtha (petroleum), hydrotreated light:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Persistence and degradability

Product:

: Remarks: No data available Biodegradability

Physico-chemical removabil- : Remarks: No data available

ity



according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Components:

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: Readily biodegradable.

Acetone:

Biodegradability : Result: rapidly biodegradable

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: rapidly biodegradable

Naphtha (petroleum), hydrotreated light:

Biodegradability : Result: Not rapidly biodegradable

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Remarks: Not applicable

Partition coefficient: n-

octanol/water

: Remarks: No data available

Acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-

octanol/water

: log Pow: 0.2

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Remarks: No data available

according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

Partition coefficient: n-

octanol/water

: Remarks: No data available

Naphtha (petroleum), hydrotreated light:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-

octanol/water

log Pow: 4

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

Remarks: No data available

Other adverse effects

Product:

Additional ecological infor-

mation

: Toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of waste product or used containers according to

local regulations.

14. TRANSPORT INFORMATION

International Regulations

according to GB/T 16483 and GB/T 17519



OKS 2660

Version Date of last issue: 2018-05-11 Revision Date:

Date of first issue: 2014-04-07 Print Date: 2022-05-19 2.1 2022-05-12

UNRTDG

UN 1993 UN number

Proper shipping name FLAMMABLE LIQUID, N.O.S.

Class 3 Packing group Ш Labels 3

IATA-DGR

UN/ID No. UN 1993

Proper shipping name Flammable liquid, n.o.s.

> (Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-

364

353

Class Packing group Ш

Labels Flammable Liquids

Packing instruction (cargo

aircraft)

Packing instruction (passen-

ger aircraft)

IMDG-Code

UN number : UN 1993

Proper shipping name FLAMMABLE LIQUID, N.O.S.

(Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics, Hydro-

carbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-

hexane)

Class 3 Ш Packing group Labels 3 **EmS Code** F-E, <u>S-E</u> Marine pollutant yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN 1993 UN number

Proper shipping name FLAMMABLE LIQUID, N.O.S.

Class 3 Packing group Ш Labels 3

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Hazardous Chemicals for Priority Management under : Not applicable

SAWS

China Severely Restricted Toxic Chemicals for Import : Not applicable

and Export

Catalogue of Hazardous Chemicals : Listed

Product name	Status	Reference number
OKS 2660	Listed	2828

List of ingredients	CAS-No.	Status	Reference number
Acetone	67-64-1	Listed	137

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

No. / Code Chemical name / Category Threshold quantity

W5.3 Flammable liquids 1,000 t

The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI : ACGIH - Biological Exposure Indices (BEI)
CN BEI : China. Biological Occupational Exposure Indices

CN OEL : Occupational exposure limits for hazardous agents in the

workplace - Chemical hazardous agents.

ACGIH / TWA : 8-hour, time-weighted average

according to GB/T 16483 and GB/T 17519



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

ACGIH / STEL : Short-term exposure limit

CN OEL / PC-TWA : Permissible concentration - time weighted average CN OEL / PC-STEL : Permissible concentration - short term exposure limit

AllC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China: IMDG - International Maritime Dangerous Goods: IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the



according to GB/T 16483 and GB/T 17519 CN



OKS 2660

Version Revision Date: Date of last issue: 2018-05-11

2.1 2022-05-12 Date of first issue: 2014-04-07 Print Date: 2022-05-19

product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.