



**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

**1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

Product name : OKS 2661

**Manufacturer or supplier's details**

Company name of supplier : OKS Spezialechmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599  
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com  
Material Compliance Management

Emergency telephone number : +7 495 628 1687  
+49 8142 3051 517

**Recommended use of the chemical and restrictions on use**

Recommended use : cleaning spray

Restrictions on use : Restricted to professional users.

**2. HAZARDS IDENTIFICATION**

**GHS Classification (According to GOST 32423, GOST 32424 and GOST 32425)**

Aerosols : Category 1  
Skin irritation : Category 2  
Eye irritation : Category 2A  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
Aspiration hazard : Category 1  
Short-term (acute) aquatic hazard : Category 2  
Long-term (chronic) aquatic hazard : Category 2

**GHS-Labeling (According to GOST 31340)**

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

Hazard pictograms :    

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurized container: May burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P273 Avoid release to the environment.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**Other hazards which do not result in classification**

None known.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

Pure substance/mixture : Mixture

Chemical nature : Active agent with propellant and solvent.

**Components**

Chemical name	Concentration (% w/w)	Occupational Exposure Limits		CAS-No.	EC-No.
		MAC value mg/m3 / TSEL value	Hazard Class		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	>= 70 - < 90	No data available			921-024-6

**OKS 2661**

Version 2.4      Revision Date: 19.05.2022      Date of last issue: 25.11.2020      Print Date: 20.05.2022  
Date of first issue: 07.04.2014

acetone	$\geq 10 - < 20$	MPC-TWA: 200 mg/m <sup>3</sup> Data Source: RU OEL  MPC-STEL: 800 mg/m <sup>3</sup> Data Source: RU OEL	4  4	67-64-1	200-662-2
propane	$\geq 1 - < 10$	No data available		74-98-6	200-827-9
isobutane	$\geq 1 - < 10$	No data available		75-28-5	200-857-2
carbon dioxide	$\geq 1 - < 10$	MPC-TWA: 9.000 mg/m <sup>3</sup> Data Source: RU OEL  MPC-STEL: 27.000 mg/m <sup>3</sup> Data Source: RU OEL	4  4	124-38-9	204-696-9

**4. FIRST AID MEASURES**

- If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
Seek medical advice.

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Aspiration hazard if swallowed - can enter lungs and cause damage.

Most important symptoms and effects, both acute and delayed : Central nervous system depression  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.  
Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema  
Aspiration may cause pulmonary oedema and pneumonitis.

Notes to physician : Treat symptomatically.

---

**5. FIREFIGHTING MEASURES**

**Flammable properties**

Flash point : 0 °C  
Method: Abel-Pensky

Ignition temperature : > 200 °C

Upper explosion limit / Upper flammability limit : 8 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Flammability (solid, gas) : Extremely flammable aerosol.

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.

**OKS 2661**

Version 2.4	Revision Date: 19.05.2022	Date of last issue: 25.11.2020 Date of first issue: 07.04.2014	Print Date: 20.05.2022
----------------	------------------------------	---	---------------------------

- Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Hazardous combustion products : Carbon oxides
- Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.  
Exposure to decomposition products may be a hazard to health.

---

**6. ACCIDENTAL RELEASE MEASURES**

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Refer to protective measures listed in sections 7 and 8.  
Only qualified personnel equipped with suitable protective equipment may intervene.
- Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Non-sparking tools should be used.

---

**7. HANDLING AND STORAGE**

- Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the

**OKS 2661**

Version 2.4	Revision Date: 19.05.2022	Date of last issue: 25.11.2020 Date of first issue: 07.04.2014	Print Date: 20.05.2022
----------------	------------------------------	---	---------------------------

application area.  
Wash hands and face before breaks and immediately after handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.  
Store in accordance with the particular national regulations.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Components with workplace control parameters**

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Data Source
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC (2000-06-16)
		MPC-TWA (vapour and/or gas)	200 mg/m3	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				
		MPC-STEL (vapour and/or gas)	800 mg/m3	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				
carbon dioxide	124-38-9	TWA	5.000 ppm 9.000 mg/m3	2006/15/EC (2006-02-09)
		MPC-TWA (vapour and/or gas)	9.000 mg/m3	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				
		MPC-STEL (vapour and/or gas)	27.000 mg/m3	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				

**Engineering measures** : Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other

**OKS 2661**

Version 2.4	Revision Date: 19.05.2022	Date of last issue: 25.11.2020 Date of first issue: 07.04.2014	Print Date: 20.05.2022
----------------	------------------------------	---	---------------------------

appropriate exhaust).

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:  
Organic gas and low boiling vapour type

Hand protection  
Material : butyl-rubber  
Break through time : > 10 min  
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.  
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : aerosol

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable  
substance/mixture is non-soluble (in water)

**OKS 2661**

Version 2.4	Revision Date: 19.05.2022	Date of last issue: 25.11.2020 Date of first issue: 07.04.2014	Print Date: 20.05.2022
----------------	------------------------------	---	---------------------------

Melting point/range : No data available

Boiling point/boiling range : < 0 °C  
(1.013 hPa)

Flash point : 0 °C  
Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : not auto-flammable

Upper explosion limit / Upper flammability limit : 8 %(V)

Lower explosion limit / Lower flammability limit : 1 %(V)

Vapour pressure : 233 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0,7060 (20 °C)  
Reference substance: Water  
The value is calculated

Density : 0,71 g/cm<sup>3</sup> (20 °C)

Bulk density : No data available

Solubility(ies)  
Water solubility : insoluble  
Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : > 200 °C

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available  
Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s ( 40 °C)

Explosive properties : Not explosive

**OKS 2661**

Version 2.4	Revision Date: 19.05.2022	Date of last issue: 25.11.2020 Date of first issue: 07.04.2014	Print Date: 20.05.2022
----------------	------------------------------	---	---------------------------

Oxidizing properties : No data available  
Sublimation point : No data available  
Metal corrosion rate : Not corrosive to metals

---

**10. STABILITY AND REACTIVITY**

Reactivity : No hazards to be specially mentioned.  
Chemical stability : Stable under normal conditions.  
Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.  
Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.  
Risk of receptacle bursting.  
Incompatible materials : Oxidizing agents  
Hazardous decomposition products : No decomposition if stored and applied as directed.

---

**11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

**Product:**

Acute oral toxicity : Remarks: Effects due to ingestion may include:  
  
Symptoms: Central nervous system depression  
  
Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.  
  
Symptoms: Inhalation may provoke the following symptoms:,  
Respiratory disorder, Dizziness, Drowsiness, Vomiting,  
Fatigue, Vertigo, Central nervous system depression  
  
Acute dermal toxicity : Symptoms: Redness, Local irritation

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg  
Assessment: The substance or mixture has no acute dermal toxicity

**acetone:**

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

**isobutane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

**Skin corrosion/irritation**

**Product:**

Remarks : Irritating to skin.

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Assessment : Irritating to skin.  
Method : OECD Test Guideline 404  
Result : Irritating to skin.

**Serious eye damage/eye irritation**

**Product:**

Remarks : Irritating to eyes.

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Result : No eye irritation  
Assessment : No eye irritation

**acetone:**

Species : Rabbit  
Result : Eye irritation

**Respiratory or skin sensitisation**

**Product:**

Remarks : This information is not available.

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Did not cause sensitisation on laboratory animals.

**Germ cell mutagenicity**

**Product:**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Test system: Rodent cell line  
Method: OECD Test Guideline 473  
Result: negative

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

**Carcinogenicity**

**Product:**

Remarks : No data available

**Reproductive toxicity**

**Product:**

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction

**STOT - single exposure**

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

**acetone:**

Exposure routes : Inhalation  
Assessment : May cause drowsiness or dizziness.

**STOT - repeated exposure**

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Exposure routes : inhalation (vapour)  
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

**Repeated dose toxicity**

**Product:**

Remarks : This information is not available.

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

**Aspiration toxicity**

**Product:**

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

May be fatal if swallowed and enters airways.

**Further information**

**Product:**

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

---

**12. ECOLOGICAL INFORMATION**

**Ecotoxicity**

**Product:**

Toxicity to fish :  
Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other :  
aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic :  
plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EbC50 (Pseudokirchneriella subcapitata (green algae)): 26 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

**Ecotoxicology Assessment**

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

**Persistence and degradability**

**Product:**

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.

**acetone:**

Biodegradability : Result: rapidly biodegradable

**Bioaccumulative potential**

**Product:**

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

**OKS 2661**

Version 2.4	Revision Date: 19.05.2022	Date of last issue: 25.11.2020 Date of first issue: 07.04.2014	Print Date: 20.05.2022
----------------	------------------------------	---	---------------------------

**Components:**

**acetone:**

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

**propane:**

Partition coefficient: n-octanol/water : log Pow: 2,36

**isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2,88  
Method: OECD Test Guideline 107

**carbon dioxide:**

Partition coefficient: n-octanol/water : log Pow: 0,83

**Mobility in soil**

**Product:**

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

**Other adverse effects**

**Product:**

Additional ecological information : Toxic to aquatic life with long lasting effects.

**Global warming potential**

**The Fifth Assessment Report of the United Nations Intergovernmental Panel on Climate Change (IPCC)**

**Components:**

**carbon dioxide:**

20-year global warming potential: 1

100-year global warming potential: 1

Further information: No single lifetime can be given. The impulse response function for CO<sub>2</sub> from Joos et al. (2013) has been used. See also Supplementary Material Section 8.SM.11.

**OKS 2661**

Version 2.4	Revision Date: 19.05.2022	Date of last issue: 25.11.2020 Date of first issue: 07.04.2014	Print Date: 20.05.2022
----------------	------------------------------	---	---------------------------

**Hygienic standards:**

**(Allowable concentration in air, water, including fishery waters, soil)**

Components	Air	Water	Soil	Data Source
acetone	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 0,35 mg/m <sup>3</sup> Limiting health hazard indicator: reflectory Class 4 - low hazard	Maximum Permissible Concentration 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3 Maximum Allowable Concentration: 2,2 mg/l Limiting health hazard indicator: general sanitary Hazard class: Class 3 - moderately dangerous		List 5
propane		Maximum Permissible Concentration 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3		List 5
isobutane	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 15 mg/m <sup>3</sup> Limiting health hazard indicator: reflectory Class 4 - low hazard	Maximum Permissible Concentration 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3		List 5

List 5: Order of the Russian Federal Fisheries Agency "Standards of maximum permissible concentrations of harmful substances in fishery water bodies"

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

**13. DISPOSAL CONSIDERATIONS**

**Disposal methods**

Waste from residues : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied  
16 05 04\*, gases in pressure containers (including halons)  
containing hazardous substances

**14. TRANSPORT INFORMATION**

**ADR**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2  
Packing group : Not assigned by regulation  
Labels : 2.1  
Tunnel restriction code : (D)  
Environmentally hazardous : yes

**IATA-DGR**

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
(naphtha (petroleum), hydrotreated light)  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : yes



**OKS 2661**

Version 2.4	Revision Date: 19.05.2022	Date of last issue: 25.11.2020 Date of first issue: 07.04.2014	Print Date: 20.05.2022
----------------	------------------------------	---	---------------------------

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

**15. REGULATORY INFORMATION**

**National regulatory information**

Federal Law of 10.01.2002 No. 184-FZ "On Technical Regulation".  
Federal Law of 10.01.2002 No. 7-FZ "On Environmental Protection".  
Federal Law of 21.07.1997 No. 116-FZ (amended on 11.06.2021) "On industrial safety of hazardous production facilities".  
Federal Law of 24.06.1998 No. 89-FZ (amended on 02.07.2021) "On production and consumption waste".  
Federal Law of 10.01.2002 No. 7-FZ (amended on 02.07.2021) "On environmental protection".  
Federal Law of 04.05.1999 No. 96-FZ "On the protection of atmospheric air" (as amended on December 8, 2020).  
Federal Law of 30.03.1999 No. 52-FZ (amended on 02.07.2021) "On the Sanitary and Epidemiological Well-Being of the Population" (amended and supplemented, entered into force on 31.10.2021).  
Federal Law of 27.12.2002 No. 184-FZ (amended on 02.07.2021) "On Technical Regulation" (amended and supplemented, entered into force on 01.09.2021).  
TECHNICAL REGULATIONS OF THE CUSTOMS UNION TR CU 030/2012 On requirements for lubricants, oils and special fluids (amended on 03.03.2017).

**16. OTHER INFORMATION**

**List of data sources used in the preparation of the Safety Data Sheet**

GOST 30333-2007. Interstate standard. Safety data sheet for chemical products. Primary requirements.  
GOST 12.1.007-76 Occupational safety standards system. Noxious substances. Classification and general safety requirements  
GOST 12.1.044-89 Occupational safety standards system. Fire and explosion hazard of substances and materials. Nomenclature of indices and methods of their determination  
GOST 14192-96. Interstate standard. Cargo marking. Minsk, 1998.  
GOST 31340-2013. Interstate standard. Precautionary labeling of chemical products. General requirements.  
GOST 32419-2013 Classification of the hazard of chemical products. General requirements.  
GOST 32421-2013 Classification of chemical products, the hazard of which is due to physical and chemical properties. Test methods for explosive chemical products.  
GOST 32423-2013 Hazard classification of mixed chemical products by their effects on the body.

**OKS 2661**

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

GOST 32424-2013 Classification of the hazard of chemical products by their impact on the environment. Basic provisions.  
GOST 32425-2013 Hazard classification of mixed chemical products in terms of environmental impact.  
GOST R 53264-2009 Fire fighting equipment. Special protective clothing for firefighters. General technical requirements. Test methods.  
GOST R 53265-2009 Fire fighting equipment. Personal protective equipment for the feet of the firefighter. General technical requirements. Test methods.  
GOST R 53268-2009 Fire fighting equipment. Fire rescue belts. General technical requirements. Test methods.  
GOST R 53269-2009 Fire fighting equipment. Firefighters helmets. General technical requirements. Test methods.  
SanPiN 1.2.3685-21 "Hygienic standards and requirements for ensuring the safety and (or) harmlessness to humans of environmental factors" dated 28.01.2021.  
SanPiN 2.1.3684-21 "Sanitary and epidemiological requirements for the maintenance of the territories of urban and rural settlements, for water bodies, drinking water and drinking water supply, atmospheric air, soils, living quarters, the operation of industrial, public premises, the organization and implementation of sanitary and anti-epidemic (preventive) measures".  
European Agreement concerning the International Carriage of Dangerous Goods by Road (ADR). United Nations. New York and Geneva, 20.  
International Maritime Dangerous Goods Code (IMDG-Code).  
Water quality standards for fishery water bodies, including standards for maximum permissible concentrations of harmful substances in the waters of fishery water bodies (approved by order of the Ministry of Agriculture of Russia dated December 13, 2016 No. 552).  
Regulations for the carriage of dangerous goods (Appendix 1 and 2) to the Agreement on International Goods Transport by Rail (SMGS), 2009.  
UN Recommendations on the Transport of Dangerous Goods. Typical rules. Twenty-first revised edition. United Nations, New York and Geneva, 2019.

**Full text of other abbreviations**

Aquatic Acute	:	Short-term (acute) aquatic hazard
Aquatic Chronic	:	Long-term (chronic) aquatic hazard
Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Press. Gas	:	Gases under pressure
Skin Irrit.	:	Skin irritation
STOT SE	:	Specific target organ toxicity - single exposure
2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2006/15/EC	:	Europe. Indicative occupational exposure limit values
RU OEL	:	SanPiN 1.2.3685-21 Table 2.1, Table 2.8, Table 2.16 & Table 2.17 Maximum permissible concentrations (MPC) in the air of the working area
2000/39/EC / TWA	:	Limit Value - eight hours
2006/15/EC / TWA	:	Limit Value - eight hours
RU OEL / MPC-STEL	:	Maximum Permissible Concentration - Short Term Exposure
RU OEL / MPC-TWA	:	Maximum Permissible Concentration - Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the

# SAFETY DATA SHEET

- RU



## OKS 2661

Version	Revision Date:	Date of last issue: 25.11.2020	Print Date:
2.4	19.05.2022	Date of first issue: 07.04.2014	20.05.2022

Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.