OKS 2670

Version	Revision Date:	Date of last issue: 23.04.2025	Print Date:
2.0	27.04.2026	Date of first issue: 13.12.2013	27.04.2026

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2670

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Detergent
Cleaning agent / Cleaner

Recommended restrictions on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
82216 Maisach
Germany
Tel.: +49 8142 3051-500
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com

National contact : Klüber Lubrication Great Britain Limited
Unit 10 Pennine Business Park
Longbow Close
Huddersfield
West Yorkshire HD2 1GQ
Great Britain
Tel: +44-1422-205115
Fax: +44-1422-206073
sales@uk.klueber.com

1.4 Emergency telephone number

Emergency telephone number : +49 8142 3051 517 (24/7 service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008) as amended by GB-CLP Regulation, UK SI 2019/720, and UK SI 2020/1567)

Hazard pictograms :

Signal word : Danger

Hazard statements :

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements :

Prevention:

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.

Response:

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTER/ doctor.
P331	Do NOT induce vomiting.
P370 + P378	In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous components which must be listed on the label:

propan-2-ol

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

ethyl acetate

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : solvent (alcohols)
solvent (hydrocarbons)

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 603-117-00-0	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system)		>= 50 - < 70
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	918-167-1	Flam. Liq. 3; H226 Asp. Tox. 1; H304 EUH066	Note P	>= 30 - < 50
ethyl acetate	141-78-6 205-500-4 607-022-00-5	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 (Central nervous system) EUH066		>= 10 - < 20

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled	:	Call a physician or poison control centre immediately. Remove person to fresh air. If signs/symptoms continue, get medical attention. Keep patient warm and at rest. If unconscious, place in recovery position and seek medical advice. Keep respiratory tract clear. If breathing is irregular or stopped, administer artificial respiration.
In case of skin contact	:	Take off all contaminated clothing immediately. Get medical attention immediately if irritation develops and persists. Wash clothing before reuse. Thoroughly clean shoes before reuse. Wash skin thoroughly with soap and water or use recognized skin cleanser.
In case of eye contact	:	Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes. Seek medical advice.
If swallowed	:	Move the victim to fresh air. If accidentally swallowed obtain immediate medical attention. If unconscious, place in recovery position and seek medical advice. Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water. Never give anything by mouth to an unconscious person. Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	:	Inhalation may provoke the following symptoms: Unconsciousness Dizziness Drowsiness Headache Nausea Tiredness Skin contact may provoke the following symptoms: Erythema Aspiration may cause pulmonary oedema and pneumonitis.
Risks	:	May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause drowsiness or dizziness. Repeated exposure may cause skin dryness or cracking.

Central nervous system depression
Can be absorbed through skin.
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Do not let product enter drains.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
Prevent further leakage or spillage if safe to do so.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only in an area containing explosion proof equipment.
Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Ensure all equipment is electrically grounded before beginning transfer operations.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
Do not enter areas where used or stored until adequately ventilated.
Do not repack.
Do not re-use empty containers.
These safety instructions also apply to empty packaging which may still contain product residues.
Keep container closed when not in use.

Advice on protection against fire and explosion	:	Keep away from heat and sources of ignition.
Hygiene measures	:	Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	:	Store in original container. Keep container closed when not in use. Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

7.3 Specific end use(s)

Specific use(s)	:	Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	STEL	500 ppm 1,250 mg/m3	GB EH40 (2006-09-01)
		TWA	400 ppm 999 mg/m3	GB EH40 (2006-09-01)
ethyl acetate	141-78-6	STEL	400 ppm 1,468 mg/m3	GB EH40 (2018-08-01)
		TWA	200 ppm 734 mg/m3	GB EH40 (2018-08-01)
		TWA	200 ppm 734 mg/m3	2017/164/EU (2017-02-01)
	Further information: Indicative			
		STEL	400 ppm 1,468 mg/m3	2017/164/EU (2017-02-01)
	Further information: Indicative			

Derived No Effect Level (DNEL)

Substance name	End Use	Exposure routes	Potential health effects	Value
ethyl acetate	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Workers	Skin contact	Long-term systemic effects	63 mg/kg

propan-2-ol	Workers	Inhalation	Long-term systemic effects	500 mg/m3
	Workers	Skin contact	Long-term systemic effects	888 mg/kg

Predicted No Effect Concentration (PNEC)

Substance name	Environmental Compartment	Value
ethyl acetate	Fresh water	0.24 mg/l
	Marine water	0.024 mg/l
	Sewage treatment plant	650 mg/l
	Fresh water sediment	1.15 mg/kg
	Marine sediment	0.115 mg/kg
	Soil	0.148 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye/face protection : Safety glasses with side-shields

Hand protection
- Material : butyl-rubber
- Break through time : > 10 min
- Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Type A (A)

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Environmental exposure controls

Air :

No special environmental precautions required.

Soil :

The product should not be allowed to enter drains, water courses or the soil.

Water :

The product should not be allowed to enter drains, water courses or the soil.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance

Physical state	:	liquid
Colour	:	colourless
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	Not applicable substance/mixture is non-soluble (in water)
	:	Not applicable
Boiling point/boiling range	:	> 36 °C (1,013 hPa)
Flash point	:	9 °C Method: ISO 13736, closed cup
Evaporation rate	:	No data available
Flammability	:	Flammability (solid, gas): Not applicable
Upper explosion limit / Upper flammability limit	:	12 %(V)
Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapour pressure	:	98 hPa (20 °C)

Relative vapour density	:	No data available
Relative density	:	0.78 (20 °C) Reference substance: Water The value is calculated
Density	:	0.78 g/cm3 (20 °C)
Bulk density	:	No data available
Solubility(ies)		
Water solubility	:	partly miscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	<= 3.5 mm2/s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available

9.2 Other information

Refractive index	:	1.3892 at 20 °C
Sublimation point	:	No data available
Self-ignition	:	No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Based on available data, the classification criteria are not met.

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

Symptoms: Skin disorders

Components:

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 5,840 mg/kg

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.6 mg/l

Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 Dermal (Rabbit): > 2,200 mg/kg
Method: OECD Test Guideline 402

Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

Symptoms: Skin disorders

ethyl acetate:

Acute oral toxicity : LD50 (Rat): 5,620 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 20,000 mg/kg

Skin corrosion/irritation

Repeated exposure may cause skin dryness or cracking.

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

ethyl acetate:

Species : Rabbit
Result : Mild skin irritation

Result : Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Causes serious eye irritation.

Product:

Remarks : This information is not available.

Components:

propan-2-ol:

Species : Rabbit
Result : Eye irritation

ethyl acetate:

Assessment	:	Irritating to eyes.
Result	:	Irritating to eyes.

Respiratory or skin sensitisation

Skin sensitisation

Based on available data, the classification criteria are not met.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Product:

Remarks	:	This information is not available.

Components:

ethyl acetate:

Test Type	:	Maximisation Test
Exposure routes	:	Dermal
Species	:	Guinea pig
Assessment	:	Does not cause skin sensitisation.
Method	:	OECD Test Guideline 406
Result	:	Does not cause skin sensitisation.

Germ cell mutagenicity

Based on available data, the classification criteria are not met.

Product:

Genotoxicity in vitro	:	Remarks: No data available
Genotoxicity in vivo	:	Remarks: No data available

Carcinogenicity

Based on available data, the classification criteria are not met.

Product:

Remarks	:	No data available

Reproductive toxicity

Based on available data, the classification criteria are not met.

Product:

Effects on fertility	:	Remarks: No data available
Effects on foetal development	:	Remarks: No data available

STOT - single exposure

May cause drowsiness or dizziness.

Product:

Remarks : No data available

Components:

propan-2-ol:

Assessment : May cause drowsiness or dizziness.

ethyl acetate:

Exposure routes : Inhalation
Target Organs : Respiratory system
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Based on available data, the classification criteria are not met.

Product:

Remarks : No data available

Components:

ethyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

May be fatal if swallowed and enters airways.

Product:

This information is not available.

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Risks of irreversible effects after a single exposure.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish	:	Remarks: No data available
Toxicity to daphnia and other aquatic invertebrates	:	Remarks: No data available
Toxicity to algae/aquatic plants	:	Remarks: No data available
Toxicity to microorganisms	:	Remarks: No data available

Components:

ethyl acetate:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 212.5 mg/l Exposure time: 96 h Test Type: static test
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 154 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (green algae)): 2,500 mg/l Exposure time: 96 h

12.2 Persistence and degradability

Product:

Biodegradability	:	Remarks: No data available
Physico-chemical removability	:	Remarks: No data available

Components:

propan-2-ol:

Biodegradability	:	Result: Readily biodegradable.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Biodegradability : Result: Readily biodegradable.

ethyl acetate:

Biodegradability : Result: rapidly biodegradable

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: No data available

Components:

propan-2-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 0.05

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0.68 (25 °C)

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Endocrine disrupting potential	:	This substance/mixture does not contain components considered to have endocrine disrupting properties for environment according to UK REACH Article 57(f) at levels of 0.1% or higher.
Additional ecological information	:	No information on ecology is available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	:	The product should not be allowed to enter drains, water courses or the soil. Do not dispose of with domestic refuse. Dispose of as hazardous waste in compliance with local and national regulations. Waste codes should be assigned by the user based on the application for which the product was used.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as the unused product. Dispose of waste product or used containers according to local regulations. The following Waste Codes are only suggestions:

SECTION 14: Transport information

14.1 UN number

ADR	:	UN 1993
RID	:	UN 1993
IMDG	:	UN 1993
IATA	:	UN 1993

14.2 UN proper shipping name

ADR	:	FLAMMABLE LIQUID, N.O.S. (Isopropanol, naphtha (petroleum), hydrotreated heavy)
RID	:	FLAMMABLE LIQUID, N.O.S.

(Isopropanol, naphtha (petroleum), hydrotreated heavy)

IMDG : FLAMMABLE LIQUID, N.O.S.
(Isopropanol, naphtha (petroleum), hydrotreated heavy)

IATA : Flammable liquid, n.o.s.
(Isopropanol, naphtha (petroleum), hydrotreated heavy)

14.3 Transport hazard class(es)

		Class	Subsidiary risks
ADR	:	3	
RID	:	3	
IMDG	:	3	
IATA	:	3	

14.4 Packing group

ADR

Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3
Tunnel restriction code	:	(D/E)

RID

Packing group	:	II
Classification Code	:	F1
Hazard Identification Number	:	33
Labels	:	3

IMDG

Packing group	:	II
Labels	:	3
EmS Code	:	F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft)	:	364
Packing instruction (LQ)	:	Y341
Packing group	:	II
Labels	:	Flammable Liquids

IATA (Passenger)

Packing instruction (passenger aircraft)	:	353
Packing instruction (LQ)	:	Y341
Packing group	:	II
Labels	:	Flammable Liquids

14.5 Environmental hazards

ADR

Environmentally hazardous	:	no

RID
Environmentally hazardous : no

IMDG
Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Relevant EU provisions transposed through retained EU law

UK REACH List of restrictions (Annex 17)	:	Conditions of restriction for the following entries should be considered: Number on list 3 Number on list 40 This substance/mixture shall not be used in aerosol dispensers intended for supply to the general public for entertainment and decorative purposes.
UK REACH Candidate list of substances of very high concern (SVHC) for Authorisation (UK SVHC)	:	This product does not contain substances of very high concern (UK: The REACH etc. (Amendment) Regulations, Article 57).
The Persistent Organic Pollutants Regulations (retained Regulation (EU) 2019/1021 as amended for Great Britain) (GB POPs)	:	Not applicable
Regulation (EU) No 2024/590 on substances that deplete the ozone layer (EC 2024/590)	:	Not applicable
UK REACH List of substances subject to authorisation (Annex XIV)	:	Not applicable

(UK. REACH Annex XIV)

GB Export and import of hazardous chemicals - Prior Informed Consent (PIC) Regulation (GB PIC)	:	Not applicable
The Control of Explosives Precursors and Poisons Regulations (Poisons Act, as amended) (GB Poisons Act)		Not applicable

Control of Major Accident Hazards Regulations 2015 (COMAH)	P5c	FLAMMABLE LIQUIDS

Volatile organic compounds	:	Directive 2010/75/EU of 24 November 2010 on industrial and livestock rearing emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 100 %
according to Detergents Regulation EC 648/2004	:	Ingredients >= 30%: Aliphatic hydrocarbons

Other regulations:

Take note of The Management of Health and Safety at Work Regulations 1999 (requirements relating to protection of young people at work contained in Regulation 19) and of Directive 94/33/EC on the protection of young people at work.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225	:	Highly flammable liquid and vapour.
H226	:	Flammable liquid and vapour.
H304	:	May be fatal if swallowed and enters airways.
H319	:	Causes serious eye irritation.
H336	:	May cause drowsiness or dizziness.
EUH066	:	Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations

Asp. Tox.	:	Aspiration hazard
Eye Irrit.	:	Eye irritation
Flam. Liq.	:	Flammable liquids
LD50 Dermal	:	LD50 Dermal
LD50 Oral	:	LD50 Oral
Note P	:	The harmonised classification as a carcinogen or mutagen applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 + P310-P331 shall apply.
STOT SE	:	Specific target organ toxicity - single exposure
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
GB EH40	:	UK. EH40 WEL - Workplace Exposure Limits
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
GB EH40 / TWA	:	Long-term exposure limit (8-hour TWA reference period)
GB EH40 / STEL	:	Short-term exposure limit (15-minute reference period)

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of very high concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals

Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:		**Classification procedure:**
Flam. Liq. 2	H225	Based on product data or assessment
Eye Irrit. 2	H319	Calculation method
STOT SE 3	H336	Calculation method
Asp. Tox. 1	H304	Calculation method

|| Relevant changes compared to the last edition are highlighted at the left margin. This version replaces all previous editions.

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

OKS 2670

Version	Revision Date:	Date of last issue: 23.04.2025	Print Date:
2.0	27.04.2026	Date of first issue: 13.12.2013	27.04.2026

Ingredients (Regulation (EC) No. 648/2004, as amended)

propan-2-ol
Naphtha (petroleum), hydrotreated heavy
ETHYL ACETATE

https://ec.europa.eu/growth/tools-databases/cosing/index.cfm?fuseaction=search.simple