

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 2671

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Cleaning agent/ Cleaner

Recommended restrictions
on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599

E-mail address of person
responsible for the SDS : mcm@oks-germany.com
National contact :

1.4 Emergency telephone number

Emergency telephone
number : +33 1 45 42 59 59

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1	H222: Extremely flammable aerosol. H229: Pressurised container: May burst if heated.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR






OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	  
Signal word	:	Danger
Hazard statements	:	H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters airways. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	Prevention: P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. Response: P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P331 Do NOT induce vomiting. Storage: P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

propan-2-ol
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature	:	Active substance with propellant Solvent mixture
-----------------	---	---

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version 1.2 Revision Date: 18.09.2018 Date of last issue: 25.07.2017 Print Date: 18.09.2018
Date of first issue: 23.06.2016

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
propan-2-ol	67-63-0 200-661-7 603-117-00-0 02-2119457558-25-XXXX	Flam. Liq.2; H225 Eye Irrit.2A; H319 STOT SE3; H336		$\geq 50 - < 70$
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	Not Assigned 918-167-1 01-2119472146-39-XXXX	Flam. Liq.3; H226 Asp. Tox.1; H304		$\geq 20 - < 30$
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		$\geq 1 - < 10$
Substances with a workplace exposure limit :				
carbon dioxide	124-38-9 204-696-9	Press. Gas Compr. Gas; H280		$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Get medical attention immediately if irritation develops and

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
Wash skin thoroughly with soap and water or use recognized skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If easy to do, remove contact lens, if worn.
Seek medical advice.

If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression
Can be absorbed through skin.
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire may cause evolution of:
Carbon oxides

Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. In the case of respirable dust and/or fumes, use self-contained breathing apparatus. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version 1.2 Revision Date: 18.09.2018 Date of last issue: 25.07.2017 Print Date: 18.09.2018
Date of first issue: 23.06.2016

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
propan-2-ol	67-63-0	VLCT (VLE)	400 ppm 980 mg/m ³	FR VLE (2005-02-01)
Further information	Indicative exposure limits			
ethyl acetate	141-78-6	VME	400 ppm 1.400 mg/m ³	FR VLE (2005-02-01)
Further information	Indicative exposure limits			
		STEL	400 ppm 1.468 mg/m ³	2017/164/EU (2017-02-01)
Further information	Indicative			
		TWA	200 ppm 734 mg/m ³	2017/164/EU (2017-02-01)
Further information	Indicative			
carbon dioxide	124-38-9	TWA	5.000 ppm 9.000 mg/m ³	2006/15/EC (2006-02-09)
Further information	Indicative			
		VME	5.000 ppm 9.000 mg/m ³	FR VLE (2007-12-01)
Further information	Regulatory indicative exposure limits			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
ethyl acetate	Consumers	Ingestion	Long-term systemic effects	4,5 mg/kg
Remarks:	Exposure time: 24 h			
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg
Remarks:	Exposure time: 24 h			
	Workers	Skin contact	Long-term systemic effects	63 mg/kg
Remarks:	Exposure time: 8 h			
	Workers	Inhalation	Acute systemic effects	1468 mg/m ³
	Consumers	Inhalation	Acute systemic effects	734 mg/m ³
	Workers	Inhalation	Acute local effects	1468 mg/m ³
	Consumers	Inhalation	Acute local effects	734 mg/m ³
	Workers	Inhalation	Long-term local effects	734 mg/m ³
	Workers	Inhalation	Long-term systemic effects	734 mg/m ³
	Consumers	Inhalation	Long-term systemic effects	367 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

	Consumers	Inhalation	Long-term local effects	367 mg/m ³
--	-----------	------------	-------------------------	-----------------------

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
ethyl acetate	Water	0,26 mg/l
	Soil	0,22 mg/kg
	Fresh water sediment	0,34 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : butyl-rubber
Protective index : Class 1

Remarks : Wear protective gloves. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : colourless

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

Odour : characteristic

Odour Threshold : No data available

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : -161 °C
(1.013 hPa)

Flash point : -15 °C
Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : 12 %(V)

Lower explosion limit : 0,6 %(V)

Vapour pressure : 3.600 hPa (20 °C)

Relative vapour density : No data available

Density : 0,78 g/cm³
(20 °C)

Bulk density : No data available

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm²/s (40 °C)

Explosive properties : Not explosive

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

Oxidizing properties : No data available

9.2 Other information

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:
Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version 1.2	Revision Date: 18.09.2018	Date of last issue: 25.07.2017 Date of first issue: 23.06.2016	Print Date: 18.09.2018
----------------	------------------------------	---	---------------------------

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

Symptoms: Skin disorders

Components:

propan-2-ol:

Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg
Method: OECD Test Guideline 402

ethyl acetate:

Acute oral toxicity : LD50 (Rat): 5.600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 58 mg/l
Exposure time: 8 h
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Acute dermal toxicity : LD50 (Rabbit): 18.000 mg/kg

Skin corrosion/irritation

Product:

Remarks: This information is not available.

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result: Repeated exposure may cause skin dryness or cracking.

ethyl acetate:

Species: Rabbit

Result: No skin irritation

Serious eye damage/eye irritation

Product:

Remarks: Irritating to eyes.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version 1.2	Revision Date: 18.09.2018	Date of last issue: 25.07.2017 Date of first issue: 23.06.2016	Print Date: 18.09.2018
----------------	------------------------------	---	---------------------------

Components:

propan-2-ol:

Result: Severe eye irritation

ethyl acetate:

Species: Rabbit

Result: Mild eye irritation

Respiratory or skin sensitisation

Product:

Remarks: This information is not available.

Components:

ethyl acetate:

Species: Guinea pig

Method: OECD Test Guideline 406

Result: Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks: No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

STOT - single exposure

Components:

propan-2-ol:

Assessment: May cause drowsiness or dizziness.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

ethyl acetate:

Exposure routes: Inhalation

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Repeated dose toxicity

Product:

Remarks: This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: Information given is based on data on the components and the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

Components:

ethyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 230 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 717 mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to microorganisms : EC10 (Pseudomonas putida): 2.900 mg/l
Exposure time: 16 h

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

propan-2-ol:

Biodegradability : Result: Readily biodegradable.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Biodegradability : Result: Not readily biodegradable.

ethyl acetate:

Biodegradability : Biodegradation: 100 %
Exposure time: 28 d
Method: OECD Test Guideline 301D
Remarks: According to the results of tests of biodegradability this product is considered as being readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

propan-2-ol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

Partition coefficient: n-octanol/water : log Pow: 0,05

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

carbon dioxide:

Partition coefficient: n-octanol/water : log Pow: 0,83

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : No information on ecology is available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

SECTION 14: Transport information

14.1 UN number

ADR	:	UN 1950
IMDG	:	UN 1950
IATA	:	UN 1950

14.2 UN proper shipping name

ADR	:	AEROSOLS (Hydrocarbons, C11-C12, isoalkanes, <2% aromatics)
IMDG	:	AEROSOLS (Hydrocarbons, C11-C12, isoalkanes, <2% aromatics)
IATA	:	Aerosols, flammable (Hydrocarbons, C11-C12, isoalkanes, <2% aromatics)

14.3 Transport hazard class(es)

ADR	:	2
IMDG	:	2.1
IATA	:	2.1

14.4 Packing group

ADR	:	
Packing group	:	Not assigned by regulation
Classification Code	:	5F
Labels	:	2.1
Tunnel restriction code	:	(D)

IMDG	:	
Packing group	:	Not assigned by regulation
Labels	:	2.1
EmS Code	:	F-D, S-U

IATA (Cargo)	:	
Packing instruction (cargo aircraft)	:	203
Packing instruction (LQ)	:	Y203
Packing group	:	Not assigned by regulation
Labels	:	Flammable Gas

IATA (Passenger)	:	
Packing instruction (passenger aircraft)	:	203

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

Packing instruction (LQ) : Y203
Packing group : Not assigned by regulation
Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

No special precautions required.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

Quantity 1

Quantity 2

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

P3b FLAMMABLE AEROSOLS 5.000 t 50.000 t

P5c

Occupational Illnesses (R-461-3, France) : 84

Installations classified for the protection of the environment (Environment Code R511-9) : 4321, 1421

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 98 %
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225 : Highly flammable liquid and vapour.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.
H319 : Causes serious eye irritation.
H336 : May cause drowsiness or dizziness.

Full text of other abbreviations

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx -

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR



OKS 2671

Version	Revision Date:	Date of last issue: 25.07.2017	Print Date:
1.2	18.09.2018	Date of first issue: 23.06.2016	18.09.2018

Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Aerosol 1	H222, H229
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Based on product data or assessment

This safety datasheet applies only to products originally packaged and labelled by OKS Spezial-schmierstoffe. The information contained therein is protected by copyright and must not be reproduced or amended without the express written approval of OKS Spezialschmierstoffe. This document may be passed on only to the extent required by law. Any dissemination of our safety datasheets (e.g. as a document for download from the Internet) beyond this legally required extent is not permitted without express written consent. OKS Spezialschmierstoffe provides its customers with amended safety datasheets as prescribed by law. The customer is responsible for passing on safety datasheets and any amendments contained therein to its own customers, employees and other users of the product. OKS Spezialschmierstoffe provides no guarantee that safety datasheets received by users from third parties are up-to-date. All information and instructions in this safety datasheets were compiled to the best of our knowledge and are based on the information available to us. The data provided are intended to describe the product in relation to the required safety measures; they are neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and do not justify any contractual legal relationships.