

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : OKS 371

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Lubricant spray

Recommended restrictions  
on use : Restricted to professional users.

#### 1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599

E-mail address of person  
responsible for the SDS : mcm@oks-germany.com  
National contact :

#### 1.4 Emergency telephone number

Emergency telephone  
number : +49 8142 3051 517

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-  
ways.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H304 May be fatal if swallowed and enters air-ways.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.

**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.

**Storage:**  
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

White mineral oil (petroleum)

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Active substance with propellant  
Mineral oil.  
ester oil

#### Hazardous components

Chemical name	CAS-No. EC-No.  Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
White mineral oil (petroleum)	8042-47-5  232-455-8	Asp. Tox.1; H304		>= 30 - < 50

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version  
1.5

Revision Date:  
19.02.2018

Date of last issue: 29.06.2016  
Date of first issue: 30.03.2013

Print Date:  
19.02.2018

	01-2119487078-27			
propane	74-98-6 200-827-9 601-003-00-5	Flam. Gas1; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	$\geq 1 - < 10$
isobutane	75-28-5 200-857-2 601-004-00-0	Flam. Gas1; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	$\geq 1 - < 10$
Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7 601-004-00-0	Flam. Gas1; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	$\geq 30 - < 50$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.  
Keep respiratory tract clear.  
Do NOT induce vomiting.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

Rinse mouth with water.  
Aspiration hazard if swallowed - can enter lungs and cause damage.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire may cause evolution of:  
Carbon oxides

Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. In the case of respirable dust and/or fumes, use self-contained breathing apparatus. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Refer to protective measures listed in sections 7 and 8.  
Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.  
Prevent further leakage or spillage if safe to do so.  
Local authorities should be advised if significant spillages cannot be contained.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Non-sparking tools should be used.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

### 7.3 Specific end use(s)

Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	STEL	750 ppm 1,810 mg/m <sup>3</sup>	GB EH40
Further information	Capable of causing cancer and/or heritable genetic damage. The identified substances include those which: - are assigned the risk phrases 'R45: May cause cancer'; 'R46: may cause heritable genetic damage'; 'R49: May cause cancer by inhalation' or - a substance or process listed in Schedule 1 of COSHH., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			
		TWA	600 ppm 1,450 mg/m <sup>3</sup>	GB EH40
Further information	Capable of causing cancer and/or heritable genetic damage. The identified substances include those which: - are assigned the risk phrases 'R45: May cause cancer'; 'R46: may cause heritable genetic damage'; 'R49: May cause cancer by inhalation' or - a substance or process listed in Schedule 1 of COSHH., Carcinogenic only applies if butane contains more than 0.1% of buta-1,3-diene			

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version 1.5      Revision Date: 19.02.2018      Date of last issue: 29.06.2016      Print Date: 19.02.2018  
Date of first issue: 30.03.2013

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Glycerides, mixed decanoyl and octanoyl	Workers	Inhalation	Long-term systemic effects	177.79 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	43.84 mg/m <sup>3</sup>

## 8.2 Exposure controls

### Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : butyl-rubber  
Protective index : Class 1

Remarks : Wear protective gloves. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Short term only

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.  
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : colourless

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version 1.5	Revision Date: 19.02.2018	Date of last issue: 29.06.2016 Date of first issue: 30.03.2013	Print Date: 19.02.2018
----------------	------------------------------	---	---------------------------

Odour : characteristic

Odour Threshold : No data available

pH : No data available

Melting point/range : No data available

Boiling point/boiling range : No data available

Flash point : -60.00 °C

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : 8.5 %(V)

Lower explosion limit : 1.5 %(V)

Vapour pressure : <= 3,500 hPa (20 °C)

Relative vapour density : No data available

Density : 0.70 g/cm<sup>3</sup>  
(20 °C)

Bulk density : No data available

Solubility(ies)

    Water solubility : partly miscible

    Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

    Viscosity, dynamic : No data available

    Viscosity, kinematic : 14.5 mm<sup>2</sup>/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

### 9.2 Other information

Sublimation point : No data available  
Self-ignition : not auto-flammable

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazards to be specially mentioned.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: This information is not available.  
Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,  
Respiratory disorder

##### Components:

#### White mineral oil (petroleum):

Acute oral toxicity : LD50 Oral (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Acute inhalation toxicity : LC50 (Rat): > 5,000 mg/l  
Exposure time: 4 h  
Method: OECD Test Guideline 403

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version 1.5	Revision Date: 19.02.2018	Date of last issue: 29.06.2016 Date of first issue: 30.03.2013	Print Date: 19.02.2018
----------------	------------------------------	---	---------------------------

Acute dermal toxicity : LD50 Dermal (Rabbit): > 3,000 mg/kg  
Method: OECD Test Guideline 402

### **isobutane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

### **butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

### **Skin corrosion/irritation**

#### **Product:**

Remarks: This information is not available.

#### **Components:**

##### **White mineral oil (petroleum):**

Species: Rabbit  
Method: OECD Test Guideline 404  
Result: No skin irritation

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks: Contact with eyes may cause irritation.

#### **Components:**

##### **White mineral oil (petroleum):**

Species: Rabbit  
Method: OECD Test Guideline 405  
Result: No eye irritation

### **Respiratory or skin sensitisation**

#### **Product:**

Remarks: This information is not available.

#### **Components:**

##### **White mineral oil (petroleum):**

Species: Guinea pig  
Method: OECD Test Guideline 406

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

---

Result: Does not cause skin sensitisation.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

### Carcinogenicity

#### Product:

Remarks: No data available

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

### Repeated dose toxicity

#### Product:

Remarks: This information is not available.

### Aspiration toxicity

#### Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

### Components:

#### **White mineral oil (petroleum):**

May be fatal if swallowed and enters airways.

### Further information

#### Product:

Remarks: Information given is based on data on the components and the toxicology of similar products.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

### Components:

#### **White mineral oil (petroleum):**

Remarks: Information given is based on data on the components and the toxicology of similar products.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

#### Components:

#### **White mineral oil (petroleum):**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): > 1,000 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version 1.5	Revision Date: 19.02.2018	Date of last issue: 29.06.2016 Date of first issue: 30.03.2013	Print Date: 19.02.2018
----------------	------------------------------	---	---------------------------

### Components:

#### **propane:**

Partition coefficient: n-octanol/water : log Pow: 2.36

#### **isobutane:**

Partition coefficient: n-octanol/water : log Pow: 2.88  
Method: OECD Test Guideline 107

#### **butane:**

Partition coefficient: n-octanol/water : log Pow: 2.89  
Method: OECD Test Guideline 107

### 12.4 Mobility in soil

#### Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Other adverse effects

#### Product:

Additional ecological information : No information on ecology is available.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : In accordance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

### SECTION 14: Transport information

#### 14.1 UN number

**ADR** : UN 1950  
**IMDG** : UN 1950  
**IATA** : UN 1950

#### 14.2 UN proper shipping name

**ADR** : AEROSOLS  
**IMDG** : AEROSOLS  
**IATA** : Aerosols, flammable

#### 14.3 Transport hazard class(es)

**ADR** : 2  
**IMDG** : 2.1  
**IATA** : 2.1

#### 14.4 Packing group

**ADR**  
Packing group : Not assigned by regulation  
Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

**IMDG**  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

**IATA (Cargo)**  
Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

**IATA (Passenger)**  
Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

#### 14.5 Environmental hazards

**ADR**  
Environmentally hazardous : no

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version 1.5	Revision Date: 19.02.2018	Date of last issue: 29.06.2016 Date of first issue: 30.03.2013	Print Date: 19.02.2018
----------------	------------------------------	---	---------------------------

### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

### 14.6 Special precautions for user

No special precautions required.

### 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

Seveso II - Directive 2003/105/EC amending Council Directive 96/82/EC on the control of major-accident hazards involving dangerous substances

		Quantity 1	Quantity 2
8	Extremely flammable	10 t	50 t

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a	FLAMMABLE AEROSOLS	150 t	500 t
-----	--------------------	-------	-------

18	Liquefied extremely flammable gases (including LPG) and natural gas	50 t	200 t
----	---	------	-------

34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home	2,500 t	25,000 t
----	---	---------	----------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 44 %  
Remarks: VOC content excluding water

### 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: Other information

### Full text of H-Statements

H220 : Extremely flammable gas.  
H280 : Contains gas under pressure; may explode if heated.  
H304 : May be fatal if swallowed and enters airways.

### Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.  
Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System;



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - GB



## OKS 371

Version	Revision Date:	Date of last issue: 29.06.2016	Print Date:
1.5	19.02.2018	Date of first issue: 30.03.2013	19.02.2018

GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Aerosol 1	H222, H229
Asp. Tox. 1	H304

#### Classification procedure:

Based on product data or assessment
Based on product data or assessment

This safety datasheet applies only to products originally packaged and labelled by OKS Spezialschmierstoffe. The information contained therein is protected by copyright and must not be reproduced or amended without the express written approval of OKS Spezialschmierstoffe. This document may be passed on only to the extent required by law. Any dissemination of our safety datasheets (e.g. as a document for download from the Internet) beyond this legally required extent is not permitted without express written consent. OKS Spezialschmierstoffe provides its customers with amended safety datasheets as prescribed by law. The customer is responsible for passing on safety datasheets and any amendments contained therein to its own customers, employees and other users of the product. OKS Spezialschmierstoffe provides no guarantee that safety datasheets received by users from third parties are up-to-date. All information and instructions in this safety datasheets were compiled to the best of our knowledge and are based on the information available to us. The data provided are intended to describe the product in relation to the required safety measures; they are neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and do not justify any contractual legal relationships.