

**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

**1. Identification of the substance/mixture and of the company/undertaking**

**Product information**

Product name : OKS 371

Use of the Substance/Mixture : Lubricant spray

Company : OKS Spezienschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599  
info@oks-germany.com

E-mail address : mcm@oks-germany.com  
Material Compliance Management

National contact :



Emergency telephone number : +7 495 628 1687  
+49 8142 3051 517

**2. Hazards identification**

**GHS Classification**

: Aerosols, Category 1  
Aspiration hazard, Category 1

**GHS-Labeling**

Symbol(s) :  

Signal word : Danger

Hazard statements : H222: Extremely flammable aerosol.  
H229: Pressurised container: May burst if heated.  
H304: May be fatal if swallowed and enters airways.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

**Storage:**

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

**3. Composition/information on ingredients**

Chemical nature : Active substance with propellant  
Mineral oil.  
ester oil

**Hazardous components**

Chemical name	CAS-No.	Concentration[%]
White mineral oil (petroleum)	8042-47-5	30 - 50
Butane	106-97-8	30 - 50
propane	74-98-6	1 - 10
Isobutane	75-28-5	1 - 10

**4. First aid measures**

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Obtain medical attention.  
Rinse mouth with water.  
Aspiration hazard if swallowed - can enter lungs and cause



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

damage.

**Notes to physician**

- Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness
- Aspiration may cause pulmonary oedema and pneumonitis.
- Risks : Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.
- Treatment : Treat symptomatically.

---

**5. Firefighting measures**

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing media : High volume water jet
- Hazardous combustion products : Carbon oxides
- Specific hazards during firefighting : Fire Hazard  
Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.  
Exposure to decomposition products may be a hazard to health.
- Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

---

**6. Accidental release measures**

- Personal precautions : Evacuate personnel to safe areas.



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

- Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Refer to protective measures listed in sections 7 and 8.
- Environmental precautions : Try to prevent the material from entering drains or water courses.  
Prevent further leakage or spillage if safe to do so.  
Local authorities should be advised if significant spillages cannot be contained.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Keep in suitable, closed containers for disposal.  
Non-sparking tools should be used.
- Additional advice : Only qualified personnel equipped with suitable protective equipment may intervene.

---

## 7. Handling and storage

### Handling

- Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

### Storage

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

or throw into fire even after use. Do not spray on flames or red-hot objects.  
Store in accordance with the particular national regulations.

**8. Exposure controls/personal protection**

**Components with workplace control parameters**

Components	CAS-No.	Value	Control parameters	Update	Basis
White mineral oil (petroleum)	8042-47-5	MPC-STEL	5 mg/m3	2018-04-23	RU OEL
Butane	106-97-8	MPC-TWA	300 mg/m3	2018-04-23	RU OEL
Butane	106-97-8	MPC-STEL	900 mg/m3	2018-04-23	RU OEL
propane	74-98-6	MPC-TWA	300 mg/m3	2018-04-23	RU OEL
propane	74-98-6	MPC-STEL	900 mg/m3	2018-04-23	RU OEL
Isobutane	75-28-5	MPC-TWA	300 mg/m3	2018-04-23	RU OEL
Isobutane	75-28-5	MPC-STEL	900 mg/m3	2018-04-23	RU OEL

**Engineering measures**

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

**Personal protective equipment**

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.  
Short term only  
Filter type A-P

Hand protection : butyl-rubber  
Manufacturer, importer, supplier: Class 1  
Break through time: > 10 min  
Wear protective gloves.



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

- Eye protection : Safety glasses with side-shields
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.  
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

---

## 9. Physical and chemical properties

### Appearance

- Physical state : aerosol
- Colour : colourless
- Odour : characteristic

### Safety data

- Flash point : -60,00 °C
- Ignition temperature : Remarks: No data available
- Lower explosion limit : 1,5 %(V)
- Upper explosion limit : 8,5 %(V)
- Flammability (solid, gas) : Extremely flammable aerosol.
- Oxidizing properties : Note: No data available
- Auto-ignition temperature : Note: not auto-flammable
- pH : Note: Not applicable  
substance/mixture is non-soluble (in water)
- Melting point/range : Note: No data available
- Boiling point/boiling range : Note: No data available
- Sublimation point : Note: No data available



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

Vapour pressure	: <= 3.500,00 hPa at 20 °C
Density	: 0,70 g/cm <sup>3</sup> at 20 °C
Bulk density	: Note: No data available
Water solubility	: Note: partly miscible
Partition coefficient: n-octanol/water	: Note: No data available
Solubility in other solvents	: Note: No data available
Viscosity, dynamic	: Note: No data available
Viscosity, kinematic	: 14,5 mm <sup>2</sup> /s at 40 °C
Relative vapour density	: Note: No data available
Evaporation rate	: Note: No data available

---

**10. Stability and reactivity**

Conditions to avoid	: Heat, flames and sparks.
Materials to avoid	: Oxidizing agents
Hazardous decomposition products	: No decomposition if stored and applied as directed.
Thermal decomposition	: Note: No data available
Hazardous reactions	: No dangerous reaction known under conditions of normal use.

---

**11. TOXICOLOGICAL INFORMATION**

**Acute toxicity**

Acute oral toxicity :  
Remarks: This information is not available.

Acute inhalation toxicity  
White mineral oil (petroleum) : LC50: > 5 mg/l  
Exposure time: 4 h  
Species: Rat  
Method: OECD Test Guideline 403



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

Butane : LC50: 658 mg/l  
Exposure time: 4 h  
Species: Rat

Isobutane : LC50: 658 mg/l  
Exposure time: 4 h  
Species: Rat

Acute dermal toxicity  
White mineral oil (petroleum) : LD50 Dermal: > 3.000 mg/kg  
Species: Rabbit  
Method: OECD Test Guideline 402

**Skin corrosion/irritation**

Skin irritation : Remarks: This information is not available.

**Serious eye damage/eye irritation**

Eye irritation : Remarks: Contact with eyes may cause irritation.

**Respiratory or skin sensitisation**

Sensitisation : Remarks: This information is not available.

**Germ cell mutagenicity**

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

**Target Organ Systemic Toxicant - Repeated exposure**

: This information is not available.

**Aspiration hazard**

Aspiration toxicity : May be fatal if swallowed and enters airways.

: May be fatal if swallowed and enters airways.

Further information : Information given is based on data on the components and the toxicology of similar products.

---

**12. Ecological information**

**Ecotoxicity effects**

Toxicity to fish :  
Remarks:





**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks:  
No data available

Toxicity to algae : Remarks:  
No data available

Toxicity to bacteria : Remarks:  
No data available

**Elimination information (persistence and degradability)**

Bioaccumulation : Remarks:  
This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Mobility : Remarks:  
No data available

Distribution among environmental compartments : Remarks:  
No data available

Biodegradability : Remarks:  
No data available

Physico-chemical removability : Remarks:  
No data available

**Further information on ecology**

Additional ecological information : No information on ecology is available.

---

**13. Disposal considerations**

Product : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

---

**14. Transport information**

**ADR**

UN number : 1950  
Description of the goods : AEROSOLS  
Class : 2  
Classification Code : 5F  
Labels : 2.1  
Environmentally hazardous : no

**IATA**

UN number : 1950  
Description of the goods : Aerosols, flammable  
Class : 2.1  
Labels : 2.1  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203  
Packing instruction (passenger aircraft) : Y203  
Environmentally hazardous : no

**IMDG**

UN number : 1950



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

Description of the goods : AEROSOLS

Class : 2.1

Labels : 2.1

EmS Number : F-D, S-U

Marine pollutant : no

**RID**

UN number : 1950

Description of the goods : AEROSOLS

Class : 2

Classification Code : 5F

Hazard Identification Number : 23

Labels : 2.1

Environmentally hazardous : no

Other information : No special precautions required.

---

**15. Regulatory information**

---

**16. Other information**

**Further information**

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The



**OKS 371**

Version 1.5

Revision Date 10.09.2021

Print Date 14.09.2021

---

information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

---