according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 4220 极端温度条件的轴承润滑脂

Chemical nature : perfluorinated polyether oil

PTFE

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

responsible for the SDS

: mcm@oks-germany.com

National contact

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)

+86 21 69225521

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance : solid
Colour : white
Odour : odourless

Not a hazardous substance or mixture.

GHS Classification

Not a hazardous substance or mixture.

GHS label elements

Not a hazardous substance or mixture.

Physical and chemical hazards

Not classified based on available information.



according to GB/T 16483 and GB/T 17519 CN



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Health hazards

Not classified based on available information.

Environmental hazards

Not classified based on available information.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
disodium sebacate	17265-14-4	>= 1 -< 2.5

4. FIRST AID MEASURES

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If breathing is irregular or stopped, administer artificial

respiration

In case of skin contact : Remove contaminated clothing. If irritation develops, get

medical attention.

Wash off with soap and water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

Do not induce vomiting without medical advice.

Most important symptoms

and effects, both acute and

delayed

None known.

No symptoms known or expected.

Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES



according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or

carbon dioxide.

Unsuitable extinguishing

media

High volume water jet

Hazardous combustion

products

: Carbon oxides

Nitrogen oxides (NOx) Halogenated compounds

Metal oxides

Specific extinguishing

methods

Standard procedure for chemical fires.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.

Use the indicated respiratory protection if the occupational exposure limit is exceeded and/or in case of product release

(dust).

Avoid breathing dust.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Try to prevent the material from entering drains or water

courses.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Clean up promptly by sweeping or vacuum. Keep in suitable, closed containers for disposal.

7. HANDLING AND STORAGE

Handling

Advice on safe handling : For personal protection see section 8.

Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Avoidance of contact : No materials to be especially mentioned.



according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Storage

Conditions for safe storage : Store in original container.

Keep container closed when not in use. Keep in a dry, cool and well-ventilated place.

Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Store in accordance with the particular national regulations.

Keep in properly labelled containers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Contains no substances with occupational exposure limit values.

Engineering measures : It is recommended that all dust control equipment such as

local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen

deficient environment.

Personal protective equipment

Respiratory protection : Not required; except in case of aerosol formation.

Filter type : Filter type A-P

Eye/face protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : For prolonged or repeated contact use protective gloves. The

break through time depends amongst other things on the material, the thickness and the type of glove and therefore

has to be measured for each case.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

according to GB/T 16483 and GB/T 17519 CN



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : solid

Colour : white

Odour : odourless

Odour Threshold : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Decomposes without melting.

Boiling point/boiling range : No data available

Flash point : Not applicable

Evaporation rate : No data available

Flammability (solid, gas) : Will not burn

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

No data available

Lower explosion limit / Lower

flammability limit

No data available

Vapour pressure : < 0.001 hPa (20 °C)

Relative vapour density : No data available

Relative density : 1.92 (20 °C)

Reference substance: Water The value is calculated

Density : 1.92 g/cm3 (20 °C)

according to GB/T 16483 and GB/T 17519 CN



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : > 280 °C

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid : No conditions to be specially mentioned.

Incompatible materials : No materials to be especially mentioned.

Hazardous decomposition

products

>280 °C danger of forming toxic fluorine-containing pyrolysis

products.

according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Remarks: This information is not available.

Acute dermal toxicity : Remarks: This information is not available.

Components:

disodium sebacate:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Method: OECD Test Guideline 401

GLP: no

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

disodium sebacate:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : no

according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Serious eye damage/eye irritation

Product:

Remarks This information is not available.

Components:

disodium sebacate:

Species Rabbit

Result : Irritating to eyes. Assessment : Irritating to eyes.

Method **OECD Test Guideline 437**

GLP yes

Respiratory or skin sensitisation

Product:

Remarks This information is not available.

Components:

disodium sebacate:

Species : Guinea pig

Assessment Did not cause sensitisation on laboratory animals. Result : Did not cause sensitisation on laboratory animals.

Germ cell mutagenicity

Product:

Genotoxicity in vitro Remarks: No data available

Genotoxicity in vivo Remarks: No data available

Components:

disodium sebacate:

Germ cell mutagenicity -

Assessment

Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

according to GB/T 16483 and GB/T 17519 CN



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development

Remarks: No data available

Components:

disodium sebacate:

Reproductive toxicity - : - Fertility -

Assessment

No toxicity to reproduction

- Teratogenicity -

No effects on or via lactation

STOT - single exposure

Product:

Remarks : No data available

STOT - repeated exposure

Product:

Remarks : No data available

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

This information is not available.



according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Components:

disodium sebacate:

No aspiration toxicity classification

Further information

Product:

Remarks : Information given is based on data on the components and

the toxicology of similar products.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

disodium sebacate:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): > 100 mg/l

Exposure time: 96 h
Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

according to GB/T 16483 and GB/T 17519 CN



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Test Type: semi-static test

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EL50 (Skeletonema costatum (marine diatom)): 38.7 mg/l

Exposure time: 72 h Test Type: static test Method: ISO 10253

GLP: yes

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

: Remarks: No data available

Components:

disodium sebacate:

Biodegradability : Result: Biodegradable

Biodegradation: 89 % Exposure time: 28 d

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

disodium sebacate:

Partition coefficient: n- : log Pow: -4.9 (20 °C)

octanol/water pH: 7.8

Mobility in soil

Product:



according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Mobility : Remarks: No data available

Distribution among : Remark

environmental compartments

Remarks: No data available

Other adverse effects

Product:

Additional ecological

information

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : The product should not be allowed to enter drains, water

courses or the soil.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Dispose of waste product or used containers according to

local regulations.

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

IATA-DGR

UN/ID No. : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable
Packing instruction (cargo : Not applicable

aircraft)

Packing instruction

(passenger aircraft)

Not applicable



according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

IMDG-Code

UN number Not applicable Proper shipping name Not applicable Class Not applicable Subsidiary risk Not applicable Packing group Not applicable Labels Not applicable **EmS Code** Not applicable Marine pollutant Not applicable

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : Not applicable
Proper shipping name : Not applicable
Class : Not applicable
Subsidiary risk : Not applicable
Packing group : Not applicable
Labels : Not applicable

Special precautions for user

Not applicable

15. REGULATORY INFORMATION

National regulatory information

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals : Not applicable

Hazardous Chemicals for Priority Management under

SAWS

Not applicable

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not applicable

and Export

International Regulations

Montreal Protocol : Not applicable

Rotterdam Convention (Prior Informed Consent) : Not applicable

according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation: DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response: ELx - Loading rate associated with x% response: EmS - Emergency Schedule: ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO -International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System



according to GB/T 16483 and GB/T 17519



OKS 4220 极端温度条件的轴承润滑脂

Version Revision Date: Date of last issue: 2023-06-14

2.1 2023-12-20 Date of first issue: 2013-07-11 Print Date: 2023-12-20

Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.