according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

VersionRevision Date:Date of last issue: 2022-03-164.12022-04-20Date of first issue: 2013-07-04Print Date: 2022-04-22

1. PRODUCT AND COMPANY IDENTIFICATION

Product name	:	OKS 451	
Chemical nature	:	Active substance with propellant Synthetic hydrocarbon oil	
Manufacturer or supplier's de	eta	ils	
Company name of supplier	:	OKS Spezialschmierstoffe GmbH Ganghoferstr. 47 D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com	
E-mail address of person responsible for the SDS	:	mcm@oks-germany.com Material Compliance Management	
National contact	:		
Emergency telephone number	:	+86 532 8388 9090 (NRCC, only for hazardous chemicals) +86 21 69225521	
Recommended use of the chemical and restrictions on use			
Recommended use	:	Lubricant spray	
Restrictions on use	:	Restricted to professional users.	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	: aerosol			
Colour	: brown			
Odour	: characteristic			
Extremely flammable aerosol. Pressurised container: May burst if heated. May cause an allergic skin reaction. Causes serious eye irritation.				
GHS Classification				

Aerosols	:	Category 1

Eye irritation	:	Category 2A
----------------	---	-------------



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version 4.1	Revision Date: 2022-04-20	Date of last issue: 2022-03-16 Date of first issue: 2013-07-04 Print Date: 2022-04-22
Skin	sensitisation	: Category 1
	S label elements ard pictograms	
Sign	al word	: Danger
Haza	ard statements	 H222 Extremely flammable aerosol. H229 Pressurised container: May burst if heated. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation.
Prec	autionary stateme	 Prevention: P210 Keep away from heat/ sparks/ open flames/ hot surfaces No smoking. P211 Do not spray on an open flame or other ignition source. P251 Do not pierce or burn, even after use. P261 Avoid breathing mist. P264 Wash skin thoroughly after handling. P272 Contaminated work clothing should not be allowed out o the workplace. P280 Wear protective gloves/ eye protection/ face protection.
		 Response: P302 + P352 IF ON SKIN: Wash with plenty of water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention. P337 + P313 If eye irritation persists: Get medical advice/ attention. P362 + P364 Take off contaminated clothing and wash it befo reuse.
		Storage: P410 + P412 Protect from sunlight. Do not expose to tempera tures exceeding 50 °C/ 122 °F.
		Disposal: P501 Dispose of contents/containers according the local gov- ernment requirements.

Physical and chemical hazards

Extremely flammable aerosol.Pressurised container: May burst if heated.



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

VersionRevision Date:Date of last issue: 2022-03-164.12022-04-20Date of first issue: 2013-07-04Print Date: 2022-04-22

Health hazards

Causes serious eye irritation. May cause an allergic skin reaction.

Environmental hazards

Not classified based on available information.

Other hazards which do not result in classification None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Butane	106-97-8	>= 30 -< 50
propane	74-98-6	>= 10 -< 20
Isobutane	75-28-5	>= 10 -< 20
Sulfonic acids, petroleum, calcium salts	61789-86-4	>= 0.1 -< 1
Molybdenum, bis[O,O-bis(2-ethylhexyl) phos- phorodithioatokappa.S,.kappa.S']dioxodimu thioxodi-, (Mo-Mo)	72030-25-2	>= 0.25 -< 1

4. FIRST AID MEASURES

If inhaled :	Remove person to fresh air. If signs/symptoms continue, get medical attention. Keep patient warm and at rest. If unconscious, place in recovery position and seek medical advice. Keep respiratory tract clear. If breathing is irregular or stopped, administer artificial respira- tion.
In case of skin contact :	Take off all contaminated clothing immediately. Wash off immediately with soap and plenty of water. Get medical attention immediately if irritation develops and persists. Wash clothing before reuse. Thoroughly clean shoes before reuse.
In case of eye contact :	Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes. Seek medical advice.



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version 4.1			ast issue: 2022-03-16 irst issue: 2013-07-04 Print Date: 2022-04-22
If swallowed		:	Move the victim to fresh air. Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.
	t important symptom effects, both acute a yed		May cause an allergic skin reaction. Inhalation may provoke the following symptoms: Unconsciousness Dizziness Drowsiness Headache Nausea Tiredness Allergic appearance
Note	Notes to physician		The first aid procedure should be established in consultation with the doctor responsible for industrial medicine. Treat symptomatically.
. FIREF	IGHTING MEASURE	ES	
Suita	able extinguishing me	edia :	ABC powder
Unsı med	uitable extinguishing lia	:	High volume water jet
Spec fight	cific hazards during f ing	ire- :	Fire Hazard Do not let product enter drains. Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.
Haza ucts	Hazardous combustion prod- ucts		Carbon oxides Nitrogen oxides (NOx)
Spec ods	Specific extinguishing meth- ods		Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.
	Special protective equipment for firefighters		In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to

6. ACCIDENTAL RELEASE MEASURES



health.

according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version 4.1	Revision Date: 2022-04-20		ast issue: 2022-03-16 irst issue: 2013-07-04 Print Date: 2022-04-22
tive e	onal precautions, equipment and em y procedures		Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Refer to protective measures listed in sections 7 and 8.
Envi	ronmental precaut	ions :	Try to prevent the material from entering drains or water courses. Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages cannot be contained.
	ods and materials ainment and clean		Contain spillage, and then collect with non-combustible ab- sorbent material, (e.g. sand, earth, diatomaceous earth, ver- miculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. Non-sparking tools should be used.
Prev haza	ention of seconda Irds	ry :	Only qualified personnel equipped with suitable protective equipment may intervene.

7. HANDLING AND STORAGE

Handling

J	
Advice on safe handling	 Do not use in areas without adequate ventilation. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes. For personal protection see section 8. Keep away from fire, sparks and heated surfaces. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Smoking, eating and drinking should be prohibited in the application area. Wash hands and face before breaks and immediately after handling the product. Do not get in eyes or mouth or on skin. Do not get on skin or clothing. Do not use sparking tools. These safety instructions also apply to empty packaging which may still contain product residues. Pressurized container: protect from sunlight and do not ex-



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version 4.1	Revision Date: 2022-04-20	2010 0.10	ast issue: 2022-03-16 rst issue: 2013-07-04 Print Date: 2022-04-22
			pose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
Avoi	dance of contact	:	Oxidizing agents
Stor	age		
Con	ditions for safe sto	rage :	BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis		
Butane	106-97-8	STEL	1,000 ppm	ACGIH (2018-03-20)		
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH (2018-03-20)		
Engineering measures	 easures : Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust). 					
Personal protective equipme	nt					
Respiratory protection	ventilation is that exposure	Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Short term only				
Filter type	: Filter type A-I	Filter type A-P				
Eye/face protection	: Safety glasse	es with side-shiel	ds			
Hand protection Material Break through time Protective index	: butyl-rubber : > 10 min : Class 1					
Remarks	break through	For prolonged or repeated contact use protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore				

Components with workplace control parameters



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version 4.1	Revision Date: 2022-04-20	Date of last issue: 2022-03-16 Date of first issue: 2013-07-04 Print Date: 2022-04-22
		has to be measured for each case.
Prot	ective measures	 The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace. Choose body protection in relation to its type, to the concen- tration and amount of dangerous substances, and to the spe- cific work-place.
Hyg	iene measures	: Wash face, hands and any exposed skin thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	:	aerosol
Colour	:	brown
Odour	:	characteristic
Odour Threshold	:	No data available
рН	:	Not applicable substance/mixture is non-soluble (in water)
Melting point/range	:	No data available
Boiling point/boiling range	:	-42 °C (1,013 hPa)
Flash point	:	-60 °C
		Method: DIN 51755, closed cup
Evaporation rate	:	No data available
Flammability (solid, gas)	:	Extremely flammable aerosol.
Self-ignition	:	not auto-flammable
Upper explosion limit / Upper flammability limit	:	10.9 %(V)



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

VersionRevision Date:Date of last issue: 2022-03-164.12022-04-20Date of first issue: 2013-07-04Print Date: 2022-04-22

Lower explosion limit / Lower flammability limit	:	1.5 %(V)
Vapour pressure	:	3,000 hPa (20 °C)
Relative vapour density	:	No data available
Relative density	:	0.67 (20 °C) Reference substance: Water The value is calculated
Density	:	0.67 g/cm3 (20 °C)
Bulk density	:	No data available
Solubility(ies) Water solubility	:	insoluble
Solubility in other solvents	:	No data available
Partition coefficient: n- octanol/water	:	No data available
Auto-ignition temperature	:	> 350 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	< 20.5 mm2/s (40 °C)
Explosive properties	:	Not explosive
Oxidizing properties	:	No data available
Sublimation point	:	No data available
Metal corrosion rate	:	Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity	:	No hazards to be specially mentioned.
Chemical stability	:	Stable under normal conditions.



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version 4.1	Revision Date: 2022-04-20	Date of last issue: 2022-03-16 Date of first issue: 2013-07-04 Print Date: 2022-04-22
Poss	sibility of hazardou	s reac- : No dangerous reaction known under conditions of normal use.
Con	ditions to avoid	: Heat, flames and sparks. Strong sunlight for prolonged periods. Risk of receptacle bursting.

Incompatible materials	:	Oxidizing agents
Hazardous decomposition products	:	No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity		
Product: Acute oral toxicity	:	Remarks: This information is not available.
Acute inhalation toxicity	:	Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder
Acute dermal toxicity	:	Symptoms: Redness, Local irritation
Components:		
Butane:		
Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l Exposure time: 4 h Test atmosphere: gas
Isobutane:		
Acute inhalation toxicity	:	LC50 (Rat): 658 mg/l
		Exposure time: 4 h Test atmosphere: gas

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioatokappa.S,.kappa.S']dioxodi-
.muthioxodi-, (Mo-Mo):

Acute dermal toxicity	:	Symptoms: Redness, Local irritation
-----------------------	---	-------------------------------------



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

VersionRevision Date:Date of last issue: 2022-03-164.12022-04-20Date of first issue: 2013-07-04Print Date: 2022-04-22

Skin corrosion/irritation

Product:

Remarks

: This information is not available.

Components:

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-.kappa.S,.kappa.S']dioxodi-.mu.-thioxodi-, (Mo-Mo):

Assessment Result	Irritating to skin. Irritating to skin.

Remarks

: Irritating to skin.

Serious eye damage/eye irritation

Product:

Result	:	Eye irritation
Remarks	:	Irritating to eyes.

Components:

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-.kappa.S,.kappa.S']dioxodi-.mu.-thioxodi-, (Mo-Mo):

Result	:	No eye irritation
Assessment	:	No eye irritation

Respiratory or skin sensitisation

Product:		
Assessment	:	May cause sensitisation by skin contact.
Result	:	May cause sensitisation by skin contact.

Components:

Sulfonic acids, petroleum, calcium salts:Assessment: The product is a skin sensitiser, sub-category 1B.



according to GB/T 16483 and GB/T 17519 CN



OKS 451

Version	Revision Date:	Date of last issue: 2022-03-16	
4.1	2022-04-20	Date of first issue: 2013-07-04	Print Date: 2022-04-22

Molybdenum, bis[O,O-bis(ź .muthioxodi-, (Mo-Mo):	2-etł	nylhexyl) phosphorodithioatokappa.S,.kappa.S']dioxodi-
Assessment Result	:	The product is a skin sensitiser, sub-category 1B. The product is a skin sensitiser, sub-category 1B.
Germ cell mutagenicity		
<u>Product:</u> Genotoxicity in vitro	:	Remarks: No data available
Genotoxicity in vivo	:	Remarks: No data available
Carcinogenicity		
<u>Product:</u> Remarks	:	No data available
Reproductive toxicity		
<u>Product:</u> Effects on fertility	:	Remarks: No data available
Effects on foetal develop- ment	:	Remarks: No data available
Repeated dose toxicity		
<u>Product:</u> Remarks	:	This information is not available.
Aspiration toxicity		
<u>Product:</u> This information is not availa	ble.	
Further information		
<u>Product:</u> Remarks	:	Information given is based on data on the components and
		a brand of



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version	Revision Date:	Date of last issue: 2022-03-16	
4.1	2022-04-20	Date of first issue: 2013-07-04	Print Date: 2022-04-22

the toxicology of similar products.

Components:

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioatokappa.S,.kappa.S']dioxodimuthioxodi-, (Mo-Mo):				
Remarks	:	Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.		

12. ECOLOGICAL INFORMATION

Ecotoxicity	
Product: Toxicity to fish :	Remarks: No data available
Toxicity to daphnia and other : aquatic invertebrates	Remarks: No data available
Toxicity to algae/aquatic : plants	Remarks: No data available
Toxicity to microorganisms :	Remarks: No data available
Components:	
Molybdenum, bis[O,O-bis(2-et .muthioxodi-, (Mo-Mo):	hylhexyl) phosphorodithioatokappa.S,.kappa.S']dioxodi-
Toxicity to fish :	LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l Exposure time: 96 h Test Type: semi-static test Method: OECD Test Guideline 203 GLP: yes
	Remarks: May cause long-term adverse effects in the aquatic environment.



according to GB/T 16483 and GB/T 17519 CN



OKS 451

rsion	Revision Date: 2022-04-20		ast issue: 2022-03-16 irst issue: 2013-07-04 Print Date: 2022-04-22
	city to daphnia and atic invertebrates	other :	EC50 (Daphnia magna (Water flea)): > 100 mg/l Exposure time: 48 h Test Type: static test Method: OECD Test Guideline 202 GLP: yes
Toxi plant	city to algae/aquations	c :	EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l Exposure time: 72 h Test Type: static test Method: OECD Test Guideline 201 GLP: yes
Pers	sistence and degra	adability	
_	<u>duct:</u> legradability	:	Remarks: No data available
Phys ity	sico-chemical remo	vabil- :	Remarks: No data available
<u>Com</u>	ponents:		
	ybdenum, bis[O,O thioxodi-, (Mo-Mo		hylhexyl) phosphorodithioatokappa.S,.kappa.S']dioxodi-
	legradability	:	Result: Not rapidly biodegradable Biodegradation: 11 % Exposure time: 28 d Method: OECD Test Guideline 301B
Bioa	accumulative pote	ntial	
	<u>duct:</u> ccumulation	:	Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT). This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).
<u>Com</u>	ponents:		
	ane: ition coefficient: n- nol/water	:	log Pow: 2.89 Method: OECD Test Guideline 107



according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version	Revision Date:	Date of last issue: 2022-03-16	
4.1	2022-04-20	Date of first issue: 2013-07-04	Print Date: 2022-04-22

propane:

Partition coefficient: n- octanol/water	:	log Pow: 2.36
Isobutane:		
Partition coefficient: n- octanol/water	:	log Pow: 2.88 Method: OECD Test Guideline 107

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-.kappa.S,.kappa.S']dioxodi-.mu.-thioxodi-, (Mo-Mo):

Partition coefficient: n-	:	log Pow: > 4
octanol/water		

Mobility in soil

Product:		
Mobility	:	Remarks: No data available
Distribution among environ- mental compartments	:	Remarks: No data available
Other adverse effects		
Product: Additional ecological infor- mation	:	No information on ecology is available.
Components:		
	- 41-	with south which and difference is the man of the main of the south of

Molybdenum, bis[O,O-bis(2-ethylhexyl) phosphorodithioato-.kappa.S,.kappa.S']dioxodi-.mu.-thioxodi-, (Mo-Mo):

Additional ecological infor-	:	May cause long lasting harmful effects to aquatic life.
mation		

13. DISPOSAL CONSIDERATIONS

Disposal methods		
Waste from residues	:	Do not dispose of with domestic refuse. Dispose of as hazardous waste in compliance with local and national regulations.
Contaminated packaging	:	Packaging that is not properly emptied must be disposed of as





according to GB/T 16483 and GB/T 17519 $\ensuremath{\text{CN}}$



OKS 451

Version	Revision Date:	Date of last issue: 2022-03-16	
4.1	2022-04-20	Date of first issue: 2013-07-04	Print Date: 2022-04-22

the unused product. Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

14. TRANSPORT INFORMATION

International Regulations		
UNRTDG		

IATA-DGRUN/ID No.:UN 1950Proper shipping name:Aerosols, flammableClass:2.1Packing group:Not assigned by regulationLabels:Flammable GasPacking instruction (cargo:203aircraft):203Packing instruction (passen- ger aircraft):203IMDG-Code:UN 1950VN number:UN 1950Proper shipping name:AEROSOLSClass:2.1Packing group:Not assigned by regulationLabels:2.1EmS Code:F-D, S-U	UN number Proper shipping name Class Packing group Labels	:	UN 1950 AEROSOLS 2.1 Not assigned by regulation 2.1	
IMDG-CodeUN number:Proper shipping name:AEROSOLSClass:Packing group:Labels:2.1	UN/ID No. Proper shipping name Class Packing group Labels Packing instruction (cargo aircraft) Packing instruction (passen-	:	Aerosols, flammable 2.1 Not assigned by regulation Flammable Gas 203	
Packing group: Not assigned by regulationLabels: 2.1	IMDG-Code UN number			
Marine pollutant : no	Packing group Labels EmS Code	:	Not assigned by regulation 2.1 F-D, S-U	

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268		
UN number	:	UN 1950
Proper shipping name	:	AEROSOLS
Class	:	2.1
Packing group	:	Not assigned by regulation
Labels	:	2.1



according to GB/T 16483 and GB/T 17519 CN



OKS 451

Version	Revision Date:	Date of last issue: 2022-03-16	
4.1	2022-04-20	Date of first issue: 2013-07-04	Print Date: 2022-04-22

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals			
Hazardous Chemicals for Priority Management under	:	Not applicable	
SAWS			

China Severely Restricted Toxic Chemicals for Import : Not applicable and Export

Catalogue of Hazardous Chemicals

: Listed

Product name	Status	Reference number
OKS 451	Listed	2828

List of ingredients	CAS-No.	Status	Reference number
Butane	106-97-8	Listed	2778
propane	74-98-6	Listed	139
Isobutane	75-28-5	Listed	2707

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)No. / CodeChemical name / CategoryW3AerosolsThreshold quantity150 t

The components of this product are reported in the following inventories:IECSC:On the inventory, or in compliance with the inventory

16. OTHER INFORMATION



according to GB/T 16483 and GB/T 17519 CN



OKS 451

VersionRevision Date:Date of last issue: 2022-03-164.12022-04-20Date of first issue: 2013-07-04Print Date: 2022-04-22

Date format

: yyyy/mm/dd

:

Full text of other abbreviations

ACGIH

: USA. ACGIH Threshold Limit Values (TLV)

Short-term exposure limit

ACGIH / STEL

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods: TECI - Thailand Existing Chemicals Inventory: TSCA - Toxic Substances Control Act (United States): UN - United Nations: UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users



according to GB/T 16483 and GB/T 17519 CN



OKS 451

Version	Revision Date:	Date of last issue: 2022-03-16	
4.1	2022-04-20	Date of first issue: 2013-07-04	Print Date: 2022-04-22

from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.

