according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 471

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant spray

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact : EagleBurgmann Hungaria Kft.

Népfürdő utca 22 1138 Budapest

Hungary

Tel.: +36 1 814 8160 Fax: +36 1 319 8125

info.hu@eagleburgmann.com

1.4 Emergency telephone number

Emergency telephone num-

0049 (0) 8142-3051-517

ber

Egészségügyi Toxikológiai Tájékoztató Szolgálat (ETTSZ)

H-1096 Budapest, Nagyvárad tér 2. Tel: +36 1 476 6464, +36 80 201 199

## **SECTION 2: Hazards identification**

## 2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

#### 2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters air-

ways.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smokina.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

## Hazardous components which must be listed on the label:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

# **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Mineral oil.

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C11- C12, isoalkanes, < 2% aromatics	918-167-1 01-2119472146-39- XXXX	Flam. Liq.3; H226 Asp. Tox.1; H304; EUH066	Note P	>= 30 - < 50
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 1 - < 10
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10
Substances with a work butane	cplace exposure limit : 106-97-8 203-448-7 601-004-00-0 01-2119474691-32-	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 20 - < 30

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

	XXXX			
distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- XXXX	Not classified	Note L	>= 10 - < 20
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified	64742-52-5 265-155-0 649-465-00-7 01-2119467170-45- XXXX	Not classified	Note L	>= 1 - < 10

For explanation of abbreviations see section 16.

## **SECTION 4: First aid measures**

# 4.1 Description of first aid measures

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

# **SECTION 5: Firefighting measures**

#### 5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

## 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod: :

ucts

Carbon oxides Metal oxides

# 5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



## **OKS 471**

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

#### **SECTION 6: Accidental release measures**

## 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

#### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

#### 6.4 Reference to other sections

For personal protection see section 8.

# **SECTION 7: Handling and storage**

## 7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular na-

tional regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

# **SECTION 8: Exposure controls/personal protection**

## 8.1 Control parameters

# **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Hydrocarbons, C11-C12, isoal- kanes, < 2% aro- matics	Not Assigned	TWA (Mist)	5 mg/m3	HU OEL (2020-02-06)
manos	Further information: SCOEL/SUM/163/2011, Substances which have a health			
	hazard after PROLONGED exposure. Corrected value = TWA x 40 / number of hours per week			
butane	106-97-8	TWA	2.350 mg/m3	HU OEL (2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required.			
		CEIL	9.400 mg/m3	HU OEL (2020-02-06)
	Further information: Irritants, simple suffocation gases, substances with minor health effects. No correction is required.			
distillates (petrole- um), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m3	HU OEL (2020-02-06)
	Further information: SCOEL/SUM/163/2011, Substances which have a health hazard after PROLONGED exposure. Corrected value = TWA x 40 / number of hours per week			
Distillates (petrole-	64742-52-5	TWA (Mist)	5 mg/m3	HU OEL



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

um), hydrotreated heavy naphthenic; Baseoil — un- specified			(2020-02-06)
	ROLONGED expos	163/2011, Substances which ure. Corrected value = TWA	

# Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
distillates (petroleum), hydrotreated heavy paraffinic	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Distillates (petrole- um), hydrotreated heavy naphthenic; Baseoil — unspecified	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg

# Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
distillates (petroleum), hy-	Oral	9,33 mg/kg
drotreated heavy paraffinic		
Distillates (petroleum), hy-	Oral	9,33 mg/kg
drotreated heavy naphthenic;		
Baseoil — unspecified		

# 8.2 Exposure controls

## **Engineering measures**

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

## Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

 Version
 Revision Date:
 Date of last issue: 12.05.2021
 Print Date: 13.12.2022

 Date of first issue: 09.07.2016
 13.12.2022

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : Respirator with combination filter for vapour/particulate (EN

141)

Short term only

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : ABEK-P3-filter

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

## **SECTION 9: Physical and chemical properties**

## 9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : white

Odour : hydrocarbon-like

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -44 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

8,5 %(V)

Lower explosion limit / Lower :

flammability limit

1,5 %(V)

Flash point : -97,00 °C

Method: Abel-Pensky



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 3.500 hPa (20 °C)

Relative density : 0,718 (20 °C)

Reference substance: Water The value is calculated

Density : 0,72 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



## **OKS 471**

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

## **SECTION 10: Stability and reactivity**

#### 10.1 Reactivity

No hazards to be specially mentioned.

#### 10.2 Chemical stability

Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

## **Acute toxicity**

**Product:** 

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

cause defatting resulting in drying, redness and possible blis-

tering.

Symptoms: Skin disorders

## **Components:**

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: ves

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Skin corrosion/irritation

**Product:** 

Remarks : This information is not available.

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



## **OKS 471**

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

#### **Components:**

#### Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

# distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

## Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

## Serious eye damage/eye irritation

#### **Product:**

Remarks : Contact with eyes may cause irritation.

# **Components:**

## distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

## Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

# Respiratory or skin sensitisation

**Product:** 

Remarks : This information is not available.

#### **Components:**

## distillates (petroleum), hydrotreated heavy paraffinic:

Species : Guinea pig

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Does not cause skin sensitisation. Assessment

**OECD Test Guideline 406** Method

Does not cause skin sensitisation. Result

**GLP** ves

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

**Species** Guinea pig

Assessment Does not cause skin sensitisation.

**OECD Test Guideline 406** Method

Result Does not cause skin sensitisation.

Germ cell mutagenicity

**Product:** 

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo Remarks: No data available

**Components:** 

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Test Type: In vitro mammalian cell gene mutation test Genotoxicity in vitro

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

Result: negative

Genotoxicity in vivo Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity- As-

sessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Carcinogenicity

**Product:** 

Remarks : No data available

**Components:** 

distillates (petroleum), hydrotreated heavy paraffinic:

Carcinogenicity - Assess- : Not classifiable as a human carcinogen.

ment



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

Reproductive toxicity

**Product:** 

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

Remarks: No data available

**Components:** 

distillates (petroleum), hydrotreated heavy paraffinic:

Reproductive toxicity - As-

: - Fertility -

sessment

No toxicity to reproduction

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Effects on foetal develop-

ment

Species: Rat

Application Route: Dermal

General Toxicity Maternal: LOAEL: 125 mg/kg body weight Teratogenicity: NOAEL: >= 2.000 mg/kg body weight

Developmental Toxicity: NOAEL: >= 2.000 mg/kg body weight

Embryo-foetal toxicity: NOAEL: >= 2.000 mg/kg body weight Method: OECD Test Guideline 414

Result: No effects on fertility and early embryonic develop-

ment were detected.

Reproductive toxicity - As-

sessment

: - Fertility -

No toxicity to reproduction

- Teratogenicity -

No toxicity to reproduction

STOT - single exposure

**Components:** 

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

**Components:** 

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



## **OKS 471**

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

#### Repeated dose toxicity

**Product:** 

Remarks : This information is not available.

## **Aspiration toxicity**

#### **Product:**

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

#### **Components:**

#### Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

## distillates (petroleum), hydrotreated heavy paraffinic:

No aspiration toxicity classification

# Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

No aspiration toxicity classification

## 11.2 Information on other hazards

#### **Endocrine disrupting properties**

#### **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### **Further information**

**Product:** 

Remarks : Information given is based on data on the components and

the toxicology of similar products.

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

# **SECTION 12: Ecological information**

#### 12.1 Toxicity

**Product:** 

Toxicity to fish : Remarks: May cause long-term adverse effects in the aquatic

environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

#### **Components:**

distillates (petroleum), hydrotreated heavy paraffinic:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

ic toxicity)

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

NOEC: 10 mg/l Exposure time: 21 d

exposure time. 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h

Test Type: static test

Method: OECD Test Guideline 202

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Toxicity to algae/aquatic

plants

LC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: >= 1.000 mg/lExposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Remarks: The value is calculated

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOELR: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea) Test Type: Reproduction Test

Method: OECD Test Guideline 211

#### 12.2 Persistence and degradability

**Product:** 

Biodegradability Remarks: No data available

ity

Physico-chemical removabil- : Remarks: No data available

## **Components:**

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Biodegradability : Result: Not readily biodegradable.

distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability Test Type: aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: ves

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Biodegradability Test Type: aerobic

Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

## 12.3 Bioaccumulative potential

**Product:** 

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-

octanol/water

Remarks: No data available

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

isobutane:

Partition coefficient: n-

octanol/water

log Pow: 2,88

Method: OECD Test Guideline 107

butane:

Partition coefficient: n-

cient: n- : log Pow: 2,89

octanol/water Method: OECD Test Guideline 107

distillates (petroleum), hydrotreated heavy paraffinic:

Partition coefficient: n-

octanol/water

: log Pow: > 2

12.4 Mobility in soil

**Product:** 

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

**Product:** 

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



## **OKS 471**

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

#### Components:

#### distillates (petroleum), hydrotreated heavy paraffinic:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

# Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

: Non-classified PBT substance. Non-classified vPvB substance Assessment

## 12.6 Endocrine disrupting properties

# **Product:**

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

#### 12.7 Other adverse effects

## **Product:**

mation

Additional ecological infor- : May cause long lasting harmful effects to aquatic life.

# **SECTION 13: Disposal considerations**

#### 13.1 Waste treatment methods

Product Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Packaging that is not properly emptied must be disposed of as Contaminated packaging

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code unused product, packagings not completely emptied

16 05 04\*, gases in pressure containers (including halons)

containing hazardous substances



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



## **OKS 471**

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

## **SECTION 14: Transport information**

## 14.1 UN number or ID number

ADN : UN 1950
ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

## 14.2 UN proper shipping name

ADN : AEROSOLS
ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

## 14.3 Transport hazard class(es)

ADN : 2
ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

# 14.4 Packing group

## **ADN**

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1

## **ADR**

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

#### **RID**

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

#### **IMDG**

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

IATA (Cargo)

Packing instruction (cargo

.

203

203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen: :

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

**ADN** 

Environmentally hazardous : no

ADR

Environmentally hazardous : no

RID

Environmentally hazardous : no

**IMDG** 

Marine pollutant : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

# **SECTION 15: Regulatory information**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

Not applicable

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

(EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Article 57).

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH-Annex XIV)

: Not applicable

Regulation (EC) No 1005/2009 on substances that de: Not applicable

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

plete the ozone layer (EC 1005/2009)

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast)

(EU POP)

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import

of dangerous chemicals

(EU PIC)

Not applicable

Not applicable

: P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

Liquefied extremely flammable gases (including LPG) and natural gas

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 78,75 %

## Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

2000 XXV. Law on chemical safety

44/2000. (XII 27) Ministry of health dangerous substances and preparations dangerous for certain procedures and arrangements for activities



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

#### 15.2 Chemical safety assessment

This information is not available.

#### **SECTION 16: Other information**

#### **Full text of H-Statements**

EUH066 : Repeated exposure may cause skin dryness or cracking.

H220 : Extremely flammable gas. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

EUH066 : Repeated exposure may cause skin dryness or cracking.

#### Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-

stance is a specific isomer or a mixture of isomers.

Note L : The harmonised classification as a carcinogen applies unless

it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method"Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard

class.

Note P : The harmonised classification as a carcinogen or mutagen

applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 +

P310-P331 shall apply.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

 Version
 Revision Date:
 Date of last issue: 12.05.2021
 Print Date:

 2.2
 13.12.2022
 Date of first issue: 09.07.2016
 13.12.2022

HU OEL : Hungary. Occupational Exposure Limits - Annex 1: Permissi-

ble concentration values

HU OEL / TWA : Mean concentration HU OEL / CEIL : Peak concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## **Further information**

#### Classification of the mixture:

#### Classification procedure:

Aerosol 1 H222, H229 Based on product data or assessment Asp. Tox. 1 H304 Based on product data or assessment

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users



according to Regulation (EC) No. 1907/2006 - HU (Commission Regulation (EU) 2020/878)



**OKS 471** 

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.