according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 471

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- : Lubricant spray

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person :

responsible for the SDS

mcm@oks-germany.com

Material Compliance Management

National contact :

1.4 Emergency telephone number

Emergency telephone num-

ber

CIAV - Information Centre of Antipoison (+351) 800 250 250 (free 24/7 service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters air-

ways.

Supplemental Hazard

Statements

EUH066

Repeated exposure may cause skin

dryness or cracking.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks,

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Mineral oil.

Components

Components				
Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C11- C12, isoalkanes, < 2% aromatics	918-167-1 01-2119472146-39- XXXX	Flam. Liq.3; H226 Asp. Tox.1; H304; EUH066	Note P	>= 30 - < 50
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1)	>= 1 - < 10
Substances with a workplace exposure limit :				
butane	106-97-8 203-448-7 601-004-00-0 01-2119474691-32- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 20 - < 30
distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7 265-157-1 649-467-00-8 01-2119484627-25- XXXX	Not classified	Note L	>= 10 - < 20
Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified	64742-52-5 265-155-0 649-465-00-7 01-2119467170-45- XXXX	Not classified	Note L	>= 1 - < 10

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

lithium 12- hydroxystearate	7620-77-1 231-536-5 01-2119970893-23- XXXX 01-2119970893-23- XXXX 01-2119970893-23- XXXX 01-2119970893-23- XXXX	Not classified		>= 1 - < 10
isobutane	75-28-5 200-857-2 601-004-00-0 01-2119485395-27- XXXX	Flam. Gas1A; H220 Press. GasCompr. Gas; H280	Note U (table 3.1), Note C	>= 1 - < 10

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes. Seek medical advice.

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod: :

ucts

Carbon oxides

Metal oxides

5.3 Advice for firefighters

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular na-

tional regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butane	106-97-8	VLE_CD	1.000 ppm	PT OEL (2014-11-14)
distillates (petrole- um), hydrotreated heavy paraffinic	64742-54-7	VLE-MP (Inhala- ble fraction)	5 mg/m3	PT OEL (2014-11-14)
	Further information: Substances that are not classified as carcinogenic for humans.			
Distillates (petrole- um), hydrotreated heavy naphthenic; Baseoil — un- specified	64742-52-5	VLE-MP (Inhala- ble fraction)	5 mg/m3	PT OEL (2014-11-14)
	Further information: Substances that are not classified as carcinogenic for humans.			
lithium 12- hydroxystearate	7620-77-1	VLE-MP	10 mg/m3	PT OEL (2007-03-26)
	Further information: Substances that are not classified as carcinogenic for humans.			



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

isobutane 75-28-5 VLE_CD 1.000 ppm PT OEL (2014-11-14)

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
distillates (petroleum), hydrotreated heavy paraffinic	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg
Distillates (petrole- um), hydrotreated heavy naphthenic; Baseoil — unspecified	Workers	Inhalation	Long-term local effects	5,58 mg/m3
	Workers	Inhalation	Long-term systemic effects	2,73 mg/m3
	Workers	Skin contact	Long-term systemic effects	0,97 mg/kg

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
distillates (petroleum), hy-	Oral	9,33 mg/kg
drotreated heavy paraffinic		
Distillates (petroleum), hy-	Oral	9,33 mg/kg
drotreated heavy naphthenic;		
Baseoil — unspecified		

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation. Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : Respirator with combination filter for vapour/particulate (EN

141)

Short term only

Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : ABEK-P3-filter

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

Colour : white

Odour : hydrocarbon-like

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -44 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

8,5 %(V)

Lower explosion limit / Lower

flammability limit

1,5 %(V)

Flash point : -97,00 °C

Method: Abel-Pensky

Auto-ignition temperature : No data available

Decomposition temperature : No data available

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 3.500 hPa (20 °C)

Relative density : 0,718 (20 °C)

Reference substance: Water The value is calculated

Density : 0,72 g/cm3

(20 °C)

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

cause defatting resulting in drying, redness and possible blis-

tering.

Symptoms: Skin disorders

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

distillates (petroleum), hydrotreated heavy paraffinic:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 5,53 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

GLP: yes

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

lithium 12-hydroxystearate:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rabbit): > 3.000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Result : Repeated exposure may cause skin dryness or cracking.

distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

lithium 12-hydroxystearate:

Assessment : No skin irritation

Method : OECD Test Guideline 439

Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

GLP : yes

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

lithium 12-hydroxystearate:

Species : Rabbit

Assessment : No eye irritation

Method : OECD Test Guideline 405

Result : No eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

lithium 12-hydroxystearate:

Exposure routes : Dermal Species : Mouse

Method : OECD Test Guideline 429

Result : negative

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster ovary cells

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 473

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

Result: negative

Genotoxicity in vivo : Test Type: Micronucleus test

Species: Mouse

Cell type: Bone marrow

Application Route: Intraperitoneal injection Method: OECD Test Guideline 474

Result: negative

Germ cell mutagenicity- As-

sessment

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Carcinogenicity - Assess-

ment

: Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

Remarks: No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Reproductive toxicity - As- : - Fertility -

sessment No toxicity to reproduction

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Effects on foetal develop-

ment

Species: Rat

Application Route: Dermal

General Toxicity Maternal: LOAEL: 125 mg/kg body weight Teratogenicity: NOAEL: >= 2.000 mg/kg body weight

Developmental Toxicity: NOAEL: >= 2.000 mg/kg body weight Embryo-foetal toxicity: NOAEL: >= 2.000 mg/kg body weight

Method: OECD Test Guideline 414

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

 Version
 Revision Date:
 Date of last issue: 12.05.2021
 Print Date: 13.12.2022

 Date of first issue: 09.07.2016
 13.12.2022

Result: No effects on fertility and early embryonic develop-

ment were detected.

Reproductive toxicity - As-

sessment

: - Fertility -

No toxicity to reproduction

- Teratogenicity -

No toxicity to reproduction

STOT - single exposure

Components:

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Components:

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Assessment : The substance or mixture is not classified as specific target

organ toxicant, repeated exposure.

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

distillates (petroleum), hydrotreated heavy paraffinic:

No aspiration toxicity classification

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

No aspiration toxicity classification



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment The substance/mixture does not contain components consid-

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks Information given is based on data on the components and

the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Remarks: May cause long-term adverse effects in the aquatic Toxicity to fish

environment.

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l Toxicity to fish

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: Immobilization

Method: OECD Test Guideline 202

GLP: yes

Toxicity to daphnia and other : NOEC: 10 mg/l

a brand of FREUDENBERG

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

aquatic invertebrates (Chron-

ic toxicity)

Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: semi-static test

Method: OECD Test Guideline 211

GLP: yes

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 10.000 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

LC50 (Pseudokirchneriella subcapitata (green algae)): > 100

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOELR: >= 1.000 mg/l

Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout)

Remarks: The value is calculated

Toxicity to daphnia and other :

aquatic invertebrates (Chron-

ic toxicity)

NOELR: 10 mg/l Exposure time: 21 d

Species: Daphnia magna (Water flea)

Test Type: Reproduction Test Method: OECD Test Guideline 211

lithium 12-hydroxystearate:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 100 mg/l

Exposure time: 96 h Test Type: semi-static test

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): > 160

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 160

mg/l

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Exposure time: 72 h

Method: OECD Test Guideline 201

12.2 Persistence and degradability

Product:

: Remarks: No data available Biodegradability

Physico-chemical removabil- : Remarks: No data available

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Biodegradability : Result: Not readily biodegradable.

distillates (petroleum), hydrotreated heavy paraffinic:

Biodegradability Test Type: aerobic

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

Biodegradability Test Type: aerobic

> Inoculum: activated sludge Result: Not rapidly biodegradable

Biodegradation: 3 % Exposure time: 28 d

Method: OECD Test Guideline 301B

GLP: yes

lithium 12-hydroxystearate:

Biodegradability Test Type: Primary biodegradation

> Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: 74,7 %

Exposure time: 28 d

Method: OECD Test Guideline 301C

12.3 Bioaccumulative potential

Product:

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

Components:

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-

octanol/water

: Remarks: No data available

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

butane:

Partition coefficient: n-

octanol/water

log Pow: 2,89

Method: OECD Test Guideline 107

distillates (petroleum), hydrotreated heavy paraffinic:

Partition coefficient: n-

octanol/water

log Pow: > 2

lithium 12-hydroxystearate:

Partition coefficient: n-

octanol/water

log Pow: 2,6

isobutane:

Partition coefficient: n-

octanol/water

log Pow: 2,88

Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Components:

distillates (petroleum), hydrotreated heavy paraffinic:

Assessment : Non-classified vPvB substance. Non-classified PBT substance

Distillates (petroleum), hydrotreated heavy naphthenic; Baseoil — unspecified:

: Non-classified PBT substance. Non-classified vPvB substance Assessment

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

12.7 Other adverse effects

Product:

mation

Additional ecological infor- : May cause long lasting harmful effects to aquatic life.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Packaging that is not properly emptied must be disposed of as Contaminated packaging

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950

RID : UN 1950

IMDG : UN 1950

IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1

EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen: 203

ger aircraft)

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

Version Revision Date: Date of last issue: 12.05.2021 Print Date: 2.2 13.12.2022 Date of first issue: 09.07.2016 13.12.2022

Y203 Packing instruction (LQ)

Not assigned by regulation Packing group

Flammable Gas Labels

14.5 Environmental hazards

Environmentally hazardous no

Environmentally hazardous

Marine pollutant no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances,

mixtures and articles (Annex XVII)

REACH - Candidate List of Substances of Very High

Concern for Authorisation (Article 59).

(EU SVHC)

Article 57).

REACH - List of substances subject to authorisation

(Annex XIV)

(EU. REACH-Annex XIV)

Regulation (EC) No 1005/2009 on substances that de-

plete the ozone layer (EC 1005/2009)

tants (recast) (EU POP)

Regulation (EU) 2019/1021 on persistent organic pollu-

Regulation (EC) No 649/2012 of the European Parlia-

ment and the Council concerning the export and import of dangerous chemicals

(EU PIC)

This product does not contain sub-

stances of very high concern (Regulation (EC) No 1907/2006 (REACH),

Not applicable

Not applicable

Not applicable

Not applicable

: Not applicable



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

: P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

18 Liquefied extremely flammable gases (including LPG) and natural gas

34 Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 78,75 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.

H220 : Extremely flammable gas. H226 : Flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

EUH066 : Repeated exposure may cause skin dryness or cracking.

Full text of other abbreviations



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

VersionRevision Date:Date of last issue: 12.05.2021Print Date:2.213.12.2022Date of first issue: 09.07.201613.12.2022

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-

stance is a specific isomer or a mixture of isomers.

Note L : The harmonised classification as a carcinogen applies unless

it can be shown that the substance contains less than 3 % of dimethyl sulphoxide extract as measured by IP 346 ("Determination of polycyclic aromatics in unused lubricating base oils and asphaltene free petroleum fractions - Dimethyl sulphoxide extraction refractive index method"Institute of Petroleum, London), in which case a classification in accordance with Title II of this Regulation shall be performed also for that hazard

class.

Note P : The harmonised classification as a carcinogen or mutagen

applies unless it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7), in which case a classification in accordance with Title II of this Regulation shall be performed also for those hazard classes. Where the substance is not classified as a carcinogen or mutagen, at least the precautionary statements (P102-)P260-P262-P301 +

P310-P331 shall apply.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

2, Section 2.3.2.1, Note 2).

PT OEL : Portugal. Security and Health at the Workplace - Occupational

exposure limits of chemical agents

PT OEL / VLE-MP : Time Weighted Average
PT OEL / VLE CD : Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships car-

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 471

 Version
 Revision Date:
 Date of last issue: 12.05.2021
 Print Date:

 2.2
 13.12.2022
 Date of first issue: 09.07.2016
 13.12.2022

rying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Classification procedure:

Aerosol 1 H222, H229 Asp. Tox. 1 H304 Based on product data or assessment Based on product data or assessment

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.