- RU



OKS 481

Print Date: Version **Revision Date:** Date of last issue: 23.01.2019 16.09.2022 Date of first issue: 07.06.2016 16.09.2022 2.1

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : OKS 481

Manufacturer or supplier's details

Company name of supplier OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

: +7 495 628 1687

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

mcm@oks-germany.com

responsible for the SDS Material Compliance Management

Emergency telephone

number +49 8142 3051 517

Recommended use of the chemical and restrictions on use

Recommended use Lubricant spray

Restrictions on use Restricted to professional users.

2. HAZARDS IDENTIFICATION

GHS Classification (According to GOST 32423, GOST 32424 and GOST 32425)

Aerosols : Category 1

Acute toxicity (Oral) Category 5

single exposure

Specific target organ toxicity - : Category 3 (Central nervous system)

Aspiration hazard Category 1

Short-term (acute) aquatic

hazard

Category 3

Long-term (chronic) aquatic

hazard

Category 2

GHS-Labelling (According to GOST 31340)

Hazard pictograms







- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H336 May cause drowsiness or dizziness.

H402 Harmful to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames

and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use. P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical nature : Active agent with propellant and solvent.

Components

Chemical name	Concentration (% w/w)	Occupational Exposure Limits		CAS-No.	EC-No.
		MAC value mg/m3 / TSEL value	Hazard Class		
pentane	>= 50 - < 70	MPC-TWA: 300 mg/m3 Data Source: RU OEL	4	109-66-0	203-692-4
		MPC-STEL: 900 mg/m3 Data Source: RU OEL	4		

- RU



OKS 481

Version	Revision Date:	Date of last issue: 23.01.2019	Print Date:
2.1	16.09.2022	Date of first issue: 07.06.2016	16.09.2022

butane	>= 10 - < 20	MPC-TWA: 300 mg/m3 Data Source: RU OEL	4	106-97-8	203-448-7
		MPC-STEL: 900 mg/m3 Data Source: RU OEL	4		
propane	>= 1 - < 10	No data available		74-98-6	200-827-9
isobutane	>= 1 - < 10	No data available		75-28-5	200-857-2
zinc oxide	>= 0,25 - < 1	MPC-TWA: 0,5 mg/m3 Data Source: RU OEL	2	1314-13-2	215-222-5
		MPC-STEL: 1,5 mg/m3 Data Source: RU OEL	2		

4. FIRST AID MEASURES

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

Wash skin thoroughly with soap and water or use recognized

skin cleanser.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

- RU



OKS 481

Version **Revision Date:** Date of last issue: 23.01.2019 Print Date: 16.09.2022 Date of first issue: 07.06.2016 16.09.2022 2.1

> for at least 10 minutes. Seek medical advice.

If swallowed Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

Most important symptoms and effects, both acute and

delayed

Central nervous system depression Can be absorbed through skin.

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea **Tiredness**

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Treat symptomatically. Notes to physician

5. FIREFIGHTING MEASURES

Flammable properties

Flash point -60 °C

Method: Abel-Pensky

Ignition temperature No data available

Upper explosion limit / Upper :

flammability limit

10,9 %(V)

Lower explosion limit / Lower :

flammability limit

1,4 %(V)

Extremely flammable aerosol. Flammability (solid, gas)

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

Specific hazards during Fire Hazard

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

firefighting Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

Special protective equipment:

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition.

Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

7. HANDLING AND STORAGE

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.



- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Conditions for safe storage

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.

Store in accordance with the particular national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Data Source	
pentane	109-66-0	TWA	1.000 ppm 3.000 mg/m3	2006/15/EC (2006-02-09)	
		MPC-TWA	300 mg/m3	RU OEL	
		(vapour		(2021-02-03)	
		and/or gas)			
	Further inforn	nation: Class 4 -	Low hazard	<u> </u>	
		MPC-STEL	900 mg/m3	RU OEL	
		(vapour		(2021-02-03)	
		and/or gas)			
	Further inforn	Further information: Class 4 - Low hazard			
butane	106-97-8	MPC-TWA	300 mg/m3	RU OEL	
		(vapour		(2021-02-03)	
		and/or gas)			
	Further inforn	Further information: Class 4 - Low hazard			
		MPC-STEL	900 mg/m3	RU OEL	
		(vapour		(2021-02-03)	
		and/or gas)			
	Further inforn	Further information: Class 4 - Low hazard			
zinc oxide	1314-13-2	MPC-TWA	0,5 mg/m3	RU OEL	
		(aerosol)		(2021-02-03)	
	Further inforn	nation: Class 2 -	Highly dangerous		

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

MPC-STEL 1,5 mg/m3 RU OEL (aerosol) (2021-02-03)

Further information: Class 2 - Highly dangerous

i dittier illioimation. Class 2 - Fignily dangerous

Engineering measures : Use only in an area equipped with explosion proof exhaust

ventilation.

Handle only in a place equipped with local exhaust (or other

appropriate exhaust).

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type : Filter type A-P

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : beige

Odour : characteristic

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Odour Threshold : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : -42 °C

(1.013 hPa)

Flash point : -60 °C

Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : not auto-flammable

Upper explosion limit / Upper

flammability limit

10,9 %(V)

Lower explosion limit / Lower

flammability limit

1,4 %(V)

Vapour pressure : 2.000 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0,65 (20 °C)

Reference substance: Water The value is calculated

Density : 0,65 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: 4.345 mg/kg

Method: Calculation method

Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may

cause defatting resulting in drying, redness and possible

blistering.

Symptoms: Skin disorders

Components:

pentane:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 25,3 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Assessment: The substance or mixture has no acute

inhalation toxicity

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h
Test atmosphere: gas

zinc oxide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5,7 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Method: OECD Test Guideline 403

Assessment: The substance or mixture has no acute

inhalation toxicity

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Acute dermal toxicity : LD50 (Rat): > 2.000 mg/kg

Method: OECD Test Guideline 402

GLP: yes

Assessment: The substance or mixture has no acute dermal

toxicity

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

pentane:

Result : Repeated exposure may cause skin dryness or cracking.

zinc oxide:

Species : Rabbit

Assessment : No skin irritation

Method : OECD Test Guideline 404

Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

pentane:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

zinc oxide:

Species : Rabbit

Result : No eye irritation
Assessment : No eye irritation

Method : OECD Test Guideline 405

GLP : yes

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

pentane:

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

zinc oxide:

Test Type : Maximisation Test

Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Does not cause skin sensitisation.

GLP : yes

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

zinc oxide:

Assessment

Germ cell mutagenicity -

Tests on bacterial or mammalian cell cultures did not show

mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

zinc oxide:

- RU



OKS 481

Version **Revision Date:** Date of last issue: 23.01.2019 Print Date: 16.09.2022 Date of first issue: 07.06.2016 16.09.2022 2.1

Carcinogenicity -

Assessment

Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Effects on fertility Remarks: No data available

Effects on foetal

development

Remarks: No data available

Components:

zinc oxide:

Reproductive toxicity -

Assessment

: - Fertility -

No toxicity to reproduction

- Teratogenicity -

No toxicity to reproduction

STOT - single exposure

Components:

pentane:

Exposure routes Inhalation

Target Organs Central nervous system, Narcotic effects May cause drowsiness or dizziness. Assessment

The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

zinc oxide:

Assessment The substance or mixture is not classified as specific target

organ toxicant, single exposure.

STOT - repeated exposure

Components:

zinc oxide:

The substance or mixture is not classified as specific target Assessment

organ toxicant, repeated exposure.

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

pentane:

May be fatal if swallowed and enters airways.

zinc oxide:

No aspiration toxicity classification

Further information

Product:

Remarks : Information given is based on data on the components and

the toxicology of similar products.

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Components:

pentane:

Ecotoxicology Assessment

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

zinc oxide:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 1,55 mg/l

Exposure time: 96 h Test Type: static test

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 1 mg/l

Exposure time: 48 h Test Type: static test

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0,136

mg/l

Exposure time: 72 h Test Type: static test

Method: OECD Test Guideline 201

GLP: yes

M-Factor (Acute aquatic

toxicity)

: 1

Toxicity to daphnia and other :

aquatic invertebrates (Chronic toxicity)

(Daphnia magna (Water flea)): 0,04 mg/l

Exposure time: 21 d Test Type: semi-static test

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic

toxicity)

: 1

Toxicity to microorganisms : EC50 (activated sludge): > 1.000 mg/l

Exposure time: 3 h

Method: OECD Test Guideline 209

GLP: yes

Persistence and degradability

Product:

- RU



OKS 481

Version **Revision Date:** Date of last issue: 23.01.2019 Print Date: 2.1 16.09.2022 Date of first issue: 07.06.2016 16.09.2022

Biodegradability Remarks: No data available

Physico-chemical removability

Remarks: No data available

Components:

pentane:

Biodegradability aerobic

> Inoculum: activated sludge Result: rapidly biodegradable Biodegradation: 87 %

Method: OECD Test Guideline 301F

GLP: yes

zinc oxide:

Biodegradability Remarks: The methods for determining biodegradability are

not applicable to inorganic substances.

Bioaccumulative potential

Product:

Bioaccumulation Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

butane:

Partition coefficient: n-

log Pow: 2,89

octanol/water

Method: OECD Test Guideline 107

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

isobutane:

Partition coefficient: n-

log Pow: 2,88

octanol/water

Method: OECD Test Guideline 107

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among :

environmental compartments

Remarks: No data available

Other adverse effects

Product:

Additional ecological

information

: Toxic to aquatic life with long lasting effects.

Components:

zinc oxide:

Results of PBT and vPvB

assessment

: Remarks: Not applicable

Hygienic standards:

(Allowable concentration in air, water, including fishery waters, soil)

Components	Air	Water	Soil	Data Source
pentane	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 100 mg/m3 Limiting health hazard indicator: Reflectory-resorptive Hazard class: Class 4 - low hazard Concentration that provides admissible (acceptable) levels of risk when exposed to at least 24 hours - average daily: 25 mg/m3 Limiting health hazard indicator: Reflectory-resorptive Hazard class: Class 4 - low hazard	No data available	No data available	List 1

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

butane	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 200 mg/m3 Limiting health hazard indicator: reflectory Hazard class: Class 4 - low hazard	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 1 List 5
propane	No data available	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 5
isobutane	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 15 mg/m3 Limiting health hazard indicator: reflectory Hazard class: Class 4 - low hazard	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 1 List 5
zinc oxide	Concentration that provides admissible (acceptable) levels of risk when exposed to at least 24 hours - average daily: 0,05 mg/m3 (Zinc) Limiting health hazard indicator: resorptive Hazard class: Class 3 - moderately dangerous Concentration that provides permissible	No data available	No data available	List 1

- RU



OKS 481			
Version Revision Date: 2.1 16.09.2022		Date of last issue: 23.01.2019 Date of first issue: 07.06.2016	Print Date: 16.09.2022
		(acceptable) levels of risk for chronic (at least 1 year) exposure - average daily: 0,035 mg/m3 (Zinc) Limiting health hazard indicator:	

For explanation of abbreviations see section 16.

resorptive

Hazard class: Class 3 - moderately dangerous

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

14. TRANSPORT INFORMATION

ADR

UN number : UN 1950 Proper shipping name : AEROSOLS

Class : 2

Packing group : Not assigned by regulation

Labels : 2.1
Tunnel restriction code : (D)
Environmentally hazardous : yes

IATA-DGR

UN/ID No. : UN 1950

- RU



OKS 481

 Version
 Revision Date:
 Date of last issue: 23.01.2019
 Print Date:

 2.1
 16.09.2022
 Date of first issue: 07.06.2016
 16.09.2022

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

Labels : Flammable Gas

Packing instruction (cargo : 203

aircraft)

Packing instruction : 203

(passenger aircraft)

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

(pentane, zinc oxide)

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U Marine pollutant : yes

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Federal Law of 10.01.2002 No. 184-FZ "On Technical Regulation".

Federal Law of 10.01.2002 No. 7-FZ "On Environmental Protection".

Federal Law of 21.07.1997 No. 116-FZ (amended on 11.06.2021) "On industrial safety of hazardous production facilities".

Federal Law of 24.06.1998 No. 89-FZ (amended on 02.07.2021) "On production and consumption waste".

Federal Law of 10.01.2002 No. 7-FZ (amended on 02.07.2021) "On environmental protection". Federal Law of 04.05.1999 No. 96-FZ "On the protection of atmospheric air" (as amended on December 8, 2020).

Federal Law of 30.03.1999 No. 52-FZ (amended on 02.07.2021) "On the Sanitary and Epidemiological Well-Being of the Population" (amended and supplemented, entered into force on 31.10.2021).

Federal Law of 27.12.2002 No. 184-FZ (amended on 02.07.2021) "On Technical Regulation" (amended and supplemented, entered into force on 01.09.2021).

TECHNICAL REGULATIONS OF THE CUSTOMS UNION TR CU 030/2012 On requirements for lubricants, oils and special fluids (amended on 03.03.2017).

International Regulations

Montreal Protocol : Not applicable

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

Rotterdam Convention (Prior Informed Consent) : Not applicable

Stockholm Convention (Persistent Organic Pollutants) : Not applicable

16. OTHER INFORMATION

List of data sources used in the preparation of the Safety Data Sheet

GOST 30333-2007. Interstate standard. Safety data sheet for chemical products. Primary requirements.

GOST 12.1.004-91 System of labor safety standards (SSBT). Fire safety. General requirements.

GOST 12.1.007-76 Occupational safety standards system. Noxious substances. Classification and general safety requirements

GOST 12.1.044-89 SSBT. Fire and explosion hazard of substances and materials. Nomenclature of indicators and methods for their determination.

GOST 12.4.021 System of labor safety standards (SSBT). Ventilation systems. General requirements.

GOST 12.4.137-2001 Special footwear with leather uppers for protection against oil, oil products, acids, alkalis, non-toxic and explosive dust. Technical conditions.

GOST 12.4.252-2013 System of labor safety standards (SSBT). Means of individual protection of hands. Gloves. General technical requirements. Test methods.

GOST 14192-96. Interstate standard. Cargo marking. Minsk, 1998.

GOST 19433-88 Dangerous goods. Classification and labeling.

GOST 31340-2013. Interstate standard. Precautionary labeling of chemical products. General requirements.

GOST 32419-2013 Classification of the hazard of chemical products. General requirements.

GOST 32421-2013 Classification of chemical products, the hazard of which is due to physical and chemical properties. Test methods for explosive chemical products.

GOST 32423-2013 Hazard classification of mixed chemical products by their effects on the body. GOST 32424-2013 Classification of the hazard of chemical products by their impact on the

environment. Basic provisions. GOST 32425-2013 Hazard classification of mixed chemical products in terms of environmental impact.

GOST R 53264-2019 Fire fighting equipment. Special protective clothing for firefighters. General technical requirements. Test methods.

GOST R 53265-2019 Fire fighting equipment. Personal protective equipment for the feet of the firefighter. General technical requirements. Test methods.

GOST R 53268-2009 Fire fighting equipment. Fire rescue belts. General technical requirements. Test methods.

GOST R 53269-2019 Fire fighting equipment. Firefighters helmets. General technical requirements. Test methods.

SanPiN 1.2.2353-08 "Carcinogenic factors and basic requirements for the prevention of carcinogenic hazard".

SanPiN 1.2.3685-21 "Hygienic standards and requirements for ensuring the safety and (or) harmlessness to humans of environmental factors" dated 28.01.2021.

SanPiN 2.1.3684-21 "Sanitary and epidemiological requirements for the maintenance of the territories of urban and rural settlements, for water bodies, drinking water and drinking water supply, atmospheric air, soils, living quarters, the operation of industrial, public premises, the organization and implementation of sanitary and anti-epidemic (preventive) measures".



- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

SanPiN 2.2.0.555-96. 2.2. Labor hygiene. Hygienic requirements for working conditions for women. Sanitary rules and regulations.

Carriage of dangerous goods, International maritime dangerous goods (IMDG) code.

Water quality standards for fishery water bodies, including standards for maximum permissible concentrations of harmful substances in the waters of fishery water bodies (approved by order of the Ministry of Agriculture of Russia dated December 13, 2016 No. 552).

Regulations for the carriage of dangerous goods (Appendix 1 and 2) to the Agreement on International Goods Transport by Rail (SMGS), 2009.

Agreement on International Goods Transport by Rail (SMGS).

UN Recommendations on the Transport of Dangerous Goods. Typical rules. Twenty-second revised edition. United Nations, New York and Geneva, 2021.

Montreal Protocol (Ozone Depleting Substances) Stockholm Convention (Persistent Organic Pollutants)

Full text of other abbreviations

Acute Tox. : Acute toxicity

Aquatic Acute : Short-term (acute) aquatic hazard Aquatic Chronic : Long-term (chronic) aquatic hazard

Asp. Tox. : Aspiration hazard
Flam. Gas : Flammable gases
Flam. Liq. : Flammable liquids
Press. Gas : Gases under pressure

STOT SE : Specific target organ toxicity - single exposure 2006/15/EC : Europe. Indicative occupational exposure limit values

RU OEL : SanPiN 1.2.3685-21 Table 2.1, Table 2.8, Table 2.16 & Table

2.17 Maximum permissible concentrations (MPC) in the air of

the working area

2006/15/EC / TWA : Limit Value - eight hours

RU OEL / MPC-STEL : Maximum Permissible Concentration - Short Term Exposure RU OEL / MPC-TWA : Maximum Permissible Concentration - Time Weighted

Average

List 1 : SanPiN 1.2.3685-21 Table 1.1, Table 1.10, & Table 1.11

Maximum permissible concentration (MPC) in the air of urban

and rural settlements

List 5 : Order of the Russian Federal Fisheries Agency "Standards of

maximum permissible concentrations of harmful substances in

fishery water bodies"

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50

- RU



OKS 481

VersionRevision Date:Date of last issue: 23.01.2019Print Date:2.116.09.2022Date of first issue: 07.06.201616.09.2022

- Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.