

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 510

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricant

Recommended restrictions
on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599

E-mail address of person
responsible for the SDS : mcm@oks-germany.com
National contact :

1.4 Emergency telephone number

Emergency telephone
number : +34 91 562 04 20

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2	H225: Highly flammable liquid and vapour.
Skin irritation, Category 2	H315: Causes skin irritation.
Serious eye damage, Category 1	H318: Causes serious eye damage.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Cat-	H411: Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES








OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

egory 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:					
Signal word	:	Danger				
Hazard statements	:	H225 H304	Highly flammable liquid and vapour. May be fatal if swallowed and enters airways.			
		H315 H318	Causes skin irritation. Causes serious eye damage.			
		H336 H411	May cause drowsiness or dizziness. Toxic to aquatic life with long lasting effects.			
Precautionary statements	:	Prevention: P210 P273 P280	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid release to the environment. Wear protective gloves/ eye protection/ face protection.			
		Response: P301 + P310 P305 + P351 + P338 + P310 P331 P370 + P378 P391	IF SWALLOWED: Immediately call a POISON CENTER/doctor. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor. Do NOT induce vomiting. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish. Collect spillage.			
		Storage: P403 + P235	Store in a well-ventilated place. Keep cool.			

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha butan-1-ol

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version
3.2

Revision Date:
17.05.2019

Date of last issue: 14.08.2018
Date of first issue: 09.07.2016

Print Date:
17.05.2019

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Solvent
Molybdenum disulfide
graphite
Silicone resin

Hazardous components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light; Low boiling point hy- drogen treated naph- tha	64742-49-0 265-151-9 649-328-00-1	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	Note P	$\geq 30 - < 50$
Hydrocarbons, C9- C10, n-alkanes, isoal- kanes, cyclics, <2% aromatics	Not Assigned 927-241-2 01-2119471843-32- XXXX	Flam. Liq.3; H226 Asp. Tox.1; H304 Aquatic Chronic3; H412		$\geq 2,5 - < 10$
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32- XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 STOT RE2; H373 Asp. Tox.1; H304	Note C	$\geq 1 - < 10$
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35- XXXX	Flam. Liq.2; H225 Acute Tox.4; H332 STOT RE2; H373 Asp. Tox.1; H304 Aquatic Chronic3; H412		$\geq 2,5 - < 10$
butan-1-ol	71-36-3 200-751-6 603-004-00-6 01-2119484630-38- XXXX	Flam. Liq.3; H226 Acute Tox.4; H302 Skin Irrit.2; H315 Eye Dam.1; H318 STOT SE3; H336 STOT SE3; H335		$\geq 3 - < 10$

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version 3.2 Revision Date: 17.05.2019 Date of last issue: 14.08.2018 Print Date: 17.05.2019
Date of first issue: 09.07.2016

Substances with a workplace exposure limit :				
molybdenum disulphide	1317-33-5 215-263-9			$\geq 10 - < 20$
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	Flam. Liq.3; H226 STOT SE3; H336		$\geq 10 - < 20$
Graphite	7782-42-5 231-955-3			$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.
Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Get medical attention immediately.
- If swallowed : Move the victim to fresh air.
If accidentally swallowed obtain immediate medical attention.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Do NOT induce vomiting.
Rinse mouth with water.
Never give anything by mouth to an unconscious person.
Aspiration hazard if swallowed - can enter lungs and cause damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Skin contact may provoke the following symptoms:
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression
Can be absorbed through skin.
Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire may cause evolution of:
Carbon oxides
Metal oxides
Sulphur oxides

Do not let product enter drains.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only in an area containing explosion proof equipment. Do not use in areas without adequate ventilation. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid exposure - obtain special instructions before use.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Ensure all equipment is electrically grounded before beginning transfer operations.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
Do not enter areas where used or stored until adequately ventilated.
Do not repack.
Do not re-use empty containers.
These safety instructions also apply to empty packaging which may still contain product residues.
Keep container closed when not in use.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
molybdenum di-sulphide	1317-33-5	VLA-ED (inhalable fraction)	10 mg/m ³ (Molybdenum)	ES VLA (2015-02-19)
Further information	The terms soluble and insoluble are understood to refer to the water., Please			

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version
3.2

Revision Date:
17.05.2019

Date of last issue: 14.08.2018
Date of first issue: 09.07.2016

Print Date:
17.05.2019

		refer to UNE EN 481: Workplaces atmospheres. Size fraction definitions for measurement of airborne particles.		
		VLA-ED (respirable fraction)	3 mg/m ³ (Molybdenum)	ES VLA (2015-02-19)
Further information	The terms soluble and insoluble are understood to refer to the water., Please refer to UNE EN 481: Workplaces atmospheres. Size fraction definitions for measurement of airborne particles.			
n-butyl acetate	123-86-4	VLA-ED	150 ppm 724 mg/m ³	ES VLA (2011-03-03)
		VLA-EC	200 ppm 965 mg/m ³	ES VLA (2011-03-03)
xylene	1330-20-7	VLA-ED	50 ppm 221 mg/m ³	ES VLA (2011-03-03)
Further information	Skin, Chemical agent for which a specific Biological Limit Value exists in this document., Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
		VLA-EC	100 ppm 442 mg/m ³	ES VLA (2011-03-03)
Further information	Skin, Chemical agent for which a specific Biological Limit Value exists in this document., Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
		TWA	50 ppm 221 mg/m ³	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m ³	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
ethylbenzene	100-41-4	TWA	100 ppm 442 mg/m ³	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	200 ppm 884 mg/m ³	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		VLA-ED	100 ppm 441 mg/m ³	ES VLA (2015-02-19)
Further information	Skin, Chemical agent for which a specific Biological Limit Value exists in this document., Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
		VLA-EC	200 ppm 884 mg/m ³	ES VLA (2015-02-19)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version 3.2 Revision Date: 17.05.2019 Date of last issue: 14.08.2018 Print Date: 17.05.2019
Date of first issue: 09.07.2016

Further information	Skin, Chemical agent for which a specific Biological Limit Value exists in this document., Chemical agent with an indicative limit value established by the EU. All these chemicals are contained in at least one of the directives of indicative limit values published so far (see Appendix C. Bibliography). Member states shall transpose the limits set in the Directives within a certain time frame. Once adopted, these values have the same validity as the rest of the values adopted by the country.			
butan-1-ol	71-36-3	VLA-EC	50 ppm 154 mg/m ³	ES VLA (2014-01-01)
		VLA-ED	20 ppm 61 mg/m ³	ES VLA (2014-01-01)
Graphite	7782-42-5	VLA-ED (respirable dust fraction)	2 mg/m ³	ES VLA (2017-02-01)
Further information	Please refer to UNE EN 481: Workplaces atmospheres. Size fraction definitions for measurement of airborne particles.			

Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
xylene	1330-20-7	methylhippuric acids: 1.5 g/g creatinine (Urine)	end of shift	ES VLB
		methylhippuric acids: 1 g/g creatinine (Urine)	End of workday	ES VLB
ethylbenzene	100-41-4	sum of mandelic acid and phenylglyoxilic acid: 700 mg/g Creatinine (Urine)	At the end of the work week	ES VLB

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	Workers	Inhalation	Long-term systemic effects	1300 mg/m ³
	Workers	Inhalation	Long-term local effects	840 mg/m ³
	Workers	Inhalation	Acute local effects	1100 mg/m ³
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m ³
	Workers	Inhalation	Acute systemic effects	600 mg/m ³
	Workers	Dermal	Long-term local effects	11 mg/cm ²
xylene	Workers	Inhalation	Long-term exposure, Systemic effects	77 mg/m ³

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version
3.2

Revision Date:
17.05.2019

Date of last issue: 14.08.2018
Date of first issue: 09.07.2016

Print Date:
17.05.2019

	Workers	Inhalation	Short-term exposure, Systemic effects	289 mg/m ³
	Workers	Skin contact	Long-term exposure, Systemic effects	180 mg/kg
	Consumers	Inhalation	Long-term exposure, Systemic effects	14,8 mg/m ³
	Consumers	Inhalation	Short-term exposure, Systemic effects	174 mg/m ³
	Consumers	Ingestion	Long-term exposure, Systemic effects	1,6 mg/kg
ethylbenzene	Workers	Skin contact	Long-term systemic effects	180 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	77 mg/m ³
	Workers	Inhalation	Acute local effects	293 mg/m ³
butan-1-ol	Workers	Inhalation	Long-term local ef- fects	310 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Microbiological Activity in Sewage Treatment Systems	35,6 mg/l
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
	Soil	0,09 mg/kg
xylene	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/l
	Marine sediment	12,46 mg/l
	Soil	2,31 mg/kg
ethylbenzene	Fresh water	0,1 mg/l
	Marine water	0,01 mg/l
	Intermittent use/release	0,1 mg/l
	Microbiological Activity in Sewage Treatment Systems	9,6 mg/l
	Fresh water sediment	13,7 mg/kg
	Marine sediment	1,37 mg/kg
	Soil	2,68 mg/kg
	Oral	20 mg/kg
butan-1-ol	Fresh water	0,082 mg/l
	Marine water	0,008 mg/l
	Intermittent use/release	2,25 mg/l
	Microbiological Activity in Sewage Treatment Systems	2476 mg/l
	Fresh water sediment	0,324 mg/kg dry weight (d.w.)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version 3.2	Revision Date: 17.05.2019	Date of last issue: 14.08.2018 Date of first issue: 09.07.2016	Print Date: 17.05.2019
----------------	------------------------------	---	---------------------------

	Marine sediment	0,032 mg/kg dry weight (d.w.)
	Soil	0,017 mg/kg dry weight (d.w.)

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

Hand protection

Material : Fluorinated rubber
Protective index : Class 1

Remarks : Wear protective gloves. The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:
Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid
Colour : black
Odour : solvent-like
Odour Threshold : No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : 57 °C
(1.013 hPa)

Flash point : < -30,00 °C
Method: DIN 51755, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit : 10,4 %(V)

Lower explosion limit : 0,6 %(V)

Vapour pressure : 149 hPa (20 °C)

Relative vapour density : No data available

Density : 0,98 g/cm³
(20 °C)

Bulk density : No data available

Solubility(ies)

 Water solubility : immiscible

 Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

 Viscosity, dynamic : No data available

 Viscosity, kinematic : < 7 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms: Local irritation, Respiratory disorders, Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Remarks: Harmful in contact with skin.

Symptoms: Redness, Local irritation

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg
Method: OECD Test Guideline 401
GLP: yes

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg
Method: OECD Test Guideline 402
GLP: yes
Assessment: The substance or mixture has no acute dermal toxicity

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Acute oral toxicity : LD50 Oral (Rat): > 5.000 mg/kg

xylene:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

ethylbenzene:

Acute oral toxicity : LD50 (Rat): 3.500 mg/kg

Acute inhalation toxicity : LC50 (Rat): 17,2 mg/l
Exposure time: 4 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): 15.400 mg/kg

butan-1-ol:

Acute oral toxicity : LD50 (Rat): 2.292 mg/kg
Method: OECD Test Guideline 401
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): > 17,76 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 3.430 mg/kg
Method: OECD Test Guideline 402
GLP: yes

molybdenum disulphide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 16.000 mg/kg

n-butyl acetate:

Acute oral toxicity : LD50 (Rat): 10.768 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 21 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: OECD Test Guideline 403
GLP: yes
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): > 17.600 mg/kg

Skin corrosion/irritation

Product:

Remarks: Irritating to skin.

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Species: Rabbit

Assessment: Irritating to skin.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Method: OECD Test Guideline 404
Result: Irritating to skin.
GLP: yes

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Result: Repeated exposure may cause skin dryness or cracking.

xylene:

Species: Rabbit
Assessment: Irritating to skin.
Result: Irritating to skin.

ethylbenzene:

Species: Rabbit
Result: Mild skin irritation

butan-1-ol:

Species: Rabbit
Assessment: Irritating to skin.
Result: Irritating to skin.

molybdenum disulphide:

Assessment: No skin irritation
Result: No skin irritation

n-butyl acetate:

Species: Rabbit
Assessment: No skin irritation
Method: OECD Test Guideline 404
Result: Repeated exposure may cause skin dryness or cracking.

Serious eye damage/eye irritation

Product:

Remarks: Risk of serious damage to eyes.

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Species: Rabbit
Assessment: No eye irritation
Method: OECD Test Guideline 405
Result: No eye irritation
GLP: yes

xylene:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Species: Rabbit
Assessment: Irritating to eyes.
Result: Irritating to eyes.

ethylbenzene:

Species: Rabbit
Assessment: No eye irritation
Result: No eye irritation

butan-1-ol:

Species: Rabbit
Assessment: Risk of serious damage to eyes.
Method: OECD Test Guideline 405
Result: Risk of serious damage to eyes.
GLP: yes

molybdenum disulphide:

Assessment: No eye irritation
Result: No eye irritation

n-butyl acetate:

Species: Rabbit
Assessment: No eye irritation
Method: OECD Test Guideline 405
Result: No eye irritation
GLP: yes

Respiratory or skin sensitisation

Product:

Remarks: This information is not available.

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Test Type: Buehler Test
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.
GLP: yes

xylene:

Species: Mouse
Assessment: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 429
Result: Did not cause sensitisation on laboratory animals.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

ethylbenzene:

Assessment: Does not cause skin sensitisation.
Result: Does not cause skin sensitisation.

butan-1-ol:

Species: Mouse
Assessment: Did not cause sensitisation on laboratory animals.
Method: OECD Test Guideline 429
Result: Did not cause sensitisation on laboratory animals.

molybdenum disulphide:

Assessment: Does not cause skin sensitisation.
Result: Does not cause skin sensitisation.

n-butyl acetate:

Test Type: Maximisation Test
Exposure routes: Dermal
Species: Guinea pig
Assessment: Does not cause skin sensitisation.
Method: OECD Test Guideline 406
Result: Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

xylene:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

ethylbenzene:

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

molybdenum disulphide:

Germ cell mutagenicity- Assessment : Animal testing did not show any mutagenic effects.

n-butyl acetate:

Genotoxicity in vitro : Test Type: Ames test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Species: Salmonella typhimurium
Method: OECD Test Guideline 471
Result: negative

: Test Type: Chromosome aberration test in vitro
Species: Chinese hamster cells
Method: OECD Test Guideline 473
Result: negative

Genotoxicity in vivo : Species: Mouse
Application Route: Oral
Method: OECD Test Guideline 474
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

Carcinogenicity

Product:

Remarks: No data available

Components:

xylene:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

ethylbenzene:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

molybdenum disulphide:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

n-butyl acetate:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Components:

xylene:

Reproductive toxicity - Assessment : No toxicity to reproduction
No toxicity to reproduction

ethylbenzene:

Reproductive toxicity - Assessment : No toxicity to reproduction
No toxicity to reproduction

n-butyl acetate:

Effects on fertility : Test Type: Two-generation study
Species: Rat
Application Route: inhalation (vapour)
General Toxicity - Parent: NOAEC: 750 mg/l
General Toxicity F1: NOAEC: 750 mg/l
General Toxicity F2: NOAEC: 750 mg/l
Method: OECD Test Guideline 416
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Reproductive toxicity - Assessment : No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.
No toxicity to reproduction

STOT - single exposure

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: May cause drowsiness or dizziness.

xylene:

Exposure routes: Inhalation
Target Organs: Respiratory system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

ethylbenzene:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

butan-1-ol:

Exposure routes: Inhalation
Target Organs: Respiratory system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

molybdenum disulphide:

Assessment: The substance or mixture is not classified as specific target organ toxicant, single exposure.

n-butyl acetate:

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

xylene:

Exposure routes: Inhalation
Target Organs: Central nervous system
Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Exposure routes: Ingestion
Target Organs: Liver, Kidney
Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

ethylbenzene:

Exposure routes: Inhalation
Target Organs: hearing organs
Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

butan-1-ol:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

molybdenum disulphide:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

n-butyl acetate:

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version
3.2

Revision Date:
17.05.2019

Date of last issue: 14.08.2018
Date of first issue: 09.07.2016

Print Date:
17.05.2019

Repeated dose toxicity

Product:

Remarks: This information is not available.

Components:

n-butyl acetate:

Species: Rat
NOAEL: 125 mg/kg
Application Route: Oral

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

xylene:

May be fatal if swallowed and enters airways.

ethylbenzene:

May be fatal if swallowed and enters airways.

butan-1-ol:

No aspiration toxicity classification

n-butyl acetate:

No aspiration toxicity classification

Further information

Product:

Remarks: Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Components:

molybdenum disulphide:

Remarks: Information given is based on data on the components and the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

- Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available
- Toxicity to algae : Remarks: No data available
- Toxicity to microorganisms : Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,5 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3,1 mg/l
Exposure time: 72 h
Test Type: static test

Ecotoxicology Assessment

- Short-term (acute) aquatic hazard : Toxic to aquatic life.
- Long-term (chronic) aquatic hazard : Toxic to aquatic life with long lasting effects.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Ecotoxicology Assessment

Long-term (chronic) aquatic hazard : Harmful to aquatic life with long lasting effects.

xylene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,82 mg/l
Exposure time: 48 h
Test Type: flow-through test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2 mg/l
Exposure time: 72 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 157 mg/l
Exposure time: 3 h
Test Type: Respiration inhibition
Method: OECD Test Guideline 209
GLP:

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l
Exposure time: 56 d
Species: Oncorhynchus mykiss (rainbow trout)
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 2,90 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: static test
Method: OECD Test Guideline 211
GLP: yes

ethylbenzene:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 4,2 mg/l
Exposure time: 96 h
Test Type: semi-static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 2,4 mg/l
Exposure time: 48 h
Test Type: static test

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Toxicity to algae : EC50 (Skeletonema costatum (marine diatom)): 4,6 mg/l
Exposure time: 72 h
Test Type: static test

Toxicity to fish (Chronic toxicity) : NOEC: 3,3 mg/l
Exposure time: 96 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 0,96 mg/l
Exposure time: 7 d
Species: Ceriodaphnia dubia (water flea)
Test Type: semi-static test

butan-1-ol:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 1.376 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.328 mg/l
Exposure time: 48 h
Test Type: static test
Method: OECD Test Guideline 202
GLP: yes

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 225 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 201
GLP: yes

Toxicity to microorganisms : EC10 (Pseudomonas putida): 2.476 mg/l
Exposure time: 17 h
Test Type: static test
Method: DIN 38 412 Part 8
GLP:

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 4,1 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: semi-static test
Method: OECD Test Guideline 211
GLP: yes

molybdenum disulphide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h

n-butyl acetate:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l
Exposure time: 96 h
Test Type: flow-through test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 44 mg/l
Exposure time: 48 h
Test Type: static test

Toxicity to algae : EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l
Exposure time: 72 h
Test Type: static test

Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l
Exposure time: 40 h
Test Type: Growth inhibition

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: Reproduction Test
GLP: yes

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: 90,35 %
Exposure time: 28 d

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Biodegradability : Result: rapidly biodegradable

xylene:

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Biodegradability : Result: Readily biodegradable.

ethylbenzene:

Biodegradability : Result: Readily biodegradable.

butan-1-ol:

Biodegradability : Test Type: aerobic
Inoculum: activated sludge
Result: rapidly biodegradable
Biodegradation: > 92 %
Exposure time: 28 d

n-butyl acetate:

Biodegradability : Test Type: Primary biodegradation
Result: rapidly biodegradable
Biodegradation: 83 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:

Partition coefficient: n-octanol/water : log Pow: 3,4 - 5,2

Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Bioaccumulation : Remarks: No data available

Partition coefficient: n-octanol/water : Remarks: No data available

xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

ethylbenzene:

Bioaccumulation : Bioconcentration factor (BCF): 1

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Partition coefficient: n-octanol/water : log Pow: 3,6 (20 °C)

butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)
pH: 7
Method: OECD Test Guideline 117
GLP: yes

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

Components:

xylene:

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

ethylbenzene:

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

n-butyl acetate:

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

12.6 Other adverse effects

Product:

Additional ecological information : Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

The following Waste Codes are only suggestions:

SECTION 14: Transport information

14.1 UN number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT
IMDG : PAINT
(naphtha (petroleum), hydrotreated light)
IATA : Paint

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

ADR

Packing group : II
Classification Code : F1
Hazard Identification Number : 33
Labels : 3
Tunnel restriction code : (D/E)

IMDG

Packing group : II
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)

Packing instruction (cargo aircraft) : 364
Packing instruction (LQ) : Y341
Packing group : II
Labels : Class 3 - Flammable liquids

IATA (Passenger)

Packing instruction (passenger aircraft) : 353
Packing instruction (LQ) : Y341
Packing group : II
Labels : Class 3 - Flammable liquids

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

No special precautions required.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : See Annex XVII to Regulation (EC) no 1907/2006 for Conditions of restriction

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha (29, 28)

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P5c	FLAMMABLE LIQUIDS	5.000 t	50.000 t
E2	ENVIRONMENTAL HAZARDS	200 t	500 t
34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t

P5c

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 66,32 %
Volatile CMR compounds: 30 %

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure if inhaled.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

Note C	: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
Note P	: The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

ply. This note applies only to certain complex oil-derived substances in Part 3.

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Dam. 1	H318
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Based on product data or assessment
Calculation method

This safety data sheet applies only to products originally packed and labelled by OKS Spezialschmierstoffe. The information contained therein may not be reproduced or modified without the express written permission of OKS Spezialschmierstoffe. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of our safety data sheets (e.g. as a document for download from the Internet) is not permitted without the

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - ES



OKS 510

Version	Revision Date:	Date of last issue: 14.08.2018	Print Date:
3.2	17.05.2019	Date of first issue: 09.07.2016	17.05.2019

express written consent of OKS Spezialschmierstoffe. OKS Spezialschmierstoffe provides its customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. OKS Spezialschmierstoffe provides no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorised trading partner of OKS Spezialschmierstoffe.