

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 530

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-
stance/Mixture : Lubricant

Recommended restrictions
on use : Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599

E-mail address of person
responsible for the SDS : mcm@oks-germany.com
National contact :

1.4 Emergency telephone number

Emergency telephone num-
ber : +49 8142 3051 517
Warszawa: +48 22 619 66 54

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Skin sensitisation, Category 1

H317: May cause an allergic skin reaction.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P261 Avoid breathing vapours.
P280 Wear protective gloves/ eye protection/ face protection.

Response:
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

Storage:
P403 + P235 Store in a well-ventilated place. Keep cool.

Hazardous components which must be listed on the label:

2-methylisothiazol-3(2H)-one

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Aqueous solution
graphite
Molybdenum disulfide
organic binding agent

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
isopropanol	67-63-0 200-661-7	Flam. Liq.2; H225 Eye Irrit.2; H319 Eye Irrit.2A; H319		>= 1 - < 10

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version
2.0

Revision Date:
05.05.2020

Date of last issue: 13.06.2019
Date of first issue: 09.07.2016

Print Date:
05.05.2020

	603-117-00-0 02-2119457558-25-XXXX	STOT SE3; H336		
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36-XXXX	Acute Tox.4; H302 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319		$\geq 1 - < 10$
dodecylguanidine monohydrochloride	13590-97-1 237-030-0	Acute Tox.4; H302 Acute Tox.2; H330 Skin Corr.1B; H314 Eye Dam.1; H318 Aquatic Acute1; H400	M-Factor: 10/	$\geq 0,0025 - < 0,025$
2-methylisothiazol-3(2H)-one	2682-20-4 220-239-6 613-326-00-9	Acute Tox.3; H301 Acute Tox.2; H330 Acute Tox.3; H311 Skin Corr.1B; H314 Eye Dam.1; H318 Skin Sens.1A; H317 STOT SE3; H335 Aquatic Acute1; H400 Aquatic Chronic1; H410	$\geq 0,0015\%$ Skin Sens.1A, H317 M-Factor: 10/1	$\geq 0,0025 - < 0,025$
Substances with a workplace exposure limit :				
Graphite	7782-42-5 231-955-3 01-2119486977-12-XXXX	Not classified		$\geq 10 - < 20$
molybdenum disulfide	1317-33-5 215-263-9	Not classified		$\geq 1 - < 10$

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

- advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
Seek medical advice.
- If swallowed : Move the victim to fresh air.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
Do NOT induce vomiting.
Rinse mouth with water.
Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Allergic appearance

- Risks : Can be absorbed through skin.
May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : The first aid procedure should be established in consultation with the doctor responsible for industrial medicine.
Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

- Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
- Unsuitable extinguishing media : High volume water jet

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Fire may cause evolution of:
Carbon oxides
Metal oxides
Nitrogen oxides (NO_x)
Sulphur oxides

Do not let product enter drains.
Container may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.
Use personal protective equipment.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Refer to protective measures listed in sections 7 and 8.

6.2 Environmental precautions

Environmental precautions : Try to prevent the material from entering drains or water courses.
Prevent further leakage or spillage if safe to do so.
Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Non-sparking tools should be used.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

- Advice on safe handling : Use only in an area containing explosion proof equipment.
Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Ensure all equipment is electrically grounded before beginning transfer operations.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
Do not enter areas where used or stored until adequately ventilated.
Do not repack.
Do not re-use empty containers.
These safety instructions also apply to empty packaging which may still contain product residues.
Keep container closed when not in use.
- Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place. Do not store together with oxidizing and self-igniting products. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version 2.0 Revision Date: 05.05.2020 Date of last issue: 13.06.2019 Print Date: 05.05.2020
Date of first issue: 09.07.2016

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Graphite	7782-42-5	NDS (inhalable fraction)	4 mg/m ³	PL OEL (2018-07-07)
		NDS (respirable fraction)	1 mg/m ³	PL OEL (2018-07-07)
isopropanol	67-63-0	NDS	900 mg/m ³	PL OEL (2018-07-07)
Further information	Skin			
		NDSch	1.200 mg/m ³	PL OEL (2018-07-07)
Further information	Skin			
molybdenum di-sulphide	1317-33-5	NDS	4 mg/m ³ (Molybdenum)	PL OEL (2018-07-07)
		NDSch	10 mg/m ³ (Molybdenum)	PL OEL (2018-07-07)
2-butoxyethanol	111-76-2	TWA	20 ppm 98 mg/m ³	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	50 ppm 246 mg/m ³	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		NDS	98 mg/m ³	PL OEL (2018-07-07)
Further information	Skin			
		NDSch	200 mg/m ³	PL OEL (2018-07-07)
Further information	Skin			

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
2-butoxyethanol	Workers	Inhalation	Long-term systemic effects	98 mg/m ³
	Workers	Inhalation	Acute systemic effects	1091 mg/m ³
	Workers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	89 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version
2.0

Revision Date:
05.05.2020

Date of last issue: 13.06.2019
Date of first issue: 09.07.2016

Print Date:
05.05.2020

			fects	bw/day
	Workers	Inhalation	Acute local effects	246 mg/m ³
2,2',2''-nitriлотриethanol	Workers	Dermal	Long-term systemic effects	6,3 mg/kg
	Workers	Inhalation	Long-term systemic effects	5 mg/m ³
	Workers	Inhalation	Long-term local effects	5 mg/m ³

Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
2-butoxyethanol	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Soil	2,33 mg/kg
2,2',2''-nitriлотриethanol	Oral	0,02 mg/kg
	Soil	0,151 mg/kg
	Microbiological Activity in Sewage Treatment Systems	10 mg/l
	Fresh water	0,32 mg/l
	Marine water	0,032 mg/l
	Fresh water sediment	1,7 mg/kg
	Marine sediment	0,17 mg/kg

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.
Maintain air concentrations below occupational exposure standards.

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : liquid

Colour : black

Odour : solvent-like

Odour Threshold : No data available

pH : 9 (20 °C)
Concentration: 100 %

Melting point/range : No data available

Boiling point/boiling range : 82 °C
(1.013 hPa)

Flash point : 37 °C
Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Not applicable

Upper explosion limit / Upper flammability limit : No data available

Lower explosion limit / Lower flammability limit : No data available

Vapour pressure : 35 hPa (20 °C)

Relative vapour density : No data available

Density : 1,10 g/cm³
(20 °C)

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

Bulk density : No data available

Solubility(ies)
Water solubility : soluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : 129 mm²/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

9.2 Other information

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg
Method: Calculation method

Symptoms: Redness, Local irritation

Components:

isopropanol:

Acute oral toxicity : LD50 Oral (Rat): 5.840 mg/kg

2-butoxyethanol:

Acute oral toxicity : LD50 (Rat): 1.746 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

dodecylguanidine monohydrochloride:

Acute oral toxicity : LD50 (Rat): Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): Test atmosphere: dust/mist
Assessment: The component/mixture is highly toxic after short term inhalation.

2-methylisothiazol-3(2H)-one:

Acute oral toxicity : LD50 Oral (Rat): > 50 mg/kg

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

Symptoms: Pain, Stomach/intestinal disorders

Remarks: Toxic if swallowed.

Acute inhalation toxicity : LC50 (Rat): 0,11 mg/l
Exposure time: 4 h
Test atmosphere: dust/mist
Method: OECD Test Guideline 403

Remarks: Risk of delayed pulmonary oedema.
Effects of breathing high concentrations of vapour may include:
Very toxic by inhalation.
Irritating to respiratory system.

Symptoms: Local irritation, Respiratory disorders, Inhalation may provoke the following symptoms:

Acute dermal toxicity : LD50 Dermal (Rabbit, female): 326 mg/kg

Remarks: Very toxic in contact with skin.

Symptoms: Blistering, Redness, Local irritation

molybdenum disulphide:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg

Acute dermal toxicity : LD50 (Rat): > 16.000 mg/kg

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Components:

2-butoxyethanol:

Species : Rabbit
Assessment : Irritating to skin.
Result : Irritating to skin.

dodecylguanidine monohydrochloride:

Assessment : Causes burns.
Result : Causes burns.

2-methylisothiazol-3(2H)-one:

Species : Rabbit
Result : Causes burns.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

Remarks : Causes skin burns.

molybdenum disulphide:

Assessment : No skin irritation
Result : No skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Irritating to eyes.

Components:

isopropanol:

Result : Irritating to eyes.

2-butoxyethanol:

Species : Rabbit
Assessment : Irritating to eyes.
Result : Irritating to eyes.

2-methylisothiazol-3(2H)-one:

Remarks : Acute eye irritation/corrosion
Causes eye burns.

molybdenum disulphide:

Assessment : No eye irritation
Result : No eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

2-butoxyethanol:

Test Type : Maximisation Test
Species : Guinea pig
Assessment : Did not cause sensitisation on laboratory animals.
Result : Did not cause sensitisation on laboratory animals.

2-methylisothiazol-3(2H)-one:

Species : Rabbit
Assessment : May cause sensitisation by skin contact.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

molybdenum disulphide:

Assessment : Does not cause skin sensitisation.
Result : Does not cause skin sensitisation.

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

2-butoxyethanol:

Germ cell mutagenicity- Assessment : In vitro tests did not show mutagenic effects

molybdenum disulphide:

Germ cell mutagenicity- Assessment : Animal testing did not show any mutagenic effects.

Carcinogenicity

Product:

Remarks : No data available

Components:

2-butoxyethanol:

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

molybdenum disulphide:

Carcinogenicity - Assessment : No evidence of carcinogenicity in animal studies.

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Components:

2-butoxyethanol:

Reproductive toxicity - Assessment : No toxicity to reproduction

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

Further information

Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

Components:

2-methylisothiazol-3(2H)-one:

Remarks : Ingestion causes burns of the upper digestive and respiratory tracts.

molybdenum disulphide:

Remarks : Information given is based on data on the components and the toxicology of similar products.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

2-butoxyethanol:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 1.474 mg/l
Exposure time: 96 h
Test Type: static test
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.550 mg/l
Exposure time: 48 h
Test Type: Immobilization
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.840 mg/l

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version 2.0	Revision Date: 05.05.2020	Date of last issue: 13.06.2019 Date of first issue: 09.07.2016	Print Date: 05.05.2020
----------------	------------------------------	---	---------------------------

Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l
Exposure time: 21 d
Species: Danio rerio (zebra fish)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 mg/l
Exposure time: 21 d
Species: Daphnia magna (Water flea)
Test Type: Reproduction Test
Method: OECD Test Guideline 211

dodecylguanidine monohydrochloride:

M-Factor (Acute aquatic toxicity) : 10

Ecotoxicology Assessment

Acute aquatic toxicity : Very toxic to aquatic life.

Chronic aquatic toxicity : This product has no known ecotoxicological effects.

2-methylisothiazol-3(2H)-one:

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 0,85 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Selenastrum capricornutum (green algae)): 0,072 mg/l
Exposure time: 72 h

M-Factor (Acute aquatic toxicity) : 10

: 10

M-Factor (Chronic aquatic toxicity) : 1

molybdenum disulphide:

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 100 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l
Exposure time: 72 h

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Components:

isopropanol:

Biodegradability : Result: Readily biodegradable.

2-butoxyethanol:

Biodegradability : Test Type: aerobic
Result: rapidly biodegradable
Biodegradation: 90 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2-methylisothiazol-3(2H)-one:

Biodegradability : Result: Readily biodegradable.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

Components:

isopropanol:

Bioaccumulation : Remarks: Bioaccumulation is unlikely.

Partition coefficient: n-octanol/water : log Pow: 0,05

2-butoxyethanol:

Bioaccumulation : Bioconcentration factor (BCF): 2,5

Partition coefficient: n-octanol/water : log Pow: 0,81 (25 °C)
Method: OECD Test Guideline 107

2-methylisothiazol-3(2H)-one:

Partition coefficient: n-octanol/water : log Pow: -0,486

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Other adverse effects

Product:

Additional ecological information : No information on ecology is available.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.
Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Dispose of waste product or used containers according to local regulations.

The following Waste Codes are only suggestions:

Waste Code : unused product
12 01 09*, machining emulsions and solutions free of halogens

uncleaned packagings
15 01 10, packaging containing residues of or contaminated

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

by hazardous substances

SECTION 14: Transport information

14.1 UN number

ADR : UN 1263
IMDG : UN 1263
IATA : UN 1263

14.2 UN proper shipping name

ADR : PAINT
IMDG : PAINT
IATA : Paint

14.3 Transport hazard class(es)

ADR : 3
IMDG : 3
IATA : 3

14.4 Packing group

ADR
Packing group : III
Classification Code : F1
Hazard Identification Number : 30
Labels : 3
Tunnel restriction code : (D/E)

IMDG
Packing group : III
Labels : 3
EmS Code : F-E, S-E

IATA (Cargo)
Packing instruction (cargo aircraft) : 366
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

IATA (Passenger)
Packing instruction (passenger aircraft) : 355
Packing instruction (LQ) : Y344
Packing group : III
Labels : Flammable Liquids

14.5 Environmental hazards

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

IATA (Passenger)

Environmentally hazardous : no

IATA (Cargo)

Environmentally hazardous : no

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P5c FLAMMABLE LIQUIDS

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)
Volatile organic compounds (VOC) content: 11,63 %

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

Act of 25 February 2011 on the Chemical Substances and Their Mixtures (consolidated text Dz. U. 2015, item 1203).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 (Official Journal of the European Union L 353 from 31.12.2008) with further adaptation to technical progress (ATP 1-7).

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (Official Journal of the European Union L 396 from 30.12.2006, as amended).

Commission Regulation (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH)

Ordinance of the Minister of Health of 10 August 2012 concerning the criteria and procedure of classification of chemical substances and their mixtures (consolidated text Dz. U. of 2015., pos. 208).

Ordinance of the Minister of Economy, Labour and Social Policy of 21st December 2005 concerning the basic requirements for personal protective equipment (Dz. U. Nr. 259, item 2173).

Ordinance of the Minister of Labour and Social Policy of 12 June 2018 concerning the highest allowable concentrations and levels of the agents harmful for health in the workplace (Dz.U 2018 pos 1286).

Ordinance of the Minister of Health of 2nd February 2011 concerning tests and measurement of agents harmful for health in the workplace (Dz. U. Nr. 33, item 166).

Ordinance of the Minister of Health of 30th December 2004 on the health and safety of workers related to chemical agents at work (Dz. U. from 2005, Nr. 11, item 86, as amended).

Act of 14 December 2012. on Waste (Journal of Laws of 2013. pos. 21, as amended).

Act of 13 June 2013. On packaging and packaging waste Journal. U. of 2013. Item. 888, as amended).

Ordinance of the Minister of Environment of 9th December 2014 on Waste Catalog (Dz. U. 2014 item 1923).

Ordinance of the Minister of Environment on the requirements for carrying out the process of thermal treatment of waste and how to deal with waste produced in the process. (Dz. U. of 2016., Pos. 108)

Act of 19 August 2011 on transport of dangerous goods (Dz. U. Nr. 227, item 1367, as amended).

Government Statement of 26 July 2005 on enforcing of changes Annexes A and B of European Agreement concerning international transport of dangerous goods by road (ADR) (Dz. U. Nr.

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

178, item 1481, as amended).

Ordinance of the Minister of Health of 20th April 2012 concerning labeling of containers of dangerous substances and dangerous mixtures and some mixtures ((consolidated text) Dz. U. z 2015 nr. 0 poz. 450).

Ordinance of the Minister of Health of 11th June 2012 concerning categories of dangerous substances and dangerous mixtures for which containers must be fitted with child-resistant fastenings and a tactile warning of danger (Dz. U. from 2012, item 688 as amended).

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H225	: Highly flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H311	: Toxic in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

2000/39/EC	: Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
PL OEL	: Poland. Occupational exposure limits for airborne toxic substances
2000/39/EC / TWA	: Limit Value - eight hours
2000/39/EC / STEL	: Short term exposure limit
PL OEL / NDS	: Maximal Admissible Concentration
PL OEL / NDSch	: Maximal Admissible Temporary Concentration

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture:

Flam. Liq. 3	H226
Eye Irrit. 2	H319

Classification procedure:

Based on product data or assessment
Calculation method

Skin Sens. 1	H317	Calculation method
---------------------	-------------	---------------------------

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean

SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - PL



OKS 530

Version	Revision Date:	Date of last issue: 13.06.2019	Print Date:
2.0	05.05.2020	Date of first issue: 09.07.2016	05.05.2020

that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.