

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : OKS 570

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Lubricant

Recommended restrictions : Restricted to professional users.  
on use

### 1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialechmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599  
info@oks-germany.com

E-mail address of person : mcm@oks-germany.com  
responsible for the SDS Material Compliance Management

National contact :

### 1.4 Emergency telephone number

Emergency telephone num- : +49 8142 3051 517  
ber

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Skin irritation, Category 2 H315: Causes skin irritation.

Eye irritation, Category 2 H319: Causes serious eye irritation.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.  
posure, Category 3, Central nervous  
system

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)







## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 2	H411: Toxic to aquatic life with long lasting effects.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :    

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P273 Avoid release to the environment.  
**Response:**  
P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish.  
P391 Collect spillage.  
**Storage:**  
P403 + P235 Store in a well-ventilated place. Keep cool.

### Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

butanone

acetone

xylene

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Solvent  
Silicone resin  
PTFE

#### Components

Chemical name	CAS-No. EC-No.  Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	921-024-6  01-2119475514-35-XXXX	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411		>= 30 - < 50
butanone	78-93-3 201-159-0  606-002-00-3 01-2119457290-43-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 10 - < 20
acetone	67-64-1 200-662-2  606-001-00-8 01-2119471330-49-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 1 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version 1.4      Revision Date: 11.07.2022      Date of last issue: 12.11.2021      Print Date: 11.07.2022  
Date of first issue: 09.07.2016

ethyl acetate	141-78-6 205-500-4  607-022-00-5 01-21119475103-46-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 1 - < 10
xylene	1330-20-7 215-535-7  601-022-00-9 01-2119488216-32-XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 STOT RE2; H373 Asp. Tox.1; H304	Note C	>= 1 - < 10
methanol	67-56-1 200-659-6  603-001-00-X	Flam. Liq.2; H225 Acute Tox.3; H301 Acute Tox.2; H330 Acute Tox.3; H311 STOT SE1; H370	>= 10 % STOT SE1, H370  3 - < 10 % STOT SE2, H371  **	>= 0,1 - < 1
Substances with a workplace exposure limit :				
Ethylene, tetrafluoro-, polymer	9002-84-0 618-337-2	Not classified		>= 1 - < 10

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.

In case of skin contact : Take off all contaminated clothing immediately.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.  
Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
Seek medical advice.

If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Never give anything by mouth to an unconscious person.  
Aspiration hazard if swallowed - can enter lungs and cause damage.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression  
Can be absorbed through skin.  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not let product enter drains.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides  
Halogenated compounds  
Metal oxides

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.  
Cool containers/tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Remove all sources of ignition.  
Do not breathe vapours or spray mist.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Refer to protective measures listed in sections 7 and 8.

### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.  
Prevent further leakage or spillage if safe to do so.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Non-sparking tools should be used.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Use only in an area containing explosion proof equipment.  
Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Ensure all equipment is electrically grounded before beginning transfer operations.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
Do not enter areas where used or stored until adequately ventilated.  
Do not repack.  
Do not re-use empty containers.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Keep container closed when not in use.
- Advice on protection against fire and explosion : Keep away from heat and sources of ignition.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.
- Storage class (TRGS 510) : 3, Flammable liquids

### 7.3 Specific end use(s)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version 1.4      Revision Date: 11.07.2022      Date of last issue: 12.11.2021      Print Date: 11.07.2022  
Date of first issue: 09.07.2016

Specific use(s) : Specific instructions for handling, not required.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
butanone	78-93-3	TWA	200 ppm 600 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
	Further information: Indicative			
		STEL	300 ppm 900 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
	Further information: Indicative			
		AGW	200 ppm 600 mg/m <sup>3</sup>	DE TRGS 900 (2010-08-04)
	Peak-limit: excursion factor (category): 1;(I)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
acetone	67-64-1	TWA	500 ppm 1.210 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
	Further information: Indicative			
		AGW	500 ppm 1.200 mg/m <sup>3</sup>	DE TRGS 900 (2015-03-02)
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
Ethylene, tetrafluoro-, polymer	9002-84-0	AGW (Inhalable fraction)	10 mg/m <sup>3</sup>	DE TRGS 900 (2020-03-30)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		AGW (Alveolate fraction)	1,25 mg/m <sup>3</sup>	DE TRGS 900 (2020-03-30)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
ethyl acetate	141-78-6	AGW	200 ppm 730 mg/m <sup>3</sup>	DE TRGS 900 (2017-06-08)
	Peak-limit: excursion factor (category): 2;(I)			
	Further information: When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			
		STEL	400 ppm	2017/164/EU



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version 1.4      Revision Date: 11.07.2022      Date of last issue: 12.11.2021      Date of first issue: 09.07.2016      Print Date: 11.07.2022

			1.468 mg/m3	(2017-02-01)
	Further information: Indicative			
		TWA	200 ppm 734 mg/m3	2017/164/EU (2017-02-01)
	Further information: Indicative			
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	2000/39/EC (2000-06-16)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC (2000-06-16)
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			
		AGW	50 ppm 220 mg/m3	DE TRGS 900 (2020-10-02)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption			
methanol	67-56-1	TWA	200 ppm 260 mg/m3	2006/15/EC (2006-02-09)
	Further information: Indicative, Identifies the possibility of significant uptake through the skin			
		AGW	100 ppm 130 mg/m3	DE TRGS 900 (2020-03-30)
	Peak-limit: excursion factor (category): 2;(II)			
	Further information: Skin absorption, When there is compliance with the OEL and biological tolerance values, there is no risk of harming the unborn child			

### Biological occupational exposure limits

Substance name	CAS-No.	Control parameters	Sampling time	Basis
butanone	78-93-3	2-butanone: 2 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2015-11-06)
acetone	67-64-1	Acetone: 80 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2004-08-01)
xylene	1330-20-7	methylhippuric acid (all isomers): 2.000 mg/l (Urine)	Immediately after exposure or after working hours	TRGS 903 (2021-01-13)
methanol	67-56-1	Methanol: 15 mg/l (Urine)	In case of long-term exposure: after more than one shift, Immediately after exposure or after working hours	TRGS 903 (2020-03-13)

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
----------------	---------	-----------------	--------------------------	-------

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version 1.4      Revision Date: 11.07.2022      Date of last issue: 12.11.2021  
Date of first issue: 09.07.2016

Print Date:  
11.07.2022

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Workers	Skin contact	Long-term systemic effects	773 mg/kg bw/day
	Workers	Inhalation	Long-term systemic effects	2035 mg/m <sup>3</sup>
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
xylene	Workers	Inhalation	Long-term exposure, Systemic effects	77 mg/m <sup>3</sup>
	Workers	Inhalation	Short-term exposure, Systemic effects	289 mg/m <sup>3</sup>
	Workers	Skin contact	Long-term exposure, Systemic effects	180 mg/kg
	Consumers	Inhalation	Long-term exposure, Systemic effects	14,8 mg/m <sup>3</sup>
	Consumers	Inhalation	Short-term exposure, Systemic effects	174 mg/m <sup>3</sup>
	Consumers	Ingestion	Long-term exposure, Systemic effects	1,6 mg/kg

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
butanone	Fresh water	55,8 mg/l
	Marine water	55,8 mg/l
	Intermittent use/release	55,8 mg/l
	Sewage treatment plant	709 mg/l
	Fresh water sediment	284,7 mg/kg
	Marine sediment	284,7 mg/kg
xylene	Soil	22,5 mg/kg
	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/l
	Marine sediment	12,46 mg/l
	Soil	2,31 mg/kg

## 8.2 Exposure controls

### Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

Eye protection : Safety glasses with side-shields

### Hand protection

Material : Fluorinated rubber  
Break through time : > 10 min  
Protective index : Class 1

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

- Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.  
The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
- Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
- Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
- Filter type : Type A (A)
- Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Colour : white
- Odour : solvent-like
- Odour Threshold : No data available
- Melting point/range : No data available
- Boiling point/boiling range : 71,5 °C (1.013 hPa)
- Flammability (solid, gas) : Not applicable
- Upper explosion limit / Upper flammability limit : 11,5 %(V)
- Lower explosion limit / Lower flammability limit : 1,0 %(V)
- Flash point : -19,00 °C  
Method: DIN 51755, closed cup

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Auto-ignition temperature : No data available

Decomposition temperature : No data available

pH : Not applicable  
substance/mixture is non-polar/aprotic

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 6,9 mm<sup>2</sup>/s (40 °C)

Solubility(ies)

Water solubility : immiscible

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Vapour pressure : 21,1 hPa (20 °C)

Relative density : 0,83 (20 °C)  
Reference substance: Water  
The value is calculated

Density : 0,83 g/cm<sup>3</sup>  
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Evaporation rate : No data available

Sublimation point : No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

### SECTION 10: Stability and reactivity

#### 10.1 Reactivity

No hazards to be specially mentioned.

#### 10.2 Chemical stability

Stable under normal conditions.

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

#### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.

#### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

#### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

##### Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute toxicity estimate: > 2.000 mg/kg

Method: Calculation method

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:,  
Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central  
nervous system depression

Acute toxicity estimate: > 20 mg/l

Exposure time: 4 h

Test atmosphere: vapour

Method: Calculation method

Acute dermal toxicity : Symptoms: Redness, Local irritation

Acute toxicity estimate: > 2.000 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version 1.4	Revision Date: 11.07.2022	Date of last issue: 12.11.2021 Date of first issue: 09.07.2016	Print Date: 11.07.2022
----------------	------------------------------	---	---------------------------

Method: Calculation method

### Components:

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

- Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg  
Assessment: The substance or mixture has no acute oral toxicity
- Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity
- Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg  
Assessment: The substance or mixture has no acute dermal toxicity

#### **butanone:**

- Acute oral toxicity : LD50 (Rat): 2.193 mg/kg  
Method: OECD Test Guideline 423  
GLP: yes
- Acute inhalation toxicity : LC50 (Rat): 34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour
- Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

#### **acetone:**

- Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

#### **ethyl acetate:**

- Acute oral toxicity : LD50 (Rat): 5.620 mg/kg
- Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

#### **xylene:**

- Acute oral toxicity : LD50 (Rat): 4.300 mg/kg
- Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.
- Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

#### **methanol:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

- Acute oral toxicity : Assessment: The component/mixture is toxic after single ingestion.  
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.
- Acute inhalation toxicity : Assessment: The component/mixture is highly toxic after short term inhalation.  
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.
- Acute dermal toxicity : Assessment: The component/mixture is toxic after single contact with skin.  
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 1.

### Ethylene, tetrafluoro-, polymer:

- Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

### Skin corrosion/irritation

#### Product:

- Remarks : Irritating to skin.

#### Components:

##### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

- Species : Rabbit  
Assessment : Irritating to skin.  
Method : OECD Test Guideline 404  
Result : Irritating to skin.

##### butanone:

- Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation

- Result : Repeated exposure may cause skin dryness or cracking.

##### acetone:

- Result : Repeated exposure may cause skin dryness or cracking.

##### ethyl acetate:

- Species : Rabbit  
Result : Mild skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Result : Repeated exposure may cause skin dryness or cracking.

### **xylene:**

Species : Rabbit  
Assessment : Irritating to skin.  
Result : Irritating to skin.

### **Ethylene, tetrafluoro-, polymer:**

Species : Rabbit  
Assessment : No skin irritation  
Result : No skin irritation

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks : Irritating to eyes.

#### **Components:**

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Assessment : No eye irritation  
Result : No eye irritation

##### **butanone:**

Species : Rabbit  
Assessment : Irritating to eyes.  
Method : OECD Test Guideline 405  
Result : Irritating to eyes.

##### **acetone:**

Species : Rabbit  
Result : Eye irritation

##### **ethyl acetate:**

Assessment : Irritating to eyes.  
Result : Irritating to eyes.

##### **xylene:**

Species : Rabbit  
Assessment : Irritating to eyes.  
Result : Irritating to eyes.

##### **Ethylene, tetrafluoro-, polymer:**

Species : Rabbit



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Assessment : No eye irritation  
Result : No eye irritation

### Respiratory or skin sensitisation

#### Product:

Remarks : This information is not available.

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Did not cause sensitisation on laboratory animals.

##### **butanone:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

##### **ethyl acetate:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

##### **xylene:**

Species : Mouse  
Assessment : Did not cause sensitisation on laboratory animals.  
Method : OECD Test Guideline 429  
Result : Did not cause sensitisation on laboratory animals.

##### **Ethylene, tetrafluoro-, polymer:**

Assessment : Did not cause sensitisation on laboratory animals.  
Result : Did not cause sensitisation on laboratory animals.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Test system: Rodent cell line  
Method: OECD Test Guideline 473  
Result: negative

##### **butanone:**

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

##### **xylene:**

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

### Carcinogenicity

#### Product:

Remarks : No data available

#### Components:

##### **butanone:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

##### **xylene:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

##### **Ethylene, tetrafluoro-, polymer:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop- : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version 1.4	Revision Date: 11.07.2022	Date of last issue: 12.11.2021 Date of first issue: 09.07.2016	Print Date: 11.07.2022
----------------	------------------------------	---	---------------------------

ment

### Components:

#### **butanone:**

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction  
- Teratogenicity -  
No effects on or via lactation

#### **xylene:**

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction  
- Teratogenicity -  
No toxicity to reproduction

### **STOT - single exposure**

### Components:

#### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

#### **butanone:**

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.,  
May cause drowsiness or dizziness.

#### **acetone:**

Exposure routes : Inhalation  
Assessment : May cause drowsiness or dizziness.

#### **ethyl acetate:**

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

#### **xylene:**

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

### methanol:

Exposure routes : Ingestion  
Assessment : Causes damage to organs.

Exposure routes : Skin contact  
Assessment : Causes damage to organs.

Exposure routes : inhalation (vapour)  
Target Organs : Nervous system  
Assessment : Causes damage to organs.

### Ethylene, tetrafluoro-, polymer:

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

### STOT - repeated exposure

#### Components:

#### Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)  
Assessment : No significant health effects observed in animals at concentrations of 1 mg/l/6h/d or less.

### butanone:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### ethyl acetate:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### xylene:

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Exposure routes : Ingestion  
Target Organs : Liver, Kidney  
Assessment : The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

### Ethylene, tetrafluoro-, polymer:

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

### Repeated dose toxicity

**Product:**

Remarks : This information is not available.

### Aspiration toxicity

**Product:**

May be fatal if swallowed and enters airways.

**Components:**

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

May be fatal if swallowed and enters airways.

**butanone:**

No aspiration toxicity classification

**xylene:**

May be fatal if swallowed and enters airways.

**Ethylene, tetrafluoro-, polymer:**

No aspiration toxicity classification

## 11.2 Information on other hazards

### Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

**Product:**

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

- Toxicity to fish : Remarks: Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available
- Toxicity to algae/aquatic plants : Remarks: No data available
- Toxicity to microorganisms : Remarks: No data available

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203  
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l  
Exposure time: 48 h  
Method: OECD Test Guideline 202  
GLP: yes
- Toxicity to algae/aquatic plants : EbC50 (Pseudokirchneriella subcapitata (green algae)): 26 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

#### **Ecotoxicology Assessment**

- Acute aquatic toxicity : Toxic to aquatic life.
- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

#### **butanone:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l  
Exposure time: 96 h  
Test Type: static test
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l  
Exposure time: 48 h  
Test Type: static test
- Toxicity to algae/aquatic : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.972

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

plants mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): 1.150 mg/l  
Exposure time: 16 h  
Test Type: static test  
Method: DIN 38 412 Part 8

### ethyl acetate:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 212,5 mg/l  
Exposure time: 96 h  
Test Type: static test

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): 154 mg/l  
aquatic invertebrates Exposure time: 48 h

Toxicity to algae/aquatic : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 2.500  
plants mg/l  
Exposure time: 96 h

### xylene:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 2,6 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other : EC50 (*Daphnia magna* (Water flea)): 3,82 mg/l  
aquatic invertebrates Exposure time: 48 h  
Test Type: flow-through test

Toxicity to algae/aquatic : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 2,2  
plants mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 157 mg/l  
Exposure time: 3 h  
Test Type: Respiration inhibition  
Method: OECD Test Guideline 209

Toxicity to fish (Chronic tox- : NOEC: > 1,3 mg/l  
icity) Exposure time: 56 d  
Species: *Oncorhynchus mykiss* (rainbow trout)  
Test Type: flow-through test

Toxicity to daphnia and other : EC50: 2,90 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

aquatic invertebrates (Chronic toxicity)      Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: static test  
Method: OECD Test Guideline 211  
GLP: yes

### 12.2 Persistence and degradability

#### Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

#### Components:

##### **Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.

##### **butanone:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
GLP: yes

##### **acetone:**

Biodegradability : Result: rapidly biodegradable

##### **ethyl acetate:**

Biodegradability : Result: rapidly biodegradable

##### **xylene:**

Biodegradability : Result: Readily biodegradable.

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

#### Components:

##### **butanone:**



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Partition coefficient: n-octanol/water : log Pow: 0,3 (40 °C)  
Method: OECD Test Guideline 117  
GLP: yes

### acetone:

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

### ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0,68 (25 °C)

### xylene:

Bioaccumulation : Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

## 12.4 Mobility in soil

### Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### Components:

#### butanone:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

#### xylene:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

**Ethylene, tetrafluoro-, polymer:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Assessment : Non-classified vPvB substance. Non-classified PBT substance

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information : Toxic to aquatic life with long lasting effects.

---

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of waste product or used containers according to local regulations.

The following Waste Codes are only suggestions:

Waste Code : used product, unused product  
08 01 11\*, waste paint and varnish containing organic solvents or other hazardous substances

uncleaned packagings  
15 01 10, packaging containing residues of or contaminated by hazardous substances

---

## SECTION 14: Transport information

### 14.1 UN number or ID number

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

**ADN** : UN 1263  
**ADR** : UN 1263  
**RID** : UN 1263  
**IMDG** : UN 1263  
**IATA** : UN 1263

### 14.2 UN proper shipping name

**ADN** : PAINT  
**ADR** : PAINT  
**RID** : PAINT  
**IMDG** : PAINT  
(naphtha (petroleum), hydrotreated light)  
**IATA** : Paint

### 14.3 Transport hazard class(es)

**ADN** : 3  
**ADR** : 3  
**RID** : 3  
**IMDG** : 3  
**IATA** : 3

### 14.4 Packing group

**ADN**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**ADR**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

**RID**  
Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

**IMDG**  
Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

**IATA (Cargo)**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

## 14.5 Environmental hazards

### ADN

Environmentally hazardous : yes

### ADR

Environmentally hazardous : yes

### RID

Environmentally hazardous : yes

### IMDG

Marine pollutant : yes

## 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered: Number on list 3

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

(EC 1005/2009)

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors : Listed

This product is regulated by Regulation (EU) 2019/1148: all suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point. Please see [https://ec.europa.eu/home-affairs/sites/homeaffairs/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list\\_of\\_competent\\_authorities\\_and\\_national\\_contact\\_points\\_en.pdf](https://ec.europa.eu/home-affairs/sites/homeaffairs/files/what-we-do/policies/crisis-and-terrorism/explosives/explosives-precursors/docs/list_of_competent_authorities_and_national_contact_points_en.pdf) acetone (ANNEX II)

: P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

E2 ENVIRONMENTAL HAZARDS

Water hazard class (Germany) : WGK 2 obviously hazardous to water  
Classification according to AwSV, Annex 1 (5.2)

TA Luft List (Germany) : Total dust:  
others: 9,18 %

Inorganic substances in powdered form:  
Not applicable  
Inorganic substances in vapour or gaseous form:  
Not applicable  
Organic Substances:  
portion Class 1: 0,12 %  
others: 72,29 %

Carcinogenic substances:  
Not applicable  
Mutagenic:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

Not applicable  
Toxic to reproduction:  
Not applicable

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 82,06 %

### Other regulations:

Take note of Law on the protection of mothers at work, in education and in studies (Maternity Protection Act - MuSchG).

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

### 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: Other information

### Full text of H-Statements

EUH066 : Repeated exposure may cause skin dryness or cracking.  
H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H301 : Toxic if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H311 : Toxic in contact with skin.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.  
H332 : Harmful if inhaled.  
H335 : May cause respiratory irritation.  
H336 : May cause drowsiness or dizziness.  
H370 : Causes damage to organs.  
H373 : May cause damage to organs through prolonged or repeated exposure if inhaled.  
H373 : May cause damage to organs through prolonged or repeated exposure if swallowed.  
H411 : Toxic to aquatic life with long lasting effects.  
EUH066 : Repeated exposure may cause skin dryness or cracking.

### Full text of other abbreviations

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

- \*\* : Route of exposure cannot be excluded: For certain hazard classes, e.g. STOT, the route of exposure should be indicated in the hazard statement only if it is conclusively proven that no other route of exposure can cause the hazard in accordance to the criteria in Annex I. Under Directive 67/548/EEC the route of exposure was indicated for classifications with R48 when there was data justifying the classification for this route of exposure. The classification under 67/548/EEC indicating the route of exposure has been translated into the corresponding class and category according to this Regulation, but with a general hazard statement not specifying the route of exposure as the necessary information is not available.
- Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2000/39/EC : Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
- 2006/15/EC : Europe. Indicative occupational exposure limit values
- 2017/164/EU : Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
- DE TRGS 900 : Germany. TRGS 900 - Occupational exposure limit values.
- TRGS 903 : TRGS 903 - Biological limit values
- 2000/39/EC / TWA : Limit Value - eight hours
- 2000/39/EC / STEL : Short term exposure limit
- 2006/15/EC / TWA : Limit Value - eight hours
- 2017/164/EU / STEL : Short term exposure limit
- 2017/164/EU / TWA : Limit Value - eight hours
- DE TRGS 900 / AGW : Time Weighted Average

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - DE  
(Commission Regulation (EU) 2020/878)



## OKS 570

Version	Revision Date:	Date of last issue: 12.11.2021	Print Date:
1.4	11.07.2022	Date of first issue: 09.07.2016	11.07.2022

of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 2	H411

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Based on product data or assessment
Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.