

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

Product name : OKS 571

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Lubricant spray

Recommended restrictions on use : Restricted to professional users.

#### 1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599

E-mail address of person responsible for the SDS : mcm@oks-germany.com  
National contact :

#### 1.4 Emergency telephone number

Emergency telephone number : 02/66101029 (Ospedale Niguarda - Milano)  
0382/24444 (Istituto Maugeri - Pavia)  
055/7947819 (Ospedale Careggi - Firenze)  
06/3054343 (Policlinico Gemelli - Roma)  
081/7472870 (Ospedale Cardarelli - Napoli)  
035/269469 - 800.883300 (Ospedali Riuniti - Bergamo)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Chronic aquatic toxicity, Category 3	H412: Harmful to aquatic life with long lasting effects.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H229 Pressurised container: May burst if heated.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statements :

#### Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.

#### Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
P331 Do NOT induce vomiting.

#### Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

Hazardous components which must be listed on the label:

Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Active substance with propellant  
Solvent  
PTFE  
Silicone resin

#### Hazardous components

Chemical name	CAS-No. EC-No.  Index-No. Registration number	Classification	Concentration limits M-Factor Notes	Concentration (% w/w)
Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha	64742-49-0 265-151-9 649-328-00-1	Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411	Note P	$\geq 10$ - $< 20$
butanone	78-93-3 201-159-0 606-002-00-3 01-2119457290-43-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		$\geq 1$ - $< 10$
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		$\geq 1$ - $< 10$
ethyl acetate	141-78-6 205-500-4 607-022-00-5 01-2119475103-46	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336		$\geq 1$ - $< 10$

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version 1.3      Revision Date: 24.07.2018      Date of last issue: 27.03.2018      Print Date: 24.07.2018  
Date of first issue: 09.07.2016

xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-XXXX	Flam. Liq.3; H226 Acute Tox.4; H332 Acute Tox.4; H312 Skin Irrit.2; H315 Eye Irrit.2; H319 STOT SE3; H335 STOT RE2; H373 STOT RE2; H373 Asp. Tox.1; H304	Note C	>= 1 - < 10
n-hexane	110-54-3 203-777-6 601-037-00-0	Flam. Liq.2; H225 Skin Irrit.2; H315 Repr.2; H361f STOT SE3; H336 STOT RE2; H373 Asp. Tox.1; H304 Aquatic Chronic2; H411	>= 5 % STOT RE2, H373  ** *** ,	>= 0,25 - < 1
Substances with a workplace exposure limit :				
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37-XXXX	Flam. Gas1; H220 Press. GasLiquefied gas; H280	Note U (table 3.1)	>= 50 - < 70

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
If easy to do, remove contact lens, if worn.  
Seek medical advice.
- If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Aspiration hazard if swallowed - can enter lungs and cause damage.

### 4.2 Most important symptoms and effects, both acute and delayed

- Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema  
  
Aspiration may cause pulmonary oedema and pneumonitis.
- Risks : Central nervous system depression  
Risk of product entering the lungs on vomiting after ingestion.  
Health injuries may be delayed.  
Causes skin irritation.

### 4.3 Indication of any immediate medical attention and special treatment needed

- Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

- Suitable extinguishing media : ABC powder
- Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

- Specific hazards during firefighting : Fire may cause evolution of:  
Carbon oxides  
Halogenated compounds
- Fire Hazard

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

Do not let product enter drains.  
Contains gas under pressure; may explode if heated.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

### 5.3 Advice for firefighters

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. In the case of respirable dust and/or fumes, use self-contained breathing apparatus. Exposure to decomposition products may be a hazard to health.

Further information : Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective equipment may intervene.

### 6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Keep in suitable, closed containers for disposal. Non-sparking tools should be used.

### 6.4 Reference to other sections

For personal protection see section 8.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

### SECTION 7: Handling and storage

#### 7.1 Precautions for safe handling

- Advice on safe handling : Do not use in areas without adequate ventilation.  
Do not breathe vapours or spray mist.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid exposure - obtain special instructions before use.  
Avoid contact with skin and eyes.  
For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.
- Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

#### 7.2 Conditions for safe storage, including any incompatibilities

- Requirements for storage areas and containers : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Store in accordance with the particular national regulations.

#### 7.3 Specific end use(s)

- Specific use(s) : Consult the technical guidelines for the use of this substance/mixture.

### SECTION 8: Exposure controls/personal protection

#### 8.1 Control parameters

##### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
dimethyl ether	115-10-6	TWA	1.000 ppm	2000/39/EC

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version 1.3      Revision Date: 24.07.2018      Date of last issue: 27.03.2018      Date of first issue: 09.07.2016      Print Date: 24.07.2018

			1.920 mg/m3	(2000-06-16)
Further information	Indicative			
		TWA	1.000 ppm 1.920 mg/m3	IT OEL (2009-08-05)
butanone	78-93-3	TWA	200 ppm 600 mg/m3	2000/39/EC (2000-06-16)
Further information	Indicative			
		STEL	300 ppm 900 mg/m3	2000/39/EC (2000-06-16)
Further information	Indicative			
		TWA	200 ppm 600 mg/m3	IT OEL (2004-03-10)
		STEL	300 ppm 900 mg/m3	IT OEL (2004-03-10)
acetone	67-64-1	TWA	500 ppm 1.210 mg/m3	2000/39/EC (2000-06-16)
Further information	Indicative			
		TWA	500 ppm 1.210 mg/m3	IT OEL (2008-02-26)
ethyl acetate	141-78-6	STEL	400 ppm 1.468 mg/m3	2017/164/EU (2017-02-01)
Further information	Indicative			
		TWA	200 ppm 734 mg/m3	2017/164/EU (2017-02-01)
Further information	Indicative			
xylene	1330-20-7	TWA	50 ppm 221 mg/m3	IT OEL (2004-03-10)
Further information	The notation 'Skin' attributes to the exposure limit values and indicates the possibility of absorption through the skin.			
		STEL	100 ppm 442 mg/m3	IT OEL (2004-03-10)
Further information	The notation 'Skin' attributes to the exposure limit values and indicates the possibility of absorption through the skin.			
		TWA	50 ppm 221 mg/m3	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
		STEL	100 ppm 442 mg/m3	2000/39/EC (2000-06-16)
Further information	Identifies the possibility of significant uptake through the skin, Indicative			
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	2006/15/EC (2006-02-09)
Further information	Indicative			
		TWA	20 ppm 72 mg/m3	IT OEL (2008-02-26)

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
dimethyl ether	Workers	Inhalation	Long-term exposure	1894 mg/m3
Naphtha (petroleum),	Workers	Inhalation	Long-term systemic	1300 mg/m3



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version  
1.3

Revision Date:  
24.07.2018

Date of last issue: 27.03.2018  
Date of first issue: 09.07.2016

Print Date:  
24.07.2018

hydrotreated light; Low boiling point hydrogen treated naphtha			effects	
	Workers	Inhalation	Long-term local effects	840 mg/m3
	Workers	Inhalation	Acute local effects	1100 mg/m3
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m3
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
ethyl acetate	Consumers	Ingestion	Long-term systemic effects	4,5 mg/kg
Remarks:	Exposure time: 24 h			
	Consumers	Skin contact	Long-term systemic effects	37 mg/kg
Remarks:	Exposure time: 24 h			
	Workers	Skin contact	Long-term systemic effects	63 mg/kg
Remarks:	Exposure time: 8 h			
	Workers	Inhalation	Acute systemic effects	1468 mg/m3
	Consumers	Inhalation	Acute systemic effects	734 mg/m3
	Workers	Inhalation	Acute local effects	1468 mg/m3
	Consumers	Inhalation	Acute local effects	734 mg/m3
	Workers	Inhalation	Long-term local effects	734 mg/m3
	Workers	Inhalation	Long-term systemic effects	734 mg/m3
	Consumers	Inhalation	Long-term systemic effects	367 mg/m3
	Consumers	Inhalation	Long-term local effects	367 mg/m3
xylene	Workers	Inhalation	Long-term exposure, Systemic effects	77 mg/m3
	Workers	Inhalation	Short-term exposure, Systemic effects	289 mg/m3
	Workers	Skin contact	Long-term exposure, Systemic effects	180 mg/kg
	Consumers	Inhalation	Long-term exposure, Systemic effects	14,8 mg/m3
	Consumers	Inhalation	Short-term exposure, Systemic effects	174 mg/m3
	Consumers	Ingestion	Long-term exposure, Systemic effects	1,6 mg/kg
n-hexane	Workers	Inhalation	Long-term systemic effects	75 mg/m3
	Workers	Skin contact	Long-term systemic effects	11 mg/kg

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version 1.3      Revision Date: 24.07.2018      Date of last issue: 27.03.2018      Print Date: 24.07.2018  
Date of first issue: 09.07.2016

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
dimethyl ether	Fresh water	0,155 mg/l
	Marine water	0,016 mg/l
	Sewage treatment plant	160 mg/l
	Fresh water sediment	0,681 mg/kg
	Marine sediment	0,069 mg/kg
	Soil	0,045 mg/kg
butanone	Fresh water	55,8 mg/l
	Marine water	55,8 mg/l
	Intermittent use/release	55,8 mg/l
	Sewage treatment plant	709 mg/l
	Fresh water sediment	284,7 mg/kg
	Marine sediment	284,7 mg/kg
ethyl acetate	Soil	22,5 mg/kg
	Water	0,26 mg/l
	Soil	0,22 mg/kg
	Fresh water sediment	0,34 mg/kg
xylene	Fresh water	0,327 mg/l
	Marine water	0,327 mg/l
	Fresh water sediment	12,46 mg/l
	Marine sediment	12,46 mg/l
	Soil	2,31 mg/kg

## 8.2 Exposure controls

### Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

Eye protection : Safety glasses with side-shields conforming to EN166

#### Hand protection

Material : butyl-rubber  
Protective index : Class 1

Remarks : Wear protective gloves. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version 1.3	Revision Date: 24.07.2018	Date of last issue: 27.03.2018 Date of first issue: 09.07.2016	Print Date: 24.07.2018
----------------	------------------------------	---	---------------------------

Filter type : Recommended Filter type:  
Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.  
Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Appearance : aerosol

Colour : white

Odour : solvent-like

Odour Threshold : No data available

  

pH : Not applicable

Melting point/range : No data available

Boiling point/boiling range : < -20 °C  
(1.013 hPa)

Flash point : < -20 °C  
Method: Abel-Pensky

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit : 26,2 %(V)

Lower explosion limit : 1,4 %(V)

Vapour pressure : 4.400 hPa (20 °C)

Relative vapour density : No data available

Density : 0,74 g/cm<sup>3</sup>  
(20 °C)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version 1.3	Revision Date: 24.07.2018	Date of last issue: 27.03.2018 Date of first issue: 09.07.2016	Print Date: 24.07.2018
----------------	------------------------------	---	---------------------------

Bulk density : No data available

Solubility(ies)  
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm<sup>2</sup>/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

### 9.2 Other information

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

Self-ignition : not auto-flammable

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazards to be specially mentioned.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: Toxicological information

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

- Acute oral toxicity : Remarks: Effects due to ingestion may include:  
Symptoms: Central nervous system depression
- Acute inhalation toxicity : Acute toxicity estimate: > 5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: Calculation method  
Remarks: Respiration of solvent vapour may cause dizziness.  
Symptoms: Inhalation may provoke the following symptoms:,  
Respiratory disorder, Dizziness, Drowsiness, Vomiting,  
Fatigue, Vertigo, Central nervous system depression
- Acute dermal toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method  
Symptoms: Redness, Local irritation

##### Components:

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

- Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401  
GLP: yes
- Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Assessment: The substance or mixture has no acute  
inhalation toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes  
Assessment: The substance or mixture has no acute dermal  
toxicity

#### **butanone:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version 1.3	Revision Date: 24.07.2018	Date of last issue: 27.03.2018 Date of first issue: 09.07.2016	Print Date: 24.07.2018
----------------	------------------------------	---	---------------------------

Acute oral toxicity : LD50 (Rat): 2.193 mg/kg  
Method: OECD Test Guideline 423  
GLP: yes

Acute inhalation toxicity : LC50 (Rat): 34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### acetone:

Acute oral toxicity : LD50 Oral (Rat): 5.800 mg/kg

### ethyl acetate:

Acute oral toxicity : LD50 (Rat): 5.600 mg/kg

Acute inhalation toxicity : LC50 (Rat): 58 mg/l  
Exposure time: 8 h  
Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

Acute dermal toxicity : LD50 (Rabbit): 18.000 mg/kg

### xylene:

Acute oral toxicity : LD50 (Rat): 4.300 mg/kg

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

Acute dermal toxicity : Assessment: The component/mixture is moderately toxic after single contact with skin.

### n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.000 mg/kg  
Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): 259,35 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403

Acute dermal toxicity : LD50 (Rabbit): 3.350 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### dimethyl ether:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version 1.3	Revision Date: 24.07.2018	Date of last issue: 27.03.2018 Date of first issue: 09.07.2016	Print Date: 24.07.2018
----------------	------------------------------	---	---------------------------

Acute inhalation toxicity : LC50 (Rat): 309 mg/l  
Exposure time: 4 h  
Test atmosphere: gas

### Skin corrosion/irritation

#### Product:

Remarks: Irritating to skin.

#### Components:

##### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Species: Rabbit  
Assessment: Irritating to skin.  
Method: OECD Test Guideline 404  
Result: Irritating to skin.  
GLP: yes

##### **butanone:**

Species: Rabbit  
Assessment: No skin irritation  
Method: OECD Test Guideline 404  
Result: No skin irritation

Result: Repeated exposure may cause skin dryness or cracking.

##### **acetone:**

Result: Repeated exposure may cause skin dryness or cracking.

##### **ethyl acetate:**

Species: Rabbit  
Result: No skin irritation

##### **xylene:**

Species: Rabbit  
Assessment: Irritating to skin.  
Result: Irritating to skin.

##### **n-hexane:**

Species: Rabbit  
Assessment: Irritating to skin.  
Method: OECD Test Guideline 404  
Result: Irritating to skin.

##### **dimethyl ether:**

Assessment: No skin irritation  
Result: No skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

---

### Serious eye damage/eye irritation

#### **Product:**

Remarks: Irritating to eyes.

#### **Components:**

##### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Species: Rabbit  
Assessment: No eye irritation  
Method: OECD Test Guideline 405  
Result: No eye irritation  
GLP: yes

##### **butanone:**

Species: Rabbit  
Assessment: Irritating to eyes.  
Method: OECD Test Guideline 405  
Result: Irritating to eyes.

##### **acetone:**

Species: Rabbit  
Result: Eye irritation

##### **ethyl acetate:**

Species: Rabbit  
Result: Mild eye irritation

##### **xylene:**

Species: Rabbit  
Assessment: Irritating to eyes.  
Result: Irritating to eyes.

##### **n-hexane:**

Species: Rabbit  
Assessment: No eye irritation  
Method: OECD Test Guideline 405  
Result: No eye irritation

##### **dimethyl ether:**

Assessment: No eye irritation  
Result: No eye irritation



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

### Respiratory or skin sensitisation

#### **Product:**

Remarks: This information is not available.

#### **Components:**

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Test Type: Buehler Test  
Species: Guinea pig  
Assessment: Does not cause skin sensitisation.  
Method: OECD Test Guideline 406  
Result: Does not cause skin sensitisation.  
GLP: yes

#### **butanone:**

Test Type: Maximisation Test  
Species: Guinea pig  
Assessment: Does not cause skin sensitisation.  
Method: OECD Test Guideline 406  
Result: Does not cause skin sensitisation.  
GLP: yes

#### **ethyl acetate:**

Species: Guinea pig  
Method: OECD Test Guideline 406  
Result: Did not cause sensitisation on laboratory animals.

#### **xylene:**

Species: Mouse  
Assessment: Did not cause sensitisation on laboratory animals.  
Method: OECD Test Guideline 429  
Result: Did not cause sensitisation on laboratory animals.

#### **n-hexane:**

Species: Mouse  
Assessment: Does not cause skin sensitisation.  
Result: Does not cause skin sensitisation.

#### **dimethyl ether:**

Assessment: Does not cause skin sensitisation.  
Result: Does not cause skin sensitisation.

### Germ cell mutagenicity

#### **Product:**

Genotoxicity in vitro : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version 1.3	Revision Date: 24.07.2018	Date of last issue: 27.03.2018 Date of first issue: 09.07.2016	Print Date: 24.07.2018
----------------	------------------------------	---	---------------------------

Genotoxicity in vivo : Remarks: No data available

### Components:

#### **butanone:**

Germ cell mutagenicity-  
Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

#### **xylene:**

Germ cell mutagenicity-  
Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

#### **dimethyl ether:**

Genotoxicity in vitro : Test Type: Ames test  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Species: Drosophila melanogaster (vinegar fly)  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 477  
Result: negative

### **Carcinogenicity**

#### Product:

Remarks: No data available

### Components:

#### **butanone:**

Carcinogenicity -  
Assessment : Not classifiable as a human carcinogen.

#### **xylene:**

Carcinogenicity -  
Assessment : Not classifiable as a human carcinogen.

#### **dimethyl ether:**

Species: Rat  
Application Route: inhalation (gas)  
Exposure time: 2 Years  
47 mg/l  
Method: OECD Test Guideline 453  
Result: negative

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version  
1.3

Revision Date:  
24.07.2018

Date of last issue: 27.03.2018  
Date of first issue: 09.07.2016

Print Date:  
24.07.2018

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### Components:

##### **butanone:**

Reproductive toxicity - Assessment : No toxicity to reproduction  
No effects on or via lactation

##### **xylene:**

Reproductive toxicity - Assessment : No toxicity to reproduction  
No toxicity to reproduction

##### **n-hexane:**

Reproductive toxicity - Assessment : Suspected human reproductive toxicant

##### **dimethyl ether:**

Reproductive toxicity - Assessment : Animal testing did not show any effects on fertility.

### STOT - single exposure

#### Components:

##### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: May cause drowsiness or dizziness.

##### **butanone:**

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects., May cause drowsiness or dizziness.

##### **acetone:**

Exposure routes: Inhalation

Assessment: May cause drowsiness or dizziness.

##### **ethyl acetate:**

Exposure routes: Inhalation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### **xylene:**

Exposure routes: Inhalation

Target Organs: Respiratory system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

### **n-hexane:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

### **STOT - repeated exposure**

#### **Components:**

##### **butanone:**

Assessment: The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### **xylene:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

Exposure routes: Ingestion

Target Organs: Liver, Kidney

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

##### **n-hexane:**

Exposure routes: Inhalation

Target Organs: Central nervous system

Assessment: The substance or mixture is classified as specific target organ toxicant, repeated exposure, category 2.

### **Repeated dose toxicity**

#### **Product:**

Remarks: This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

### Aspiration toxicity

#### Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

#### Components:

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

May be fatal if swallowed and enters airways.

#### **butanone:**

No aspiration toxicity classification

#### **xylene:**

May be fatal if swallowed and enters airways.

#### **n-hexane:**

May be fatal if swallowed and enters airways.

#### **dimethyl ether:**

No aspiration toxicity classification

### Further information

#### Product:

Remarks: Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

### Components:

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

- Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 10 mg/l  
Exposure time: 96 h  
Test Type: semi-static test  
Method: OECD Test Guideline 203  
GLP: yes
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 4,5 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 3,1 mg/l  
Exposure time: 72 h  
Test Type: static test

### **Ecotoxicology Assessment**

- Acute aquatic toxicity : Toxic to aquatic life.
- Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

### **butanone:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l  
Exposure time: 96 h  
Test Type: static test
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l  
Exposure time: 48 h  
Test Type: static test
- Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.972 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes
- Toxicity to microorganisms : EC50 (Pseudomonas putida): 1.150 mg/l  
Exposure time: 16 h  
Test Type: static test  
Method: DIN 38 412 Part 8  
GLP:

### **ethyl acetate:**

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 230 mg/l  
Exposure time: 96 h

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 717 mg/l  
Exposure time: 48 h  
Method: DIN 38412

Toxicity to microorganisms : EC10 (Pseudomonas putida): 2.900 mg/l  
Exposure time: 16 h

### **xylene:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 2,6 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 3,82 mg/l  
Exposure time: 48 h  
Test Type: flow-through test

Toxicity to algae : EC50 (Pseudokirchneriella subcapitata (green algae)): 2,2 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to microorganisms : EC50 (activated sludge): > 157 mg/l  
Exposure time: 3 h  
Test Type: Respiration inhibition  
Method: OECD Test Guideline 209  
GLP:

Toxicity to fish (Chronic toxicity) : NOEC: > 1,3 mg/l  
Exposure time: 56 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Test Type: flow-through test

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : EC50: 2,90 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: static test  
Method: OECD Test Guideline 211  
GLP: yes

### **n-hexane:**

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 12,51 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 21,85 mg/l  
Exposure time: 48 h

Toxicity to algae : ErC50 (Pseudokirchneriella subcapitata (green algae)): 9,285

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

mg/l  
Exposure time: 72 h

### dimethyl ether:

Toxicity to fish : LC50 (Poecilia reticulata (guppy)): > 4.100 mg/l  
Exposure time: 96 h  
Test Type: semi-static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 4.400 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae : EC50 (green algae): 154,9 mg/l  
Exposure time: 96 h

## 12.2 Persistence and degradability

### Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

### Components:

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 90,35 %  
Exposure time: 28 d

#### **butanone:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
GLP: yes

#### **acetone:**

Biodegradability : Result: rapidly biodegradable

#### **ethyl acetate:**

Biodegradability : Biodegradation: 100 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
Remarks: According to the results of tests of biodegradability



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

this product is considered as being readily biodegradable.

### **xylene:**

Biodegradability : Result: Readily biodegradable.

### **n-hexane:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 21 %  
Exposure time: 28 d  
GLP: yes

### **dimethyl ether:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: Not readily biodegradable.  
Biodegradation: 5 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

## 12.3 Bioaccumulative potential

### **Product:**

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

### **Components:**

#### **Naphtha (petroleum), hydrotreated light; Low boiling point hydrogen treated naphtha:**

Partition coefficient: n-octanol/water : log Pow: 3,4 - 5,2

#### **butanone:**

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Partition coefficient: n-octanol/water : log Pow: 0,3 (40 °C)  
Method: OECD Test Guideline 117  
GLP: yes

#### **acetone:**

Bioaccumulation : Remarks: Does not bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: 0,2

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

### **xylene:**

Bioaccumulation : Bioconcentration factor (BCF): 25,9

Partition coefficient: n-octanol/water : log Pow: 2,77 - 3,15

### **n-hexane:**

Bioaccumulation : Bioconcentration factor (BCF): 501,19

Partition coefficient: n-octanol/water : log Pow: 4 (20 °C)  
pH: 7

### **dimethyl ether:**

Partition coefficient: n-octanol/water : log Pow: 0,07 (25 °C)

## 12.4 Mobility in soil

### **Product:**

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

## 12.5 Results of PBT and vPvB assessment

### **Product:**

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### **Components:**

#### **butanone:**

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

#### **xylene:**

Assessment : Non-classified PBT substance. Non-classified vPvB substance.

#### **dimethyl ether:**

Assessment : Non-classified vPvB substance. Non-classified PBT substance.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

### 12.6 Other adverse effects

**Product:**

Additional ecological information : Harmful to aquatic life with long lasting effects.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Offer empty spray cans to an established disposal company.  
Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

## SECTION 14: Transport information

### 14.1 UN number

ADR : UN 1950  
IMDG : UN 1950  
IATA : UN 1950

### 14.2 UN proper shipping name

ADR : AEROSOLS  
IMDG : AEROSOLS  
IATA : Aerosols, flammable

### 14.3 Transport hazard class(es)

ADR : 2  
IMDG : 2.1  
IATA : 2.1

### 14.4 Packing group

ADR  
Packing group : Not assigned by regulation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

Classification Code : 5F  
Labels : 2.1  
Tunnel restriction code : (D)

### IMDG

Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U

### IATA (Cargo)

Packing instruction (cargo aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

### IATA (Passenger)

Packing instruction (passenger aircraft) : 203  
Packing instruction (LQ) : Y203  
Packing group : Not assigned by regulation  
Labels : Flammable Gas

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### IATA (Passenger)

Environmentally hazardous : no

### IATA (Cargo)

Environmentally hazardous : no

## 14.6 Special precautions for user

No special precautions required.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59).	: This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).
REACH - List of substances subject to authorisation (Annex XIV)	: Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer : Not applicable

Regulation (EC) No 850/2004 on persistent organic pollutants : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals : Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, preparations and articles (Annex XVII) : Not applicable

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

		Quantity 1	Quantity 2
P3a	FLAMMABLE AEROSOLS	150 t	500 t

P2

34	Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a) to (d)	2.500 t	25.000 t
----	---	---------	----------

P5c

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 92,92 %  
Volatile CMR compounds: 15,01 %  
Remarks: VOC content excluding water

Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

Legislative Decree April 9, 2008, 81 (Implementation of Article 1 of the Law of 3 August 2007, n. 123, concerning the protection of health and safety in the workplace.) and subsequent amendments

Legislative Decree April 3, 2006, n.152, (Environmental standards) and subsequent amendments

Legislative Decree February 6, 2009, 21 (Regulations for the execution of the provisions laid down in Regulation (EC) no. 648/2004 on detergents)

### 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: Other information

### Full text of H-Statements

H220	: Extremely flammable gas.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H280	: Contains gas under pressure; may explode if heated.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H361f	: Suspected of damaging fertility.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

\*\* : Route of exposure cannot be excluded: For certain hazard classes, e.g. STOT, the route of exposure should be indicated in the hazard statement only if it is conclusively proven that no other route of exposure can cause the hazard in accordance to the criteria in Annex I. Under Directive 67/548/EEC the route of exposure was indicated for classifications with R48 when there was data justifying the classification for this route of exposure. The classification under 67/548/EEC indicating the route of exposure has been translated into the

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

- corresponding class and category according to this Regulation, but with a general hazard statement not specifying the route of exposure as the necessary information is not available.
- \*\*\* : Hazard statements for reproductive toxicity: Hazard statements H360 and H361 indicate a general concern for effects on fertility and/or development: 'May damage/Suspected of damaging fertility or the unborn child'. According to the criteria, the general hazard statement can be replaced by the hazard statement indicating the specific effect of concern in accordance with Section 1.1.2.1.2. When the other differentiation is not mentioned, this is due to evidence proving no such effect, inconclusive data or no data and the obligations in Article 4(3) shall apply for that differentiation. In order not to lose information from the harmonised classifications for fertility and developmental effects under Directive 67/548/EEC, the classifications have been translated only for those effects classified under that Directive
- Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- Note P : The classification as a carcinogen or mutagen need not apply if it can be shown that the substance contains less than 0,1 % w/w benzene (Einecs No 200-753-7). When the substance is not classified as a carcinogen at least the precautionary statements (P102-)P260- P262-P301 + P310-P331 shall apply. This note applies only to certain complex oil-derived substances in Part 3.
- Note U (table 3.1) : When put on the market gases have to be classified as "Gases under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case.

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - IT



## OKS 571

Version	Revision Date:	Date of last issue: 27.03.2018	Print Date:
1.3	24.07.2018	Date of first issue: 09.07.2016	24.07.2018

population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Aerosol 1	H222, H229
Skin Irrit. 2	H315
Eye Irrit. 2	H319
STOT SE 3	H336
Asp. Tox. 1	H304
Aquatic Chronic 3	H412

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method
Calculation method
Based on product data or assessment
Calculation method

This safety datasheet applies only to products originally packaged and labelled by OKS Spezienschmierstoffe. The information contained therein is protected by copyright and must not be reproduced or amended without the express written approval of OKS Spezienschmierstoffe. This document may be passed on only to the extent required by law. Any dissemination of our safety datasheets (e.g. as a document for download from the Internet) beyond this legally required extent is not permitted without express written consent. OKS Spezienschmierstoffe provides its customers with amended safety datasheets as prescribed by law. The customer is responsible for passing on safety datasheets and any amendments contained therein to its own customers, employees and other users of the product. OKS Spezienschmierstoffe provides no guarantee that safety datasheets received by users from third parties are up-to-date. All information and instructions in this safety datasheets were compiled to the best of our knowledge and are based on the information available to us. The data provided are intended to describe the product in relation to the required safety measures; they are neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and do not justify any contractual legal relationships.