

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifier

Product name : OKS 589

### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-  
stance/Mixture : Lubricant

Recommended restrictions : Restricted to professional users.  
on use

### 1.3 Details of the supplier of the safety data sheet

Company : OKS Spezialschmierstoffe GmbH  
Ganghoferstr. 47  
D-82216 Maisach-Gernlinden  
Tel.: +49 8142 3051 500  
Fax.: +49 8142 3051 599  
info@oks-germany.com

E-mail address of person : mcm@oks-germany.com  
responsible for the SDS Material Compliance Management

National contact :

### 1.4 Emergency telephone number

Emergency telephone num- : +33 1 45 42 59 59  
ber

## SECTION 2: Hazards identification

### 2.1 Classification of the substance or mixture

#### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 2 H225: Highly flammable liquid and vapour.

Serious eye damage, Category 1 H318: Causes serious eye damage.

Specific target organ toxicity - single ex- H336: May cause drowsiness or dizziness.  
posure, Category 3, Central nervous  
system

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)






## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms	:	  
Signal word	:	Danger
Hazard statements	:	H225 Highly flammable liquid and vapour. H318 Causes serious eye damage. H336 May cause drowsiness or dizziness.
Supplemental Hazard Statements	:	EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	<b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P233 Keep container tightly closed. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. <b>Response:</b> P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/ doctor. P370 + P378 In case of fire: Use alcohol-resistant foam, carbon dioxide or water mist to extinguish. <b>Storage:</b> P403 + P235 Store in a well-ventilated place. Keep cool.

#### Hazardous components which must be listed on the label:

n-butyl acetate  
butanone  
ethyl acetate  
butan-1-ol

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: Composition/information on ingredients

### 3.2 Mixtures

Chemical nature : Solvent mixture  
epoxy resin  
solid lubricant  
PTFE  
Molybdenum disulfide

#### Components

Chemical name	CAS-No. EC-No.  Index-No. Registration number	Classification	specific concentration limit M-Factor Notes Acute toxicity estimate	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1  607-025-00-1 01-2119485493-29-XXXX	Flam. Liq.3; H226 STOT SE3; H336; EUH066		>= 30 - < 50
butanone	78-93-3 201-159-0  606-002-00-3 01-2119457290-43-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 20 - < 30
ethyl acetate	141-78-6 205-500-4  607-022-00-5 01-21119475103-46-XXXX	Flam. Liq.2; H225 Eye Irrit.2; H319 STOT SE3; H336; EUH066		>= 10 - < 20
butan-1-ol	71-36-3 200-751-6	Flam. Liq.3; H226 Acute Tox.4; H302 Skin Irrit.2; H315		>= 3 - < 10

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version 1.2      Revision Date: 11.05.2022      Date of last issue: 20.08.2018      Print Date: 12.05.2022  
Date of first issue: 09.07.2016

	603-004-00-6 01-2119484630-38-XXXX	Eye Dam.1; H318 STOT SE3; H336 STOT SE3; H335		
aluminium dihydrogen triphosphate	13939-25-8 237-714-9  01-2119970565-28-XXXX	Eye Irrit.2; H319		$\geq 1 - < 10$
ethylene glycol mono-butyl ether	111-76-2 203-905-0  603-014-00-0 01-2119475108-36-XXXX	Acute Tox.4; H302 Acute Tox.4; H332 Skin Irrit.2; H315 Eye Irrit.2; H319	ATE (Oral): 1.200 mg/kg;	$\geq 1 - < 10$
Substances with a workplace exposure limit :				
Graphite	7782-42-5 231-955-3	Not classified		$\geq 1 - < 10$

For explanation of abbreviations see section 16.

## SECTION 4: First aid measures

### 4.1 Description of first aid measures

- If inhaled : Call a physician or poison control centre immediately.  
Remove person to fresh air. If signs/symptoms continue, get medical attention.  
Keep patient warm and at rest.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.  
Get medical attention immediately if irritation develops and persists.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.  
Get medical attention immediately.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

If swallowed : Move the victim to fresh air.  
If accidentally swallowed obtain immediate medical attention.  
If unconscious, place in recovery position and seek medical advice.  
Keep respiratory tract clear.  
Do NOT induce vomiting.  
Rinse mouth with water.  
Never give anything by mouth to an unconscious person.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:  
Unconsciousness  
Dizziness  
Drowsiness  
Headache  
Nausea  
Tiredness  
Skin contact may provoke the following symptoms:  
Erythema

Risks : Central nervous system depression  
Can be absorbed through skin.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-fighting : Do not let product enter drains.  
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides  
Sulphur oxides  
Oxides of phosphorus  
Halogenated compounds  
Metal oxides

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### 5.3 Advice for firefighters

- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposition products may be a hazard to health.
- Further information : Standard procedure for chemical fires. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Cool containers/tanks with water spray.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : Evacuate personnel to safe areas. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist. Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8.

### 6.2 Environmental precautions

- Environmental precautions : Do not allow contact with soil, surface or ground water. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Non-sparking tools should be used.

### 6.4 Reference to other sections

For personal protection see section 8.

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

- Advice on safe handling : Use only in an area containing explosion proof equipment. Do not use in areas without adequate ventilation. Do not breathe vapours or spray mist. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

For personal protection see section 8.  
Keep away from fire, sparks and heated surfaces.  
Smoking, eating and drinking should be prohibited in the application area.  
Wash hands and face before breaks and immediately after handling the product.  
Ensure all equipment is electrically grounded before beginning transfer operations.  
Do not get in eyes or mouth or on skin.  
Do not get on skin or clothing.  
Do not ingest.  
Do not use sparking tools.  
Do not enter areas where used or stored until adequately ventilated.  
Do not repack.  
Do not re-use empty containers.  
These safety instructions also apply to empty packaging which may still contain product residues.  
Keep container closed when not in use.

Advice on protection against fire and explosion : Keep away from heat and sources of ignition.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Store in original container. Keep container closed when not in use. Keep in a cool place away from oxidizing agents. Keep in a dry, cool and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in accordance with the particular national regulations. Keep in properly labelled containers.

### 7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	VME	150 ppm 710 mg/m <sup>3</sup>	FR VLE (2005-02-01)
Further information: Indicative exposure limits				
		VLCT (VLE)	200 ppm 940 mg/m <sup>3</sup>	FR VLE (2005-02-01)

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version  
1.2

Revision Date:  
11.05.2022

Date of last issue: 20.08.2018  
Date of first issue: 09.07.2016

Print Date:  
12.05.2022

		Further information: Indicative exposure limits		
		STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU (2019-10-31)
		Further information: Indicative		
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU (2019-10-31)
		Further information: Indicative		
butanone	78-93-3	TWA	200 ppm 600 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
		Further information: Indicative		
		STEL	300 ppm 900 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
		Further information: Indicative		
		VME	200 ppm 600 mg/m <sup>3</sup>	FR VLE (2012-05-10)
		Further information: Risk of penetration through skin, Regulatory binding exposure limits		
		VLCT (VLE)	300 ppm 900 mg/m <sup>3</sup>	FR VLE (2012-05-10)
		Further information: Risk of penetration through skin, Regulatory binding exposure limits		
ethyl acetate	141-78-6	VME	200 ppm 734 mg/m <sup>3</sup>	FR VLE (2019-12-29)
		Further information: Regulatory binding exposure limits		
		STEL	400 ppm 1.468 mg/m <sup>3</sup>	2017/164/EU (2017-02-01)
		Further information: Indicative		
		TWA	200 ppm 734 mg/m <sup>3</sup>	2017/164/EU (2017-02-01)
		Further information: Indicative		
		VLCT (VLE)	400 ppm 1.468 mg/m <sup>3</sup>	FR VLE (2019-12-29)
		Further information: Regulatory binding exposure limits		
butan-1-ol	71-36-3	VLCT (VLE)	50 ppm 150 mg/m <sup>3</sup>	FR VLE (2005-02-01)
		Further information: Indicative exposure limits		
ethylene glycol monobutyl ether	111-76-2	TWA	20 ppm 98 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		STEL	50 ppm 246 mg/m <sup>3</sup>	2000/39/EC (2000-06-16)
		Further information: Identifies the possibility of significant uptake through the skin, Indicative		
		VME	10 ppm 49 mg/m <sup>3</sup>	FR VLE (2012-07-01)
		Further information: Risk of penetration through skin, Regulatory binding exposure limits		
		VLCT (VLE)	50 ppm	FR VLE



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version 1.2      Revision Date: 11.05.2022      Date of last issue: 20.08.2018      Print Date: 12.05.2022  
Date of first issue: 09.07.2016

			246 mg/m3	(2012-07-01)
	Further information: Risk of penetration through skin, Regulatory binding exposure limits			
Graphite	7782-42-5	VME (Alveolar fraction)	2 mg/m3	FR VLE (2007-12-01)
	Further information: Indicative exposure limits			

### Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

Substance name	End Use	Exposure routes	Potential health effects	Value
n-butyl acetate	Workers	Inhalation	Long-term systemic effects	300 mg/m3
	Workers	Inhalation	Acute systemic effects	600 mg/m3
	Workers	Dermal	Long-term local effects	11 mg/cm2
butanone	Workers	Inhalation	Long-term systemic effects	600 mg/m3
	Workers	Skin contact	Long-term systemic effects	1161 mg/kg
butan-1-ol	Workers	Inhalation	Long-term local effects	310 mg/m3
ethylene glycol monobutyl ether	Workers	Inhalation	Long-term systemic effects	98 mg/m3
	Workers	Inhalation	Acute systemic effects	1091 mg/m3
	Workers	Skin contact	Long-term systemic effects	125 mg/kg bw/day
	Workers	Skin contact	Acute systemic effects	89 mg/kg bw/day
	Workers	Inhalation	Acute local effects	246 mg/m3
Graphite	Workers	Inhalation	Long-term local effects	1,2 mg/m3

### Predicted No Effect Concentration (PNEC) according to Regulation (EC) No. 1907/2006:

Substance name	Environmental Compartment	Value
n-butyl acetate	Fresh water	0,18 mg/l
	Marine water	0,018 mg/l
	Microbiological Activity in Sewage Treatment Systems	35,6 mg/l
	Fresh water sediment	0,981 mg/kg
	Marine sediment	0,0981 mg/kg
butanone	Soil	0,09 mg/kg
	Fresh water	55,8 mg/l
	Marine water	55,8 mg/l
	Intermittent use/release	55,8 mg/l
	Sewage treatment plant	709 mg/l
butan-1-ol	Fresh water sediment	284,7 mg/kg
	Marine sediment	284,7 mg/kg
	Soil	22,5 mg/kg
butan-1-ol	Fresh water	0,082 mg/l
	Marine water	0,008 mg/l

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version 1.2      Revision Date: 11.05.2022      Date of last issue: 20.08.2018      Print Date: 12.05.2022  
Date of first issue: 09.07.2016

	Intermittent use/release	2,25 mg/l
	Microbiological Activity in Sewage Treatment Systems	2476 mg/l
	Fresh water sediment	0,324 mg/kg dry weight (d.w.)
	Marine sediment	0,032 mg/kg dry weight (d.w.)
	Soil	0,017 mg/kg dry weight (d.w.)
ethylene glycol monobutyl ether	Fresh water	8,8 mg/l
	Marine water	0,88 mg/l
	Sewage treatment plant	463 mg/l
	Fresh water sediment	34,6 mg/kg
	Marine sediment	3,46 mg/kg
	Soil	2,33 mg/kg
	Intermittent use/release	26,4 mg/l

## 8.2 Exposure controls

### Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.  
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

### Personal protective equipment

Eye protection : Tightly fitting safety goggles

#### Hand protection

Material : butyl-rubber  
Break through time : > 10 min  
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Filter type A-P

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	black
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/range	:	No data available
Boiling point/boiling range	:	76 °C
Flammability (solid, gas)	:	Not applicable
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	0,5 °C(1.013 hPa) Method: Abel-Pensky, closed cup
Auto-ignition temperature	:	No data available
Decomposition temperature	:	No data available
pH	:	Not applicable substance/mixture is non-polar/aprotic
Viscosity		
Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	No data available
Solubility(ies)		
Water solubility	:	immiscible
Solubility in other solvents	:	No data available
Partition coefficient: n-octanol/water	:	No data available

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Vapour pressure : < 1.100 hPa (20 °C)

Relative density : 1,0 (20 °C)  
Reference substance: Water  
The value is calculated

Density : 1,00 g/cm<sup>3</sup>  
(20 °C)

Bulk density : No data available

Relative vapour density : No data available

### 9.2 Other information

Explosives : Not explosive

Oxidizing properties : No data available

Self-ignition : No data available

Evaporation rate : No data available

Sublimation point : No data available

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

No hazards to be specially mentioned.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

### 10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.  
Strong sunlight for prolonged periods.

### 10.5 Incompatible materials

Materials to avoid : Oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### SECTION 11: Toxicological information

#### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

##### Acute toxicity

###### Product:

- Acute oral toxicity : Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method  
  
Remarks: Effects due to ingestion may include:  
  
Symptoms: Central nervous system depression
- Acute inhalation toxicity : Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method  
  
Remarks: Respiration of solvent vapour may cause dizziness.  
  
Symptoms: Inhalation may provoke the following symptoms:,  
Dizziness, Drowsiness, Vomiting, Fatigue, Vertigo, Central  
nervous system depression
- Acute dermal toxicity : Remarks: Prolonged or repeated skin contact with liquid may  
cause defatting resulting in drying, redness and possible blister-  
ing.  
  
Symptoms: Skin disorders

###### Components:

###### **n-butyl acetate:**

- Acute oral toxicity : LD50 (Rat): 10.768 mg/kg
- Acute inhalation toxicity : LC50 (Rat): > 21 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
GLP: yes  
Assessment: The substance or mixture has no acute inhala-  
tion toxicity
- Acute dermal toxicity : LD50 (Rabbit): > 17.600 mg/kg

###### **butanone:**

- Acute oral toxicity : LD50 (Rat): 2.193 mg/kg  
Method: OECD Test Guideline 423  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Acute inhalation toxicity : LC50 (Rat): 34 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 5.000 mg/kg  
Method: OECD Test Guideline 402

### ethyl acetate:

Acute oral toxicity : LD50 (Rat): 5.620 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 20.000 mg/kg

### butan-1-ol:

Acute oral toxicity : LD50 (Rat): 2.292 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : LC50 (Rat): > 17,76 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity

Acute dermal toxicity : LD50 (Rabbit): 3.430 mg/kg  
Method: OECD Test Guideline 402  
GLP: yes

### aluminium dihydrogen triphosphate:

Acute oral toxicity : LD50 Oral (Rat): > 2.500 mg/kg  
Method: OECD Test Guideline 420  
Assessment: The substance or mixture has no acute oral toxicity

Acute inhalation toxicity : LC50 (Rat): > 3,46 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Assessment: The substance or mixture has no acute inhalation toxicity

### ethylene glycol monobutyl ether:

Acute oral toxicity : Acute toxicity estimate: 1.200 mg/kg  
Method: Converted acute toxicity point estimate

Assessment: The component/mixture is moderately toxic after single ingestion.

Acute inhalation toxicity : Assessment: The component/mixture is moderately toxic after short term inhalation.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Acute dermal toxicity : LD50 (Guinea pig): > 2.000 mg/kg  
Method: OECD Test Guideline 402  
Assessment: The substance or mixture has no acute dermal toxicity

### Graphite:

Acute oral toxicity : LD50 (Rat): > 2.000 mg/kg  
Method: OECD Test Guideline 401  
Assessment: The substance or mixture has no acute oral toxicity

### Skin corrosion/irritation

#### Product:

Remarks : This information is not available.

#### Components:

##### **n-butyl acetate:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : Repeated exposure may cause skin dryness or cracking.

##### **butanone:**

Species : Rabbit  
Assessment : No skin irritation  
Method : OECD Test Guideline 404  
Result : No skin irritation  
  
Result : Repeated exposure may cause skin dryness or cracking.

##### **ethyl acetate:**

Species : Rabbit  
Result : Mild skin irritation  
  
Result : Repeated exposure may cause skin dryness or cracking.

##### **butan-1-ol:**

Species : Rabbit  
Assessment : Irritating to skin.  
Result : Irritating to skin.

##### **aluminium dihydrogen triphosphate:**

Assessment : No skin irritation  
Result : No skin irritation

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### ethylene glycol monobutyl ether:

Species : Rabbit  
Assessment : Irritating to skin.  
Result : Irritating to skin.

### Serious eye damage/eye irritation

#### Product:

Remarks : Risk of serious damage to eyes.

#### Components:

##### **n-butyl acetate:**

Species : Rabbit  
Assessment : No eye irritation  
Method : OECD Test Guideline 405  
Result : No eye irritation  
GLP : yes

##### **butanone:**

Species : Rabbit  
Assessment : Irritating to eyes.  
Method : OECD Test Guideline 405  
Result : Irritating to eyes.

##### **ethyl acetate:**

Assessment : Irritating to eyes.  
Result : Irritating to eyes.

##### **butan-1-ol:**

Species : Rabbit  
Assessment : Risk of serious damage to eyes.  
Method : OECD Test Guideline 405  
Result : Risk of serious damage to eyes.  
GLP : yes

##### **aluminium dihydrogen triphosphate:**

Assessment : Irritating to eyes.  
Result : Irritating to eyes.

##### **ethylene glycol monobutyl ether:**

Species : Rabbit  
Assessment : Irritating to eyes.  
Result : Irritating to eyes.



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### Respiratory or skin sensitisation

#### Product:

Remarks : This information is not available.

#### Components:

##### **n-butyl acetate:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

##### **butanone:**

Test Type : Buehler Test  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.  
GLP : yes

##### **ethyl acetate:**

Test Type : Maximisation Test  
Exposure routes : Dermal  
Species : Guinea pig  
Assessment : Does not cause skin sensitisation.  
Method : OECD Test Guideline 406  
Result : Does not cause skin sensitisation.

##### **butan-1-ol:**

Species : Mouse  
Assessment : Did not cause sensitisation on laboratory animals.  
Method : OECD Test Guideline 429  
Result : Did not cause sensitisation on laboratory animals.

##### **aluminium dihydrogen triphosphate:**

Assessment : Did not cause sensitisation on laboratory animals.  
Result : Did not cause sensitisation on laboratory animals.

##### **ethylene glycol monobutyl ether:**

Test Type : Maximisation Test  
Species : Guinea pig  
Assessment : Did not cause sensitisation on laboratory animals.  
Result : Did not cause sensitisation on laboratory animals.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

#### Components:

##### **n-butyl acetate:**

Genotoxicity in vitro : Test Type: Ames test  
Test system: Salmonella typhimurium  
Method: OECD Test Guideline 471  
Result: negative

Test Type: Chromosome aberration test in vitro  
Test system: Chinese hamster cells  
Method: OECD Test Guideline 473  
Result: negative

Genotoxicity in vivo : Species: Mouse  
Application Route: Oral  
Method: OECD Test Guideline 474  
Result: negative

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects., Animal testing did not show any mutagenic effects.

##### **butanone:**

Germ cell mutagenicity- Assessment : Tests on bacterial or mammalian cell cultures did not show mutagenic effects.

##### **ethylene glycol monobutyl ether:**

Germ cell mutagenicity- Assessment : In vitro tests did not show mutagenic effects

### Carcinogenicity

#### Product:

Remarks : No data available

#### Components:

##### **n-butyl acetate:**

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

##### **butanone:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Carcinogenicity - Assessment : Not classifiable as a human carcinogen.

### ethylene glycol monobutyl ether:

Carcinogenicity - Assessment : Animal testing did not show any carcinogenic effects.

### Reproductive toxicity

#### Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

#### Components:

##### **n-butyl acetate:**

Effects on fertility : Test Type: Two-generation study  
Species: Rat  
Application Route: inhalation (vapour)  
General Toxicity - Parent: NOAEC: 750 mg/l  
General Toxicity F1: NOAEC: 750 mg/l  
General Toxicity F2: NOAEC: 750 mg/l  
Method: OECD Test Guideline 416  
Result: Embryotoxic effects and adverse effects on the offspring were detected.

Reproductive toxicity - Assessment : - Fertility -  
No evidence of adverse effects on sexual function and fertility, or on development, based on animal experiments.  
- Teratogenicity -  
No toxicity to reproduction

##### **butanone:**

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction  
- Teratogenicity -  
No effects on or via lactation

##### **aluminium dihydrogen triphosphate:**

Reproductive toxicity - Assessment : - Fertility -  
No toxicity to reproduction

##### **ethylene glycol monobutyl ether:**

Reproductive toxicity - Assessment : - Fertility -

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

essment No toxicity to reproduction  
- Teratogenicity -  
  
Animal testing did not show any effects on foetal development.

### STOT - single exposure

#### Components:

##### **n-butyl acetate:**

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

##### **butanone:**

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.,  
May cause drowsiness or dizziness.

##### **ethyl acetate:**

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

##### **butan-1-ol:**

Exposure routes : Inhalation  
Target Organs : Respiratory system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with respiratory tract irritation.

Exposure routes : Inhalation  
Target Organs : Central nervous system  
Assessment : The substance or mixture is classified as specific target organ toxicant, single exposure, category 3 with narcotic effects.

##### **aluminium dihydrogen triphosphate:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

##### **ethylene glycol monobutyl ether:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, single exposure.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### STOT - repeated exposure

#### Components:

##### **n-butyl acetate:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### **butanone:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### **ethyl acetate:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### **butan-1-ol:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### **aluminium dihydrogen triphosphate:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

##### **ethylene glycol monobutyl ether:**

Assessment : The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

### Repeated dose toxicity

#### Product:

Remarks : This information is not available.

#### Components:

##### **n-butyl acetate:**

Species : Rat  
NOAEL : 125 mg/kg  
Application Route : Oral

### Aspiration toxicity

#### Product:

This information is not available.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### Components:

#### **n-butyl acetate:**

No aspiration toxicity classification

#### **butanone:**

No aspiration toxicity classification

#### **butan-1-ol:**

No aspiration toxicity classification

#### **aluminium dihydrogen triphosphate:**

No aspiration toxicity classification

#### **ethylene glycol monobutyl ether:**

No aspiration toxicity classification

## 11.2 Information on other hazards

### **Endocrine disrupting properties**

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### **Further information**

#### Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

#### Components:

#### **aluminium dihydrogen triphosphate:**

Remarks : Ingestion causes irritation of upper respiratory system and gastrointestinal disturbance.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

#### Product:

Toxicity to fish : Remarks: Harmful to aquatic organisms.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

### Components:

#### **n-butyl acetate:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 18 mg/l  
Exposure time: 96 h  
Test Type: flow-through test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia (water flea)): 44 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Desmodesmus subspicatus (green algae)): 397 mg/l  
Exposure time: 72 h  
Test Type: static test

Toxicity to microorganisms : EC50 (Tetrahymena pyriformis): 356 mg/l  
Exposure time: 40 h  
Test Type: Growth inhibition

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 23 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: Reproduction Test  
GLP: yes

#### **butanone:**

Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): 2.993 mg/l  
Exposure time: 96 h  
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 308 mg/l  
Exposure time: 48 h  
Test Type: static test

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.972 mg/l  
Exposure time: 72 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Toxicity to microorganisms : EC50 (*Pseudomonas putida*): 1.150 mg/l  
Exposure time: 16 h  
Test Type: static test  
Method: DIN 38 412 Part 8

### ethyl acetate:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 212,5 mg/l  
Exposure time: 96 h  
Test Type: static test

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 154 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 2.500 mg/l  
Exposure time: 96 h

### butan-1-ol:

Toxicity to fish : LC50 (*Pimephales promelas* (fathead minnow)): 1.376 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203  
GLP: yes

Toxicity to daphnia and other aquatic invertebrates : EC50 (*Daphnia magna* (Water flea)): 1.328 mg/l  
Exposure time: 48 h  
Test Type: static test  
Method: OECD Test Guideline 202  
GLP: yes

Toxicity to algae/aquatic plants : EC50 (*Pseudokirchneriella subcapitata* (green algae)): 225 mg/l  
Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 201  
GLP: yes

Toxicity to microorganisms : EC10 (*Pseudomonas putida*): 2.476 mg/l  
Exposure time: 17 h  
Test Type: static test  
Method: DIN 38 412 Part 8

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 4,1 mg/l  
Exposure time: 21 d  
Species: *Daphnia magna* (Water flea)  
Test Type: semi-static test  
Method: OECD Test Guideline 211  
GLP: yes

### ethylene glycol monobutyl ether:

Toxicity to fish : LC50 (*Oncorhynchus mykiss* (rainbow trout)): 1.474 mg/l



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Exposure time: 96 h  
Test Type: static test  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 1.550 mg/l  
Exposure time: 48 h  
Test Type: Immobilization  
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): 1.840 mg/l  
Exposure time: 72 h  
Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOEC: > 100 mg/l  
Exposure time: 21 d  
Species: Danio rerio (zebra fish)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC: 100 mg/l  
Exposure time: 21 d  
Species: Daphnia magna (Water flea)  
Test Type: Reproduction Test  
Method: OECD Test Guideline 211

### 12.2 Persistence and degradability

#### **Product:**

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

#### **Components:**

##### **n-butyl acetate:**

Biodegradability : Test Type: Primary biodegradation  
Result: rapidly biodegradable  
Biodegradation: 83 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D

##### **butanone:**

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: 98 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D  
GLP: yes

##### **ethyl acetate:**

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Biodegradability : Result: rapidly biodegradable

### butan-1-ol:

Biodegradability : Test Type: aerobic  
Inoculum: activated sludge  
Result: rapidly biodegradable  
Biodegradation: > 92 %  
Exposure time: 28 d

### ethylene glycol monobutyl ether:

Biodegradability : Test Type: aerobic  
Result: rapidly biodegradable  
Biodegradation: 90 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301B

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).  
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

### Components:

#### n-butyl acetate:

Partition coefficient: n-octanol/water : log Pow: 2,3 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117  
GLP: yes

#### butanone:

Bioaccumulation : Remarks: Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

Partition coefficient: n-octanol/water : log Pow: 0,3 (40 °C)  
Method: OECD Test Guideline 117  
GLP: yes

#### ethyl acetate:

Partition coefficient: n-octanol/water : log Pow: 0,68 (25 °C)

#### butan-1-ol:

Partition coefficient: n-octanol/water : log Pow: 1 (25 °C)  
pH: 7  
Method: OECD Test Guideline 117

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

GLP: yes

### ethylene glycol monobutyl ether:

Bioaccumulation : Bioconcentration factor (BCF): 2,5

Partition coefficient: n-octanol/water : log Pow: 0,81 (25 °C)  
Method: OECD Test Guideline 107

### Graphite:

Partition coefficient: n-octanol/water : Remarks: No data available

## 12.4 Mobility in soil

### Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

### Components:

#### n-butyl acetate:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

#### butanone:

Assessment : Non-classified PBT substance. Non-classified vPvB substance

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Additional ecological information : No information on ecology is available.

## SECTION 13: Disposal considerations

### 13.1 Waste treatment methods

Product : The product should not be allowed to enter drains, water courses or the soil.  
Do not dispose of with domestic refuse.  
Dispose of as hazardous waste in compliance with local and national regulations.

Waste codes should be assigned by the user based on the application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.  
Dispose of waste product or used containers according to local regulations.

The following Waste Codes are only suggestions:

Waste Code : used product, unused product  
08 01 11\*, waste paint and varnish containing organic solvents or other hazardous substances  
  
uncleaned packagings  
15 01 10, packaging containing residues of or contaminated by hazardous substances

## SECTION 14: Transport information

### 14.1 UN number or ID number

ADN : UN 1263  
ADR : UN 1263  
RID : UN 1263  
IMDG : UN 1263  
IATA : UN 1263

### 14.2 UN proper shipping name

ADN : PAINT  
ADR : PAINT  
RID : PAINT

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

**IMDG** : PAINT

**IATA** : Paint

### 14.3 Transport hazard class(es)

**ADN** : 3

**ADR** : 3

**RID** : 3

**IMDG** : 3

**IATA** : 3

### 14.4 Packing group

#### ADN

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

#### ADR

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3  
Tunnel restriction code : (D/E)

#### RID

Packing group : II  
Classification Code : F1  
Hazard Identification Number : 33  
Labels : 3

#### IMDG

Packing group : II  
Labels : 3  
EmS Code : F-E, S-E

#### IATA (Cargo)

Packing instruction (cargo aircraft) : 364  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

#### IATA (Passenger)

Packing instruction (passenger aircraft) : 353  
Packing instruction (LQ) : Y341  
Packing group : II  
Labels : Flammable Liquids

### 14.5 Environmental hazards

#### ADN

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

Environmentally hazardous : no

### ADR

Environmentally hazardous : no

### RID

Environmentally hazardous : no

### IMDG

Marine pollutant : no

### 14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks : Not applicable for product as supplied.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Conditions of restriction for the following entries should be considered:  
Number on list 3

ethylene glycol monobutyl ether  
(Number on list 3)  
formaldehyde (Number on list 72,  
28)

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC) : This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV) (EU. REACH-Annex XIV) : Not applicable

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009) : Not applicable

Regulation (EU) 2019/1021 on persistent organic pollutants (recast) (EU POP) : Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals (EU PIC) : Not applicable

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

: P5c

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances. P5c FLAMMABLE LIQUIDS

Occupational Illnesses (R-461-3, France) : 84, 25

Reinforced medical supervision (R4624-18) : The product has no CMR properties

Installations classified for the protection of the environment (Environment Code R511-9) : 4331, 1436

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 69,92 %  
Volatile CMR compounds: 0,01 %

### Other regulations:

Take note of Directive 92/85/EEC regarding maternity protection or stricter national regulations, where applicable.

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

## 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: Other information

### Full text of H-Statements

EUH066	: Repeated exposure may cause skin dryness or cracking.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
EUH066	: Repeated exposure may cause skin dryness or cracking.

# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

### Full text of other abbreviations

2000/39/EC	:	Europe. Commission Directive 2000/39/EC establishing a first list of indicative occupational exposure limit values
2017/164/EU	:	Europe. Commission Directive 2017/164/EU establishing a fourth list of indicative occupational exposure limit values
2019/1831/EU	:	Europe. Commission Directive 2019/1831/EU establishing a fifth list of indicative occupational exposure limit values
FR VLE	:	France. Occupational Exposure Limits (INRS)
2000/39/EC / TWA	:	Limit Value - eight hours
2000/39/EC / STEL	:	Short term exposure limit
2017/164/EU / STEL	:	Short term exposure limit
2017/164/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / TWA	:	Limit Value - eight hours
2019/1831/EU / STEL	:	Short term exposure limit
FR VLE / VME	:	Time Weighted Average
FR VLE / VLCT (VLE)	:	Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet;



# SAFETY DATA SHEET

according to Regulation (EC) No. 1907/2006 - FR  
(Commission Regulation (EU) 2020/878)



## OKS 589

Version	Revision Date:	Date of last issue: 20.08.2018	Print Date:
1.2	11.05.2022	Date of first issue: 09.07.2016	12.05.2022

SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECl - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

#### Classification of the mixture:

Flam. Liq. 2	H225
Eye Dam. 1	H318
STOT SE 3	H336

#### Classification procedure:

Based on product data or assessment
Calculation method
Calculation method

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.