according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 14.11.2022 Date of first issue: 09.07.2016 14.11.2022 1.3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Product name : OKS 621

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub-: Auxiliary

stance/Mixture

Recommended restrictions

on use

Restricted to professional users.

1.3 Details of the supplier of the safety data sheet

Company OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person mcm@oks-germany.com

responsible for the SDS

Material Compliance Management

National contact

1.4 Emergency telephone number

Emergency telephone num-CIAV - Information Centre of Antipoison

ber (+351) 800 250 250 (free 24/7 service)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H315: Causes skin irritation. Skin irritation, Category 2

Specific target organ toxicity - single ex-

posure, Category 3, Central nervous

system

H336: May cause drowsiness or dizziness.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters air-

ways.

Long-term (chronic) aquatic hazard, Cat-H411: Toxic to aquatic life with long lasting effects.

egory 2

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters air-

ways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Supplemental Hazard

Statements

EUH018

In use may form flammable/explosive

vapour-air mixture.

Precautionary statements : Prevention:

P210 Keep away from heat, hot surfaces, sparks.

open flames and other ignition sources. No

smoking.

P211 Do not spray on an open flame or other

ignition source.

P251 Do not pierce or burn, even after use.
P273 Avoid release to the environment.

Response:

P301 + P310 IF SWALLOWED: Immediately call a

POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Hazardous components which must be listed on the label:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane

Kerosine (petroleum), hydrodesulfurized; Kerosine — unspecified

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Active agent with propellant and solvent.

Components

| Chemical name | CAS-No. EC-No. Index-No. Registration number | Classification | specific concentration limit M-Factor Notes Acute toxicity estimate | Concentration (% w/w) |
|--|---|--|---|--------------------------|
| Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane | 921-024-6 01-2119475514-35- XXXX | Flam. Liq.2; H225 Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411 | | >= 10 - < 20 |
| propane | 74-98-6 200-827-9 601-003-00-5 01-2119486944-21- XXXX | Flam. Gas1A; H220 Press. GasCompr. Gas; H280 | Note U (table 3.1) | >= 10 - < 20 |
| Kerosine (petroleum), hydrodesulfurized; Kerosine — unspeci- fied | 64742-81-0 265-184-9 649-423-00-8 01-2119462828-25 | Skin Irrit.2; H315 STOT SE3; H336 Asp. Tox.1; H304 Aquatic Chronic2; H411 | | >= 2,5 - < 10 |
| Substances with a workplace exposure limit : | | | | |
| butane | 106-97-8 203-448-7 | Flam. Gas1A; H220 | | >= 30 - < 50 |

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

VersionRevision Date:Date of last issue: 21.01.2021Print Date:1.314.11.2022Date of first issue: 09.07.201614.11.2022

| | 601-004-00-0 01-2119474691-32- XXXX | Press. GasCompr. Gas; H280 | Note U (table 3.1), Note C | |
|-----------|---|--|----------------------------|--------------|
| isobutane | 75-28-5 200-857-2 | Flam. Gas1A; H220 Press. GasCompr. | Note U (table | >= 10 - < 20 |
| | 601-004-00-0 01-2119485395-27- XXXX | Gas; H280 | 3.1), Note C | |

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

If inhaled : Call a physician or poison control centre immediately.

Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial respira-

tion.

In case of skin contact : Take off all contaminated clothing immediately.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse. Wash off immediately with plenty of water.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

If accidentally swallowed obtain immediate medical attention.

Keep respiratory tract clear. Do NOT induce vomiting. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Inhalation may provoke the following symptoms:

Unconsciousness

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

Dizziness Drowsiness Headache Nausea Tiredness

Skin contact may provoke the following symptoms:

Erythema

Aspiration may cause pulmonary oedema and pneumonitis.

Risks : Central nervous system depression

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Causes skin irritation.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

5.2 Special hazards arising from the substance or mixture

Specific hazards during fire-

fighting

Fire Hazard

Do not let product enter drains.

In use, may form flammable/explosive vapour-air mixture.

Container may explode if heated.

Contains gas under pressure; may explode if heated.

Beware of vapours accumulating to form explosive concentra-

tions. Vapours can accumulate in low areas.

Hazardous combustion prod: :

ucts

Carbon oxides

5.3 Advice for firefighters

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment. Exposure to decomposi-

tion products may be a hazard to health.

Further information : Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : Evacuate personnel to safe areas.

Ensure adequate ventilation. Remove all sources of ignition. Do not breathe vapours or spray mist.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray. Refer to protective measures listed in sections 7 and 8. Only qualified personnel equipped with suitable protective

equipment may intervene.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Contain spillage, and then collect with non-combustible ab-

sorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local

/ national regulations (see section 13).

Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

6.4 Reference to other sections

For personal protection see section 8.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling : Use only in an area containing explosion proof equipment.

Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces.

Smoking, eating and drinking should be prohibited in the ap-

plication area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

Do not ingest.

Do not use sparking tools.

Do not enter areas where used or stored until adequately ven-

tilated.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn,

even after use.

Advice on protection against :

fire and explosion

Keep away from heat and sources of ignition.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects. Do not store together with oxidizing and self-igniting products. Store in accordance with the particular na-

tional regulations.

7.3 Specific end use(s)

Specific use(s) : Specific instructions for handling, not required.

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

| Components | CAS-No. | Value type (Form of exposure) | Control parameters | Basis |
|--|--|-------------------------------|-----------------------------------|------------------------|
| butane | 106-97-8 | VLE_CD | 1.000 ppm | PT OEL (2014-11-14) |
| isobutane | 75-28-5 | VLE_CD | 1.000 ppm | PT OEL (2014-11-14) |
| Kerosine (petrole- um), hydrodesulfu- rized; Kerosine — unspecified | 64742-81-0 | VLE-MP (Va- pour) | 200 mg/m3 (total hydrocarbons) | PT OEL (2014-11-14) |
| | Further information: Danger for absorption by the skin, Substances of which the carcinogenic effect has been confirmed in laboratory tests on animals with confirmed relevance for humans. | | | |

Derived No Effect Level (DNEL) according to Regulation (EC) No. 1907/2006:

| Substance name | End Use | Exposure routes | Potential health ef- | Value |
|----------------|---------|-----------------|----------------------|-------|
| | | | fects | |



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

| Hydrocarbons, C6- C7, n-alkanes, isoal- kanes, cyclics, <5% n-hexane | Workers | Skin contact | Long-term systemic effects | 773 mg/kg bw/day |
|---|---------|--------------|----------------------------|---------------------|
| | Workers | Inhalation | Long-term systemic effects | 2035 mg/m3 |

8.2 Exposure controls

Engineering measures

Use only in an area equipped with explosion proof exhaust ventilation.

Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Eye protection : Safety glasses with side-shields

Hand protection

Material : Nitrile rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374

derived from it.

Skin and body protection : Choose body protection in relation to its type, to the concen-

tration and amount of dangerous substances, and to the spe-

cific work-place.

Respiratory protection : Use respiratory protection unless adequate local exhaust ven-

tilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Recommended Filter type:

Organic gas and low boiling vapour type (AX)

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state : aerosol

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

 Version
 Revision Date:
 Date of last issue: 21.01.2021
 Print Date: 1.3

 1.3
 14.11.2022
 Date of first issue: 09.07.2016
 14.11.2022

Colour : colourless

Odour : characteristic

Odour Threshold : No data available

Melting point/range : No data available

Boiling point/boiling range : -161 °C (1.013 hPa)

Flammability (solid, gas) : Extremely flammable aerosol.

Upper explosion limit / Upper

flammability limit

10,9 %(V)

Lower explosion limit / Lower :

flammability limit

0,6 %(V)

Flash point : -60 °C

Method: DIN 51755, closed cup

Auto-ignition temperature : 230 °C

Decomposition temperature : No data available

pH : Not applicable

substance/mixture is non-soluble (in water)

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20,5 mm2/s (40 °C)

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Vapour pressure : 4.000 hPa (20 °C)

Relative density : 0,6 (20 °C)

Reference substance: Water The value is calculated

Density : 0,60 g/cm3

(20 °C)

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

Bulk density : No data available

Relative vapour density : No data available

9.2 Other information

Explosives : In use may form flammable/explosive vapour-air mixture.

Oxidizing properties : No data available

Self-ignition : not auto-flammable

Metal corrosion rate : Not corrosive to metals

Evaporation rate : No data available

Sublimation point : No data available

SECTION 10: Stability and reactivity

10.1 Reactivity

No hazards to be specially mentioned.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

10.5 Incompatible materials

Materials to avoid : Oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

SECTION 11: Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity : Remarks: Effects due to ingestion may include:

Symptoms: Central nervous system depression

Acute inhalation toxicity : Remarks: Respiration of solvent vapour may cause dizziness.

Symptoms: Inhalation may provoke the following symptoms:, Respiratory disorder, Dizziness, Drowsiness, Vomiting, Fa-

tigue, Vertigo, Central nervous system depression

Acute dermal toxicity : Symptoms: Redness, Local irritation

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Acute oral toxicity : LD50 (Rat): > 5.840 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Acute inhalation toxicity : LC50 (Rat): > 25,2 mg/l

Exposure time: 4 h
Test atmosphere: vapour

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Acute dermal toxicity : LD50 (Rat): > 2,8 g/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Kerosine (petroleum), hydrodesulfurized; Kerosine — unspecified:

Acute inhalation toxicity : Assessment: The substance or mixture is classified as specific

target organ toxicant, single exposure, category 3 with narcot-

ic effects.

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : Irritating to skin.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : Irritating to skin.

Method : OECD Test Guideline 404

Result : Irritating to skin.

Kerosine (petroleum), hydrodesulfurized; Kerosine — unspecified:

Result : Skin irritation

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Species : Rabbit

Assessment : No eye irritation Result : No eye irritation

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Test Type : Maximisation Test

Exposure routes : Dermal Species : Guinea pig

Assessment : Does not cause skin sensitisation.

Method : OECD Test Guideline 406

Result : Did not cause sensitisation on laboratory animals.



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Test system: Rodent cell line Method: OECD Test Guideline 473

Result: negative

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal develop-

ment

Remarks: No data available

STOT - single exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment : May cause drowsiness or dizziness.

Kerosine (petroleum), hydrodesulfurized; Kerosine — unspecified:

Exposure routes : Inhalation

Assessment : The substance or mixture is classified as specific target organ

toxicant, single exposure, category 3 with narcotic effects.

STOT - repeated exposure

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Exposure routes : inhalation (vapour)

Assessment : No significant health effects observed in animals at concentra-

tions of 1 mg/l/6h/d or less.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 14.11.2022 Date of first issue: 09.07.2016 14.11.2022 1.3

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

May be fatal if swallowed and enters airways.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Kerosine (petroleum), hydrodesulfurized; Kerosine — unspecified:

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

Endocrine disrupting properties

Product:

The substance/mixture does not contain components consid-Assessment

> ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

Further information

Product:

Remarks Ingestion causes irritation of upper respiratory system and

gastrointestinal disturbance.

SECTION 12: Ecological information

12.1 Toxicity

Product:

Toxicity to fish Remarks: Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Toxicity to daphnia and other : Remarks: No data available

aquatic invertebrates



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

Toxicity to algae/aquatic

plants

: Remarks: No data available

Toxicity to microorganisms

Remarks: No data available

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 22 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

GLP: yes

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): 3 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

GLP: yes

Toxicity to algae/aquatic

plants

EbC50 (Pseudokirchneriella subcapitata (green algae)): 26

mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

Kerosine (petroleum), hydrodesulfurized; Kerosine — unspecified:

Ecotoxicology Assessment

Acute aquatic toxicity : Toxic to aquatic life.

Chronic aquatic toxicity : Toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removabil- : Remarks: No data available

ıty

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Biodegradability : Result: Readily biodegradable.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very

persistent and very bioaccumulating (vPvB).

Components:

propane:

Partition coefficient: n-

octanol/water

log Pow: 2,36

butane:

Partition coefficient: n-

octanol/water

log Pow: 2,89

Method: OECD Test Guideline 107

isobutane:

Partition coefficient: n-

octanol/water

log Pow: 2,88

Method: OECD Test Guideline 107

12.4 Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environ-

mental compartments

Remarks: No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This substance/mixture contains no components considered

to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of

0.1% or higher.

12.6 Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components consid-

ered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at

levels of 0.1% or higher.

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

VersionRevision Date:Date of last issue: 21.01.2021Print Date:1.314.11.2022Date of first issue: 09.07.201614.11.2022

12.7 Other adverse effects

Product:

Additional ecological infor-

mation

: Toxic to aquatic life with long lasting effects.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Waste codes should be assigned by the user based on the

application for which the product was used.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.

The following Waste Codes are only suggestions:

Waste Code : unused product, packagings not completely emptied

16 05 04*, gases in pressure containers (including halons)

containing hazardous substances

SECTION 14: Transport information

14.1 UN number or ID number

ADR : UN 1950
RID : UN 1950
IMDG : UN 1950
IATA : UN 1950

14.2 UN proper shipping name

ADR : AEROSOLS
RID : AEROSOLS
IMDG : AEROSOLS

(naphtha (petroleum), hydrotreated light,)

IATA : Aerosols, flammable

14.3 Transport hazard class(es)

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

ADR : 2
RID : 2
IMDG : 2.1
IATA : 2.1

14.4 Packing group

ADR

Packing group : Not assigned by regulation

Classification Code : 5F Labels : 2.1 Tunnel restriction code : (D)

RID

Packing group : Not assigned by regulation

Classification Code : 5F Hazard Identification Number : 23 Labels : 2.1

IMDG

Packing group : Not assigned by regulation

Labels : 2.1 EmS Code : F-D, S-U

IATA (Cargo)

Packing instruction (cargo : 203

aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

IATA (Passenger)

Packing instruction (passen- : 203

ger aircraft)

Packing instruction (LQ) : Y203

Packing group : Not assigned by regulation

Labels : Flammable Gas

14.5 Environmental hazards

ADR

Environmentally hazardous : yes

RID

Environmentally hazardous : yes

IMDG

Marine pollutant : yes

14.6 Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

14.7 Maritime transport in bulk according to IMO instruments



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

Remarks : Not applicable for product as supplied.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII) : Not applicable

REACH - Candidate List of Substances of Very High Concern for Authorisation (Article 59). (EU SVHC)

This product does not contain substances of very high concern (Regulation (EC) No 1907/2006 (REACH), Article 57).

REACH - List of substances subject to authorisation (Annex XIV)

Not applicable

(EU. REACH-Annex XIV)

Regulation (EC) No 1005/2009 on substances that deplete the ozone layer (EC 1005/2009)

Not applicable

Regulation (EU) 2019/1021 on persistent organic pollu-

tants (recast) (EU POP)

(EU PIC)

: Not applicable

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

Not applicable

: P2

Seveso III: Directive 2012/18/EU of the European Parliament and of the Council on the control of major-accident hazards involving dangerous substances.

P3a FLAMMABLE AEROSOLS

E2 ENVIRONMENTAL HAZARDS

18 Liquefied extremely flammable gases (including LPG) and natural gas

Petroleum products: (a) gasolines and naphthas, (b) kerosenes (including jet fuels), (c) gas oils (including diesel fuels, home



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

heating oils and gas oil blending streams),(d) heavy fuel oils (e) alternative fuels serving the same purposes and with similar properties as regards flammability and environmental hazards as the products referred to in points (a)

to (d)

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial

emissions (integrated pollution prevention and control) Volatile organic compounds (VOC) content: 100 %

Other regulations:

Take note of Directive 94/33/EC on the protection of young people at work or stricter national regulations, where applicable.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: Other information

Full text of H-Statements

H220 : Extremely flammable gas.

H225 : Highly flammable liquid and vapour.

H280 : Contains gas under pressure; may explode if heated.

H304 : May be fatal if swallowed and enters airways.

H315 : Causes skin irritation.

H336 : May cause drowsiness or dizziness.

H411 : Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Note C : Some organic substances may be marketed either in a specif-

ic isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the sub-

stance is a specific isomer or a mixture of isomers.

Note U (table 3.1) : When put on the market gases have to be classified as "Gas-

es under pressure", in one of the groups compressed gas, liquefied gas, refrigerated liquefied gas or dissolved gas. The group depends on the physical state in which the gas is packaged and therefore has to be assigned case by case. The following codes are assigned: Press. Gas (Comp.) Press. Gas (Liq.) Press. Gas (Ref. Liq.) Press. Gas (Diss.) Aerosols shall not be classified as gases under pressure (See Annex I, Part

according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

 Version
 Revision Date:
 Date of last issue: 21.01.2021
 Print Date:

 1.3
 14.11.2022
 Date of first issue: 09.07.2016
 14.11.2022

2, Section 2.3.2.1, Note 2).

PT OEL : Portugal. Security and Health at the Workplace - Occupational

exposure limits of chemical agents

PT OEL / VLE-MP : Time Weighted Average PT OEL / VLE CD : Short Term Exposure Limit

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail: SADT - Self-Accelerating Decomposition Temperature: SDS - Safety Data Sheet: SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI -Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Classification of the mixture: Classification procedure:

| Aerosol 1 | H222, H229 | Based on product data or assessment |
|-------------------|------------|-------------------------------------|
| Skin Irrit. 2 | H315 | Calculation method |
| STOT SE 3 | H336 | Calculation method |
| Asp. Tox. 1 | H304 | Based on product data or assessment |
| Aquatic Chronic 2 | H411 | Calculation method |

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particu-



according to Regulation (EC) No. 1907/2006 - PT (Commission Regulation (EU) 2020/878)



OKS 621

Version Revision Date: Date of last issue: 21.01.2021 Print Date: 1.3 14.11.2022 Date of first issue: 09.07.2016 14.11.2022

lar public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.