according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : OKS 701

Chemical nature : Active substance with propellant

Synthetic hydrocarbon oil

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH

Ganghoferstr. 47

D-82216 Maisach-Gernlinden Tel.: +49 8142 3051 500 Fax.: +49 8142 3051 599 info@oks-germany.com

E-mail address of person

son : mcm@oks-germany.com

responsible for the SDS Material Compliance Management

National contact :

Emergency telephone number : +86 532 8388 9090 (NRCC, only for hazardous chemicals)

+86 21 69225521

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant spray

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: aerosolColour: brownOdour: characteristic

Extremely flammable aerosol. Pressurised container: May burst if heated. May be fatal if

swallowed and enters airways.

GHS Classification

Aerosols : Category 1

Aspiration hazard : Category 1

GHS label elements



according to GB/T 16483 and GB/T 17519 CN



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

Hazard pictograms :





Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.

H229 Pressurised container: May burst if heated. H304 May be fatal if swallowed and enters airways.

Precautionary statements : Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces.

No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON

CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to

temperatures exceeding 50 °C/ 122 °F.

Disposal:

P501 Dispose of contents/containers according the local

government requirements.

Physical and chemical hazards

Extremely flammable aerosol. Pressurised container: May burst if heated.

Health hazards

May be fatal if swallowed and enters airways.

Environmental hazards

Not classified based on available information.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components



2/16

according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

Chemical name	CAS-No.	Concentration (% w/w)
Butene, polymers	9003-29-6	>= 30 -< 50
Butane	106-97-8	>= 30 -< 50
propane	74-98-6	>= 1 -< 10
Sulfonic acids, petroleum, calcium salts	61789-86-4	>= 1 -< 10
Isobutane	75-28-5	>= 1 -< 10

4. FIRST AID MEASURES

If inhaled : Remove person to fresh air. If signs/symptoms continue, get

medical attention.

Keep patient warm and at rest.

If unconscious, place in recovery position and seek medical

advice.

Keep respiratory tract clear.

If breathing is irregular or stopped, administer artificial

respiration.

In case of skin contact : Take off all contaminated clothing immediately.

Wash off immediately with soap and plenty of water.

Get medical attention immediately if irritation develops and

persists.

Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : Rinse immediately with plenty of water, also under the eyelids,

for at least 10 minutes.

If eye irritation persists, consult a specialist.

If swallowed : Move the victim to fresh air.

Keep respiratory tract clear. Do NOT induce vomiting. Obtain medical attention. Rinse mouth with water.

Aspiration hazard if swallowed - can enter lungs and cause

damage.

Most important symptoms and effects, both acute and

delayed

Risk of product entering the lungs on vomiting after ingestion.

Health injuries may be delayed.

Inhalation may provoke the following symptoms:

Unconsciousness

Dizziness Drowsiness Headache Nausea Tiredness

Aspiration may cause pulmonary oedema and pneumonitis.

Notes to physician : Treat symptomatically.

according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

5. FIREFIGHTING MEASURES

Suitable extinguishing media : ABC powder

Unsuitable extinguishing

media

High volume water jet

Specific hazards during

firefighting

: Fire Hazard

Do not let product enter drains.

Contains gas under pressure; may explode if heated. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion

products

Carbon oxides

Nitrogen oxides (NOx)

Sulphur oxides

Specific extinguishing

methods

Standard procedure for chemical fires.

Collect contaminated fire extinguishing water separately. This

must not be discharged into drains. Cool containers/tanks with water spray.

Special protective equipment :

for firefighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

Exposure to decomposition products may be a hazard to

health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Evacuate personnel to safe areas. Ensure adequate ventilation.

Remove all sources of ignition. Do not breathe vapours or spray mist.

Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Try to prevent the material from entering drains or water

Try to prevent the material norm entening drains of

courses.

Prevent further leakage or spillage if safe to do so. Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to

local / national regulations (see section 13). Keep in suitable, closed containers for disposal.

Non-sparking tools should be used.

Prevention of secondary

hazards

Only qualified personnel equipped with suitable protective

equipment may intervene.

according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

7. HANDLING AND STORAGE

Handling

Advice on safe handling : Do not use in areas without adequate ventilation.

Do not breathe vapours or spray mist.

In case of insufficient ventilation, wear suitable respiratory

equipment.

Avoid contact with skin and eyes. For personal protection see section 8.

Keep away from fire, sparks and heated surfaces. Smoking, eating and drinking should be prohibited in the

application area.

Wash hands and face before breaks and immediately after

handling the product.

Do not get in eyes or mouth or on skin.

Do not get on skin or clothing.

Do not ingest.

Do not use sparking tools.

These safety instructions also apply to empty packaging which

may still contain product residues.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or

burn, even after use.

Avoidance of contact : Oxidizing agents

Storage

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun

exposure and temperatures over 50 $^{\circ}$ C. Do not open by force or throw into fire even after use. Do not spray on flames or

red-hot objects.

Store in accordance with the particular national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Butane	106-97-8	STEL	1,000 ppm	ACGIH (2018-03-20)
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH (2018-03-20)



according to GB/T 16483 and GB/T 17519 CN



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

Engineering measures : Use only in an area equipped with explosion proof exhaust

ventilation.

Handle only in a place equipped with local exhaust (or other

appropriate exhaust).

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust

ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Short term only

Filter type : Filter type A-P

Eye/face protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the

concentration and amount of dangerous substances, and to

the specific work-place.

Hand protection

Material : Fluorinated rubber

Break through time : > 10 min Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends

amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each

case.

Protective measures : The type of protective equipment must be selected according

to the concentration and amount of the dangerous substance

at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after

handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : brown

Odour : characteristic

Odour Threshold : No data available

according to GB/T 16483 and GB/T 17519 CN



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

pH : Not applicable

substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : -44 °C

(1,013 hPa)

Flash point : -97 °C

Method: Abel-Pensky, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : No data available

Upper explosion limit / Upper

flammability limit

10.5 %(V)

Lower explosion limit / Lower

flammability limit

1.5 %(V)

Vapour pressure : 5,000 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0.698 (20 °C)

Reference substance: Water The value is calculated

Density : 0.70 g/cm3 (20 °C)

Bulk density : No data available

Solubility(ies)

Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

Viscosity

according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

Viscosity, dynamic : No data available

Viscosity, kinematic : < 20.5 mm2/s (40 °C)

Explosive properties : Not explosive

Oxidizing properties : No data available

Sublimation point : No data available

Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.

Chemical stability : Stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid : Heat, flames and sparks.

Strong sunlight for prolonged periods.

Risk of receptacle bursting.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.

Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,

Respiratory disorder

Acute dermal toxicity : Remarks: This information is not available.

according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

Components:

Butene, polymers:

Acute oral toxicity : LD50 (Rat): > 34,600 mg/kg

Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 10,250 mg/kg

Butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l

Exposure time: 4 h Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Sulfonic acids, petroleum, calcium salts:

Assessment : The product is a skin sensitiser, sub-category 1B.

according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development

: Remarks: No data available

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Butene, polymers:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Information given is based on data on the components and

the toxicology of similar products.

according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish

Remarks: No data available

Toxicity to daphnia and other :

aquatic invertebrates

Remarks: No data available

Toxicity to algae/aquatic

plants

Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Butene, polymers:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1,000 mg/l

Exposure time: 96 h

Toxicity to daphnia and other :

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 1,000 mg/l

Exposure time: 48 h
Test Type: Immobilization

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical

removability

Remarks: No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to

be persistent, bioaccumulating and toxic (PBT).

This mixture contains no substance considered to be very



according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

persistent and very bioaccumulating (vPvB).

Components:

Butane:

Partition coefficient: n-

octanol/water

log Pow: 2.89

Method: OECD Test Guideline 107

propane:

Partition coefficient: n-

octanol/water

log Pow: 2.36

Isobutane:

Partition coefficient: n-

octanol/water

log Pow: 2.88

Method: OECD Test Guideline 107

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among

environmental compartments

Remarks: No data available

Other adverse effects

Product:

Additional ecological

information

No information on ecology is available.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Do not dispose of with domestic refuse.

Dispose of as hazardous waste in compliance with local and

national regulations.

Contaminated packaging : Packaging that is not properly emptied must be disposed of as

the unused product.

Offer empty spray cans to an established disposal company. Pressurized container: Do not pierce or burn, even after use.



according to GB/T 16483 and GB/T 17519



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

IATA-DGR

UN/ID No. : UN 1950

Proper shipping name : Aerosols, flammable

Class : 2.1

Packing group : Not assigned by regulation

203

Labels : Flammable Gas

Packing instruction (cargo

aircraft)

Packing instruction : 203

(passenger aircraft)

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

GB 6944/12268

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1

Packing group : Not assigned by regulation

Labels : 2.1

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.



according to GB/T 16483 and GB/T 17519



OKS 701

Version Date of last issue: 2019-07-31 Revision Date:

2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18 3.3

15. REGULATORY INFORMATION

National regulatory information Law on the Prevention and Control of Occupational Diseases

Regulations on Safety Management of Hazardous Chemicals

Catalogue of Hazardous Chemicals

Product name		Status	Reference number
OKS 701		Listed	2828
	•		

List of ingredients	CAS-No.	Status	Reference number
Butane	106-97-8	Listed	2778
propane	74-98-6	Listed	139
Isobutane	75-28-5	Listed	2707

Identification of Major Hazard Installations for Hazardous Chemicals (GB 18218)

Category Threshold quantity

Aerosols 150 t

Hazardous Chemicals for Priority Management under

SAWS

: Not applicable

Regulations on Labour Protection in Workplaces where Toxic Substances are Used

Catalogue of Highly Toxic Chemicals : Not applicable

Regulation of Environmental Management on the First Import of Chemicals and the Import and Export of Toxic Chemicals

China Severely Restricted Toxic Chemicals for Import : Not applicable

and Export

International Regulations

Montreal Protocol Not applicable

Rotterdam Convention (Prior Informed Consent) Not applicable

Stockholm Convention (Persistent Organic Pollutants) Not applicable

according to GB/T 16483 and GB/T 17519 CN



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

The components of this product are reported in the following inventories:

IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

Date format : yyyy/mm/dd

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

ACGIH / STEL : Short-term exposure limit

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR -Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO -International Maritime Organization: ISHL - Industrial Safety and Health Law (Japan): ISO -International Organisation for Standardization: KECI - Korea Existing Chemicals Inventory: LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

Disclaimer



according to GB/T 16483 and GB/T 17519 CN



OKS 701

Version Revision Date: Date of last issue: 2019-07-31

3.3 2022-10-18 Date of first issue: 2014-04-22 Print Date: 2022-10-18

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.