

OKS 701

Version	Revision Date:	Date of last issue:	Print Date:
3.3	18.10.2022	31.07.2019 Date of first issue: 22.04.2014	18.10.2022

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Product name : OKS 701

Manufacturer or supplier's details

Company name of supplier : OKS Spezialschmierstoffe GmbH
Ganghoferstr. 47
D-82216 Maisach-Gernlinden
Tel.: +49 8142 3051 500
Fax.: +49 8142 3051 599
info@oks-germany.com

E-mail address of person responsible for the SDS : mcm@oks-germany.com
Material Compliance Management

Emergency telephone number : +7 495 628 1687
+49 8142 3051 517

Recommended use of the chemical and restrictions on use

Recommended use : Lubricant spray

Restrictions on use : Restricted to professional users.

2. HAZARDS IDENTIFICATION

GHS Classification (According to GOST 32423, GOST 32424 and GOST 32425)

Aerosols : Category 1

Aspiration hazard : Category 1

GHS-Labeling (According to GOST 31340)

Hazard pictograms :  

Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H304 May be fatal if swallowed and enters airways.

Precautionary statements : **Prevention:**
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

P251 Do not pierce or burn, even after use.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.

P331 Do NOT induce vomiting.

Storage:

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Other hazards which do not result in classification

None known.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Pure substance/mixture : Mixture

Chemical nature : Active substance with propellant
Synthetic hydrocarbon oil

Components

Chemical name	Concentration (% w/w)	Occupational Exposure Limits		CAS-No.	EC-No.
		MAC value mg/m ³ / TSEL value	Hazard Class		
Butene, polymers	>= 30 - < 50	No data available		9003-29-6	500-004-7
butane	>= 30 - < 50	MPC-TWA: 300 mg/m ³ Data Source: RU OEL MPC-STEL: 900 mg/m ³ Data Source: RU OEL	4 4	106-97-8	203-448-7
propane	>= 1 - < 10	No data available		74-98-6	200-827-9
Sulfonic acids, petroleum, calcium salts	>= 1 - < 10	No data available		61789-86-4	263-093-9
isobutane	>= 1 - < 10	No data available		75-28-5	200-857-2

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

4. FIRST AID MEASURES

- If inhaled : Remove person to fresh air. If signs/symptoms continue, get medical attention.
Keep patient warm and at rest.
If unconscious, place in recovery position and seek medical advice.
Keep respiratory tract clear.
If breathing is irregular or stopped, administer artificial respiration.
- In case of skin contact : Take off all contaminated clothing immediately.
Wash off immediately with soap and plenty of water.
Get medical attention immediately if irritation develops and persists.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : Rinse immediately with plenty of water, also under the eyelids, for at least 10 minutes.
If eye irritation persists, consult a specialist.
- If swallowed : Move the victim to fresh air.
Keep respiratory tract clear.
Do NOT induce vomiting.
Obtain medical attention.
Rinse mouth with water.
Aspiration hazard if swallowed - can enter lungs and cause damage.
- Most important symptoms and effects, both acute and delayed : Risk of product entering the lungs on vomiting after ingestion.
Health injuries may be delayed.
Inhalation may provoke the following symptoms:
Unconsciousness
Dizziness
Drowsiness
Headache
Nausea
Tiredness
Aspiration may cause pulmonary oedema and pneumonitis.
- Notes to physician : Treat symptomatically.

5. FIREFIGHTING MEASURES

Flammable properties

- Flash point : -97 °C
Method: Abel-Pensky, closed cup

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

Ignition temperature : No data available

Upper explosion limit / Upper flammability limit : 10,5 %(V)

Lower explosion limit / Lower flammability limit : 1,5 %(V)

Flammability (solid, gas) : Extremely flammable aerosol.

Suitable extinguishing media : ABC powder

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Fire Hazard
Do not let product enter drains.
Contains gas under pressure; may explode if heated.
Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

Hazardous combustion products : Carbon oxides
Nitrogen oxides (NOx)
Sulphur oxides

Further information : Standard procedure for chemical fires.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Cool containers/tanks with water spray.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
Exposure to decomposition products may be a hazard to health.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Ensure adequate ventilation.
Remove all sources of ignition.
Do not breathe vapours or spray mist.
Refer to protective measures listed in sections 7 and 8.
Only qualified personnel equipped with suitable protective equipment may intervene.

Environmental precautions : Try to prevent the material from entering drains or water courses.
Prevent further leakage or spillage if safe to do so.
Local authorities should be advised if significant spillages cannot be contained.

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

Methods and materials for containment and cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Keep in suitable, closed containers for disposal.
Non-sparking tools should be used.

7. HANDLING AND STORAGE

Advice on safe handling : Do not use in areas without adequate ventilation.
Do not breathe vapours or spray mist.
In case of insufficient ventilation, wear suitable respiratory equipment.
Avoid contact with skin and eyes.
For personal protection see section 8.
Keep away from fire, sparks and heated surfaces.
Smoking, eating and drinking should be prohibited in the application area.
Wash hands and face before breaks and immediately after handling the product.
Do not get in eyes or mouth or on skin.
Do not get on skin or clothing.
Do not ingest.
Do not use sparking tools.
These safety instructions also apply to empty packaging which may still contain product residues.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

Conditions for safe storage : BEWARE: Aerosol is pressurized. Keep away from direct sun exposure and temperatures over 50 °C. Do not open by force or throw into fire even after use. Do not spray on flames or red-hot objects.
Store in accordance with the particular national regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Data Source
butane	106-97-8	MPC-TWA (vapour and/or gas)	300 mg/m ³	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

		MPC-STEL (vapour and/or gas)	900 mg/m3	RU OEL (2021-02-03)
Further information: Class 4 - Low hazard				

Engineering measures : Use only in an area equipped with explosion proof exhaust ventilation.
Handle only in a place equipped with local exhaust (or other appropriate exhaust).

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.
Short term only

Filter type : Filter type A-P

Hand protection

Material : Fluorinated rubber
Break through time : > 10 min
Protective index : Class 1

Remarks : Wear protective gloves. The break through time depends amongst other things on the material, the thickness and the type of glove and therefore has to be measured for each case.

Eye protection : Safety glasses with side-shields

Skin and body protection : Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.

Protective measures : The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures : Wash face, hands and any exposed skin thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

Colour : brown

Odour : characteristic

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

Odour Threshold : No data available

pH : Not applicable
substance/mixture is non-soluble (in water)

Melting point/range : No data available

Boiling point/boiling range : -44 °C
(1.013 hPa)

Flash point : -97 °C
Method: Abel-Pensky, closed cup

Evaporation rate : No data available

Flammability (solid, gas) : Extremely flammable aerosol.

Self-ignition : No data available

Upper explosion limit / Upper flammability limit : 10,5 %(V)

Lower explosion limit / Lower flammability limit : 1,5 %(V)

Vapour pressure : 5.000 hPa (20 °C)

Relative vapour density : No data available

Relative density : 0,698 (20 °C)
Reference substance: Water
The value is calculated

Density : 0,70 g/cm³ (20 °C)

Bulk density : No data available

Solubility(ies)
Water solubility : insoluble

Solubility in other solvents : No data available

Partition coefficient: n-octanol/water : No data available

Auto-ignition temperature : No data available

Decomposition temperature : No data available

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

Viscosity
Viscosity, dynamic : No data available
Viscosity, kinematic : < 20,5 mm²/s (40 °C)
Explosive properties : Not explosive
Oxidizing properties : No data available
Sublimation point : No data available
Metal corrosion rate : Not corrosive to metals

10. STABILITY AND REACTIVITY

Reactivity : No hazards to be specially mentioned.
Chemical stability : Stable under normal conditions.
Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.
Conditions to avoid : Heat, flames and sparks.
Strong sunlight for prolonged periods.
Risk of receptacle bursting.
Incompatible materials : Oxidizing agents
Hazardous decomposition products : No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION

Acute toxicity

Product:

Acute oral toxicity : Remarks: This information is not available.
Acute inhalation toxicity : Symptoms: Inhalation may provoke the following symptoms:,
Respiratory disorder
Acute dermal toxicity : Remarks: This information is not available.

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

Components:

Butene, polymers:

Acute oral toxicity : LD50 (Rat): > 34.600 mg/kg
Method: OECD Test Guideline 401

Acute dermal toxicity : LD50 (Rat): > 10.250 mg/kg

butane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

isobutane:

Acute inhalation toxicity : LC50 (Rat): 658 mg/l
Exposure time: 4 h
Test atmosphere: gas

Skin corrosion/irritation

Product:

Remarks : This information is not available.

Serious eye damage/eye irritation

Product:

Remarks : Contact with eyes may cause irritation.

Respiratory or skin sensitisation

Product:

Remarks : This information is not available.

Components:

Sulfonic acids, petroleum, calcium salts:

Assessment : The product is a skin sensitizer, sub-category 1B.

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Genotoxicity in vivo : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

Reproductive toxicity

Product:

Effects on fertility : Remarks: No data available

Effects on foetal development : Remarks: No data available

Repeated dose toxicity

Product:

Remarks : This information is not available.

Aspiration toxicity

Product:

May be fatal if swallowed and enters airways.

Components:

Butene, polymers:

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks : Information given is based on data on the components and the toxicology of similar products.

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

12. ECOLOGICAL INFORMATION

Ecotoxicity

Product:

Toxicity to fish : Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates : Remarks: No data available

Toxicity to algae/aquatic plants : Remarks: No data available

Toxicity to microorganisms : Remarks: No data available

Components:

Butene, polymers:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 1.000 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 1.000 mg/l
Exposure time: 48 h
Test Type: Immobilization

Persistence and degradability

Product:

Biodegradability : Remarks: No data available

Physico-chemical removability : Remarks: No data available

Bioaccumulative potential

Product:

Bioaccumulation : Remarks: This mixture contains no substance considered to be persistent, bioaccumulating and toxic (PBT).
This mixture contains no substance considered to be very persistent and very bioaccumulating (vPvB).

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

Components:

butane:

Partition coefficient: n-octanol/water : log Pow: 2,89
Method: OECD Test Guideline 107

propane:

Partition coefficient: n-octanol/water : log Pow: 2,36

isobutane:

Partition coefficient: n-octanol/water : log Pow: 2,88
Method: OECD Test Guideline 107

Mobility in soil

Product:

Mobility : Remarks: No data available

Distribution among environmental compartments : Remarks: No data available

Other adverse effects

Product:

Additional ecological information : No information on ecology is available.

Hygienic standards:

(Allowable concentration in air, water, including fishery waters, soil)

Components	Air	Water	Soil	Data Source
butane	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 200 mg/m ³ Limiting health hazard indicator: reflectory Hazard class: Class 4 - low hazard	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 1 List 5

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

propane	No data available	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 5
isobutane	Concentration that prevents irritation, reflex reactions, odors when exposed to 20-30 minutes - maximum one-time: 15 mg/m ³ Limiting health hazard indicator: reflectory Hazard class: Class 4 - low hazard	Maximum Permissible Concentration: 0,05 Milligrams per cubed decimeter Limiting health hazard indicator: toxic Hazard class: 3	No data available	List 1 List 5

For explanation of abbreviations see section 16.

13. DISPOSAL CONSIDERATIONS

Disposal methods

- Waste from residues : Do not dispose of with domestic refuse.
Dispose of as hazardous waste in compliance with local and national regulations.
- Contaminated packaging : Packaging that is not properly emptied must be disposed of as the unused product.
Offer empty spray cans to an established disposal company.
Pressurized container: Do not pierce or burn, even after use.
- The following Waste Codes are only suggestions:
- Waste Code : unused product, packagings not completely emptied
16 05 04*, gases in pressure containers (including halons)
containing hazardous substances

14. TRANSPORT INFORMATION

ADR
UN number : UN 1950

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

Proper shipping name : AEROSOLS
Class : 2
Packing group : Not assigned by regulation
Labels : 2.1
Tunnel restriction code : (D)

IATA-DGR

UN/ID No. : UN 1950
Proper shipping name : Aerosols, flammable
Class : 2.1
Packing group : Not assigned by regulation
Labels : Flammable Gas
Packing instruction (cargo aircraft) : 203
Packing instruction (passenger aircraft) : 203

IMDG-Code

UN number : UN 1950
Proper shipping name : AEROSOLS

Class : 2.1
Packing group : Not assigned by regulation
Labels : 2.1
EmS Code : F-D, S-U
Marine pollutant : no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

15. REGULATORY INFORMATION

National regulatory information

Federal Law of 21.07.1997 No. 116-FZ (amended on 11.06.2021) "On industrial safety of hazardous production facilities".

Federal Law of 24.06.1998 No. 89-FZ (amended on 02.07.2021) "On production and consumption waste".

Federal Law of 30.03.1999 No. 52-FZ (amended on 02.07.2021) "On the Sanitary and Epidemiological Well-Being of the Population" (amended and supplemented, entered into force on 31.10.2021).

Federal Law of 04.05.1999 No. 96-FZ "On the protection of atmospheric air" (as amended on December 8, 2020).

Federal Law of 27.12.2002 No. 184-FZ (amended on 02.07.2021) "On Technical Regulation" (amended and supplemented, entered into force on 01.09.2021).

Federal Law of 10.01.2002 No. 7-FZ (amended on 02.07.2021) "On environmental protection".

Federal Law of 22.07.2008 No. 123-FZ "Technical Regulations on Fire Safety Requirements"

OKS 701

Version 3.3	Revision Date: 18.10.2022	Date of last issue: 31.07.2019 Date of first issue: 22.04.2014	Print Date: 18.10.2022
----------------	------------------------------	---	---------------------------

TECHNICAL REGULATIONS OF THE CUSTOMS UNION TR CU 030/2012 On requirements for lubricants, oils and special fluids (amended on 03.03.2017).

International Regulations

Montreal Protocol	:	Not applicable
Rotterdam Convention (Prior Informed Consent)	:	Not applicable
Stockholm Convention (Persistent Organic Pollutants)	:	Not applicable

16. OTHER INFORMATION

List of data sources used in the preparation of the Safety Data Sheet

GOST 30333-2007. Interstate standard. Safety data sheet for chemical products. Primary requirements.

GOST 12.1.004-91 System of labor safety standards (SSBT). Fire safety. General requirements.

GOST 12.1.007-76 Occupational safety standards system. Noxious substances. Classification and general safety requirements

GOST 12.1.044-89 SSBT. Fire and explosion hazard of substances and materials. Nomenclature of indicators and methods for their determination.

GOST 12.4.021 System of labor safety standards (SSBT). Ventilation systems. General requirements.

GOST 12.4.137-2001 Special footwear with leather uppers for protection against oil, oil products, acids, alkalis, non-toxic and explosive dust. Technical conditions.

GOST 12.4.252-2013 System of labor safety standards (SSBT). Means of individual protection of hands. Gloves. General technical requirements. Test methods.

GOST 14192-96. Interstate standard. Cargo marking. Minsk, 1998.

GOST 19433-88 Dangerous goods. Classification and labeling.

GOST 31340-2013. Interstate standard. Precautionary labeling of chemical products. General requirements.

GOST 32419-2013 Classification of the hazard of chemical products. General requirements.

GOST 32421-2013 Classification of chemical products, the hazard of which is due to physical and chemical properties. Test methods for explosive chemical products.

GOST 32423-2013 Hazard classification of mixed chemical products by their effects on the body.

GOST 32424-2013 Classification of the hazard of chemical products by their impact on the environment. Basic provisions.

GOST 32425-2013 Hazard classification of mixed chemical products in terms of environmental impact.

GOST R 53264-2019 Fire fighting equipment. Special protective clothing for firefighters. General technical requirements. Test methods.

GOST R 53265-2019 Fire fighting equipment. Personal protective equipment for the feet of the firefighter. General technical requirements. Test methods.

GOST R 53268-2009 Fire fighting equipment. Fire rescue belts. General technical requirements. Test methods.

GOST R 53269-2019 Fire fighting equipment. Firefighters helmets. General technical requirements. Test methods.

SAFETY DATA SHEET

- RU



OKS 701

Version	Revision Date:	Date of last issue: 31.07.2019	Print Date:
3.3	18.10.2022	Date of first issue: 22.04.2014	18.10.2022

SanPiN 1.2.2353-08 "Carcinogenic factors and basic requirements for the prevention of carcinogenic hazard".

SanPiN 1.2.3685-21 "Hygienic standards and requirements for ensuring the safety and (or) harmlessness to humans of environmental factors" dated 28.01.2021.

SanPiN 2.1.3684-21 "Sanitary and epidemiological requirements for the maintenance of the territories of urban and rural settlements, for water bodies, drinking water and drinking water supply, atmospheric air, soils, living quarters, the operation of industrial, public premises, the organization and implementation of sanitary and anti-epidemic (preventive) measures".

SanPiN 2.2.0.555-96. 2.2. Labor hygiene. Hygienic requirements for working conditions for women. Sanitary rules and regulations.

Carriage of dangerous goods, International maritime dangerous goods (IMDG) code.

Water quality standards for fishery water bodies, including standards for maximum permissible concentrations of harmful substances in the waters of fishery water bodies (approved by order of the Ministry of Agriculture of Russia dated December 13, 2016 No. 552).

Regulations for the carriage of dangerous goods (Appendix 1 and 2) to the Agreement on International Goods Transport by Rail (SMGS), 2009.

Agreement on International Goods Transport by Rail (SMGS).

UN Recommendations on the Transport of Dangerous Goods. Typical rules. Twenty-second revised edition. United Nations, New York and Geneva, 2021.

Montreal Protocol (Ozone Depleting Substances)

Stockholm Convention (Persistent Organic Pollutants)

Full text of other abbreviations

Asp. Tox.	:	Aspiration hazard
Flam. Gas	:	Flammable gases
Flam. Liq.	:	Flammable liquids
Press. Gas	:	Gases under pressure
Skin Sens.	:	Skin sensitisation
RU OEL	:	SanPiN 1.2.3685-21 Table 2.1, Table 2.8, Table 2.16 & Table 2.17 Maximum permissible concentrations (MPC) in the air of the working area
RU OEL / MPC-STEL	:	Maximum Permissible Concentration - Short Term Exposure
RU OEL / MPC-TWA	:	Maximum Permissible Concentration - Time Weighted Average
List 1	:	SanPiN 1.2.3685-21 Table 1.1, Table 1.10, & Table 1.11 Maximum permissible concentration (MPC) in the air of urban and rural settlements
List 5	:	Order of the Russian Federal Fisheries Agency "Standards of maximum permissible concentrations of harmful substances in fishery water bodies"

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of

OKS 701

Version	Revision Date:	Date of last issue: 31.07.2019	Print Date:
3.3	18.10.2022	Date of first issue: 22.04.2014	18.10.2022

Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

This safety data sheet applies only to products as originally packed and labelled. The information contained therein may not be reproduced or modified without our express written permission. Any forwarding of this document is only permitted to the extent required by law. Any further, in particular public, dissemination of the safety data sheet (e.g. as a document for download from the Internet) is not permitted without our express written consent. We provide our customers with amended safety data sheets as prescribed by law. The customer is responsible for passing on safety data sheets and any amendments contained therein to its own customers, employees and other users of the product. We provide no guarantee that safety data sheets received by users from third parties are up-to-date. All information and instructions in this safety data sheet have been compiled to the best of our knowledge and are based on the information available to us on the day of publication. The information provided is intended to describe the product in relation to the required safety measures; it is neither an assurance of characteristics nor a guarantee of the product's suitability for particular applications and does not justify any contractual legal relationship. The existence of a safety data sheet for a particular jurisdiction does not necessarily mean that import or use within that jurisdiction is legally permitted. If you have any questions, please contact your responsible sales contact or authorized trading partner.